



FCC RF Test Report

APPLICANT : 70mai Co., Ltd.
EQUIPMENT : 70mai 4G Hardwire Kit
BRAND NAME : 70mai
MODEL NAME : Midrive UP05
FCC ID : 2AOK9-MDUP5
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
TEST DATE(S) : Dec. 15, 2023 ~ Dec. 22, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test 5

 1.4 Product Specification of Equipment Under Test 6

 1.5 Modification of EUT 6

 1.6 Maximum ERP/EIRP Power, and Emission Designator 6

 1.7 Testing Location 7

 1.8 Test Software 7

 1.9 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 8

 2.3 Support Unit used in test configuration 9

 2.4 Measurement Results Explanation Example 9

 2.5 Frequency List of Low/Middle/High Channels..... 9

3 CONDUCTED TEST RESULT..... 10

 3.1 Measuring Instruments..... 10

 3.2 Test Setup 10

 3.3 Test Result of Conducted Test..... 10

 3.4 Conducted Output Power and ERP/EIRP 11

 3.5 Peak-to-Average Ratio 12

 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 13

 3.7 Conducted Band Edge 14

 3.8 Conducted Spurious Emission 15

 3.9 Frequency Stability..... 16

4 RADIATED TEST ITEMS 17

 4.1 Measuring Instruments..... 17

 4.2 Test Setup 17

 4.3 Test Result of Radiated Test..... 18

 4.4 Field Strength of Spurious Radiation Measurement 19

5 LIST OF MEASURING EQUIPMENT 20

6 MEASUREMENT UNCERTAINTY 21

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 38.92 dB at 5730.00 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

70mai Co., Ltd.

Room 2220, building 2, No. 588, Zixing road, MinHang District, Shanghai.CHINA

1.2 Manufacturer

70mai Co., Ltd.

Room 2220, building 2, No. 588, Zixing road, MinHang District, Shanghai.CHINA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	70mai 4G Hardwire Kit
Brand Name	70mai
Model Name	Midrive UP05
FCC ID	2AOK9-MDUP5
IMEI Code	Conducted: 868260056486690 Radiation: 868260051281674
HW Version	LGDM0009
SW Version	1.0.6
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	WCDMA: Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
Rx Frequency	WCDMA: Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz
Maximum Output Power to Antenna	WCDMA: Band V: 23.68 dBm Band II: 23.67 dBm Band IV: 23.61 dBm
Antenna Type	Monopole Antenna
Antenna Gain	Cellular Band: 1.81 dBi PCS Band: 3.61 dBi AWS Band: 3.50 dBi
Type of Modulation	WCDMA: BPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 22	WCDMA Band V	826.4 ~ 846.6	BPSK	0.2158	4M15F9W
Part 24	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.5346	4M13F9W
Part 27	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.5140	4M14F9W



1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People’s Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	SPORTON	Part2224_Ver5.0 200330	5.0
2.	03CH04-KS	AUDIX	E3	210616

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.6 dB and a 10dB attenuator.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.6 + 10 = 14.6 \text{ (dB)}
 \end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Dec. 15, 2023	Oct. 10, 2024	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Dec. 15, 2023	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 06, 2023	Dec. 15, 2023	Jul. 05, 2024	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz-44G, MAX 30dB	Oct. 10, 2023	Dec. 22, 2023	Oct. 09, 2024	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 11 2023	Dec. 22, 2023	Sep. 10, 2024	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Apr. 09, 2023	Dec. 22, 2023	Apr. 08, 2024	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1284	1GHz~18GHz	Oct. 10, 2023	Dec. 22, 2023	Oct. 09, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 08, 2023	Dec. 22, 2023	Jan. 07, 2024	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380827	9KHz-1GHz	Jul. 06, 2023	Dec. 22, 2023	Jul. 05, 2024	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 05, 2023	Dec. 22, 2023	Jan. 04, 2024	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz-18Ghz	Oct. 10, 2023	Dec. 22, 2023	Oct. 09, 2024	Radiation (03CH04-KS)
Amplifier	Agilent	8449B	3008A02370	1Ghz-18Ghz	Oct. 10, 2023	Dec. 22, 2023	Oct. 09, 2024	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Dec. 22, 2023	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 22, 2023	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 22, 2023	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Peak to Average Ratio	±0.46 dB
Frequency Stability	±0.4 Hz

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.82
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.56
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.54
---	------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%

Conducted Output Power(Average power) and ERP/EIRP

Band		WCDMA V			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458			
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.39	23.58	23.40	0.2018	0.2109	0.2023
3GPP Rel 99	RMC 12.2Kbps	23.45	23.68	23.52	0.2046	0.2158	0.2080
3GPP Rel 6	HSDPA Subtest-1	22.46	22.63	22.47	0.1629	0.1694	0.1633
3GPP Rel 6	HSDPA Subtest-2	22.55	22.85	22.77	0.1663	0.1782	0.1750
3GPP Rel 6	HSDPA Subtest-3	21.49	21.62	21.64	0.1303	0.1343	0.1349
3GPP Rel 6	HSDPA Subtest-4	21.56	21.66	21.64	0.1324	0.1355	0.1349
3GPP Rel 6	HSUPA Subtest-1	21.63	21.90	21.84	0.1346	0.1432	0.1413
3GPP Rel 6	HSUPA Subtest-2	19.99	20.23	20.02	0.0923	0.0975	0.0929
3GPP Rel 6	HSUPA Subtest-3	20.94	21.18	21.15	0.1148	0.1213	0.1205
3GPP Rel 6	HSUPA Subtest-4	20.03	20.18	20.26	0.0931	0.0964	0.0982
3GPP Rel 6	HSUPA Subtest-5	21.92	22.08	22.13	0.1439	0.1493	0.1510

Band		WCDMA IV			EIRP(W)		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.33	23.39	23.57	0.4819	0.4887	0.5093
3GPP Rel 99	RMC 12.2Kbps	23.42	23.61	23.58	0.4920	0.5140	0.5105
3GPP Rel 6	HSDPA Subtest-1	22.41	22.43	22.53	0.3899	0.3917	0.4009
3GPP Rel 6	HSDPA Subtest-2	22.51	22.61	22.73	0.3990	0.4083	0.4198
3GPP Rel 6	HSDPA Subtest-3	21.97	21.99	22.07	0.3524	0.3540	0.3606
3GPP Rel 6	HSDPA Subtest-4	21.75	21.99	22.09	0.3350	0.3540	0.3622
3GPP Rel 6	HSUPA Subtest-1	22.23	22.33	22.46	0.3741	0.3828	0.3945
3GPP Rel 6	HSUPA Subtest-2	20.37	20.52	20.49	0.2438	0.2523	0.2506
3GPP Rel 6	HSUPA Subtest-3	21.43	21.34	21.55	0.3112	0.3048	0.3199
3GPP Rel 6	HSUPA Subtest-4	20.39	20.53	20.59	0.2449	0.2529	0.2564
3GPP Rel 6	HSUPA Subtest-5	22.28	22.32	22.45	0.3784	0.3819	0.3936




Band		WCDMA II			EIRP(W)		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938			
Frequency (MHz)		1852.4	1880	1907.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.42	23.59	23.51	0.5047	0.5248	0.5152
3GPP Rel 99	RMC 12.2Kbps	23.46	23.67	23.55	0.5093	0.5346	0.5200
3GPP Rel 6	HSDPA Subtest-1	22.37	22.61	22.42	0.3963	0.4188	0.4009
3GPP Rel 6	HSDPA Subtest-2	22.37	22.63	22.57	0.3963	0.4207	0.4150
3GPP Rel 6	HSDPA Subtest-3	21.98	22.11	22.01	0.3622	0.3733	0.3648
3GPP Rel 6	HSDPA Subtest-4	21.93	22.09	21.92	0.3581	0.3715	0.3573
3GPP Rel 6	HSUPA Subtest-1	22.36	22.56	22.57	0.3954	0.4140	0.4150
3GPP Rel 6	HSUPA Subtest-2	20.42	20.62	20.64	0.2529	0.2649	0.2661
3GPP Rel 6	HSUPA Subtest-3	21.44	21.57	21.55	0.3199	0.3296	0.3281
3GPP Rel 6	HSUPA Subtest-4	20.37	20.66	20.50	0.2500	0.2673	0.2576
3GPP Rel 6	HSUPA Subtest-5	22.21	22.55	22.39	0.3819	0.4130	0.3981



A2. WCDMA

Peak-to-Average Ratio


Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.75	3.22	2.38	PASS
Middle CH	2.93	2.93	3.13	
Highest CH	2.90	2.99	2.96	






WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 15 DEC 2023 17:39:29

Middle Channel



Date: 15 DEC 2023 17:39:40

Highest Channel



Date: 15 DEC 2023 17:39:52




26dB Bandwidth

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.755	4.695	4.755
Middle CH	4.735	4.725	4.705
Highest CH	4.735	4.705	4.705



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 15 DEC 2023 17:44:56


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 15 DEC 2023 17:18:44

Middle Channel




Date: 15 DEC 2023 17:45:23

Middle Channel




Date: 15 DEC 2023 17:19:09

Highest Channel



Date: 15 DEC 2023 17:45:45

Highest Channel




Date: 15 DEC 2023 17:19:43




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 15.DEC.2023 17:30:25

Middle Channel



Date: 15.DEC.2023 17:30:48

Highest Channel



Date: 15.DEC.2023 17:31:13




Occupied Bandwidth

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.146	4.126	4.136
Middle CH	4.136	4.116	4.116
Highest CH	4.126	4.116	4.126



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 15 DEC 2023 17:47:44


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 15 DEC 2023 17:22:03

Middle Channel




Date: 15 DEC 2023 17:48:07

Middle Channel




Date: 15 DEC 2023 17:22:26

Highest Channel



Date: 15 DEC 2023 17:48:30

Highest Channel




Date: 15 DEC 2023 17:22:50




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 15 DEC 2023 17:47:44

Middle Channel



Date: 15 DEC 2023 17:48:07



Highest Channel



Date: 15 DEC 2023 17:48:30



Conducted Band Edge







WCDMA Band IV (RMC 12.2Kbps)

Lowest Band Edge

Highest Band Edge




Date: 15.DEC.2023 17:37:11



Date: 15.DEC.2023 17:37:44




Conducted Spurious Emission






WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 15 DEC 2023 17:38:13

Middle Channel



Date: 15 DEC 2023 17:38:34

Highest Channel



Date: 15 DEC 2023 17:38:59



Frequency Stability

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0056	PASS
40	Normal Voltage	0.0351	
30	Normal Voltage	0.0562	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0071	
0	Normal Voltage	0.0332	
-10	Normal Voltage	0.0079	
-20	Normal Voltage	0.0103	
-30	Normal Voltage	0.0357	
20	Maximum Voltage	0.0437	
20	Normal Voltage	0.0146	
20	Battery End Point	0.0025	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0172	PASS
40	Normal Voltage	0.0168	
30	Normal Voltage	0.0121	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0108	
0	Normal Voltage	0.0398	
-10	Normal Voltage	0.0451	
-20	Normal Voltage	0.0638	
-30	Normal Voltage	0.0249	
20	Maximum Voltage	0.0179	
20	Normal Voltage	0.0027	
20	Battery End Point	0.0036	



Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0052	PASS
40	Normal Voltage	0.0164	
30	Normal Voltage	0.0097	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0154	
0	Normal Voltage	0.0268	
-10	Normal Voltage	0.0191	
-20	Normal Voltage	0.0567	
-30	Normal Voltage	0.0048	
20	Maximum Voltage	0.0044	
20	Normal Voltage	0.0022	
20	Minimum Voltage	0.0116	

Note:

1. Normal Voltage = 13V ; Minimum Voltage =12V. ; Maximum Voltage =30V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Carry Xu	Temperature :	23~25°C
		Relative Humidity :	41~42%

WCDMA Band V(RMC 12.2Kbps)								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1656	-63.86	-13	-50.86	-70.83	1.58	10.70	H
	2480	-61.93	-13	-48.93	-70.18	2.102	12.50	H
	3304	-60.78	-13	-47.78	-69.67	2.856	13.90	H
	1656	-62.65	-13	-49.65	-69.62	1.58	10.70	V
	2480	-59.87	-13	-46.87	-68.12	2.10	12.50	V
	3304	-60.20	-13	-47.20	-69.09	2.86	13.90	V
Middle	1672	-65.37	-13	-52.37	-72.34	1.58	10.70	H
	2512	-61.48	-13	-48.48	-69.73	2.102	12.50	H
	3344	-61.26	-13	-48.26	-70.15	2.856	13.90	H
	1672	-63.45	-13	-50.45	-70.42	1.58	10.70	V
	2512	-59.78	-13	-46.78	-68.03	2.10	12.50	V
	3344	-59.95	-13	-46.95	-68.84	2.86	13.90	V
Highest	1696	-64.15	-13	-51.15	-71.12	1.58	10.70	H
	2536	-61.18	-13	-48.18	-69.43	2.102	12.50	H
	3384	-60.83	-13	-47.83	-69.72	2.856	13.90	H
	1696	-61.53	-13	-48.53	-68.50	1.58	10.70	V
	2536	-60.24	-13	-47.24	-68.49	2.10	12.50	V
	3384	-61.11	-13	-48.11	-70.00	2.86	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II(RMC 12.2Kbps)								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3705	-57.90	-13	-44.90	-70.16	2.64	14.90	H
	5550	-57.33	-13	-44.33	-69.19	2.94	14.80	H
	7410	-54.03	-13	-41.03	-63.80	3.39	13.16	H
	3705	-58.08	-13	-45.08	-70.34	2.64	14.90	V
	5550	-56.97	-13	-43.97	-68.83	2.94	14.80	V
	7410	-53.88	-13	-40.88	-63.65	3.39	13.16	V
Middle	3765	-58.16	-13	-45.16	-70.42	2.64	14.90	H
	5640	-56.18	-13	-43.18	-68.04	2.94	14.80	H
	7515	-53.71	-13	-40.71	-63.48	3.39	13.16	H
	3765	-57.86	-13	-44.86	-70.12	2.64	14.90	V
	5640	-56.68	-13	-43.68	-68.54	2.94	14.80	V
	7515	-53.82	-13	-40.82	-63.59	3.39	13.16	V
Highest	3810	-57.87	-13	-44.87	-70.13	2.641	14.90	H
	5730	-51.92	-13	-38.92	-63.78	2.94	14.80	H
	7635	-53.41	-13	-40.41	-63.18	3.39	13.16	H
	3810	-57.71	-13	-44.71	-69.97	2.64	14.90	V
	5730	-55.50	-13	-42.50	-67.36	2.94	14.80	V
	7635	-53.48	-13	-40.48	-63.25	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band IV (RMC 12.2Kbps)								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3420	-58.25	-13	-45.25	-68.99	2.604	13.34	H
	5130	-55.91	-13	-42.91	-66.42	3.011	13.52	H
	6855	-55.71	-13	-42.71	-65.91	3.271	13.47	H
	3420	-58.95	-13	-45.95	-69.69	2.604	13.34	V
	5130	-56.16	-13	-43.16	-66.67	3.011	13.52	V
	6855	-55.89	-13	-42.89	-66.09	3.271	13.47	V
Middle	3465	-58.47	-13	-45.47	-69.21	2.604	13.34	H
	5205	-53.28	-13	-40.28	-63.79	3.011	13.52	H
	6930	-55.16	-13	-42.16	-65.36	3.271	13.47	H
	3465	-58.31	-13	-45.31	-69.05	2.604	13.34	V
	5205	-55.97	-13	-42.97	-66.48	3.011	13.52	V
	6930	-55.61	-13	-42.61	-65.81	3.271	13.47	V
Highest	3510	-58.79	-13	-45.79	-69.53	2.604	13.34	H
	5265	-55.60	-13	-42.60	-66.11	3.011	13.52	H
	7005	-55.48	-13	-42.48	-65.68	3.271	13.47	H
	3510	-58.68	-13	-45.68	-69.42	2.604	13.34	V
	5265	-56.00	-13	-43.00	-66.51	3.011	13.52	V
	7005	-55.35	-13	-42.35	-65.55	3.271	13.47	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.