

ISED Test Report

Report No.: AGC01110201238CE02B

IC 23451-A3126

APPLICATION PURPOSE : Class II Equipment

Soundcore Select Pro PRODUCT DESIGNATION

BRAND NAME soundcore

MODEL NAME : A3126

APPLICANT Anker Innovations Limited

DATE OF ISSUE : Apr. 21, 2023

RSS-GEN: issue 5 STANDARD(S) RSS-247: issue 2

REPORT VERSION : V1.0

> <u>e (Shenzhen) Co., Ltd</u> Attestation of Globa



Page 2 of 23

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Apr. 21, 2023	Valid	Initial Release

Note: The original test report AGC01110201238CE02A (dated Aug. 04, 2021 and tested from Jul. 09, 2021 to Aug. 04, 2021) was modified on Apr. 21, 2023, including the following changes and additions:

- -Replaced the OVP chip (from LP53010 to ETA7014S2G);
- -Replaced the IC of the analog switch (from DI01159 to RS2057XC6);
- -Replaced the DC-DC (from SM8102HABC to FR9850S6);
- -Replaced the MOS (from VS304RZ to KJ0503G), (from SP3OP13TH to WMO5OP03T1) and (from LPM9017B3F to WMO3P42M);
- -Replaced the hardware version and software version of the EUT;
- For the above described change(s), the Radiated Emission and Conducted Emission had been tested for the Class II device.







TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
2.2. TABLE OF CARRIER FREQUENCYS	5
2.3. RELATED SUBMITTAL(S)/GRANT(S)	6
2.4. TEST METHODOLOGY	6
2.5. SPECIAL ACCESSORIES	6
2.6. EQUIPMENT MODIFICATIONS	6
2.7. ANTENNA REQUIREMENT	6
3. MEASUREMENT UNCERTAINTY	7
4. DESCRIPTION OF TEST MODES	8
5. SYSTEM TEST CONFIGURATION	9
5.1. CONFIGURATION OF TESTED SYSTEM	9
5.2. EQUIPMENT USED IN TESTED SYSTEM	9
5.3. SUMMARY OF TEST RESULTS	9
6. TEST FACILITY	10
7. RADIATED EMISSION	11
7.1. MEASUREMENT PROCEDURE	11
7.2. TEST SETUP	12
7.3. LIMITS AND MEASUREMENT RESULT	13
7.4. TEST RESULT	13
8. LINE CONDUCTED EMISSION TEST	19
8.1. LIMITS OF LINE CONDUCTED EMISSION TEST	19
8.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	19
8.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	20
8.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	20
8.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	20
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	23
APPENDIX B: PHOTOGRAPHS OF EUT	23





1. VERIFICATION OF COMPLIANCE

Applicant	Anker Innovations Limited		
Address	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hongkong		
Manufacturer	Anker Innovations Limited		
Address	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hongkong		
Product Designation	Soundcore Select Pro		
Brand Name	soundcore		
Test Model	A3126		
Date of receipt of test item	Apr. 06, 2023		
Date of test	Apr. 08, 2023 to Apr. 20, 2023		
Deviation	No any deviation from the test method		
Condition of Test Sample	Normal		
Test Result	Pass		
Report Template	AGCRT-US-BLE/RF		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of RSS-247.

Prepared By	Alan Duan	
	Alan Duan (Project Engineer)	Apr. 21, 2023
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Apr. 21, 2023
Approved By	Max Zhang	
	Max Zhang	Apr. 21, 2023
	(Authorized Officer)	, ,, ====



Page 5 of 23

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as a "Soundcore Select Pro". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402GHz to 2.480GHz		
RF Output Power	2.670dBm(Max)		
EIRP	5.920dBm (Max)		
Bluetooth Version	V5.0		
Modulation	BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE ☑GFSK 1Mbps □GFSK 2Mbps		
Number of channels	40 Channels		
Antenna Designation	FPC Antenna (Comply with requirements of the RSS-Gen 6.8)		
Antenna Gain	3.25dBi		
Hardware Version	VA.0		
Software Version	V0.25		
Power Supply	DC 7.2V by battery or DC 5V by adapter		

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency	
	0	2402 MHz	
	1	2404 MHz	
2400~2483.5MHz	:	·	
	38	2478 MHz	
	39	2480 MHz	



Page 6 of 23

2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for IC: 23451-A3126 filing to comply with the RSS-247 requirements.

2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



Page 7 of 23

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.8 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	$U_c = \pm 2.7 \%$		
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$		



Page 8 of 23

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION		
1	Low channel TX_2402MHz		
2	Middle channel TX_2440MHz		
3	High channel TX_2480MHz		

Note: 1. Only the result of the worst case was recorded in the report, if no other cases.

- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.




Page 9 of 23


5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:



Conducted Emission Configure:



5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	ment Model No. ID or Specification		Remark
1	1 Soundcore Select Pro A312		23451-A3126	EUT
2	2 iPod MG		1.2m unshielded	AE
3	Adapter K-T10E050200 DC 5V		DC 5V	AE
4	Xiaomi phone Mi 10 1.0m unshielded		1.0m unshielded	AE
5	Adapter	HW-050200C0 1 DC 5V		AE

5.3. SUMMARY OF TEST RESULTS

ISED RULES	DESCRIPTION OF TEST	RESULT
RSS-GEN 8.9	Radiated Emission	Compliant
RSS-GEN 8.8	Conducted Emission	Compliant



Page 10 of 23

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd	
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community Fuhai Street, Bao'an District, Shenzhen, Guangdong, China	
IC Designation Number	24842	
A2LA Cert. No.	5054.02	
ISED CAB Identifier	CN0063	
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA	

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Feb. 18, 2023	Feb. 17, 2024
LISN	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test software	R&S	ES-K1(Ver.V1.71)	N/A	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Agilent	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Signal Analyzer	Aglient	N9020A	MY52090123	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn Antenna	SCHWARZBEC	BBHA9170	768	Oct. 31, 2021	Oct. 30, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Double-Ridged Waveguide Horn	ETS	3117	00154520	Sep. 06, 2021	Sep. 05, 2023
Preamplifier Assembly	ETS	3117PA	00225134	Sep. 01, 2022	Sep. 02, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-49 4	Jan. 05, 2023	Jan. 04, 2025
Test software	FARA	EZ-EMC(Ver RA-03A)	N/A	N/A	N/A




Page 11 of 23

7. RADIATED EMISSION

7.1. MEASUREMENT PROCEDURE


- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.






7.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 13 of 23

7.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

7.4. TEST RESULT


Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.




Radiated emission from 30MHz to 1000MHz

EUT	Soundcore Select Pro	Model Name	A3126
Temperature	21°C	Relative Humidity	53%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal




RESULT: PASS





EUT	Soundcore Select Pro	Model Name	A3126
Temperature	21°C	Relative Humidity	53%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical



RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Limit-Level.

2. All test modes had been tested. The mode 2 is the worst case and recorded in the report.



Page 16 of 23

Radiated emission above 1GHz

EUT	Soundcore Select Pro	Model Name	A3126
Temperature	21°C	Relative Humidity	53%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	46.29	0.08	46.37	74	-27.63	peak
4804.000	37.51	0.08	37.59	54	-16.41	AVG
7206.000	42.15	2.21	44.36	74	-29.64	peak
7206.000	31.49	2.21	33.7	54	-20.3	AVG


Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT	Soundcore Select Pro	Model Name	A3126
Temperature	21°C	Relative Humidity	53%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
46.29	0.08	46.37	74	-27.63	peak
36.54	0.08	36.62	54	-17.38	AVG
40.25	2.21	42.46	74	-31.54	peak
31.59	2.21	33.8	54	-20.2	AVG
	(dBµV) 46.29 36.54 40.25	(dBµV) (dB) 46.29 0.08 36.54 0.08 40.25 2.21	(dBμV) (dB) (dBμV/m) 46.29 0.08 46.37 36.54 0.08 36.62 40.25 2.21 42.46	(dBμV) (dB) (dBμV/m) (dBμV/m) 46.29 0.08 46.37 74 36.54 0.08 36.62 54 40.25 2.21 42.46 74	(dBμV) (dB) (dBμV/m) (dBμV/m) (dBμV/m) 46.29 0.08 46.37 74 -27.63 36.54 0.08 36.62 54 -17.38 40.25 2.21 42.46 74 -31.54

Factor = Antenna Factor + Cable Loss - Pre-amplifier.





EUT	Soundcore Select Pro	Model Name	A3126
Temperature	21°C	Relative Humidity	53%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	47.51	0.14	47.65	74	-26.35	peak
4880.000	38.51	0.14	38.65	54	-15.35	AVG
7320.000	42.15	2.36	44.51	74	-29.49	peak
7320.000	32.46	2.36	34.82	54	-19.18	AVG
Remark:						
actor = Anter	na Factor + Cabl	e Loss – Pre-	amplifier			

EUT	Soundcore Select Pro	Model Name	A3126
Temperature	21°C	Relative Humidity	53%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	47.51	0.14	47.65	74	-26.35	peak
4880.000	37.54	0.14	37.68	54	-16.32	AVG
7320.000	41.26	2.36	43.62	74	-30.38	peak
7320.000	32.59	2.36	34.95	54	-19.05	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 18 of 23

EUT	Soundcore Select Pro	Model Name	A3126
Temperature	21°C	Relative Humidity	53%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	49.64	0.22	49.86	74	-24.14	peak
4960.000	38.54	0.22	38.76	54	-15.24	AVG
7440.000	7440.000 43.58 2.64 7440.000 34.56 2.64		46.22	74	-27.78	peak
7440.000			37.2 54		-16.8	AVG
Remark:	•		•	•		•
actor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			

EUT	Soundcore Select Pro	Model Name	A3126
Temperature	21°C	Relative Humidity	53%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type	
4960.000	47.54	0.22	47.76	74	-26.24	peak	
4960.000	37.54	0.22	37.76	54	-16.24	AVG	
7440.000	42.15	2.64	44.79	74	-29.21	peak	
7440.000	32.16	2.64	34.8	54	-19.2	AVG	

Remark:


Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: PASS

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Emission Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.





8. LINE CONDUCTED EMISSION TEST


8.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francisco	Maximum RF Line Voltage				
Frequency	Q.P.(dBuV)	Average(dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

8.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Page 20 of 23

8.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


8.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The BLE 1Mpbs test data of the worst case condition(s) was reported on the Summary Data page.

8.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT: "agc fin"

2	2023/4/10 15:	10					
	Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
	0.170000	56.10	6.2	65	8.9	QP	L1
	0.462000	39.40	6.2	57	17.3	QP	L1
	1.470000	40.60	6.3	56	15.4	QP	L1
	1.518000	40.70	6.3	56	15.3	QP	L1
	1.530000	38.60	6.3	56	17.4	QP	L1
	2.654000	38.30	6.4	56	17.7	QP	L1


MEASUREMENT RESULT: "agc_fin2"

2023/4/10	15:07					
Frequen M	icy Level IHz dBµ		Limit dBµV	Margin dB	Detector	Line
0.1700 0.1940			55 54	21.6 22.4		L1 L1
0.5060	00 33.1	6.2	46	12.9	AV	L1
0.5980	00 31.2	6.2	46	14.8	AV	L1
1.5300	00 29.3	6.3	46	16.7	AV	L1
2.6620	00 31.0	6.4	46	15.0	AV	L1

RESULT: PASS



Line Conducted Emission Test Line 2-N



MEASUREMENT RESULT: "agc_fin"

20	23/4/10 15: Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
	0.494000	45.00	6.2	56	11.1	QP	N
	1.134000	43.70	6.3	56	12.3	QP	N
	1.330000	42.90	6.3	56	13.1	QP	N
	1.526000	43.90	6.3	56	12.1	QP	N
	2.662000	41.70	6.4	56	14.3	QP	N
	2.706000	42.10	6.4	56	13.9	QP	N

MEASUREMENT RESULT: "agc_fin2"

2023/4/10	15:19	9					
Freque	ncy MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.462	000	29.40	6.2	47	17.3	AV	N
0.514	000	30.00	6.2	46	16.0	AV	N
0.606	000	28.70	6.2	46	18.3	AV	N
0.762	000	25.70	6.3	46	20.3	AV	N
1.022	000	24.90	6.3	46	21.1	AV	N
1.126	000	24.40	6.3	46	21.6	AV	N

RESULT: PASS

Note: All test modes had been tested. The mode 2 is the worst case and recorded in the report.



Page 23 of 23

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC01110201238AP02B

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC01110201238AP03B

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.