

FCC Test Report

Report No.: AGC01110230761FR01

FCC ID : 2AOKB-A3131

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Wireless Speaker

BRAND NAME: soundcore

MODEL NAME : A3131

APPLICANT: Anker Innovations Limited

DATE OF ISSUE : Sep. 26, 2023

STANDARD(S) : FCC Part 15.247

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 61

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 26, 2023	Valid	Initial Release



TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION 2.2. TABLE OF CARRIER FREQUENCYS 2.3. RELATED SUBMITTAL(S)/GRANT(S) 2.4. TEST METHODOLOGY 2.5. SPECIAL ACCESSORIES 2.6. EQUIPMENT MODIFICATIONS 2.7. ANTENNA REQUIREMENT	
3. MEASUREMENT UNCERTAINTY	8
4. DESCRIPTION OF TEST MODES	g
5. SYSTEM TEST CONFIGURATION	10
5.1. CONFIGURATION OF TESTED SYSTEM	10 10
6. TEST FACILITY	
7. DUTY CYCLE MEASUREMENT	
8. PEAK OUTPUT POWER	
8.1. MEASUREMENT PROCEDURE 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 8.3. LIMITS AND MEASUREMENT RESULT	13
9. BANDWIDTH	18
9.1. MEASUREMENT PROCEDURE 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 9.3. LIMITS AND MEASUREMENT RESULTS	18
10. CONDUCTED SPURIOUS EMISSION	25
10.1. MEASUREMENT PROCEDURE	25 25
11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	37
11.1. MEASUREMENT PROCEDURE	37 37
12. RADIATED EMISSION	41
12.1. MEASUREMENT PROCEDURE	
12 LINE CONDUCTED EMISSION TEST	E7



Report No.: AGC01110230761FR01 Page 4 of 61

13.1. LIMITS OF LINE CONDUCTED EMISSION TEST	57
13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	
13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	58
13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	58
13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	58
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	61
APPENDIX B. PHOTOGRAPHS OF FUT	61



Report No.: AGC01110230761FR01 Page 5 of 61

1. VERIFICATION OF COMPLIANCE

Applicant	Anker Innovations Limited	
Address	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hongkong	
Manufacturer	Anker Innovations Limited	
Address	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hongkong	
Factory	N/A	
Address	N/A	
Product Designation	Wireless Speaker	
Brand Name	soundcore	
Test Model	A3131	
Date of receipt of test item	Aug. 31, 2023	
Date of test	Aug. 31, 2023 to Sep. 26, 2023	
Deviation	No any deviation from the test method	
Condition of Test Sample	Normal	
Test Result	Pass	
Report Template	AGCRT-US-BLE/RF	

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By	Cool chery	
	Cool Cheng (Project Engineer)	Sep. 26, 2023
Reviewed By	Calin	Lin
	Calvin Liu (Reviewer)	Sep. 26, 2023
Approved By	Max 21	ang
- -	Max Zhang Authorized Officer	Sep. 26, 2023



Page 6 of 61

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as a "Wireless Speaker". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

A triager teermined decemption of Ee the decembed de relienting		
Operation Frequency	2.402 GHz to 2.480GHz	
RF Output Power	GFSK 1Mbps: 4.281dBm (Max) GFSK 2Mbps: 3.973dBm (Max)	
Bluetooth Version	V5.3	
Modulation	BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE ☑GFSK 1Mbps ☑GFSK 2Mbps	
Number of channels	40 Channels	
Antenna Designation	FPC Antenna (Comply with requirements of the FCC part 15.203)	
Antenna Gain	2.13dBi	
Hardware Version	V0.3	
Software Version	V1.0.2	
Power Supply	DC 7.3V by battery or 5V by adapter	

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2402 MHz
	1	2404 MHz
2400~2483.5MHz	:	:
	38	2478 MHz
	39	2480 MHz



Page 7 of 61

2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2AOKB-A3131** filing to comply with the FCC Part 15.247 requirements.

2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.




Page 8 of 61

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %






4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX for GFSK 1Mbps
2	Middle channel TX for GFSK 1Mbps
3	High channel TX for GFSK 1Mbps
4	Low channel TX for GFSK 2Mbps
5	Middle channel TX for GFSK 2Mbps
6	High channel TX for GFSK 2Mbps

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting






Page 10 of 61

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:



Conducted Emission Configure:

EUT	AE

5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Wireless Speaker	A3131	2AOKB-A3131	EUT
2	Control Box	N/A	USB-TTL	AE
3	Xiaomi phone	Mi 10	1m,unshielded	AE
4	adapter	HW-200440C00	N/A	AE

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



Page 11 of 61

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Jun. 03, 2023	Jun. 02, 2024
LISN	R&S	ESH2-Z5	100086	Jun. 03, 2023	Jun. 02, 2024
Attenuator	Dongfang Xupu	LM-XX-6-5W	N/A	Jun. 09, 2023	Jun. 08, 2024
Test software	R&S	Ver.V1.71	N/A	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Jun. 01, 2023	May 31, 2024
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2023	Apr. 22, 2024
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 01, 2022	Sep. 02, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 05, 2023	Jan. 04, 2025
Test software	FARA	Ver RA-03A	N/A	N/A	N/A



Report No.: AGC01110230761FR01 Page 12 of 61

7. Duty Cycle Measurement


The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
BLE_1Mbps	2120	84.80	0.72	0.47
BLE_2Mbps	1070	85.60	0.68	0.93

Remark:

- Duty Cycle factor = 10 * log (1/ Duty cycle)
- The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value

The test plots as follows:





Page 13 of 61

8. PEAK OUTPUT POWER


8.1. MEASUREMENT PROCEDURE


For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer.
- 2. RBW ≥ DTS bandwidth
- 3. VBW≥3*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for cables.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP








8.3. LIMITS AND MEASUREMENT RESULT

C.C. EIMITO AND INCACONCINCIN NECOCI					
Test Data of Conducted Output Power					
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail	
	2402	4.281	≤30	Pass	
GFSK 1M	2440	4.213	≤30	Pass	
	2480	4.150	≤30	Pass	
	2402	3.973	≤30	Pass	
GFSK 2M	2440	3.864	≤30	Pass	
	2480	3.808	≤30	Pass	

Test Graphs of Conducted Output Power





























Page 18 of 61

9. BANDWIDTH

9.1. MEASUREMENT PROCEDURE

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer.
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW ≥ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer.
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
 The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
 bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.


9.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	-6dB Limits (MHz)	Pass or Fail
	2402	1.062	0.725	≥0.5	Pass
GFSK 1M	2440	1.059	0.724	≥0.5	Pass
	2480	1.062	0.728	≥0.5	Pass
	2402	2.061	1.183	≥0.5	Pass
GFSK 2M	2440	2.062	1.182	≥0.5	Pass
	2480	2.065	1.180	≥0.5	Pass
































Test_Graph_LE1M_ANT1_2440_1Mbps_DTSBW







Test_Graph_LE2M_ANT1_2402_2Mbps_DTSBW







Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 25 of 61

10. CONDUCTED SPURIOUS EMISSION

10.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer.
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 7.2.

10.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.


10.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT				
A Paral In I have	Measurement Result			
Applicable Limits	Test Data	Criteria		
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS		





Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE1M_ANT1_2402_1Mbps_Lower Band Emissions



0 Hz






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE1M_ANT1_2440_1Mbps_Reference Level


#VBW 300 kHz


Span 3.000 MHz Sweep 2.000 ms (30000 pts)

Center 2.440000 GHz #Res BW 100 kHz
























Test_Graph_LE2M_ANT1_2402_2Mbps_Reference Level


#VBW 300 kHz


Span 5.000 MHz Sweep 2.000 ms (30000 pts)


Center 2.402000 GHz #Res BW 100 kHz
























Freq Offset 0 Hz






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE2M_ANT1_2480_2Mbps_Reference Level


#VBW 300 kHz


Span 5.000 MHz Sweep 2.000 ms (30000 pts)


Center 2.480000 GHz #Res BW 100 kHz














Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands Frequency Center Freq 2.398500000 GHz Avg Type: Log-Pwr Avg|Hold: 100/100 Trig: Free Run #Atten: 30 dB **Auto Tune** Mkr2 2.400 000 0 GHz -52.246 dBm Ref 20.00 dBm Center Freq 2.398500000 GHz Start Freq 2.390000000 GHz 2.407000000 GHz **CF Step** 1.700000 MHz Start 2.390000 GHz #Res BW 100 kHz Stop 2.407000 GHz Sweep 2.000 ms (30000 pts) **#VBW** 300 kHz Man FUNCTION FUNCTION WIDTH 2.402 246 1 GHz 2.400 000 0 GHz 3.324 dBm -52.246 dBm Freq Offset 0 Hz Test_Graph_LE1M_ANT1_2402_1Mbps_Lower Band Edge Emissions 09:38:37 AM Sep 06, 2023 TRACE 1 2 3 4 5 6 TYPE MWWWWW DET P N N N N Frequency Avg Type: Log-Pwi Avg|Hold: 100/100 Center Freq 2.487500000 GHz Trig: Free Run #Atten: 30 dB **Auto Tune** Mkr2 2.483 500 0 GHz -55.830 dBm Ref 20.00 dBm Center Freq 2.487500000 GHz Start Freq 2.475000000 GHz Stop Freq 2.500000000 GHz Start 2.47500 GHz Stop 2.50000 GHz Sweep 4.000 ms (30000 pts) **CF Step** 2.500000 MHz #Res BW 100 kHz #VBW 300 kHz Man FUNCTION FUNCTION WIDTH Freq Offset

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE1M_ANT1_2480_1Mbps_Higher Band Edge Emissions



2.500000 MHz


Freq Offset

Man

Sweep 4.000 ms (30000 pts)

FUNCTION WIDTH





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE2M_ANT1_2480_2Mbps_Higher Band Edge Emissions

#VBW 300 kHz

#Res BW 100 kHz



Page 37 of 61

11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

11.1. MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer.
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

11.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


Refer to Section 7.2.

11.3. MEASUREMENT EQUIPMENT USED

Refer to Section 6.

11.4. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power Spectral Density								
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail				
	2402	-11.875	≤8	Pass				
GFSK 1M	2440	-12.031	≪8	Pass				
	2480	-11.540	≤8	Pass				
	2402	-14.578	≤8	Pass				
GFSK 2M	2440	-14.964	≪8	Pass				
	2480	-14.997	≤8	Pass				





Test Graphs of Conducted Output Power Spectral Density 09:31:48 AM Sep 06, 2023 Frequency Center Freq 2.402000000 GHz Avg Type: Log-Pwr Avg|Hold: 81/100 Trig: Free Run #Atten: 30 dB PNO: Wide ↔ IFGain:Low Auto Tune Mkr1 2.402 034 3 GHz -11.875 dBm 10 dB/div Ref 20.00 dBm Center Freq 2.402000000 GHz Start Freq 2.401456250 GHz may palaya mahrat ya wama mari mhoran Stop Freq 2.402543750 GHz CF Step 108.750 kHz Man Freq Offset 0 Hz Center 2.4020000 GHz #Res BW 3.0 kHz Span 1.088 MHz Sweep 114.7 ms (1000 pts) #VBW 10 kHz Test_Graph_LE1M_ANT1_2402_1Mbps_PSD Frequency Avg Type: Log-Pwr Avg|Hold: 96/100 Center Freq 2.440000000 GHz PNO: Wide → Trig: Free Run IFGain:Low #Atten: 30 dB **Auto Tune** Mkr1 2.439 876 6 GHz -12.031 dBm 10 dB/div Ref 20.00 dBm Center Freq 2.440000000 GHz Start Freq 2.439457000 GHz Warra mayor Stop Freq 2.440543000 GHz CF Step 108.600 kHz Man Freq Offset


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE1M_ANT1_2440_1Mbps_PSD


#VBW 10 kHz

Span 1.086 MHz Sweep 114.6 ms (1000 pts)

Center 2.4400000 GHz #Res BW 3.0 kHz








Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE2M_ANT1_2402_2Mbps_PSD

#VBW 10 kHz







Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE2M_ANT1_2480_2Mbps_PSD

#VBW 10 kHz

Span 1.770 MHz Sweep 186.7 ms (1000 pts)

Center 2.4800000 GHz #Res BW 3.0 kHz



Page 41 of 61

12. RADIATED EMISSION


12.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.




12.2. TEST SETUP


Radiated Emission Test Setup 9KHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 43 of 61

12.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed


Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

12.4. TEST RESULT

Radiated emission below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.






Radiated emission from 30MHz to 1000MHz

EUT	Wireless Speaker	Model Name	A3131
Temperature	24.3° C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal



No.	MI	k. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	440.1963	14.68	25.09	39.77	46.00	-6.23	peak
2		460.7271	14.88	24.31	39.19	46.00	-6.81	peak
3		480.5276	16.19	21.81	38.00	46.00	-8.00	peak
4		501.1790	15.27	22.28	37.55	46.00	-8.45	peak
5		520.8882	14.47	25.14	39.61	46.00	-6.39	peak
6		906.4824	6.79	30.89	37.68	46.00	-8.32	peak

RESULT: PASS





EUT	Wireless Speaker	Model Name	A3131
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		43.0504	12.46	16.93	29.39	40.00	-10.61	peak
2		52.3912	11.42	17.02	28.44	40.00	-11.56	peak
3		99.8777	17.75	14.22	31.97	43.50	-11.53	peak
4		120.2766	14.24	17.71	31.95	43.50	-11.55	peak
5		158.1123	15.23	18.20	33.43	43.50	-10.07	peak
6	*	441.7425	12.71	26.02	38.73	46.00	-7.27	peak

RESULT: PASS Note:

- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. All test modes had been tested. The mode 1 is the worst case and recorded in the report.



Page 46 of 61

Radiated emission above 1GHz

EUT	Wireless Speaker	Model Name	A3131
Temperature	24.3° C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	- Value Type	
4804.000	45.36	0.08	45.44	74	-28.56	peak	
4804.000	36.14	0.08	36.22	54	-17.78	AVG	
7206.000	41.05	2.21	43.26	74	-30.74	peak	
7206.000	32.49	2.21	34.7	54	-19.3	AVG	

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Wireless Speaker	Model Name	A3131
Temperature	24.3° C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type	
4804.000	46.25	0.08	46.33	74	-27.67	peak	
4804.000	35.47	0.08	35.55	54	-18.45	AVG	
7206.000	40.13	2.21	42.34	74	-31.66	peak	
7206.000	31.59	2.21	33.8	54	-20.2	AVG	

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Report No.: AGC01110230761FR01 Page 47 of 61

EUT	Wireless Speaker	Model Name	A3131
Temperature	24.3° C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	- Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
4880.000	46.28	0.14	46.42	74	-27.58	peak			
4880.000	36.27	0.14	36.41	54	-17.59	AVG			
7320.000	40.14	2.36	42.5	74	-31.5	peak			
7320.000	31.58	2.36	33.94	54	-20.06	AVG			
Remark:									
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

			T
EUT	Wireless Speaker	Model Name	A3131
Temperature	24.3° C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	46.29	0.14	46.43	74	-27.57	peak
4880.000	34.28	0.14	34.42	54	-19.58	AVG
7320.000	41.05	2.36	43.41	74	-30.59	peak
7320.000	32.48	2.36	34.84	54	-19.16	AVG

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Page 48 of 61

EUT	Wireless Speaker	Model Name	A3131
Temperature	24.3° C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4960.000	45.25	0.22	45.47	74	-28.53	peak	
4960.000	35.74	0.22	35.96	54	-18.04	AVG	
7440.000	38.64	2.64	41.28	74	-32.72	peak	
7440.000	29.64	2.64	32.28	54	-21.72	AVG	
Remark:							
Factor = Anter	na Factor + Cabl	actor = Δntenna Factor + Cable Loss – Pre-amplifier					

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Wireless Speaker	Model Name	A3131
Temperature	24.3° C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	45.26	0.22	45.48	74	-28.52	peak
4960.000	36.21	0.22	36.43	54	-17.57	AVG
7440.000	41.05	2.64	43.69	74	-30.31	peak
7440.000	30.58	2.64	33.22	54	-20.78	AVG
Remark:	Remark:					
Factor = Anter	Factor = Antenna Factor + Cable Loss – Pre-amplifier.					


RESULT: PASS

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been tested. The GFSK 1Mbps is the worst case and recorded in the report.







Test result for band edge emission at restricted bands

EUT	Wireless Speaker	Model Name	A3131
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Test Graph for Peak Measurement








RESULT: PASS







EUT	Wireless Speaker	Model Name	A3131
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical








RESULT: PASS







EUT	Wireless Speaker	Model Name	A3131
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal








RESULT: PASS






EUT Model Name Wireless Speaker A3131 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 3 **Antenna** Vertical


Test Graph for Peak Measurement








RESULT: PASS






EUT	Wireless Speaker	Model Name	A3131
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Horizontal








RESULT: PASS







EUT	Wireless Speaker	Model Name	A3131
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Vertical








RESULT: PASS







EUT	Wireless Speaker	Model Name	A3131
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Horizontal








RESULT: PASS






EUT	Wireless Speaker	Model Name	A3131
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Vertical







RESULT: PASS

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



Page 57 of 61

13. LINE CONDUCTED EMISSION TEST


13.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF Line Voltage				
Frequency	Q.P.(dBuV)	Average(dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Page 58 of 61

13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT: "agc_fin"


2023/9/4 16: Frequency MHz	Level	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.258000	22.90	6.1	62	38.6	QP	L1
0.750000	21.20	6.2	56	34.8	QP	L1
0.934000	21.30	6.2	56	34.7	QP	L1
1.306000	22.20	6.2	56	33.8	QP	L1
1.610000	20.50	6.2	56	35.5	QP	L1
1.666000	19.80	6.2	56	36.2	QP	L1

MEASUREMENT RESULT: "agc_fin2"

2023/9/4 16:40						
Frequency MHz	Level dBµV	Transd dB		Margin dB	Detector	Line
0.362000	16.60	6.1	49	32.1	AV	L1
0.602000	17.00	6.2	46	29.0	AV	L1
1.258000	17.50	6.2	46	28.5	AV	L1
3.602000	10.50	6.3	46	35.5	AV	L1
12.030000	16.50	6.8	50	33.5	AV	L1
13.786000	16.70	6.8	50	33.3	AV	L1



Line Conducted Emission Test Line 2-N



MEASUREMENT RESULT: "agc_fin"

2023/9/4 16:4 Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.586000	21.10	6.2	56	34.9	QP	N
0.778000	28.10	6.2	56	27.9	QP	N
0.854000	22.10	6.2	56	33.9	QP	N
0.918000	21.50	6.2	56	34.5	QP	N
1.254000	23.40	6.2	56	32.6	QP	N
1.430000	21.60	6.2	56	34.4	QP	N

MEASUREMENT RESULT: "agc fin2"

2023/9/4 Freque			Transd dB	Limit dBµV	Margin dB	Detector	Line
0.358		16.90 21.20	6.1 6.2	49 46	31.9 24.8		N N
1.298	000	16.70	6.2	46	29.3	AV	N
3.138	000	13.10	6.3	46	32.9	AV	N
12.266		16.30	6.8	50		AV	N
13.578	000	17.50	6.8	50	32.5	AV	N

RESULT: PASS

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.



Page 61 of 61

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC01110230761AP01

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC01110230761AP02

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.