

FCC Test Report

Report No.: AGC01110230744FE02

FCC ID : 2AOKB-A3136

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: soundcore Glow Mini

BRAND NAME: soundcore

MODEL NAME : A3136

APPLICANT: Anker Innovations Limited

DATE OF ISSUE : Jul. 25, 2023

STANDARD(S) : FCC Part 15.247

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 60

REPORT REVISE RECORD

| Report Version | Revise Time | Issued Date | Valid Version | Notes |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0 | / | Jul. 25, 2023 | Valid | Initial Release |





TABLE OF CONTENTS

| 1. VERIFICATION OF COMPLIANCE | 5 |
|---|----|
| 2. GENERAL INFORMATION | 6 |
| 2.1. PRODUCT DESCRIPTION | 6 |
| 2.2. TABLE OF CARRIER FREQUENCYS | 6 |
| 2.3. RELATED SUBMITTAL(S)/GRANT(S) | 7 |
| 2.4. TEST METHODOLOGY | 7 |
| 2.5. SPECIAL ACCESSORIES | |
| 2.6. EQUIPMENT MODIFICATIONS | |
| 2.7. ANTENNA REQUIREMENT | 7 |
| 3. MEASUREMENT UNCERTAINTY | 8 |
| 4. DESCRIPTION OF TEST MODES | 9 |
| 5. SYSTEM TEST CONFIGURATION | 10 |
| 5.1. CONFIGURATION OF TESTED SYSTEM | 10 |
| 5.2. EQUIPMENT USED IN TESTED SYSTEM | 10 |
| 5.3. SUMMARY OF TEST RESULTS | 10 |
| 6. TEST FACILITY | 11 |
| 7. PEAK OUTPUT POWER | 12 |
| 7.1. MEASUREMENT PROCEDURE | 12 |
| 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 12 |
| 7.3. LIMITS AND MEASUREMENT RESULT | 13 |
| 8. BANDWIDTH | 17 |
| 8.1. MEASUREMENT PROCEDURE | 17 |
| 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 17 |
| 8.3. LIMITS AND MEASUREMENT RESULTS | 17 |
| 9. CONDUCTED SPURIOUS EMISSION | 24 |
| 9.1. MEASUREMENT PROCEDURE | 24 |
| 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 24 |
| 9.3. MEASUREMENT EQUIPMENT USED | |
| 9.4. LIMITS AND MEASUREMENT RESULT | 24 |
| 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY | 36 |



Report No.: AGC01110230744FE02 Page 4 of 60

11.1. MEASUREMENT PROCEDURE40 11.2. TEST SETUP........41 11.3. LIMITS AND MEASUREMENT RESULT42 11.4. TEST RESULT42 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST56 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST........57 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.......57 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST.......57 APPENDIX I: PHOTOGRAPHS OF TEST SETUP60



Page 5 of 60

1. VERIFICATION OF COMPLIANCE

| Applicant | Anker Innovations Limited | | |
|---|---------------------------|--|--|
| Address Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kow Hongkong | | | |
| Manufacturer Anker Innovations Limited | | | |
| Address Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kov Hongkong | | | |
| Factory | N/A | | |
| Address | N/A | | |
| Product Designation | soundcore Glow Mini | | |
| Brand Name soundcore | | | |
| Test Model A3136 | | | |
| Date of receipt of test item | Jul. 14, 2023 | | |
| Date of test Jul. 17, 2023 to Jul. 25, 2023 | | | |
| Deviation No any deviation from the test method | | | |
| Condition of Test Sample | Normal | | |
| Test Result Pass | | | |
| Report Template | AGCRT-US-BLE/RF | | |

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

| Prepared By | Cool cheng | |
|-------------|-----------------------------------|---------------|
| | Cool Cheng (Project Engineer) | Jul. 25, 2023 |
| Reviewed By | Calin Lin | |
| , | Calvin Liu (Reviewer) | Jul. 25, 2023 |
| Approved By | Max Zhang | |
| | Max Zhang (Authorized Officer) | Jul. 25, 2023 |



Page 6 of 60

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as a "soundcore Glow Mini". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

| Operation Frequency | 2.402 GHz to 2.480GHz | | |
|---------------------|---|--|--|
| RF Output Power | GFSK 1Mbps: 6.870dBm (Max) GFSK 2Mbps: 6.663dBm (Max) | | |
| Bluetooth Version | V5.3 | | |
| Modulation | BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE □GFSK 1Mbps □GFSK 2Mbps | | |
| Number of channels | 40 Channels | | |
| Antenna Designation | PCB Antenna (Comply with requirements of the FCC part 15.203) | | |
| Antenna Gain | 0.6dBi | | |
| Hardware Version | V3.0 | | |
| Software Version | V1.3 | | |
| Power Supply | DC 3.7V by battery or 5V by adapter | | |

2.2. TABLE OF CARRIER FREQUENCYS

| Frequency Band | Channel Number | Frequency | | |
|----------------|----------------|-----------|--|--|
| | 0 | 2402 MHz | | |
| | 1 | 2404 MHz | | |
| 2400~2483.5MHz | : | : | | |
| | 38 | 2478 MHz | | |
| | 39 | 2480 MHz | | |



Page 7 of 60

2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2AOKB-A3136** filing to comply with the FCC Part 15.247 requirements.

2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.




Page 8 of 60

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

| Item | Measurement Uncertainty | | |
|---|----------------------------|--|--|
| Uncertainty of Conducted Emission for AC Port | $U_c = \pm 3.1 \text{ dB}$ | | |
| Uncertainty of Radiated Emission below 1GHz | $U_c = \pm 4.0 \text{ dB}$ | | |
| Uncertainty of Radiated Emission above 1GHz | $U_c = \pm 4.8 \text{ dB}$ | | |
| Uncertainty of total RF power, conducted | $U_c = \pm 0.8 \text{ dB}$ | | |
| Uncertainty of RF power density, conducted | $U_c = \pm 2.6 \text{ dB}$ | | |
| Uncertainty of spurious emissions, conducted | $U_c = \pm 2.7 \%$ | | |
| Uncertainty of Occupied Channel Bandwidth | U _c = ±2 % | | |






4. DESCRIPTION OF TEST MODES

| NO. | TEST MODE DESCRIPTION |
|-----|----------------------------------|
| 1 | Low channel TX for GFSK 1Mbps |
| 2 | Middle channel TX for GFSK 1Mbps |
| 3 | High channel TX for GFSK 1Mbps |
| 4 | Low channel TX for GFSK 2Mbps |
| 5 | Middle channel TX for GFSK 2Mbps |
| 6 | High channel TX for GFSK 2Mbps |

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting







Page 10 of 60

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:





5.2. EQUIPMENT USED IN TESTED SYSTEM

| Item | Equipment | Model No. | ID or Specification | Remark |
|------|---------------------|--------------|---------------------|--------|
| 1 | soundcore Glow Mini | A3136 | 2AOKB-A3136 | EUT |
| 2 | Control Box | N/A | USB-TTL | AE |
| 3 | Huawei adapter | HW-200325CP0 | N/A | AE |

5.3. SUMMARY OF TEST RESULTS

| FCC RULES | DESCRIPTION OF TEST | RESULT |
|---------------|--|-----------|
| 15.247 (b)(3) | Peak Output Power | Compliant |
| 15.247 (a)(2) | 6 dB Bandwidth | Compliant |
| 15.247 (d) | Conducted Spurious Emission | Compliant |
| 15.247 (e) | Maximum Conducted Output Power Density | Compliant |
| 15.209 | Radiated Emission | Compliant |
| 15.207 | Conducted Emission | Compliant |



Page 11 of 60

6. TEST FACILITY

| Test Site | Attestation of Global Compliance (Shenzhen) Co., Ltd |
|--|--|
| Location 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community Fuhai Street, Bao'an District, Shenzhen, Guangdong, China | |
| Designation Number | CN1259 |
| FCC Test Firm Registration Number | 975832 |
| A2LA Cert. No. | 5054.02 |
| Description | Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA |

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Due | |
|---------------|--------------|------------------|--------|---------------|---------------|--|
| TEST RECEIVER | R&S | ESPI | 101206 | Jun. 03, 2023 | Jun. 02, 2024 | |
| LISN | R&S | ESH2-Z5 | 100086 | Jun. 03, 2023 | Jun. 02, 2024 | |
| Test software | R&S | ES-K1(Ver.V1.71) | N/A | N/A | N/A | |

TEST EQUIPMENT OF RADIATED EMISSION TEST

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Due |
|--------------------------------------|----------------|----------------------|------------------|---------------|---------------|
| TEST RECEIVER | R&S | ESCI | 10096 | Feb. 18, 2023 | Feb. 17, 2024 |
| EXA Signal Analyzer | Aglient | N9010A | MY53470504 | Aug. 04, 2022 | Aug. 03, 2023 |
| 2.4GHz Filter | EM Electronics | N/A | N/A | Mar. 18, 2022 | Mar. 19, 2024 |
| Attenuator | ZHINAN | E-002 | N/A | Aug. 04, 2022 | Aug. 03, 2024 |
| Horn antenna | SCHWARZBECK | BBHA 9170 | #768 | Oct. 31, 2021 | Oct. 30, 2023 |
| Active loop antenna (9K-30MHz) | ZHINAN | ZN30900C | 18051 | Mar. 12, 2022 | Mar. 11, 2024 |
| Double-Ridged Waveguide Horn | ETS LINDGREN | 3117 | 00034609 | Apr. 23, 2023 | Apr. 22, 2024 |
| Broadband Preamplifier | ETS LINDGREN | 3117PA | 00225134 | Sep. 01, 2022 | Sep. 02, 2024 |
| ANTENNA | SCHWARZBECK | VULB9168 | VULB9168-49 4 | Jan. 05, 2023 | Jan. 04, 2025 |
| Test software | Tonscend | JS32-RE (Ver.2.5) | N/A | N/A | N/A |



Page 12 of 60

7. PEAK OUTPUT POWER


7.1. MEASUREMENT PROCEDURE


For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW ≥ DTS bandwidth
- 3. VBW≥3*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP








7.3. LIMITS AND MEASUREMENT RESULT

| 7.5. LIMITS AND MEASUREMENT RESULT | | | | | |
|-------------------------------------|-----------------------|---------------------|-----------------|--------------|--|
| Test Data of Conducted Output Power | | | | | |
| Test Mode | Test Channel (MHz) | Peak Power (dBm) | Limits (dBm) | Pass or Fail | |
| | 2402 | 6.500 | ≤30 | Pass | |
| GFSK 1M | 2440 | 6.642 | ≤30 | Pass | |
| | 2480 | 6.870 | ≤30 | Pass | |
| GFSK 2M | 2402 | 6.278 | ≤30 | Pass | |
| | 2440 | 6.455 | ≤30 | Pass | |
| | 2480 | 6.663 | ≤30 | Pass | |

Test Graphs of Conducted Output Power



















Center Freq 2.44000000 GHz

Start Freq 2.437500000 GHz

Stop Freq 2.442500000 GHz

CF Step 500.000 kHz
Auto Man


Freq Offset 0 Hz

Center 2.440000 GHz


#WBW 5.0 MHz

Sweep 1.066 ms (1000 pts)

Test_Graph_LE2M_ANT1_2440_2Mbps_Peak Power









Page 17 of 60

8. BANDWIDTH

8.1. MEASUREMENT PROCEDURE

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW ≥ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
 The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
 bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.


Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.


8.3. LIMITS AND MEASUREMENT RESULTS

| Test Data of Occupied Bandwidth and DTS Bandwidth | | | | | |
|---|-----------------------|---------------------------------|-------------------------|-----------------|--------------|
| Test Mode | Test Channel (MHz) | 99% Occupied Bandwidth (MHz) | -6dB Bandwidth (MHz) | Limits (MHz) | Pass or Fail |
| GFSK 1M | 2402 | 1.025 | 0.698 | ≥0.5 | Pass |
| | 2440 | 1.025 | 0.694 | ≥0.5 | Pass |
| | 2480 | 1.026 | 0.697 | ≥0.5 | Pass |
| GFSK 2M | 2402 | 1.964 | 1.169 | ≥0.5 | Pass |
| | 2440 | 1.962 | 1.167 | ≥0.5 | Pass |
| | 2480 | 1.962 | 1.167 | ≥0.5 | Pass |































Test Graphs of DTS Bandwidth



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test_Graph_LE1M_ANT1_2440_1Mbps_DTSBW

Web: http://www.agccert.com/



Freq Offset





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE2M_ANT1_2402_2Mbps_DTSBW

OBW Power

x dB

99.00 %


-6.00 dB

Transmit Freg Error


x dB Bandwidth


2.464 kHz

1.169 MHz









Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 24 of 60

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 7.2.

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

9.4. LIMITS AND MEASUREMENT RESULT

| LIMITS AND MEASUREMENT RESULT | | | | | |
|--|--|----------|--|--|--|
| And Park In Live | Measurement Result | | | | |
| Applicable Limits | Test Data | Criteria | | | |
| In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. | At least -20dBc than the reference level | PASS | | | |






Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE1M_ANT1_2402_1Mbps_Lower Band Emissions





























CF Step 500.000 kHz


Freq Offset

Man

Auto

Span 5.000 MHz Sweep 2.000 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test_Graph_LE2M_ANT1_2402_2Mbps_Reference Level

#VBW 300 kHz


Center 2.402000 GHz #Res BW 100 kHz













































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands





Freq Offset





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE2M_ANT1_2480_2Mbps_Higher Band Edge Emissions



Page 36 of 60

10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1. MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


Refer to Section 7.2.

10.3. MEASUREMENT EQUIPMENT USED

Refer to Section 6.

10.4. LIMITS AND MEASUREMENT RESULT

| Test Data of Conducted Output Power Spectral Density | | | | | |
|--|-----------------------|-----------------------------|---------------------|--------------|--|
| Test Mode | Test Channel (MHz) | Power density (dBm/3kHz) | Limit (dBm/3kHz) | Pass or Fail | |
| | 2402 | -8.535 | ≤8 | Pass | |
| GFSK 1M | 2440 | -8.443 | ≪8 | Pass | |
| | 2480 | -8.295 | ≤8 | Pass | |
| | 2402 | -12.586 | ≤8 | Pass | |
| GFSK 2M | 2440 | -12.356 | ≤8 | Pass | |
| | 2480 | -11.990 | ≤8 | Pass | |





Test Graphs of Conducted Output Power Spectral Density 01:12:01 AM Jul 20, 2023 Avg Type: Log-Pwr Avg|Hold: 100/100 Frequency RACE 1 2 3 4
TYPE MWWW
DET PNNN Center Freq 2.402000000 GHz Trig: Free Run #Atten: 30 dB PNO: Wide IFGain:Low **Auto Tune** Mkr1 2.402 001 6 GHz -8.535 dBm 10 dB/div Ref 20.00 dBm Center Freq 2.402000000 GHz Start Freq 2.401476500 GHz mondifferential Stop Freq 2.402523500 GHz CF Step 104.700 kHz Auto Man Freq Offset 0 Hz Center 2.4020000 GHz #Res BW 3.0 kHz Span 1.047 MHz Sweep 110.4 ms (1000 pts) #VBW 10 kHz Test_Graph_LE1M_ANT1_2402_1Mbps_PSD Center Freq 2.440000000 GHz Avg Type: Log-Pwr Avg|Hold: 100/100 Frequency Trig: Free Run #Atten: 30 dB PNO: Wide ↔ IFGain:Low **Auto Tune** Mkr1 2.440 005 7 GHz -8.443 dBm Ref 20.00 dBm 10 dB/div Center Frea 2.440000000 GHz Start Freq 2.439479500 GHz My how my happy Stop Freq 2 440520500 GHz CF Step 104.100 kHz <u>Auto</u> Freq Offset 0 Hz


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE1M_ANT1_2440_1Mbps_PSD


#VBW 10 kHz

Span 1.041 MHz Sweep 109.8 ms (1000 pts)

Center 2.4400000 GHz #Res BW 3.0 kHz









Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE2M_ANT1_2402_2Mbps_PSD

#VBW 10 kHz







Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE2M_ANT1_2480_2Mbps_PSD

#VBW 10 kHz

Span 1.751 MHz Sweep 184.6 ms (1000 pts)

Center 2.4800000 GHz #Res BW 3.0 kHz




Page 40 of 60

11. RADIATED EMISSION

11.1. MEASUREMENT PROCEDURE


- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.






11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 42 of 60

11.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|----------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT

Radiated emission below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



Page 43 of 60

Radiated emission from 30MHz to 1000MHz

| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 3 | Antenna | Horizontal |




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure- ment | Limit | Over | |
|-----|-----|----------|------------------|-------------------|------------------|-------|--------|----------|
| | | MHz | dBuV | dB | dBuV/m | dB/m | dB | Detector |
| 1 | | 50.2324 | 7.38 | 13.18 | 20.56 | 40.00 | -19.44 | peak |
| 2 | | 122.4040 | 6.82 | 16.26 | 23.08 | 43.50 | -20.42 | peak |
| 3 | | 452.7197 | 6.53 | 24.65 | 31.18 | 46.00 | -14.82 | peak |
| 4 | | 520.8882 | 6.92 | 25.14 | 32.06 | 46.00 | -13.94 | peak |
| 5 | | 614.2142 | 6.96 | 25.17 | 32.13 | 46.00 | -13.87 | peak |
| 6 | * | 900.1474 | 5.77 | 31.78 | 37.55 | 46.00 | -8.45 | peak |

RESULT: PASS



Report No.: AGC01110230744FE02 Page 44 of 60

| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 3 | Antenna | Vertical |



| No. | Mk | . Freq. | Reading Level | Correct Factor | Measure- ment | Limit | Over | |
|-----|----|----------|------------------|-------------------|------------------|-------|--------|----------|
| | | MHz | dBuV | dB | dBuV/m | dB/m | dB | Detector |
| 1 | | 40.9881 | 6.42 | 16.91 | 23.33 | 40.00 | -16.67 | peak |
| 2 | | 61.7781 | 6.79 | 17.08 | 23.87 | 40.00 | -16.13 | peak |
| 3 | | 153.7384 | 7.45 | 18.20 | 25.65 | 43.50 | -17.85 | peak |
| 4 | | 457.5072 | 6.70 | 25.31 | 32.01 | 46.00 | -13.99 | peak |
| 5 | | 721.7259 | 6.11 | 28.64 | 34.75 | 46.00 | -11.25 | peak |
| 6 | * | 945.4398 | 6.72 | 30.78 | 37.50 | 46.00 | -8.50 | peak |

RESULT: PASS Note:

- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. All test modes had been tested. The mode 3 is the worst case and recorded in the report.



Page 45 of 60

Radiated emission above 1GHz

| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 1 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4804.000 | 46.35 | 0.08 | 46.43 | 74 | -27.57 | peak |
| 4804.000 | 37.14 | 0.08 | 37.22 | 54 | -16.78 | AVG |
| 7206.000 | 41.05 | 2.21 | 43.26 | 74 | -30.74 | peak |
| 7206.000 | 32.49 | 2.21 | 34.7 | 54 | -19.3 | AVG |
| | | | | | | |
| | | | | | | |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 1 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4804.000 | 46.28 | 0.08 | 46.36 | 74 | -27.64 | peak |
| 4804.000 | 36.27 | 0.08 | 36.35 | 54 | -17.65 | AVG |
| 7206.000 | 41.05 | 2.21 | 43.26 | 74 | -30.74 | peak |
| 7206.000 | 31.59 | 2.21 | 33.8 | 54 | -20.2 | AVG |
| | | | | | | |
| | | | | | | |

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Page 46 of 60

| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 2 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type | | |
|----------------|------------------|---|----------------|----------|--------|------------|--|--|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type | | |
| 4880.000 | 46.38 | 0.14 | 46.52 | 74 | -27.48 | peak | | |
| 4880.000 | 37.45 | 0.14 | 37.59 | 54 | -16.41 | AVG | | |
| 7320.000 | 40.15 | 2.36 | 42.51 | 74 | -31.49 | peak | | |
| 7320.000 | 31.58 | 2.36 | 33.94 | 54 | -20.06 | AVG | | |
| | | | | | | | | |
| Remark: | | | | | | | | |
| Factor = Anter | na Factor + Cabl | actor = Antenna Factor + Cable Loss – Pre-amplifier | | | | | | |

<u> Factor = Antenna Factor + Cable Loss — Pre-amplifier.</u>

| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 2 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4880.000 | 45.37 | 0.14 | 45.51 | 74 | -28.49 | peak |
| 4880.000 | 36.05 | 0.14 | 36.19 | 54 | -17.81 | AVG |
| 7320.000 | 40.27 | 2.36 | 42.63 | 74 | -31.37 | peak |
| 7320.000 | 31.59 | 2.36 | 33.95 | 54 | -20.05 | AVG |
| | | | | | | |
| | | · | | | | |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Page 47 of 60

| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 3 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | - Value Type | | | |
|--|---------------------|--------|----------------|----------|--------|--------------|--|--|--|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type | | | |
| 4960.000 | 45.39 | 0.22 | 45.61 | 74 | -28.39 | peak | | | |
| 4960.000 | 36.27 | 0.22 | 36.49 | 54 | -17.51 | AVG | | | |
| 7440.000 | 40.18 | 2.64 | 42.82 | 74 | -31.18 | peak | | | |
| 7440.000 | 7440.000 30.57 2.64 | | 2.64 33.21 54 | | -20.79 | AVG | | | |
| | | | | | | | | | |
| Remark: | | | | | | | | | |
| Factor = Antenna Factor + Cable Loss - Pre-amplifier | | | | | | | | | |

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 3 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type | | |
|----------------|-------------------|---------------|----------------|----------|--------|------------|--|--|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type | | |
| 4960.000 | 45.28 | 0.22 | 45.5 | 74 | -28.5 | peak | | |
| 4960.000 | 35.17 | 0.22 | 35.39 | 54 | -18.61 | AVG | | |
| 7440.000 | 40.29 | 2.64 | 42.93 | 74 | -31.07 | peak | | |
| 7440.000 | 39.67 | 2.64 | 42.31 | 54 | -11.69 | AVG | | |
| | | | | | | | | |
| Remark: | | | | | | | | |
| =actor = Anter | nna Factor + Cabl | e Loss – Pre- | amplifier. | | | | | |


RESULT: PASS

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been tested. The GFSK 1Mbps is the worst case and recorded in the report.







Test result for band edge emission at restricted bands


| EUT | soundcore Glow Mini | Model Name | A3136 |
|-------------|---------------------|-------------------|----------------|
| Temperature | 25° C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 1 | Antenna | Horizontal |

Test Graph for Peak Measurement





RESULT: PASS







EUT soundcore Glow Mini **Model Name** A3136 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 1 **Antenna** Vertical

Test Graph for Peak Measurement






RESULT: PASS







EUT soundcore Glow Mini **Model Name** A3136 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 3 **Antenna** Horizontal

Test Graph for Peak Measurement






RESULT: PASS







EUT soundcore Glow Mini **Model Name** A3136 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 3 **Antenna** Vertical

Test Graph for Peak Measurement





RESULT: PASS







EUT soundcore Glow Mini **Model Name** A3136 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 4 **Antenna** Horizontal

Test Graph for Peak Measurement





RESULT: PASS







EUT soundcore Glow Mini **Model Name** A3136 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 4 **Antenna** Vertical

Test Graph for Peak Measurement





RESULT: PASS







EUT soundcore Glow Mini **Model Name** A3136 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 6 **Antenna** Horizontal

Test Graph for Peak Measurement






RESULT: PASS






EUT soundcore Glow Mini **Model Name** A3136 25° C **Temperature Relative Humidity** 55.4% 960hPa Normal Voltage **Pressure Test Voltage Test Mode** Mode 6 **Antenna** Vertical

Test Graph for Peak Measurement





RESULT: PASS

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



Page 56 of 60

12. LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Francisco | Maximum RF Line Voltage | | | | |
|---------------|-------------------------|----------------|--|--|--|
| Frequency | Q.P.(dBuV) | Average(dBuV) | | | |
| 150kHz~500kHz | 66-56 | 56-46 | | | |
| 500kHz~5MHz | 56 | 46 | | | |
| 5MHz~30MHz | 60 | 50 | | | |

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Page 57 of 60

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT: "agc_fin"


| 2 | 023/7/20 18: | 39 | | | | | |
|---|------------------|---------------|--------------|---------------|--------------|----------|------|
| | Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| | 0.150000 | 49.20 | 6.1 | 66 | 16.8 | QP | L1 |
| | 0.174000 | 45.60 | 6.1 | 65 | 19.2 | QP | L1 |
| | 0.198000 | 42.00 | 6.1 | 64 | 21.7 | QP | L1 |
| | 0.226000 | 36.90 | 6.1 | 63 | 25.7 | QP | L1 |
| | 0.250000 | 36.10 | 6.1 | 62 | 25.7 | QP | L1 |
| | 0.274000 | 34.90 | 6.1 | 61 | 26.1 | QP | L1 |

MEASUREMENT RESULT: "agc fin2"

| 2023/7/20 18: | 39 | | | | | |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| 0.150000 | 34.40 | 6.1 | 56 | 21.6 | AV | L1 |
| 0.174000 | 32.10 | 6.1 | 55 | 22.7 | AV | L1 |
| 0.546000 | 25.10 | 6.2 | 46 | 20.9 | AV | L1 |
| 3.426000 | 23.00 | 6.3 | 46 | 23.0 | AV | L1 |
| 3.450000 | 23.20 | 6.3 | 46 | 22.8 | AV | L1 |
| 3.474000 | 23.30 | 6.3 | 46 | 22.7 | AV | L1 |



Line Conducted Emission Test Line 2-N



MEASUREMENT RESULT: "agc_fin"

| 202 | 23/7/20 18: | 43 | | | | | |
|-----|------------------|---------------|--------------|---------------|--------------|----------|------|
| | Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| | 0.150000 | 49.10 | 6.1 | 66 | 16.9 | QP | N |
| | 0.174000 | 45.50 | 6.1 | 65 | 19.3 | QP | N |
| | 0.198000 | 41.80 | 6.1 | 64 | 21.9 | QP | N |
| | 0.222000 | 38.20 | 6.1 | 63 | 24.5 | QP | N |
| | 0.250000 | 35.80 | 6.1 | 62 | 26.0 | QP | N |
| | 1.366000 | 23.60 | 6.2 | 56 | 32.4 | QP | N |

MEASUREMENT RESULT: "agc fin2"

| 2023/7/20 18 | 8:43 | | | | | |
|------------------|-------|--------------|---------------|--------------|----------|------|
| Frequency MHz | | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| 0.150000 | 34.60 | 6.1 | 56 | 21.4 | AV | N |
| 0.174000 | 32.40 | 6.1 | 55 | 22.4 | AV | N |
| 0.546000 | 26.20 | 6.2 | 46 | 19.8 | AV | N |
| 3.402000 | 22.20 | 6.3 | 46 | 23.8 | AV | N |
| 3.426000 | 22.60 | 6.3 | 46 | 23.4 | AV | N |
| 4.046000 | 22.10 | 6.3 | 46 | 23.9 | AV | N |

RESULT: PASS

Note: All the test modes had been tested, the mode 3 was the worst case. Only the data of the worst case would be record in this test report.



Page 60 of 60

APPENDIX I: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC01110230744AP02

APPENDIX II: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC01110230744AP03

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.