

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Soundcore Mega, Soundcore Trance
Model Name	A3392, A3393
FCC ID	2AOKB-A3392

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

BR/EDR:

$$P_{t1}=6.448\text{dBm}=4.4\text{mW}$$

The value of the Maximum output power P_{t1} is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR}=(4.4\text{mW}/5\text{mm}) \cdot [\sqrt{2.480(\text{GHz})}]=1.38<3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BLE:

$$P_{t2}=7.699\text{dBm}=5.9\text{mW}$$

The value of the Maximum output power P_{t2} is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR}=(5.9\text{mW}/5\text{mm}) \cdot [\sqrt{2.480(\text{GHz})}]=1.86<3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.