

# **FCC Test Report**

Report No.: AGC01110231241FR01A

**FCC ID** : 2AOKB-A6611L

**APPLICATION PURPOSE**: Class II Permissive Change

**PRODUCT DESIGNATION**: Wireless Headphone

**BRAND NAME** : soundcore

MODEL NAME : A6611L

**APPLICANT**: Anker Innovations Limited

**DATE OF ISSUE** : Jun. 18, 2024

**STANDARD(S)** : FCC Part 15 Subpart C §15.247

**REPORT VERSION**: V1.0

Attestation Of Global Conciliance (Shenzhen) Co., Ltd



Page 2 of 25

# Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jun. 18, 2024	Valid	Initial Release

Note: The original test report AGC01110231241FR01 (dated Feb. 02, 2024 and tested from Jan. 04, 2024 – Feb. 02, 2024) was modified on Jun. 18, 2024, including the following changes and additions:

- Added the battery of earphone and charging case, the batteries are the same except for the manufacturer and model, see below for details:

## Original:

Original.			
	Model: ZWD1040S1H		
Battery Information (Earphone)	Rated Voltage & Cap.: 3.85V 38mAh		
	Manufacturer name: Guangdong Mic-power New Energy Co., Ltd.		
Dottom / Information	Model: M652040		
Battery Information	Rated Voltage & Cap.: 3.72V 580mAh		
(Charging case)	Manufacturer name: Guangdong Mic-power New Energy Co., Ltd.		

## Updated:

	opaatoa.	
		Model: VDL 1040W7
Battery Information (Earpho	Battery Information (Earphone)	Rated Voltage & Cap.: 3.85V 38mAh
		Chongqing VDL Electronics Co., LTD.
	Dattery Information	Model: 672040PN3A
	Battery Information	Rated Voltage & Cap.: 3.72V 580mAh
	(Charging case)	Chongqing VDL Electronics Co., LTD.

<sup>-</sup>Changed the Applicant address;

For the above described change(s) the following tests was considered to be necessary:

Clause	Testing
§15.209	Radiated Emission

<sup>-</sup>Changed the Manufacturer address;



## **Table of Contents**

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Test Frequency List	5
2.3 Related Submittal(S) / Grant (S)	6
2.4 Test Methodology	6
2.5 Special Accessories	6
2.6 Equipment Modifications	6
2.7 Antenna Requirement	6
3. Test Environment	7
3.1 Address of the Test Laboratory	7
3.2 Test Facility	7
3.3 Environmental Conditions	8
3.4 Measurement Uncertainty	8
3.5 List of Equipment Use	9
4.System Test Configuration	10
4.1 EUT Configuration	10
4.2 EUT Exercise	10
4.3 Configuration of Tested System	10
4.4 Equipment Used In Tested System	10
4.5 Summary of Test Results	11
5. Description of Test Modes	12
6. Radiated Spurious Emission	13
6.1 Measurement Limit	13
6.2 Measurement Procedure	13
6.3 Measurement Setup (Block Diagram of Configuration)	16
6.4 Measurement Result	17
Appendix I: Photographs of Test Setup	25
Appendix II: Photographs of Test EUT	25



## 1. General Information

Applicant Anker Innovations Limited  Address Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong  Manufacturer Anker Innovations Limited  Address Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong  Factory N/A  Address N/A  Product Designation Wireless Headphone  Brand Name soundcore  Test Model A6611L  Series Model(s) N/A  Difference Description N/A  Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 –Jun. 18, 2024  Deviation from Standard No any deviation from the test method  Condition of Test Sample Normal  Test Result Pass  Test Report Form No AGCER-FCC-BLE-V1		
Manufacturer Anker Innovations Limited  Address Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong  Factory N/A  Address N/A  Product Designation Wireless Headphone Brand Name soundcore  Test Model A6611L  Series Model(s) N/A  Difference Description N/A  Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 –Jun. 18, 2024  Deviation from Standard Condition of Test Sample Normal  Test Result Pass	Applicant	Anker Innovations Limited
Address Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong Factory N/A Address N/A Product Designation Wireless Headphone Brand Name soundcore Test Model A6611L Series Model(s) N/A Difference Description N/A Date of receipt of test item Jun. 04, 2024 Date of Test Jun. 04, 2024 – Jun. 18, 2024 Deviation from Standard No any deviation from the test method Condition of Test Sample Normal Test Result Pass	Address	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Factory N/A  Address N/A  Product Designation Wireless Headphone  Brand Name soundcore  Test Model A6611L  Series Model(s) N/A  Difference Description N/A  Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 – Jun. 18, 2024  Deviation from Standard Normal  Test Result Pass	Manufacturer	Anker Innovations Limited
Address N/A  Product Designation Wireless Headphone  Brand Name soundcore  Test Model A6611L  Series Model(s) N/A  Difference Description N/A  Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 – Jun. 18, 2024  Deviation from Standard No any deviation from the test method  Condition of Test Sample Normal  Test Result Pass	Address	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Product Designation Wireless Headphone  Brand Name soundcore  Test Model A6611L  Series Model(s) N/A  Difference Description N/A  Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 – Jun. 18, 2024  Deviation from Standard No any deviation from the test method  Condition of Test Sample Normal  Test Result Pass	Factory	N/A
Brand Name soundcore  Test Model A6611L  Series Model(s) N/A  Difference Description N/A  Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 –Jun. 18, 2024  Deviation from Standard No any deviation from the test method  Condition of Test Sample Normal  Test Result Pass	Address	N/A
Test Model A6611L  Series Model(s) N/A  Difference Description N/A  Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 – Jun. 18, 2024  Deviation from Standard No any deviation from the test method  Condition of Test Sample Normal  Test Result Pass	Product Designation	Wireless Headphone
Series Model(s)  N/A  Difference Description  N/A  Date of receipt of test item  Jun. 04, 2024  Date of Test  Jun. 04, 2024 – Jun. 18, 2024  Deviation from Standard  No any deviation from the test method  Condition of Test Sample  Normal  Test Result  Pass	Brand Name	soundcore
Difference Description N/A  Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 – Jun. 18, 2024  Deviation from Standard No any deviation from the test method  Condition of Test Sample Normal  Test Result Pass	Test Model	A6611L
Date of receipt of test item Jun. 04, 2024  Date of Test Jun. 04, 2024 – Jun. 18, 2024  Deviation from Standard No any deviation from the test method  Condition of Test Sample Normal  Test Result Pass	Series Model(s)	N/A
Date of Test  Jun. 04, 2024 – Jun. 18, 2024  Deviation from Standard  No any deviation from the test method  Condition of Test Sample  Normal  Test Result  Pass	Difference Description	N/A
Deviation from Standard No any deviation from the test method  Condition of Test Sample Normal  Test Result Pass	Date of receipt of test item	Jun. 04, 2024
Condition of Test Sample Normal  Test Result Pass	Date of Test	Jun. 04, 2024 –Jun. 18, 2024
Test Result Pass	Deviation from Standard	No any deviation from the test method
	Condition of Test Sample	Normal
Test Report Form No AGCER-FCC-BLE-V1	Test Result	Pass
•	Test Report Form No	AGCER-FCC-BLE-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Cool Cheng (Project Engineer)

Reviewed By


Calvin Liu (Reviewer)

Approved By

Max Zhang Authorized Officer

Jun. 18, 2024

Jun. 18, 2024





# 2. Product Information

# 2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.3
Modulation Type	BLE ⊠GFSK 1Mbps □GFSK 2Mbps
Number of channels	40
Carrier Frequency of Each Channel	40 Channels (37 hopping + 3 advertising channels)
Channel Separation	2 MHz
Maximum Transmitter Power	Bluetooth LE (1Mbps): 3.566dBm Bluetooth LE (2Mbps): 3.958dBm
Hardware Version	D
Software Version	V0.09
Antenna Designation	LDS Antenna
Antenna Gain	-4.2dBi
Power Supply	DC 3.85V by battery
Adapter Information	N/A

# 2.2 Test Frequency List

Frequency Band	Channel Number	Frequency		
	0	2402 MHz		
	1	2404 MHz		
2400~2483.5MHz	:	:		
	19	2440MHz		
	:	:		
	38	2478 MHz		
	39	2480 MHz		
Note: f = 2402 + 2*k MHz, k = 0,, 39 f is the operating frequency (MHz); k is the operating channel.				



Page 6 of 25

## 2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: 2AOKB-A6611L, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

## 2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

# 2.5 Special Accessories

Not available for this EUT intended for grant.

## 2.6 Equipment Modifications

Not available for this EUT intended for grant.

## 2.7 Antenna Requirement

# Standard Requirement

### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

## 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

## **EUT Antenna:**

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is -4.2dBi.



Page 7 of 25

## 3. Test Environment

# 3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

## CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

## A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

## FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

## IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 8 of 25


#### 3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.85V by battery

# 3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$		
Uncertainty of Occupied Channel Bandwidth	U <sub>c</sub> = ±2 %		





# 3.5 List of Equipment Use

• F	Radiated Spurious Emission						
Used Equipment No. Test Equipment Manufacturer Model No. Serial I			Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31
$\boxtimes$	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27
$\boxtimes$	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30
$\boxtimes$	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03
$\boxtimes$	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22
	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08

• Tes	Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information			
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A			
	AGC-EM-S011	RSE Test System	Tonscend	TS <sup>+</sup> Ver2.1(JS36-RSE)	4.0.0.0			



Report No.: AGC01110231241FR01A Page 10 of 25

# **4.System Test Configuration**

# 4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

## 4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

# 4.3 Configuration of Tested System

Radiated Emission Configure:

EUT	

## 4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No. Equipment		Equipment	Model No.	Manufacturer	Specification Information	Cable
	1	Xiaomi Phone	MI 10	Xiaomi		
	2	Control Box	USB-TTL			

☐ Test Accessories Come From The Manufacturer

	<del></del>						
No	. Equipment	Model No.	Manufacturer	Specification Information	Cable		
1							



Page 11 of 25

# 4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.209	Radiated Emission	Pass




# 5. Description of Test Modes

Summary Table of Test Cases				
	Data Rate / Modulation			
Test Item	Bluetooth – LE(1Mbps/2Mbps) / GFSK			
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps(Battery powered)			
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps(Battery powered)			
Radiated & Conducted	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps(Battery powered)			
Test Cases	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps(Battery powered)			
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps(Battery powered)			
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps(Battery powered)			
AC Conducted Emission	N/A			

#### Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- For Conducted Test method, a temporary antenna connector is provided by the manufacture.
   Software Setting Diagram





Page 13 of 25

# 6. Radiated Spurious Emission

### **6.1 Measurement Limit**


FCC Part 15.209 Limit in the below table to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

#### **6.2 Measurement Procedure**

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.





As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP



Report No.: AGC01110231241FR01A Page 15 of 25

## Quasi-Peak Measurements below 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

## Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

## Average Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3.  $VBW \ge [3 \times RBW]$
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10\*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.






# 6.3 Measurement Setup (Block Diagram of Configuration)


# Radiated Emission Test Setup 9KHz-30MHz



# Radiated Emission Test Setup 30MHz-1000MHz



## Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/




#### **6.4 Measurement Result**

## **Radiated Emission Below 30MHz**

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.


Radiated Emission Test Results at 30MHz-1GHz					
<b>EUT Name</b>	Wireless Headphone	Model Name	A6611L		
Temperature	22.8℃	Relative Humidity	59.8%		
Pressure	960hPa	Test Voltage	Normal Voltage		
Test Mode	Mode 6	Antenna Polarity	Horizontal		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		46.5030	6.42	13.44	19.86	40.00	-20.14	peak
2	,	108.6470	5.46	16.29	21.75	43.50	-21.75	peak
3	2	243.3772	4.70	15.30	20.00	46.00	-26.00	peak
4	4	147.9822	6.99	24.82	31.81	46.00	-14.19	peak
5	į	68.6127	7.43	24.24	31.67	46.00	-14.33	peak
6	* (	900.1474	5.31	31.78	37.09	46.00	-8.91	peak



Radiated Emission Test Results at 30MHz-1GHz					
EUT Name	Wireless Headphone	Model Name	A6611L		
Temperature	22.8℃	Relative Humidity	59.8%		
Pressure	960hPa	Test Voltage	Normal Voltage		
Test Mode	Mode 6	Antenna Polarity	Vertical		



No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		42.6000	6.64	16.93	23.57	40.00	-16.43	peak
2		69.3568	7.80	17.01	24.81	40.00	-15.19	peak
3		167.8243	6.82	18.32	25.14	43.50	-18.36	peak
4		438.6554	6.38	25.88	32.26	46.00	-13.74	peak
5		714.1734	6.60	28.60	35.20	46.00	-10.80	peak
6	*	948.7610	6.98	30.65	37.63	46.00	-8.37	peak

# **RESULT: Pass**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.



Page 19 of 25

## **Radiated Emissions Test Results for Above 1GHz**

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Horizontal

(dBµV)	(dB)	(10.)(()			
	(~-)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
48.91	0.08	48.99	74	-25.01	peak
37.49	0.08	37.57	54	-16.43	AVG
41.26	2.21	43.47	74	-30.53	peak
32.65	2.21	34.86	54	-19.14	AVG
_	37.49 41.26	37.49 0.08 41.26 2.21	37.49         0.08         37.57           41.26         2.21         43.47	37.49     0.08     37.57     54       41.26     2.21     43.47     74	37.49     0.08     37.57     54     -16.43       41.26     2.21     43.47     74     -30.53

Factor = Antenna Factor + Cable Loss – Pre-amplifier.


EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	48.61	0.08	48.69	74	-25.31	peak
4804.000	38.94	0.08	39.02	54	-14.98	AVG
7206.000	42.47	2.21	44.68	74	-29.32	peak
7206.000	32.16	2.21	34.37	54	-19.63	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

# **RESULT: Pass**





**Radiated Emissions Test Results for Above 1GHz** 

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	- Value Type
4880.000	48.62	0.14	48.76	74	-25.24	peak
4880.000	37.61	0.14	37.75	54	-16.25	AVG
7320.000	41.26	2.36	43.62	74	-30.38	peak
7320.000	32.69	2.36	35.05	54	-18.95	AVG

Remark

Factor = Antenna Factor + Cable Loss – Pre-amplifier.


EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	48.62	0.14	48.76	74	-25.24	peak
4880.000	37.94	0.14	38.08	54	-15.92	AVG
7320.000	42.16	2.36	44.52	74	-29.48	peak
7320.000	32.35	2.36	34.71	54	-19.29	AVG
7320.000	32.35	2.30	34.71	04	-19.29	<del>                                     </del>

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

# **RESULT: Pass**





## **Radiated Emissions Test Results for Above 1GHz**

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	48.62	0.22	48.84	74	-25.16	peak
4960.000	37.69	0.22	37.91	54	-16.09	AVG
7440.000	41.26	2.64	43.9	74	-30.1	peak
7440.000	32.65	2.64	35.29	54	-18.71	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	49.63	0.22	49.85	74	-24.15	peak
4960.000	38.52	0.22	38.74	54	-15.26	AVG
7440.000	42.14	2.64	44.78	74	-29.22	peak
7440.000	31.26	2.64	33.9	54	-20.1	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

# **RESULT: Pass**



Page 22 of 25

## Radiated Emissions Test Results for Above 1GHz

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	48.65	0.08	48.73	74	-25.27	peak
4804.000	37.53	0.08	37.61	54	-16.39	AVG
7206.000	42.66	2.21	44.87	74	-29.13	peak
7206.000	32.29	2.21	34.5	54	-19.5	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.


EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	47.94	0.08	48.02	74	-25.98	peak
4804.000	37.55	0.08	37.63	54	-16.37	AVG
7206.000	42.54	2.21	44.75	74	-29.25	peak
7206.000	31.68	2.21	33.89	54	-20.11	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

# **RESULT: Pass**



Report No.: AGC01110231241FR01A Page 23 of 25

# **Radiated Emissions Test Results for Above 1GHz**

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 5	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4882.000	47.62	0.14	47.76	74	-26.24	peak
4882.000	38.42	0.14	38.56	54	-15.44	AVG
7323.000	42.19	2.36	44.55	74	-29.45	peak
7323.000	32.35	2.36	34.71	54	-19.29	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 5	Antenna Polarity	Vertical

(MHz)	(dBµV)	(dB)	(dBµV/m)	(-ID\ // \	( ID)	<ul><li>Value Type</li></ul>
		(40)	(ubµv/III)	(dBµV/m)	(dB)	
4882.000	48.65	0.14	48.79	74	-25.21	peak
4882.000	38.53	0.14	38.67	54	-15.33	AVG
7323.000	42.55	2.36	44.91	74	-29.09	peak
7323.000	32.47	2.36	34.83	54	-19.17	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

# **RESULT: Pass**



Page 24 of 25

## **Radiated Emissions Test Results for Above 1GHz**

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	48.62	0.22	48.84	74	-25.16	peak
4960.000	38.29	0.22	38.51	54	-15.49	AVG
7440.000	41.24	2.64	43.88	74	-30.12	peak
7440.000	32.43	2.64	35.07	54	-18.93	AVG

|Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Wireless Headphone	Model Name	A6611L
Temperature	22.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4960.000	47.25	0.22	47.47	74	-26.53	peak
4960.000	37.43	0.22	37.65	54	-16.35	AVG
7440.000	42.31	2.64	44.95	74	-29.05	peak
7440.000	31.59	2.64	34.23	54	-19.77	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

# **RESULT: Pass**

## Note:

- The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 25 of 25

# **Appendix I: Photographs of Test Setup**

Refer to the Report No.: AGC01110231241AP01A

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC01110231241AP02A

----End of Report----



# Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.