



RF EXPOSURE EVALUATION REPORT

APPLICANT : Anker Innovations Limited
PRODUCT NAME : Nebula Solar
MODEL NAME : D2130
BRAND NAME : NEBULA
FCC ID : 2AOKB-D2130
STANDARD(S) : 47CFR 2.1091
KDB 447498
RECEIPT DATE : 2020-07-01
TEST DATE : 2020-07-30 to 2020-08-28
ISSUE DATE : 2020-09-07

Edited by: Chen Bilian
Chen Bilian (Rapporteur)
Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information..... 3
- 1.1 Applicant and Manufacturer Information..... 3
- 1.2 Equipment under Test (EUT) Description..... 3
- 1.3 Applied Reference Documents 4
- 2. Device Category and RF Exposure Limit 5
- 3. RF Output Power..... 6
- 4. RF Exposure Assessment..... 12
- Annex A General Information..... 13

Change History		
Version	Date	Reason for Change
1.0	2020-09-07	First edition



1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	Anker Innovations Limited
Applicant Address:	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong
Manufacturer:	Anker Innovations Limited
Manufacturer Address:	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong

1.2 Equipment under Test (EUT) Description

Product Name:	Nebula Solar
Serial No.:	(N/A, marked #1 by test site)
Hardware Version:	V0.2
Software Version:	H2_V2.0.1
Frequency Bands:	WLAN 2.4GHz: 2412 MHz~2462 MHz WLAN 5.2GHz: 5180 MHz~5240 MHz WLAN 5.8GHz: 5745 MHz~5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Modulation Mode:	802.11b: DSSS 802.11a/g/n-HT20/n-HT40/ac-VHT20/ac-VHT40/VHT80: OFDM Bluetooth BR+EDR: GFSK, $\pi/4$ -DQPSK, 8-DPSK Bluetooth LE: GFSK
Antenna Type:	Bluetooth:FPC Antenna WLAN2.4G:FPC Antenna WLAN5G:FPC Antenna
Antenna Gain:	Bluetooth:0dBi WLAN2.4G:ANTL: 0dBi; ANT R: 0dBi WLAN5G:ANTL: 0dBi; ANT R: 0dBi

Note:

When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% risk level.



1.3 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title	Method determination /Remark
1	47 CFR§2.1091	Radio Frequency Radiation Exposure Assessment: mobile devices	No deviation
2	KDB 447498 D01v06	General RF Exposure Guidance	No deviation

Note 1: The test item is not applicable.

Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.



2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz* = Plane-wave equivalent power density



3. RF Output Power

<WLAN 2.4GHz> ANT L

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	CH 1	2412	13.38	14.00	100.00
		CH 6	2437	13.61	14.00	
		CH 11	2462	13.78	14.00	
	802.11g 6Mbps	CH 1	2412	13.64	14.00	97.22
		CH 6	2437	14.13	15.00	
		CH 11	2462	14.11	15.00	
	802.11n-HT20 MCS0	CH 1	2412	13.95	14.50	97.04
		CH 6	2437	14.22	15.00	
		CH 11	2462	14.46	15.00	

<WLAN 2.4GHz> ANT R

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	CH 1	2412	13.16	14.00	100.00
		CH 6	2437	13.41	14.00	
		CH 11	2462	13.28	14.00	
	802.11g 6Mbps	CH 1	2412	13.36	14.00	97.22
		CH 6	2437	13.72	14.00	
		CH 11	2462	13.90	14.00	
	802.11n-HT20 MCS0	CH 1	2412	13.87	14.00	97.04
		CH 6	2437	14.00	14.50	
		CH 11	2462	14.37	15.00	



ANT L+ANT R

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
	802.11n-HT20 MCS0	CH 1	2412	16.90	17.00	97.04
		CH 6	2437	17.16	18.00	
		CH 11	2462	17.40	18.00	

<WLAN 5GHz> ANT L

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
	802.11a6Mbps	CH 36	5180	14.31	15.00	97.22
		CH 40	5200	14.25	15.00	
		CH 48	5240	14.39	15.00	
	802.11n-HT20 MCS0	CH 36	5180	14.33	15.00	97.04
		CH 40	5200	14.56	15.00	
		CH 48	5240	14.68	15.00	
	802.11n-HT40 MCS0	CH 38	5190	14.37	15.00	94.20
		CH 46	5230	14.33	15.00	
	802.11ac-VHT20 MCS0	CH 36	5180	14.53	15.00	97.06
		CH 40	5200	15.00	15.50	
		CH 48	5240	14.92	15.50	
	802.11ac-VHT40 MCS0	CH 38	5190	14.21	15.00	94.20
		CH 46	5230	14.24	15.00	
	802.11ac-VHT80 MCS0	CH 42	5210	12.75	13.00	88.89



	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
5.8GHz WLAN	802.11a6Mbps	CH 149	5745	12.43	13.00	97.22
		CH 157	5785	12.30	13.00	
		CH 165	5825	12.29	13.00	
	802.11n-HT20 MCS0	CH 149	5745	12.36	13.00	97.04
		CH 157	5785	12.49	13.00	
		CH 165	5825	12.35	13.00	
	802.11n-HT40 MCS0	CH 151	5755	14.06	14.50	94.20
		CH 159	5795	14.09	14.50	
	802.11ac-VHT20 MCS0	CH 149	5745	12.87	13.00	97.06
		CH 157	5785	12.88	13.00	
		CH 165	5825	12.84	13.00	
	802.11ac-VHT40 MCS0	CH 151	5755	13.43	14.00	94.20
		CH 159	5795	13.40	14.00	
	802.11ac-VHT80 MCS0	CH 155	5775	12.80	13.00	88.89



ANT R

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
5.2GHz WLAN	802.11a6Mbps	CH 36	5180	14.09	14.50	97.22
		CH 40	5200	14.26	14.50	
		CH 48	5240	14.63	15.00	
	802.11n-HT20 MCS0	CH 36	5180	14.40	15.00	97.04
		CH 40	5200	14.37	15.00	
		CH 48	5240	14.65	15.00	
	802.11n-HT40 MCS0	CH 38	5190	14.27	15.00	94.20
		CH 46	5230	14.43	15.00	
	802.11ac-VHT20 MCS0	CH 36	5180	14.41	15.00	97.06
		CH 40	5200	14.33	15.00	
		CH 48	5240	14.39	15.00	
	802.11ac-VHT40 MCS0	CH 38	5190	14.09	14.50	94.20
		CH 46	5230	14.18	14.50	
	802.11ac-VHT80 MCS0	CH 42	5210	12.66	13.00	88.89



5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
	802.11a6Mbps	CH 149	5745	12.70	13.00	97.22
		CH 157	5785	12.70	13.00	
		CH 165	5825	12.50	13.00	
	802.11n-HT20 MCS0	CH 149	5745	13.07	13.50	97.04
		CH 157	5785	12.81	13.00	
		CH 165	5825	12.51	13.00	
	802.11n-HT40 MCS0	CH 151	5755	13.34	14.00	94.20
		CH 159	5795	13.53	14.00	
	802.11ac-VHT20 MCS0	CH 149	5745	12.98	13.00	97.06
CH 157		5785	12.75	13.00		
CH 165		5825	12.31	12.50		
802.11ac-VHT40 MCS0	CH 151	5755	13.35	13.50	94.20	
	CH 159	5795	13.15	13.50		
802.11ac-VHT80 MCS0	CH 155	5775	12.72	13.00	88.89	

ANT L+ANT R

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
	802.11n-HT20 MCS0	CH 36	5180	17.40	18.00	97.04
		CH 40	5200	17.48	18.00	
		CH 48	5240	17.71	18.00	
	802.11n-HT40 MCS0	CH 38	5190	17.32	18.00	94.20
		CH 46	5230	17.40	18.00	
	802.11ac-VHT20 MCS0	CH 36	5180	17.48	18.00	97.06
		CH 40	5200	17.71	18.00	
		CH 48	5240	17.71	18.00	
	802.11ac-VHT40 MCS0	CH 38	5190	17.16	18.00	94.20
CH 46		5230	17.24	18.00		
802.11ac-VHT80 MCS0	CH 42	5210	15.68	16.00	88.89	



5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
	802.11n-HT20 MCS0	CH 149	5745	15.68	16.00	97.04
		CH 157	5785	15.68	16.00	
		CH 165	5825	15.44	16.00	
	802.11n-HT40 MCS0	CH 151	5755	16.72	17.00	94.20
		CH 159	5795	16.81	17.00	
	802.11ac-VHT20 MCS0	CH 149	5745	15.91	16.00	97.06
		CH 157	5785	15.80	16.00	
		CH 165	5825	15.56	16.00	
	802.11ac-VHT40 MCS0	CH 151	5755	16.43	17.00	94.20
CH 159		5795	16.33	17.00		
802.11ac-VHT80 MCS0	CH 155	5775	15.80	16.00	88.89	

<Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)
			GFSK
BluetoothLE	CH 00	2402	6.47
	CH 19	2440	6.85
	CH 39	2480	6.47
Tune-up Limit			7.00

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
Bluetooth classic	CH 00	2402	7.82	3.30	3.47
	CH 39	2441	7.67	3.69	3.79
	CH 78	2480	7.17	3.47	3.48
Tune-up Limit			8.00	4.00	4.00

Note:

1. According to KDB 447498 Section 4.3, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. The output power is refer from the report SZ20070001W01/W02/W03/ W04.

4. RF Exposure Assessment

➤ Standalone Transmission Assessment:

<Standalone Antenna Transmission Assessment>

Bands	Frequency (MHz)	Maximum Tune-up Power (dBm)	Antenna Gain (dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit for MPE (mW/cm ²)
WLAN 2.4GHz	2462	15.00	0	31.62	0.006	1.0
WLAN 5GHz	5200	15.50	0	35.48	0.007	1.0

<MIMO Transmission Assessment>

Bands	Frequency (MHz)	Maximum Tune-up Power (dBm)	Antenna Gain (dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit for MPE (mW/cm ²)
WLAN 2.4GHz	2462	18.00	0	63.10	0.013	1.0
WLAN 5GHz	5240	18.00	0	63.10	0.013	1.0

Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. This device supports WLAN MIMO Transmission, only the worst antenna of WLAN 2.4GHz & WLAN 5GHz was used for calculating MPE.
3. MPE calculate method

$$\text{Power Density} = \text{E.I.R.P.}/4\pi R^2$$

Where: E.I.R.P. = P+G

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)

➤ Simultaneous Transmission Assessment:

According to the user manual, both the WLAN and Bluetooth transmitters in the device cannot operate simultaneously, therefore simultaneous transmission analysis is not required.

➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



Annex A General Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

The FCC designation number is CN1192, the test firm registration number is 226174.

_____ END OF REPORT _____