



REPORT No. : SZ23030340S01

RF EXPOSURE EVALUATION REPORT

APPLICANT : Anker Innovations Limited

PRODUCT NAME : S350 Indoor Cam

MODEL NAME : T8416

BRAND NAME : eufy SECURITY

FCC ID : 2AOKB-T8416

STANDARD(S) : 47 CFR Part 2(2.1091)

RECEIPT DATE : 2023-03-29

TEST DATE : 2023-04-27 to 2023-05-14

ISSUE DATE : 2023-05-24

Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1 Applicant and Manufacturer Information	3
1.2 Equipment under Test (EUT) Description	3
1.3 Applied Reference Documents	4
2. Device Category and RF Exposure Limit	5
3. RF Output Power	6
4. RF Exposure Assessment	11
Annex A Testing Laboratory Information	12

Change History		
Version	Date	Reason for change
1.0	2023-05-24	First edition



1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	Anker Innovations Limited
Applicant Address:	Room 1318-19,Hollywood Plaza,610 Nathan Road,Mongkok,Kowloon,Hong Kong
Manufacturer:	Anker Innovations Limited
Manufacturer Address:	Room 1318-19,Hollywood Plaza,610 Nathan Road,Mongkok,Kowloon,Hong Kong

1.2 Equipment under Test (EUT) Description

Product Name:	S350 Indoor Cam	
Sample No.:	1#	
Hardware Version:	T8416-MAIN-V04	
Software Version:	1.3.1.1	
Frequency Bands:	Bluetooth	2402MHz-2480MHz
	WLAN 2.4GHz	2412MHz-2462MHz
	WLAN 5GHz	5180MHz-5240MHz
		5260MHz-5320MHz
		5500MHz-5720MHz
		5745MHz-5825MHz
Modulation Mode:	Bluetooth	GFSK
	WLAN 2.4GHz	DSSS, OFDM, OFDMA
	WLAN 5GHz	OFDM, OFDMA
Antenna Type:	PIFA Antenna	
Antenna Gain:	Bluetooth	3.60dBi
	WLAN 2.4GHz	3.60dBi
	WLAN 5GHz	2.75dBi



1.3 Applied Reference Documents

Leading reference documents for testing:

Identity	Document Title	Method Determination /Remark
47 CFR Part 2(2.1091)	Radio Frequency Radiation Exposure Assessment: mobile devices	No deviation
KDB 447498 D01v06	General RF Exposure Guidance	No deviation
Note 1: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table. Note 2: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.		



2. Device Category and RF Exposure Limit

Per user manual, based on 47 CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47 CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Table 1 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz* = Plane-wave equivalent power density



3. RF Output Power

Mode	Channel	Frequency (MHz)	Average Power (dBm)
			GFSK
BLE 1Mbps	CH 00	2402	8.30
	CH 19	2440	7.86
	CH 39	2480	7.26
BLE 2Mbps	CH 00	2402	8.53
	CH 19	2440	7.79
	CH 39	2480	7.33
Tune-up Limit			9.00

2.4GHz WLAN					
Mode	Channel	Frequency (MHz)	Average Power (dBm)	Tune-up Power	Duty Cycle %
802.11b	CH 1	2412	21.71	22.00	99.35
	CH 6	2437	21.02	21.50	99.59
	CH 11	2462	20.69	21.00	98.61
802.11g	CH 1	2412	16.01	16.50	97.14
	CH 6	2437	20.66	21.00	96.23
	CH 11	2462	14.82	15.00	94.44
802.11n (HT20)	CH 1	2412	15.89	16.00	95.96
	CH 6	2437	20.78	21.00	89.52
	CH 11	2462	14.89	15.00	94.95
802.11n (HT40)	CH 3	2422	12.40	13.00	93.94
	CH 6	2437	21.08	21.50	82.30
	CH 9	2452	12.33	13.00	85.32
802.11ax (HE20)	CH 1	2412	15.87	16.00	96.05
	CH 6	2437	20.78	21.00	92.41
	CH 11	2462	14.66	15.00	93.51
802.11ax (HE40)	CH 3	2422	14.87	15.00	80.43
	CH 6	2437	20.69	21.00	83.33
	CH 9	2452	15.25	16.00	83.33



5GHz WLAN					
Mode	Channel	Frequency (MHz)	Average (dBm)	Tune-up Power	Duty Cycle %
802.11a	CH 36	5180	15.85	16.00	95.49
	CH 44	5220	15.89	16.00	
	CH 48	5240	15.78	16.00	
	CH 52	5260	16.13	16.50	
	CH 60	5300	16.51	17.00	
	CH 64	5320	16.42	17.00	
	CH 100	5500	20.20	20.50	
	CH 120	5600	18.28	18.50	
	CH 144	5720	12.60	13.00	
	CH 149	5745	11.68	12.00	
	CH 157	5785	11.10	11.50	
	CH 165	5825	11.03	11.50	

5GHz WLAN					
Mode	Channel	Frequency (MHz)	Average (dBm)	Tune-up Power	Duty Cycle %
802.11n (HT20)	CH 36	5180	15.79	16.00	94.79
	CH 44	5220	16.02	16.50	
	CH 48	5240	15.77	16.00	
	CH 52	5260	16.16	16.50	
	CH 60	5300	16.51	17.00	
	CH 64	5320	16.42	17.00	
	CH 100	5500	20.24	21.00	
	CH 120	5600	18.18	18.50	
	CH 144	5720	12.34	13.00	
	CH 149	5745	11.57	12.00	
	CH 157	5785	11.09	11.50	
	CH 165	5825	11.10	11.50	



5GHz WLAN					
Mode	Channel	Frequency (MHz)	Average (dBm)	Tune-up Power	Duty Cycle %
802.11n (HT40)	CH 38	5190	10.12	10.50	80.48
	CH 46	5230	15.70	16.00	
	CH 54	5270	15.96	16.50	
	CH 62	5310	11.02	11.50	
	CH 102	5510	14.91	15.50	
	CH 110	5550	19.64	20.00	
	CH 142	5710	12.72	13.00	
	CH 151	5755	11.57	12.00	
	CH 159	5795	11.17	11.50	

5GHz WLAN					
Mode	Channel	Frequency (MHz)	Average (dBm)	Tune-up Power	Duty Cycle %
802.11ac (VHT20)	CH 36	5180	16.31	17.00	92.50
	CH 44	5220	16.38	17.00	
	CH 48	5240	16.18	16.50	
	CH 52	5260	16.45	17.00	
	CH 60	5300	16.78	17.00	
	CH 64	5320	16.67	17.00	
	CH 100	5500	20.38	21.00	
	CH 120	5600	18.47	19.00	
	CH 144	5720	12.46	13.00	
	CH 149	5745	11.66	12.00	
	CH 157	5785	11.10	11.50	
	CH 165	5825	11.13	11.50	



5GHz WLAN					
Mode	Channel	Frequency (MHz)	Average (dBm)	Tune-up Power	Duty Cycle %
802.11ac (VHT40)	CH 38	5190	9.69	10.00	84.17
	CH 46	5230	15.69	16.00	
	CH 54	5270	16.02	16.50	
	CH 62	5310	10.75	11.00	
	CH 102	5510	14.42	15.00	
	CH 110	5550	19.54	20.00	
	CH 142	5710	12.68	13.00	
	CH 151	5755	11.54	12.00	
	CH 159	5795	11.23	12.00	

5GHz WLAN					
Mode	Channel	Frequency (MHz)	Average (dBm)	Tune-up Power	Duty Cycle %
802.11ax (HE20)	CH 36	5180	15.73	16.00	89.09
	CH 44	5220	15.95	16.50	
	CH 48	5240	15.76	16.50	
	CH 52	5260	16.10	16.50	
	CH 60	5300	16.49	17.00	
	CH 64	5320	16.42	17.00	
	CH 100	5500	20.23	21.00	
	CH 120	5600	18.42	19.00	
	CH 144	5720	12.39	13.00	
	CH 149	5745	11.68	12.00	
	CH 157	5785	11.11	11.50	
	CH 165	5825	10.87	11.50	



5GHz WLAN					
Mode	Channel	Frequency (MHz)	Average (dBm)	Tune-up Power	Duty Cycle %
802.11ax (HE40)	CH 38	5190	9.44	10.00	81.62
	CH 46	5230	15.79	16.00	
	CH 54	5270	16.13	16.50	
	CH 62	5310	10.54	11.00	
	CH 102	5510	14.11	14.50	
	CH 110	5550	19.64	20.00	
	CH 142	5710	12.89	13.00	
	CH 151	5755	11.61	12.00	
	CH 159	5795	11.02	11.50	

Note 1: According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

Note 2: The output power refers to report (Report No.: SZ23030340W01/W02/W03).

4. RF Exposure Assessment

➤ Standalone Transmission Assessment:

Bands	Frequency (MHz)	Tune-up Power(dBm)	Antenna Gain(dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit for MPE (mW/cm ²)
Bluetooth	2402	9.00	3.60	18.20	0.004	1.0
WLAN 2.4GHz	2412	22.00	3.60	363.08	0.072	1.0
WLAN 5GHz	5500	21.00	2.75	237.14	0.047	1.0

Note:

1. The WLAN 2.4G, WLAN 5G and Bluetooth transmitter share the same antenna, Therefore simultaneous transmission assessment is not required.
2. For 5GHz WLAN, only the worst case will be used for calculating the power density.
3. MPE calculate method

$$S = PG/4\pi R^2$$

Where: S= Power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune-up power (in appropriate units, e.g. dBm)

G = numeric gain of the antenna (in appropriate units, e.g. dBi)

R = Separation distance to the centre of radiation of the antenna (20cm)

➤ Simultaneous Transmission Assessment:

According to the user manual, both the WLAN and Bluetooth transmitters in the device cannot operate simultaneously, therefore simultaneous transmission analysis is not required.

➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



Annex A Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

————— END OF REPORT —————