

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AOKB-T8420X

### EUT Specification

<b>EUT</b>	Floodlight Cam E 2K
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others: 2.402GHz~2.480GHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure ( $S = 5\text{mW/cm}^2$ ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1\text{mW/cm}^2$ )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	WIFI: 16.77dBm (0.0475W); BLE: 7.816dBm (0.0060W)
<b>Antenna gain (Max)</b>	2.6 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density( $\text{mW/cm}^2$ )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

## Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$ = Power density in  $\text{mW/cm}^2$

$P_{out}$ =output power to antenna in  $\text{Mw}$

$G$ = gain of antenna in linear scale

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1\text{mW/cm}^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

### 2.4GHz WiFi:

Operating Mode	Channel Frequency	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits ( $\text{mW/cm}^2$ )
	(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ $\text{cm}^2$ )	
802.11b	2412	16.06	16.06±1	17.06	2.6	0.0263	1
	2437	16.56	16.56±1	17.56	2.6	0.0295	1
	2462	16.69	16.69±1	17.69	2.6	0.0304	1
802.11g	2412	16.55	16.55±1	17.55	2.6	0.0294	1
	2437	16.25	16.25±1	17.25	2.6	0.0275	1
	2462	16.10	16.10±1	17.1	2.6	0.0265	1
802.11n (HT20)	2412	16.45	16.45±1	17.45	2.6	0.0288	1
	2437	16.56	16.56±1	17.56	2.6	0.0295	1
	2462	16.77	16.77±1	17.77	2.6	0.0310	1
BLE	2402	7.493	7.493±1	8.493	2.6	0.0037	1
	2440	7.142	7.142±1	8.142	2.6	0.0034	1
	2480	7.816	7.816±1	8.816	2.6	0.0039	1