

FCC TEST REPORT

Client Name : Anker Innovations Limited
Address : Room 1318-19, Hollywood Plaza, 610 Nathan Road,
Mongkok, Kowloon, Hongkong
Product Name : eufy Security Smart Lock R10
Date : Oct. 14, 2021

Shenzhen Anbotek Compliance Laboratory Limited



Contents

| | |
|---|----|
| 1. General Information..... | 4 |
| 1.1. Client Information..... | 4 |
| 1.2. Description of Device (EUT)..... | 4 |
| 1.3. Auxiliary Equipment Used During Test..... | 5 |
| 1.4. Description of Test Modes..... | 5 |
| 1.5. List of channels..... | 6 |
| 1.6. Description Of Test Setup..... | 7 |
| 1.7. Test Equipment List..... | 8 |
| 1.8. Measurement Uncertainty..... | 9 |
| 1.9. Description of Test Facility..... | 9 |
| 2. Summary of Test Results..... | 10 |
| 3. Conducted Emission Test..... | 11 |
| 3.1. Test Standard and Limit..... | 11 |
| 3.2. Test Setup..... | 11 |
| 3.3. Test Procedure..... | 11 |
| 4. Radiation Spurious Emission and Band Edge..... | 12 |
| 4.1. Test Standard and Limit..... | 12 |
| 4.2. Test Setup..... | 12 |
| 4.3. Test Procedure..... | 13 |
| 4.4. Test Data..... | 14 |
| 5. Antenna Requirement..... | 23 |
| 5.1. Test Standard and Requirement..... | 23 |
| 5.2. Antenna Connected Construction..... | 23 |
| APPENDIX I -- TEST SETUP PHOTOGRAPH..... | 24 |
| APPENDIX II -- EXTERNAL PHOTOGRAPH..... | 24 |
| APPENDIX III -- INTERNAL PHOTOGRAPH..... | 24 |

TEST REPORT

Applicant : Anker Innovations Limited
Manufacturer : Anker Innovations Limited
Product Name : eufy Security Smart Lock R10
Model No. : T8503
Trade Mark : eufy SECURITY
Rating(s) : Input: DC 6V by CR123A*4 batteries inside

Test Standard(s) : FCC Part15 Subpart C, Section 15.247

Test Method(s) : ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Sept. 07, 2021

Date of Test

Sept. 07~Oct. 14, 2021

Prepared by



(Ella Liang)

Approved & Authorized Signer



(Kingkong Jin)

1. General Information

1.1. Client Information

| | | |
|--------------|---|--|
| Applicant | : | Anker Innovations Limited |
| Address | : | Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hongkong |
| Manufacturer | : | Anker Innovations Limited |
| Address | : | Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hongkong |

1.2. Description of Device (EUT)

| | | |
|---------------------|----------------------|---|
| Product Name | : | eufy Security Smart Lock R10 |
| Model No. | : | T8503 |
| Trade Mark | : | eufy SECURITY |
| Test Power Supply | : | DC 6V battery inside |
| Test Sample No. | : | 1-2-1(Normal Sample), 1-2-2(Engineering Sample) |
| Product Description | Operation Frequency: | BLE: 2402~2480MHz WiFi 2.4G: 2412-2462MHz for 802.11b/g/n(HT20) |
| | Number of Channel: | BLE: 40 Channels WiFi 2.4G: 802.11b/ g/ n(HT20): 11 Channels |
| | Modulation Type: | BLE: GFSK WiFi 2.4G: CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM |
| | Antenna Type: | BLE: FPC antenna WiFi 2.4G: Steel sheet antenna |
| | Antenna Gain(Peak): | BLE: 1.11 dBi WiFi 2.4G: 4.27 dBi |
| | Adapter: | N.A. |

Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2) This report is for WiFi 2.4G module.

1.3. Auxiliary Equipment Used During Test

| | | |
|------|---|--|
| N.A. | : | |
|------|---|--|

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

RADIATED EMISSION TEST (BELOW 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| Mode | Available Channel | Test Channel | Modulation Tech. | Data Rate (Mbps) |
|---------|-------------------|--------------|------------------|------------------|
| 802.11b | 1 to 11 | 1, 6, 11 | DSSS | 1.0 |

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| Mode | Available Channel | Test Channel | Modulation Tech. | Data Rate (Mbps) |
|---------|-------------------|--------------|------------------|------------------|
| 802.11b | 1 to 11 | 1, 6, 11 | DSSS | 1.0 |

POWER LINE CONDUCTED EMISSION TEST:

The EUT was tested with the following mode

| Mode | Available Channel | Test Channel | Modulation Tech. | Data Rate (Mbps) |
|----------------|-------------------|--------------|------------------|------------------|
| 802.11b | 1 to 11 | 1, 6, 11 | DSSS | 1.0 |
| 802.11g | 1 to 11 | 1, 6, 11 | OFDM | 6.0 |
| 802.11n (HT20) | 1 to 11 | 1, 6, 11 | OFDM | 6.5 |

BANDEDGE MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

| Mode | Available Channel | Test Channel | Modulation Tech. | Data Rate (Mbps) |
|----------------|-------------------|--------------|------------------|------------------|
| 802.11b | 1 to 11 | 1, 6, 11 | DSSS | 1.0 |
| 802.11g | 1 to 11 | 1, 6, 11 | OFDM | 6.0 |
| 802.11n (HT20) | 1 to 11 | 1, 6, 11 | OFDM | 6.5 |

ANTENNA PORT CONDUCTED MEASUREMENT:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.


| Mode | Available Channel | Test Channel | Modulation Tech. | Data Rate (Mbps) |
|----------------|-------------------|--------------|------------------|------------------|
| 802.11b | 1 to 11 | 1, 6, 11 | DSSS | 1.0 |
| 802.11g | 1 to 11 | 1, 6, 11 | OFDM | 6.0 |
| 802.11n (HT20) | 1 to 11 | 1, 6, 11 | OFDM | 6.5 |

1.5. List of channels

| Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) |
|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| 01 | 2412 | 04 | 2427 | 07 | 2442 | 10 | 2457 |
| 02 | 2417 | 05 | 2432 | 08 | 2447 | 11 | 2462 |
| 03 | 2422 | 06 | 2437 | 09 | 2452 | | |

1.6. Description Of Test Setup

RE



1.5m

1.7. Test Equipment List

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|---|----------------------------|------------------|---------------|---------------|---------------|
| 1. | L.I.S.N. Artificial Mains Network | Rohde & Schwarz | ENV216 | 100055 | Oct. 26, 2020 | 1 Year |
| 2. | EMI Test Receiver | Rohde & Schwarz | ESCI | 100627 | Oct. 26, 2020 | 1 Year |
| 3. | EMI Test Receiver | Rohde & Schwarz | ESR26 | 101481 | Oct. 26, 2020 | 1 Year |
| 4. | RF Switching Unit | Compliance Direction | RSU-M2 | 38303 | Oct. 26, 2020 | 1 Year |
| 5. | MAX Spectrum Analysis | Agilent | N9020A | MY51170037 | Oct. 26, 2020 | 1 Year |
| 6. | Preamplifier | SKET Electronic | BK1G18G30 D | KD17503 | Oct. 26, 2020 | 1 Year |
| 7. | Double Ridged Horn Antenna | Instruments corporation | GTH-0118 | 351600 | Nov. 02, 2020 | 2 Year |
| 8. | Bilog Broadband Antenna | Schwarzbeck | VULB9163 | VULB 9163-289 | Nov. 02, 2020 | 2 Year |
| 9. | Loop Antenna | Schwarzbeck | FMZB1519B | 00053 | Nov. 02, 2020 | 2 Year |
| 10. | Horn Antenna | A-INFO | LB-180400- KF | J211060628 | Nov. 02, 2020 | 2 Year |
| 11. | Pre-amplifier | SONOMA | 310N | 186860 | Oct. 26, 2020 | 1 Year |
| 12. | EMI Test Software EZ-EMC | SHURPLE | N/A | N/A | N/A | N/A |
| 13. | RF Test Control System | YIHENG | YH3000 | 2017430 | Oct. 26, 2020 | 1 Year |
| 14. | Power Sensor | DAER | RPR3006W | 15100041SN045 | Oct. 26, 2020 | 1 Year |
| 15. | Power Sensor | DAER | RPR3006W | 15100041SN046 | Oct. 26, 2020 | 1 Year |
| 16. | MXA Spectrum Analysis | Agilent | N9020A | MY51170037 | Oct. 26, 2020 | 1 Year |
| 17. | MXG RF Vector Signal Generator | Agilent | N5182A | MY48180656 | Oct. 26, 2020 | 1 Year |
| 18. | Signal Generator | Agilent | E4421B | MY41000743 | Oct. 26, 2020 | 1 Year |
| 19. | DC Power Supply | IVYTECH | IV3605 | 1804D360510 | Oct. 26, 2020 | 1 Year |
| 20. | Constant Temperature Humidity Chamber | ZHONGJIAN | ZJ-KHWS80 B | N/A | Oct. 26, 2020 | 1 Year |

1.8. Measurement Uncertainty

| | | |
|------------------------|---|--------------------------|
| Radiation Uncertainty | : | Ur = 3.9 dB (Horizontal) |
| | | Ur = 3.8 dB (Vertical) |
| Conduction Uncertainty | : | Uc = 3.4 dB |

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

| Standard Section | Test Item | Result |
|---|---------------------|--------|
| 15.203/15.247(c) | Antenna Requirement | PASS |
| 15.207 | Conducted Emission | N/A |
| 15.205/15.209 | Spurious Emission | PASS |
| 15.247(d) | Band Edge | PASS |
| Remark: "N/A" is an abbreviation for Not Applicable. | | |

Note: Note: This is a Class II application of the device, the difference between the original device and current one described as following:

- (1) Change the product name to "eufy Security Smart Lock R10"
- (2) Change the transistor to a diode, and change the PCB board. Change the tag number from Q6, Q7 to D3, D4.
- (3) Change the HW Version to V1.1
- (4) Change the SW Version to 1.0.2.3

The changes are not related with the other RF parameters, only the radiated spurious emission has been re-tested, and the conducted power quotes the data of the original report 18220WC10182302.


3. Conducted Emission Test

3.1. Test Standard and Limit

| Test Standard | FCC Part15 Section 15.207 | | |
|---------------|---------------------------|--------------------------------|---------------|
| Test Limit | Frequency | Maximum RF Line Voltage (dBuV) | |
| | | Quasi-peak Level | Average Level |
| | 150kHz~500kHz | 66 ~ 56 * | 56 ~ 46 * |
| | 500kHz~5MHz | 56 | 46 |
| 5MHz~30MHz | 60 | 50 | |

Remark: (1) *Decreasing linearly with logarithm of the frequency.
 (2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Not applicable for equipment operated with DC power supply.

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

| Test Standard | FCC Part15 C Section 15.209 and 15.205 | | | | |
|---------------|--|----------------------------------|----------------|------------|--------------------------|
| Test Limit | Frequency (MHz) | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz~0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz-30MHz | 30 | - | - | 30 |
| | 30MHz~88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz~216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz~960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz~1000MHz | 500 | 54.0 | Quasi-peak | 3 |
| | | | 54.0 | Average | 3 |
| Above 1000MHz | - | 74.0 | Peak | 3 | |

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9kHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement:

-VBW=10Hz, When duty cycle is no less than 98 percent

-VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, and found the 802.11b CH06 which is the worst case, only the worst case is recorded in the report.



Test Results (30~1000MHz)


Test Mode: 802.11b CH06
 Power Source: DC 6V battery inside
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 24.8°C/49%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Height (cm) | degree (deg) | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|-------------|--------------|--------|
| 1 | 55.2207 | 45.33 | -16.51 | 28.82 | 40.00 | -11.18 | QP | 100 | 0 | |
| 2 | 165.4866 | 51.48 | -21.52 | 29.96 | 43.50 | -13.54 | QP | 100 | 360 | |
| 3 | 242.5252 | 52.78 | -18.99 | 33.79 | 46.00 | -12.21 | QP | 100 | 360 | |
| 4 | 252.9482 | 54.88 | -18.57 | 36.31 | 46.00 | -9.69 | QP | 100 | 0 | |
| 5 | 857.0247 | 44.35 | -2.96 | 41.39 | 46.00 | -4.61 | QP | 100 | 0 | |
| 6 | 903.3093 | 42.16 | -1.65 | 40.51 | 46.00 | -5.49 | QP | 100 | 360 | |

Test Results (30~1000MHz)

Test Mode: 802.11b CH06
 Power Source: DC 6V battery inside
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 24.8°C/49%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Height (cm) | degree (deg) | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|-------------|--------------|--------|
| 1 | 49.0144 | 46.88 | -14.70 | 32.18 | 40.00 | -7.82 | QP | 100 | 360 | |
| 2 | 72.5916 | 54.36 | -18.46 | 35.90 | 40.00 | -4.10 | QP | 100 | 0 | |
| 3 | 80.9274 | 50.07 | -17.53 | 32.54 | 40.00 | -7.46 | QP | 100 | 0 | |
| 4 | 143.3257 | 51.99 | -20.02 | 31.97 | 43.50 | -11.53 | QP | 100 | 360 | |
| 5 | 154.2786 | 51.99 | -19.70 | 32.29 | 43.50 | -11.21 | QP | 100 | 360 | |
| 6 | 242.5252 | 50.35 | -15.56 | 34.79 | 46.00 | -11.21 | QP | 100 | 0 | |

Test Results (Above 1000MHz)

| | |
|-------------------------|----------------------|
| Test Mode: 802.11b Mode | Test channel: Lowest |
|-------------------------|----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 4824.00 | 27.11 | 15.31 | 42.42 | 74.00 | -31.58 | Vertical |
| 7236.00 | 27.88 | 18.06 | 45.94 | 74.00 | -28.06 | Vertical |
| 9648.00 | 28.62 | 23.77 | 52.39 | 74.00 | -21.61 | Vertical |
| 12060.00 | * | | | 74.00 | | Vertical |
| 14472.00 | * | | | 74.00 | | Vertical |
| 4824.00 | 26.71 | 15.31 | 42.02 | 74.00 | -31.98 | Horizontal |
| 7236.00 | 29.24 | 18.06 | 47.30 | 74.00 | -26.70 | Horizontal |
| 9648.00 | 28.64 | 23.77 | 52.41 | 74.00 | -21.59 | Horizontal |
| 12060.00 | * | | | 74.00 | | Horizontal |
| 14472.00 | * | | | 74.00 | | Horizontal |

Average value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 4824.00 | 18.19 | 15.31 | 33.50 | 54.00 | -20.50 | Vertical |
| 7236.00 | 18.75 | 18.06 | 36.81 | 54.00 | -17.19 | Vertical |
| 9648.00 | 18.97 | 23.77 | 42.74 | 54.00 | -11.26 | Vertical |
| 12060.00 | * | | | 54.00 | | Vertical |
| 14472.00 | * | | | 54.00 | | Vertical |
| 4824.00 | 18.24 | 15.31 | 33.55 | 54.00 | -20.45 | Horizontal |
| 7236.00 | 20.48 | 18.06 | 38.54 | 54.00 | -15.46 | Horizontal |
| 9648.00 | 19.39 | 23.77 | 43.16 | 54.00 | -10.84 | Horizontal |
| 12060.00 | * | | | 54.00 | | Horizontal |
| 14472.00 | * | | | 54.00 | | Horizontal |



Test Results (Above 1000MHz)

| | |
|-------------------------|----------------------|
| Test Mode: 802.11b Mode | Test channel: Middle |
|-------------------------|----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 4874.00 | 27.16 | 15.41 | 42.57 | 74.00 | -31.43 | Vertical |
| 7311.00 | 27.94 | 18.01 | 45.95 | 74.00 | -28.05 | Vertical |
| 9748.00 | 28.64 | 23.79 | 52.43 | 74.00 | -21.57 | Vertical |
| 12185.00 | * | | | 74.00 | | Vertical |
| 14622.00 | * | | | 74.00 | | Vertical |
| 4874.00 | 27.56 | 15.41 | 42.97 | 74.00 | -31.03 | Horizontal |
| 7311.00 | 28.86 | 18.01 | 46.87 | 74.00 | -27.13 | Horizontal |
| 9748.00 | 28.96 | 23.79 | 52.75 | 74.00 | -21.25 | Horizontal |
| 12185.00 | * | | | 74.00 | | Horizontal |
| 14622.00 | * | | | 74.00 | | Horizontal |

Average value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 4874.00 | 18.00 | 15.41 | 33.41 | 54.00 | -20.59 | Vertical |
| 7311.00 | 19.26 | 18.01 | 37.27 | 54.00 | -16.73 | Vertical |
| 9748.00 | 19.89 | 23.79 | 43.68 | 54.00 | -10.32 | Vertical |
| 12185.00 | * | | | 54.00 | | Vertical |
| 14622.00 | * | | | 54.00 | | Vertical |
| 4874.00 | 19.67 | 15.41 | 35.08 | 54.00 | -18.92 | Horizontal |
| 7311.00 | 19.95 | 18.01 | 37.96 | 54.00 | -16.04 | Horizontal |
| 9748.00 | 18.68 | 23.79 | 42.47 | 54.00 | -11.53 | Horizontal |
| 12185.00 | * | | | 54.00 | | Horizontal |
| 14622.00 | * | | | 54.00 | | Horizontal |

Test Results (Above 1000MHz)

| | |
|-------------------------|-----------------------|
| Test Mode: 802.11b Mode | Test channel: Highest |
|-------------------------|-----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 4924.00 | 27.72 | 15.51 | 43.23 | 74.00 | -30.77 | Vertical |
| 7386.00 | 28.64 | 17.97 | 46.61 | 74.00 | -27.39 | Vertical |
| 9848.00 | 29.45 | 23.82 | 53.27 | 74.00 | -20.73 | Vertical |
| 12310.00 | * | | | 74.00 | | Vertical |
| 14772.00 | * | | | 74.00 | | Vertical |
| 4924.00 | 26.95 | 15.51 | 42.46 | 74.00 | -31.54 | Horizontal |
| 7386.00 | 27.82 | 17.97 | 45.79 | 74.00 | -28.21 | Horizontal |
| 9848.00 | 28.56 | 23.82 | 52.38 | 74.00 | -21.62 | Horizontal |
| 12310.00 | * | | | 74.00 | | Horizontal |
| 14772.00 | * | | | 74.00 | | Horizontal |

Average value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 4924.00 | 17.63 | 15.51 | 33.14 | 54.00 | -20.86 | Vertical |
| 7386.00 | 18.56 | 17.97 | 36.53 | 54.00 | -17.47 | Vertical |
| 9848.00 | 19.45 | 23.82 | 43.27 | 54.00 | -10.73 | Vertical |
| 12310.00 | * | | | 54.00 | | Vertical |
| 14772.00 | * | | | 54.00 | | Vertical |
| 4924.00 | 17.31 | 15.51 | 32.82 | 54.00 | -21.18 | Horizontal |
| 7386.00 | 18.29 | 17.97 | 36.26 | 54.00 | -17.74 | Horizontal |
| 9848.00 | 18.17 | 23.82 | 41.99 | 54.00 | -12.01 | Horizontal |
| 12310.00 | * | | | 54.00 | | Horizontal |
| 14772.00 | * | | | 54.00 | | Horizontal |

Remark:

1. During the test, pre-scan the 802.11b,g,n(HT20) mode, and found the 802.11b mode is worse case , the report only record this mode.
2. Level =Read level + Factor
3. “*”, means this data is the too weak instrument of signal is unable to test.

Radiated Band Edge:

| | |
|-------------------------|----------------------|
| Test Mode: 802.11b Mode | Test channel: Lowest |
|-------------------------|----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 2386.08 | 45.03 | 9.72 | 54.75 | 74.00 | -19.25 | Horizontal |
| 2390.00 | 41.39 | 9.73 | 51.12 | 74.00 | -22.88 | Horizontal |
| 2386.44 | 42.59 | 9.72 | 52.31 | 74.00 | -21.69 | Vertical |
| 2390.00 | 40.11 | 9.73 | 49.84 | 74.00 | -24.16 | Vertical |

Average value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|----------------|---------------|-----------------|---------------------|-----------------|--------------|
| 2386.08 | 34.06 | 9.72 | 43.78 | 54.00 | -10.22 | Horizontal |
| 2390.00 | 28.67 | 9.73 | 38.40 | 54.00 | -15.60 | Horizontal |
| 2386.44 | 31.06 | 9.72 | 40.78 | 54.00 | -13.22 | Vertical |
| 2390.00 | 27.33 | 9.73 | 37.06 | 54.00 | -16.94 | Vertical |

| | |
|-------------------------|-----------------------|
| Test Mode: 802.11b Mode | Test channel: Highest |
|-------------------------|-----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 2483.50 | 44.58 | 9.91 | 54.49 | 74.00 | -19.51 | Horizontal |
| 2483.65 | 45.35 | 9.91 | 55.26 | 74.00 | -18.74 | Horizontal |
| 2483.50 | 43.19 | 9.91 | 53.10 | 74.00 | -20.90 | Vertical |
| 2484.00 | 45.47 | 9.91 | 55.38 | 74.00 | -18.62 | Vertical |

Average value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|----------------|---------------|-----------------|---------------------|-----------------|--------------|
| 2483.50 | 34.26 | 9.91 | 44.17 | 54.00 | -9.83 | Horizontal |
| 2483.65 | 34.57 | 9.91 | 44.48 | 54.00 | -9.52 | Horizontal |
| 2483.50 | 33.29 | 9.91 | 43.20 | 54.00 | -10.80 | Vertical |
| 2484.00 | 33.24 | 9.91 | 43.15 | 54.00 | -10.85 | Vertical |

Remark:

1. Level = Read level + Factor

Radiated Band Edge:

| | |
|-------------------------|----------------------|
| Test Mode: 802.11g Mode | Test channel: Lowest |
|-------------------------|----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 2389.54 | 57.26 | 9.73 | 66.99 | 74.00 | -7.01 | Horizontal |
| 2390.00 | 58.34 | 9.73 | 68.07 | 74.00 | -5.93 | Horizontal |
| 2389.92 | 54.22 | 9.73 | 63.95 | 74.00 | -10.05 | Vertical |
| 2390.00 | 54.19 | 9.73 | 63.92 | 74.00 | -10.08 | Vertical |

Average value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 2389.54 | 39.26 | 9.73 | 48.99 | 54.00 | -5.01 | Horizontal |
| 2390.00 | 39.87 | 9.73 | 49.60 | 54.00 | -4.40 | Horizontal |
| 2389.92 | 34.85 | 9.73 | 44.58 | 54.00 | -9.42 | Vertical |
| 2390.00 | 35.77 | 9.73 | 45.50 | 54.00 | -8.50 | Vertical |

| | |
|-------------------------|-----------------------|
| Test Mode: 802.11g Mode | Test channel: Highest |
|-------------------------|-----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 2483.50 | 61.06 | 9.91 | 70.97 | 74.00 | -3.03 | Horizontal |
| 2483.55 | 60.89 | 9.91 | 70.80 | 74.00 | -3.20 | Horizontal |
| 2483.50 | 58.26 | 9.91 | 68.17 | 74.00 | -5.83 | Vertical |
| 2483.60 | 59.73 | 9.91 | 69.64 | 74.00 | -4.36 | Vertical |

Average value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|----------------|---------------|-----------------|---------------------|-----------------|--------------|
| 2483.50 | 43.26 | 9.91 | 53.17 | 54.00 | -0.83 | Horizontal |
| 2483.55 | 43.22 | 9.91 | 53.13 | 54.00 | -0.87 | Horizontal |
| 2483.50 | 42.71 | 9.91 | 52.62 | 54.00 | -1.38 | Vertical |
| 2483.60 | 42.39 | 9.91 | 52.30 | 54.00 | -1.70 | Vertical |

Remark:

1. Level = Read level + Factor

Radiated Band Edge:

| | |
|---------------------------|----------------------|
| Test Mode: 802.11n20 Mode | Test channel: Lowest |
|---------------------------|----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 2389.92 | 59.28 | 9.72 | 69.00 | 74.00 | -5.00 | Horizontal |
| 2390.00 | 59.71 | 9.73 | 69.44 | 74.00 | -4.56 | Horizontal |
| 2389.92 | 56.06 | 9.73 | 65.79 | 74.00 | -8.21 | Vertical |
| 2390.00 | 55.17 | 9.73 | 64.90 | 74.00 | -9.10 | Vertical |

Average value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|----------------|---------------|-----------------|---------------------|-----------------|--------------|
| 2389.92 | 40.16 | 9.72 | 49.88 | 54.00 | -4.12 | Horizontal |
| 2390.00 | 40.37 | 9.73 | 50.10 | 54.00 | -3.90 | Horizontal |
| 2389.92 | 36.91 | 9.73 | 46.64 | 54.00 | -7.36 | Vertical |
| 2390.00 | 37.29 | 9.73 | 47.02 | 54.00 | -6.98 | Vertical |

| | |
|---------------------------|-----------------------|
| Test Mode: 802.11n20 Mode | Test channel: Highest |
|---------------------------|-----------------------|

Peak value:

| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|---------------|----------------|---------------------|-----------------|--------------|
| 2483.50 | 63.15 | 9.91 | 73.06 | 74.00 | -0.94 | Horizontal |
| 2483.60 | 63.29 | 9.91 | 73.20 | 74.00 | -0.80 | Horizontal |
| 2483.50 | 61.05 | 9.91 | 70.96 | 74.00 | -3.04 | Vertical |
| 2484.00 | 62.41 | 9.91 | 72.32 | 74.00 | -1.68 | Vertical |

Average value:

| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|----------------|---------------|-----------------|---------------------|-----------------|--------------|
| 2483.50 | 43.26 | 9.91 | 53.17 | 54.00 | -0.83 | Horizontal |
| 2483.60 | 43.15 | 9.91 | 53.06 | 54.00 | -0.94 | Horizontal |
| 2483.50 | 42.87 | 9.91 | 52.78 | 54.00 | -1.22 | Vertical |
| 2484.00 | 42.36 | 9.91 | 52.27 | 54.00 | -1.73 | Vertical |

Remark:

1. Level = Read level + Factor

5. Antenna Requirement

5.1. Test Standard and Requirement

| Test Standard | FCC Part15 Section 15.203 /247(c) |
|---------------|---|
| Requirement | <p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p> |

5.2. Antenna Connected Construction

The antenna is a Steel sheet antenna which permanently attached, and the best case gain of the antenna is 4.27 dBi It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files for Test Setup Photos of the EUT.

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files for External Photos of the EUT.

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files for Internal Photos of the EUT.

