Maximum Permissible Exposure

Applicable Standard

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1) **For BT:** The maximum output power for antenna is 6.33dBm (4.30mW) at 2480MHz, 2dBi antenna gain(with 1.58 numeric antenna gain.)

For BLE: The maximum output power for antenna is 3.58dBm (2.28mW) at 2480MHz, 2dBi antenna gain(with 1.58 numeric antenna gain.)

For 2.4G WIFI: The maximum output power for antenna is 21.40dBm (138.04mW) at 2462MHz, 5.01dBi antenna gain(with 3.17 numeric antenna gain.)

For Band 1: The maximum output power for antenna is 17.84dBm (60.81mW) at 5180MHz, 5.01dBi antenna gain(with 3.17 numeric antenna gain.)

For Band 2A: The maximum output power for antenna is 18.11dBm (64.71mW) at 5320MHz, 5.01dBi antenna gain(with 3.17 numeric antenna gain.)

For Band 2C: The maximum output power for antenna is 17.64dBm (58.08mW) at 5600MHz, 5.01dBi antenna gain(with 3.17 numeric antenna gain.)

For Band 3: The maximum output power for antenna is 17.58dBm (57.28mW) at 5785MHz, 5.01dBi antenna gain(with 3.17 numeric antenna gain.)

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Substituting the MPE safe distance using d=20cm into above equation.

Yields: S=0.000199*P*G

Maximum Emissions Level					
Mode	Power(mW)	numeric antenna gain	Power density (mW/cm²)	Limit (mW/cm²)	Result
вт	4.30	1.58	0.001352		
BLE	2.28	1.58	0.000717		
2.4G WIFI	138.04	3.17	0.087080		
Band 1	60.81	3.17	0.038361	1.0	PASS
Band 2A	64.71	3.17	0.040821		
Band 2C	58.08	3.17	0.036639		
Band 3	57.28	3.17	0.036134		