

User's Manual

Electronic Key

FCC ID: 2AOKM- G2ABC

IC: 24223-G2ABC

MODEL: RT-G0812E, RT-G0811E, RT-G0800E, RT-G8506E, RT-G0797E

This remote has lock, unlock, power back door, Remote Start, panic buttons; you can open or close the vehicle with the remote transmitter.

LOCK Button:

When you press the LOCK button, it locks all the doors

UNLOCK Button:

Pressing the button unlocks the driver's door. Pressing the button again within 5 seconds unlocks the other doors.

LIFT GATE Button:

Pressing the LIFTGATE button twice on the remote opens and closes the LIFTGATE.

LIFT Glass Buttons:

Pressing LIFT Glass buttons twice within five seconds on the remote opens and closes the LIFT Glass.

REMOTE START Button:

Press the remote start button twice within 5 seconds. The vehicle will stay in the Remote Start mode for a 15-minute cycle. Press and release remote start button once to exit Remote Start mode.

PANIC Button:

When you press the PANIC button, the vehicle will start sounding the horn and flashing the hazard lamp. To stop the alarm, press any button on the electronic key.

TRUNK Button:

Pressing the TRUNK button twice on the remote opens and closes the trunk.

HATCH Button:

Pressing the trunk or hatch button opens and closes the hatch.

FCC COMPLIANCE STATEMENT:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

IC WARNING:

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

(1) This device may not cause interference.

(2) This device must accept any interference, including interference that may cause undesired operation of the device

ADVERTENCIA IC

Cet appareil contient des émetteurs / récepteurs exemptés de licence conformes aux RSS (RSS)d'Innovation, Sciences et Développement économique Canada. Le fonctionnement est soumis auxdeux conditions suivantes :

(1) Cet appareil ne doit pas causer d'interférences.

(2) Cet appareil doit accepter toutes les interférences, y compris celles susceptibles de provoquer un fonctionnement indésirable de l'appareil.