

## **User's Manual**

Electronic Key

FCC ID: 2AOKM-NI16

IC: 24223-NI16

MODEL: RT-N1020

This remote has lock, unlock, trunk, remote start, and panic buttons; you can lock and unlock the vehicle doors and trunk with the remote transmitter as well as start the engine remotely.

### **LOCK Button:**

When you press the LOCK button, it locks all the doors.

### **UNLOCK Button:**

Pressing the button unlocks the driver's door. Pressing the button again within 5 seconds unlocks the other doors.

### **TRUNK Button:**

Pressing the button opens and closes the trunk.

### **REMOTE START Button:**

Press the remote start button twice within 5 seconds. The vehicle will stay in the Remote Start mode for a 15-minute cycle. Press and release remote start button once to exit Remote Start mode.

### **PANIC Button:**

When you press the PANIC button, the vehicle will start sounding the horn and flashing the hazard lamp. To stop the alarm, press any button on the electronic key.

### **FCC COMPLIANCE STATEMENT:**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

### **IC WARNING:**

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

(1) This device may not cause interference.  
(2) This device must accept any interference, including interference that may cause undesired operation of the device

### **ADVERTENCIA IC**

Cet appareil contient des émetteurs / récepteurs exemptés de licence conformes aux RSS (RSS)d'Innovation, Sciences et Développement économique Canada. Le fonctionnement est soumis auxdeux conditions suivantes :

(1) Cet appareil ne doit pas causer d'interférences.  
(2) Cet appareil doit accepter toutes les interférences, y compris celles susceptibles de provoquer un fonctionnement indésirable de l'appareil.