



RF Exposure Evaluation Declaration

FCC ID: 2AOLGVS332I
APPLICANT: Honeywell, spol, s.r.o.-HTS CZ o.z.
Application Type: Certification
Product: Hearing protection headset
Model No.: VS332i
Brand Name: Honeywell
FCC Classification: Digital Transmission System (DTS)
FCC Part 15 Spread Spectrum Transmitter (DSS)
Test Procedure(s): KDB 447498 D01v06

Reviewed By:

Jame Yuan

(Jame Yuan)

Approved By:

Robin Wu

(Robin Wu)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1906RSU033-U3	Rev. 01	Initial Report	07-26-2019	Valid

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	Hearing protection headset
Model No.:	VS332i
Brand Name:	Honeywell
Bluetooth Version:	v5.0 single mode (BLE Only)
Bluetooth Version:	v5.0 single mode (Basic and EDR Only)
RFID Specification:	902MHz ~ 928MHz (Passive)
Accessories	
Battery:	Model No.: 30001-10 Capacitance: 2.7Wh, 750mAh Rated Voltage: 3.6V

Note: This device has two Bluetooth modules located on the right and left side of the headset.

1.2. Radio Specification

Frequency Range:	2402~2480MHz
Number of Channels:	For Bluetooth: 79 For BT-LE: 40
Channel Spacing:	For Bluetooth: 1MHz For BT-LE: 2MHz
Type of Modulation:	For Bluetooth: 1Mbps (GFSK), 2Mbps (Pi/4 DQPSK), 3Mbps (8DPSK) For BT-LE: GFSK
Data Rate:	Up to 2Mbps
Antenna Type:	Chip Antenna
Antenna Gain:	1.5dBi

2. RF Exposure Evaluation

2.1. Limits

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in Note 1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

Note: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] * \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2.2. Test Result of RF Exposure Evaluation

Product	Hearing Protection Headset
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum Output Power		SAR Test Exclusion Threshold (mW)
		(dBm)	(mW)	
Bluetooth-EDR	2402 ~ 2480	5.19	3.30	10
Bluetooth-LE	2402 ~ 2480	4.39	2.75	10

Note 1: Per FCC KDB 447498 D01v06, the SAR exclusion threshold for distances < 50mm is defined by the following equation:

$$\frac{P}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency (GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth and the antenna to use separation distance, Bluetooth SAR was not required;

For Bluetooth-EDR, $\left(\frac{3.30\text{mW}}{5}\right) * \sqrt{2.480} = 1.04 < 3.00$

For Bluetooth-LE, $\left(\frac{2.75\text{mW}}{5}\right) * \sqrt{2.402} = 0.85 < 3.00$

Both of the Bluetooth-EDR and Bluetooth-LE can transmit simultaneously.

The Max $P_d = 1.04 + 0.85 = 1.89 < 3.0$

Note 2: When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

_____ The End _____

Appendix A - EUT Photograph

Refer to "1906RSU033-UE" file.