

APPLICATION CERTIFICATION FCC Part 15C

On Behalf of

TZUMI Electronics, LLC

POP SOLO KARAOKE MICROPHONE

Model No.: 6979, 6947, 6948, 6980, 6954, 6955, KM1002, 4955, 4956

FCC ID: 2AON7-6979

Prepared for : TZUMI Electronics, LLC
Address : 16 EAST, 34TH STREET, 16TH FLOOR, NEW YORK, United States

Prepared by : Shenzhen Accurate Technology Co., Ltd.
Address : 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report No. : ATE20191068
Date of Test : July 19-July 23, 2019
Date of Report : July 25, 2019

TABLE OF CONTENTS

Description	Page
Test Report Certification	
TABLE OF CONTENTS	2
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Accessory and Auxiliary Equipment	5
1.3. Description of Test Facility	6
1.4. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode	8
3.2. Configuration and peripherals	8
4. FREQUENCY HOPPING SYSTEM REQUIREMENTS	9
4.1. Standard and Limit	9
4.2. EUT Pseudorandom Frequency Hopping Sequence.....	9
4.3. Frequency Hopping System.....	10
5. TEST PROCEDURES AND RESULTS	11
6. 20DB BANDWIDTH TEST	12
6.1. Block Diagram of Test Setup.....	12
6.2. The Requirement For Section 15.247(a)(1).....	12
6.3. EUT Configuration on Measurement	12
6.4. Operating Condition of EUT	12
6.5. Test Procedure	12
6.6. Test Result	13
7. CARRIER FREQUENCY SEPARATION TEST	17
7.1. Block Diagram of Test Setup.....	17
7.2. The Requirement For Section 15.247(a)(1).....	17
7.3. EUT Configuration on Measurement	17
7.4. Operating Condition of EUT	17
7.5. Test Procedure	18
7.6. Test Result	18
8. NUMBER OF HOPPING FREQUENCY TEST	22
8.1. Block Diagram of Test Setup.....	22
8.2. The Requirement For Section 15.247(a)(1)(iii).....	22
8.3. EUT Configuration on Measurement	22
8.4. Operating Condition of EUT	22
8.5. Test Procedure	22
8.6. Test Result	23
9. DWELL TIME TEST	25
9.1. Block Diagram of Test Setup.....	25
9.2. The Requirement For Section 15.247(a)(1)(iii).....	25
9.3. EUT Configuration on Measurement	25
9.4. Operating Condition of EUT	25

9.5.	Test Procedure	25
9.6.	Test Result	26
10.	MAXIMUM PEAK OUTPUT POWER TEST	30
10.1.	Block Diagram of Test Setup.....	30
10.2.	The Requirement For Section 15.247(b)(1).....	30
10.3.	EUT Configuration on Measurement	30
10.4.	Operating Condition of EUT	30
10.5.	Test Procedure	30
10.6.	Test Result	31
11.	RADIATED EMISSION TEST	35
11.1.	Block Diagram of Test Setup.....	35
11.2.	The Limit For Section 15.247(d)	36
11.3.	Restricted bands of operation	37
11.4.	Configuration of EUT on Measurement	37
11.5.	Operating Condition of EUT	38
11.6.	Test Procedure	38
11.7.	Data Sample.....	39
11.8.	Test Result	39
12.	BAND EDGE COMPLIANCE TEST	52
12.1.	Block Diagram of Test Setup.....	52
12.2.	The Requirement For Section 15.247(d)	52
12.3.	EUT Configuration on Measurement	52
12.4.	Operating Condition of EUT	52
12.5.	Test Procedure	53
12.6.	Test Result	53
13.	AC POWER LINE CONDUCTED EMISSION TEST	63
13.1.	Block Diagram of Test Setup.....	63
13.2.	Test Limits	64
13.3.	Configuration of EUT on Measurement	64
13.4.	Operating Condition of EUT	64
13.5.	Test Procedure	64
13.6.	Data Sample.....	65
13.7.	Test Result	65
14.	ANTENNA REQUIREMENT.....	70
14.1.	The Requirement	70
14.2.	Antenna Construction	70

Test Report Certification

Applicant : TZUMI Electronics, LLC
Address : 16 EAST, 34TH STREET, 16TH FLOOR, NEW YORK, United States
EUT Description : POP SOLO KARAOKE MICROPHONE
Model No. : 6979, 6947, 6948, 6980, 6954, 6955, KM1002, 4955, 4956

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.10: 2013


The device described above is tested by Shenzhen Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and Shenzhen Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Shenzhen Accurate Technology Co., Ltd.

Date of Test : July 19-July 23, 2019
Date of Report : July 25, 2019

Test Engineer : 
(Ben Jin, Engineer)

Prepared by : 
(Star Yang, Engineer)

Approved & Authorized Signer : 
(Sean Liu, Manager)



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Model Number	:	6979, 6947, 6948, 6980, 6954, 6955, KM1002, 4955, 4956 (Note: We hereby state that these models are identical in interior structure, electrical circuits and components, It's just that the appearance shape is different, Therefore, only model 6979 is for tested.)
Bluetooth version	:	V5.0 (BR+EDR)
Frequency Range	:	2402MHz-2480MHz
Number of Channels	:	79
Antenna Gain(Max)	:	-0.58dBi
Antenna type	:	PCB antenna
Modulation mode	:	GFSK, $\pi/4$ DQPSK
Hardware version	:	V1.0
Software version	:	V1.0
Trade Mark	:	TZUMI
Power Supply	:	DC 3.7V (Powered by Lithium battery) or DC 5V (Powered by charging port)
Applicant Address	:	TZUMI Electronics, LLC 16 EAST, 34TH STREET, 16TH FLOOR, NEW YORK, United States
Manufacturer Address	:	Shenzhen Kinlan Technology Company Limited West of 3F, Building A4, Yinlong Industrial Park, No.292 Shenshan Road, Longgang District, Shenzhen, Guangdong, China

1.2. Accessory and Auxiliary Equipment

AC/DC Power Adapter: (provided by laboratory)	:	Model: TEKA006-0501000UKU
		Input: 100-240V~50/60Hz 0.3A
		Output: DC 5V/1A

1.3. Description of Test Facility

EMC Lab	:	Recognition of accreditation by Federal Communications Commission (FCC) The Designation Number is CN1189 The Registration Number is 708358
		Listed by Innovation, Science and Economic Development Canada (ISED) The Registration Number is 5077A-2
		Accredited by China National Accreditation Service for Conformity Assessment (CNAS) The Registration Number is CNAS L3193
		Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01
Name of Firm	:	Shenzhen Accurate Technology Co., Ltd.
Site Location	:	1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

1.4. Measurement Uncertainty

Radiated Emission Expanded Uncertainty (9kHz-30MHz)	:	U=2.66dB, k=2
Radiated Emission Expanded Uncertainty (30MHz-1000MHz)	:	U=4.28dB, k=2
Radiated Emission Expanded Uncertainty (1G-18GHz)	:	U=4.98dB, k=2
Radiated Emission Expanded Uncertainty (18G-26.5GHz)	:	U=5.06dB, k=2
Conduction Emission Expanded Uncertainty (Mains ports, 9kHz-30MHz)	:	U=2.72dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 05, 2019	One Year
EMI Test Receiver	Rohde&Schwarz	ESR	101817	Jan. 05, 2019	One Year
Spectrum Analyzer	Rohde&Schwarz	FSV-40	101495	Jan. 05, 2019	One Year
Pre-Amplifier	Compliance Direction	RSU-M2	38322	Jan. 05, 2019	One Year
Pre-Amplifier	Agilent	8447D	294A10619	Jan. 05, 2019	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 05, 2019	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 05, 2019	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 05, 2019	One Year
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 05, 2019	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 05, 2019	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18G-10SS	N/A	Jan. 05, 2019	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2485-237 5/2510-60/11SS	N/A	Jan. 05, 2019	One Year
RF Coaxial Cable (Conducted Emission)	SUHNER	N-2m	No.2	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	RESENBERGER	N-12m	No.11	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	RESENBERGER	N-0.5m	No.12	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	SUHNER	N-2m	No.13	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	SUHNER	N-0.5m	No.15	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	SUHNER	N-2m	No.16	Jan. 05, 2019	One Year
RF Coaxial Cable (Radiated Emission)	RESENBERGER	N-6m	No.17	Jan. 05, 2019	One Year
Temporary antenna connector	NTGS	14AE	N/A	July 23, 2019	N/A
Conducted Emission Measurement Software: ES-K1 V1.71					
Radiated Emission Measurement Software: EZ_EMV V1.1.4.2					

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

3. OPERATION OF EUT DURING TESTING

3.1. Operating Mode


The mode is used: Transmitting mode
Low Channel: 2402MHz
Middle Channel: 2441MHz
High Channel: 2480MHz
Hopping

Note: The equipment under test (EUT) was tested under fully-charged battery.
The Bluetooth has been tested under continuous transmission mode.

EUT is connected to a computer through the usb-serial controller tool and Use test software to set the test mode.

Test software is (FCCAssist_2.4)

3.2. Configuration and peripherals



4. FREQUENCY HOPPING SYSTEM REQUIREMENTS

4.1. Standard and Limit

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

4.2. EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 34, 51, 72, 09, 01, 64, 22, 33, 41, 32, 47, 65, 73, 53, 69, 06, 17, 04, 20, 36, 52, 38, 66, 70, 78, 68, 76, 21, 29, 10, 26, 49, 00, 58, 44, 59, 75, 13, 03, 14, 11, 35, 43, 37, 50, 61, 77, 55, 71, 02, 23, 07, 27, 39, 54, 46, 48, 15, 63, 62, 67, 25, 31, 12, 28, 19, 60, 42, 57, 74, 16, 05, 18, 30, 45, etc.

The system receiving have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

4.3.Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.


This device was tested with a bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements FCC Part 15.247 rule.

5. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.207	AC Power Line Conducted Emissions Limits Test	Compliant
Section 15.203	Antenna Requirement	Compliant

6. 20DB BANDWIDTH TEST

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.247(a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.5.2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.

6.5.3. RBW shall be in the range of 1% to 5% of the OBW and VBW shall be approximately three times RBW.

6.5.4. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

6.6. Test Result

Test Lab: Shielding room


Test Engineer: Ben

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	$\Pi/4$ -DQPSK 20dB Bandwidth (MHz)	Result
Low	2402	1.050	1.332	Pass
Middle	2441	1.044	1.350	Pass
High	2480	1.050	1.344	Pass

The spectrum analyzer plots are attached as below.


GFSK Mode

Low channel




Date: 23.JUL.2019 13:28:08

Middle channel



Date: 23.JUL.2019 13:28:47


High channel



Date: 23.JUL.2019 13:29:28


Π/4-DQPSK Mode

Low channel



Date: 23.JUL.2019 13:32:19


Middle channel



Date: 23.JUL.2019 13:31:42

7. CARRIER FREQUENCY SEPARATION TEST

7.1. Block Diagram of Test Setup



7.2. The Requirement For Section 15.247(a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

7.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 3 MHz.

7.5.3. Set the adjacent channel of the EUT maxhold another trace.

7.5.4. Measurement the channel separation

7.6. Test Result

Test Lab: Shielding room

Test Engineer: Ben

GFSK


Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2403			
Middle	2440	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2441			
High	2479	0.996	25KHz or 2/3*20dB bandwidth	Pass
	2480			

Π/4-DQPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.020	25KHz or 2/3*20dB bandwidth	Pass
	2403			
Middle	2440	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2441			
High	2479	1.014	25KHz or 2/3*20dB bandwidth	Pass
	2480			


GFSK Mode

Low channel




Date: 23.JUL.2019 11:12:19

Middle channel



Date: 23.JUL.2019 11:15:33


High channel



Date: 23.JUL.2019 11:16:35


$\Pi/4$ -DQPSK Mode

Low channel




Date: 23.JUL.2019 11:13:37

Middle channel



Date: 23.JUL.2019 11:14:48


High channel



Date: 23.JUL.2019 11:17:35

8. NUMBER OF HOPPING FREQUENCY TEST

8.1. Block Diagram of Test Setup



8.2. The Requirement For Section 15.247(a)(1)(iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz.

8.5.3. Max hold, view and count how many channel in the band.

8.6. Test Result


Test Lab: Shielding room

Test Engineer: Ben

Total number of hopping channel	Measurement result(CH)	Limit(CH)	Result
	79	≥15	Pass


The spectrum analyzer plots are attached as below.

Number of hopping channels (GFSK Mode)



Date: 23.JUL.2019 11:34:17


Number of hopping channels ($\Pi/4$ -DQPSK Mode)



Date: 23.JUL.2019 11:31:51

9. DWELL TIME TEST

9.1. Block Diagram of Test Setup



9.2. The Requirement For Section 15.247(a)(1)(iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

9.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set center frequency of spectrum analyzer = operating frequency.

9.5.3. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=5ms, 10ms, 15ms. Get the pulse time.

9.5.4. Repeat above procedures until all frequency measured were complete.

9.6. Test Result

Test Lab: Shielding room

Test Engineer: Ben

GFSK Mode (Worse case)

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.420	134.40	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
DH3	2441	1.660	265.60	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
DH5	2441	2.860	305.07	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

$\Pi/4$ -DQPSK Mode (Worse case)


Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
2-DH1	2441	0.420	134.40	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2*79)) \times 31.6$				
2-DH3	2441	1.600	256.00	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4*79)) \times 31.6$				
2-DH5	2441	2.840	302.93	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6*79)) \times 31.6$				

Note: We tested GFSK mode and $\Pi/4$ -DQPSK mode the low, middle and high channel and recorded the worse case data for all test mode.

The spectrum analyzer plots are attached as below.


GFSK Mode

DH1 Middle channel




Date: 23.JUL.2019 12:54:29

DH3 Middle channel



Date: 23.JUL.2019 11:44:52


DH5 Middle channel



Date: 23.JUL.2019 11:45:38


Π/4-DQPSK Mode

2-DH1 Middle channel




Date: 23.JUL.2019 12:50:02

2-DH3 Middle channel



Date: 23.JUL.2019 11:52:29


2-DH5 Middle channel



Date: 23.JUL.2019 11:51:33

10. MAXIMUM PEAK OUTPUT POWER TEST

10.1. Block Diagram of Test Setup



10.2. The Requirement For Section 15.247(b)(1)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.4. Operating Condition of EUT

10.4.1. Setup the EUT and simulator as shown as Section 10.1.

10.4.2. Turn on the power of all equipment.

10.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

10.5. Test Procedure

10.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

10.5.2. Set RBW of spectrum analyzer to 3MHz and VBW to 10MHz.

10.5.3. Measurement the maximum peak output power.

10.6. Test Result

Test Lab: Shielding room

Test Engineer: Frank

GFSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits (dBm/W)	Result
Low	2402	-0.88/0.0008	21 / 0.125	Pass
Middle	2441	-1.34/0.0007	21 / 0.125	Pass
High	2480	-2.01/0.0006	21 / 0.125	Pass


II/4-DQPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits (dBm/W)	Result
Low	2402	-0.85/0.0008	21 / 0.125	Pass
Middle	2441	-1.31/0.0007	21 / 0.125	Pass
High	2480	-2.01/0.0006	21 / 0.125	Pass

The spectrum analyzer plots are attached as below.


GFSK Mode

Low channel




Date: 23.JUL.2019 11:10:10

Middle channel



Date: 23.JUL.2019 11:09:41


High channel



Date: 23.JUL.2019 11:09:13


Π/4-DQPSK Mode

Low channel




Date: 23.JUL.2019 11:06:49

Middle channel



Date: 23.JUL.2019 11:07:42

High channel




Date: 23.JUL.2019 11:08:43

11. RADIATED EMISSION TEST


11.1. Block Diagram of Test Setup

11.1.1. Block diagram of connection between the EUT and peripherals




11.1.2. Semi-Anechoic Chamber Test Setup Diagram


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency 30MHz-1GHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz



11.2. The Limit For Section 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3.Restricted bands of operation

11.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

11.4.Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.5. Operating Condition of EUT

11.5.1. Setup the EUT and simulator as shown as Section 11.1.

11.5.2. Turn on the power of all equipment.

11.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

11.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground (Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground (Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. This EUT was tested in 3 orthogonal positions and the Worst case position data was reported.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

11.7.Data Sample

Frequency (MHz)	Reading (dB μ v)	Factor (dB/m)	Result (dB μ v/m)	Limit (dB μ v/m)	Margin (dB)	Remark
X.XX	28.66	-15.19	13.47	40.0	-26.53	QP

Frequency(MHz) = Emission frequency in MHz

Reading(dB μ v) = Uncorrected Analyzer/Receiver reading

Factor (dB/m) = Antenna factor + Cable Loss – Amplifier gain

Result(dB μ v/m) = Reading(dB μ v) + Factor(dB/m)

Limit (dB μ v/m) = Limit stated in standard

Margin (dB) = Result(dB μ v/m) - Limit (dB μ v/m)

QP = Quasi-peak Reading

Calculation Formula:

Margin(dB) = Result (dB μ V/m)–Limit(dB μ V/m)

Result(dB μ V/m)= Reading(dB μ V)+ Factor(dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit.

11.8.Test Result

Pass.

Test Lab: 3m Anechoic chamber

Test Engineer: Ben

Note: 1.We tested GFSK mode, $\Pi/4$ -DQPSK Mode and recorded the Worse case data ($\Pi/4$ -DQPSK mode) for all test mode.

2. Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and 18 to 26.5GHz.

The spectrum analyzer plots are attached as below.

Below 1GHz




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JPZRLK #1	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/07/20
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:42:43
EUT: KARAOKE MICOPHONE	Engineer Signature: Ben
Mode: TX 2402MHz	Distance: 3m
Model: 6979	
Manufacturer: Kinlan	

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	187.7833	39.80	-25.30	14.50	43.50	-29.00	QP	200	123	
2	285.2611	54.27	-21.87	32.40	46.00	-13.60	QP	200	163	
3	354.6912	37.04	-19.14	17.90	46.00	-28.10	QP	200	195	
4	377.8481	51.26	-18.66	32.60	46.00	-13.40	QP	200	245	
5	478.1394	36.25	-16.65	19.60	46.00	-26.40	QP	200	263	
6	672.3104	36.21	-12.11	24.10	46.00	-21.90	QP	200	312	



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JPZRLK #2
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: KARAOKE MICOPHONE
Mode: TX 2402MHz
Model: 6979
Manufacturer: Kinlan

Polarization: Vertical
Power Source: DC 3.7V
Date: 2019/07/20
Time: 16:43:34
Engineer Signature: Ben
Distance: 3m

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	165.4716	40.68	-26.48	14.20	43.50	-29.30	QP	100	114	
2	181.9380	40.04	-25.84	14.20	43.50	-29.30	QP	100	302	
3	302.8193	43.53	-21.13	22.40	46.00	-23.60	QP	100	145	
4	411.0925	44.51	-18.11	26.40	46.00	-19.60	QP	100	163	
5	544.5202	42.17	-14.97	27.20	46.00	-18.80	QP	100	195	
6	615.7743	38.56	-13.36	25.20	46.00	-20.80	QP	100	215	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JPZRLK #4	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/07/20
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:45:08
EUT: KARAOKE MICOPHONE	Engineer Signature: Ben
Mode: TX 2441MHz	Distance: 3m
Model: 6979	
Manufacturer: Kinlan	

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	182.5784	40.48	-25.78	14.70	43.50	-28.80	QP	200	123	
2	285.2611	48.97	-21.87	27.10	46.00	-18.90	QP	200	163	
3	377.8481	53.16	-18.66	34.50	46.00	-11.50	QP	200	186	
4	478.1394	36.65	-16.65	20.00	46.00	-26.00	QP	200	215	
5	582.1122	34.68	-14.08	20.60	46.00	-25.40	QP	200	236	
6	672.3104	39.01	-12.11	26.90	46.00	-19.10	QP	200	315	



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JPZRLK #3
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: KARAOKE MICOPHONE
Mode: TX 2441MHz
Model: 6979
Manufacturer: Kinlan

Polarization: Vertical
Power Source: DC 3.7V
Date: 2019/07/20
Time: 16:44:23
Engineer Signature: Ben
Distance: 3m

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	155.8771	41.52	-27.52	14.00	43.50	-29.50	QP	100	101	
2	227.0164	44.10	-23.90	20.20	46.00	-25.80	QP	100	126	
3	318.0875	42.68	-20.68	22.00	46.00	-24.00	QP	100	156	
4	337.6661	45.31	-19.81	25.50	46.00	-20.50	QP	100	186	
5	368.6681	43.40	-18.80	24.60	46.00	-21.40	QP	100	216	
6	548.3600	41.45	-14.85	26.60	46.00	-19.40	QP	100	286	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JPZRLK #6
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: KARAOKE MICOPHONE
Mode: TX 2480MHz
Model: 6979
Manufacturer: Kinlan

Polarization: Horizontal
Power Source: DC 3.7V
Date: 2019/07/20
Time: 16:47:00
Engineer Signature: Ben
Distance: 3m

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	168.9970	35.31	-26.11	9.20	43.50	-34.30	QP	200	136	
2	189.1076	43.39	-25.19	18.20	43.50	-25.30	QP	200	186	
3	285.2611	49.97	-21.87	28.10	46.00	-17.90	QP	200	204	
4	377.8481	50.96	-18.66	32.30	46.00	-13.70	QP	200	236	
5	428.7960	33.93	-17.83	16.10	46.00	-29.90	QP	200	296	
6	672.3104	38.81	-12.11	26.70	46.00	-19.30	QP	200	315	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JPZRLK #5	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/07/20
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:46:00
EUT: KARAOKE MICOPHONE	Engineer Signature: Ben
Mode: TX 2480MHz	Distance: 3m
Model: 6979	
Manufacturer: Kinlan	

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	124.4868	42.68	-27.58	15.10	43.50	-28.40	QP	100	102	
2	253.1402	42.96	-23.46	19.50	46.00	-26.50	QP	100	134	
3	312.5482	40.66	-20.86	19.80	46.00	-26.20	QP	100	163	
4	416.9108	39.84	-18.04	21.80	46.00	-24.20	QP	100	186	
5	481.5112	37.99	-16.59	21.40	46.00	-24.60	QP	100	246	
6	533.1611	37.39	-15.29	22.10	46.00	-23.90	QP	100	312	

Above 1GHz



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JP2018 #428

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: KARAOKE MICOPHONE

Mode: TX 2402MHz

Model: 6979

Manufacturer: Kinlan

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/22

Time: 16:40:12

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	97.81	-6.24	91.57	/	/	peak			
2	4804.328	54.61	1.00	55.61	74.00	-18.39	peak			
3	4804.328	47.40	1.00	48.40	54.00	-5.60	AVG	200	163	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #427

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: KARAOKE MICOPHONE

Mode: TX 2402MHz

Model: 6979

Manufacturer: Kinlan

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/22

Time: 16:38:58

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	100.34	-6.24	94.10	/	/	peak			
2	4804.328	55.65	1.00	56.65	74.00	-17.35	peak			
3	4804.328	48.30	1.00	49.30	54.00	-4.70	AVG	150	186	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JP2018 #425	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/07/22
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:35:42
EUT: KARAOKE MICOPHONE	Engineer Signature: Ben
Mode: TX 2441MHz	Distance: 3m
Model: 6979	
Manufacturer: Kinlan	

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.007	97.12	-6.10	91.02	/	/	peak			
2	4881.917	54.09	1.36	55.45	74.00	-18.55	peak			
3	4881.917	46.94	1.36	48.30	54.00	-5.70	AVG	200	136	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #426

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: KARAOKE MICOPHONE

Mode: TX 2441MHz

Model: 6979

Manufacturer: Kinlan

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/22

Time: 16:37:12

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.007	99.87	-6.10	93.77	/	/	peak			
2	4881.917	55.65	1.36	57.01	74.00	-16.99	peak			
3	4881.917	48.34	1.36	49.70	54.00	-4.30	AVG	150	215	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JP2018 #424

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: KARAOKE MICOPHONE

Mode: TX 2480MHz

Model: 6979

Manufacturer: Kinlan

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/22

Time: 16:33:36

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.038	96.72	-5.90	90.82	/	/	peak			
2	4960.146	53.44	1.68	55.12	74.00	-18.88	peak			
3	4960.046	46.22	1.68	47.90	54.00	-6.10	AVG	200	236	



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JP2018 #423

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: KARAOKE MICOPHONE

Mode: TX 2480MHz

Model: 6979

Manufacturer: Kinlan

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/22

Time: 16:31:02

Engineer Signature: Ben

Distance: 3m


Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.038	99.73	-5.90	93.83	/	/	peak			
2	4960.046	55.44	1.68	57.12	74.00	-16.88	peak			
3	4960.046	47.92	1.68	49.60	54.00	-4.40	AVG	150	254	

12. BAND EDGE COMPLIANCE TEST

12.1. Block Diagram of Test Setup



12.2. The Requirement For Section 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

12.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

12.4. Operating Condition of EUT

12.4.1. Setup the EUT and simulator as shown as Section 12.1.

12.4.2. Turn on the power of all equipment.

12.4.3. Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

12.5. Test Procedure

12.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

12.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

12.5.3. The band edges was measured and recorded.

12.6. Test Result

Test Lab: Shielding room

Test Engineer: Ben

Note: Both hopping-on mode and hopping-off mode had been pre-tested, and only the Worse case was recorded in the test report.


Conducted Band Edge Result

Non-hopping mode


Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)	Result
GFSK Mode			
2400.00	34.96	> 20dBc	Pass
2483.50	28.4	> 20dBc	Pass
Π/4-DQPSK Mode			
2400.00	34.15	> 20dBc	Pass
2483.50	29.19	> 20dBc	Pass

The spectrum analyzer plots are attached as below.

GFSK Mode




Date: 23.JUL.2019 11:21:01




Date: 23.JUL.2019 11:24:27

Π/4-DQPSK Mode



Date: 23.JUL.2019 11:22:45



Date: 23.JUL.2019 11:25:48

Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

3. Display the measurement of peak values.

Test Procedure:

The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

Let the EUT work in TX (Hopping off, Hopping on) modes measure it.
We select 2402MHz, 2480MHz TX frequency to transmit(Hopping off mode).
We select 2402-2480MHz TX frequency to transmit(Hopping on mode).

During the radiated emission test, the spectrum analyzer was set with the following configurations:

- 1.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
- 2.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
- 3.All modes of operation were investigated and the Worse case ($\Pi/4$ -DQPSK Mode) emissions are reported.

Test Lab: 3m Anechoic chamber

Test Engineer: Ben

The spectrum analyzer plots are attached as below.




Non-hopping mode
ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: JP2018 #429	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/07/22
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:42:36
EUT: KARAOKE MICOPHONE	Engineer Signature: Ben
Mode: TX 2402MHz	Distance: 3m
Model: 6979	
Manufacturer: Kinlan	

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.05	-6.32	34.73	74.00	-39.27	peak			
2	2390.000	33.82	-6.32	27.50	54.00	-26.50	AVG	200	156	
3	2400.000	59.18	-6.27	52.91	74.00	-21.09	peak			
4	2400.000	50.07	-6.27	43.80	54.00	-10.20	AVG	200	236	

Note: Average measurement with peak detection at No.2&4



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: JP2018 #430	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/07/22
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:44:16
EUT: KARAOKE MICOPHONE	Engineer Signature: Ben
Mode: TX 2402MHz	Distance: 3m
Model: 6979	
Manufacturer: Kinlan	

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.55	-6.32	35.23	74.00	-38.77	peak			
2	2390.000	31.82	-6.32	25.50	54.00	-28.50	AVG	150	176	
3	2400.000	58.89	-6.27	52.62	74.00	-21.38	peak			
4	2400.000	48.97	-6.27	42.70	54.00	-11.30	AVG	150	263	

Note: Average measurement with peak detection at No.2&4




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JP2018 #432	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/07/22
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:47:12
EUT: KARAOKE MICOPHONE	Engineer Signature: Ben
Mode: TX 2480MHz	Distance: 3m
Model: 6979	
Manufacturer: Kinlan	

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.85	-5.89	42.96	74.00	-31.04	peak			
2	2483.500	38.29	-5.89	32.40	54.00	-21.60	AVG	200	165	
3	2500.000	40.63	-5.81	34.82	74.00	-39.18	peak			
4	2500.000	30.51	-5.81	24.70	54.00	-29.30	AVG	200	245	

Note: Average measurement with peak detection at No.2&4




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JP2018 #431	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/07/22
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:45:57
EUT: KARAOKE MICOPHONE	Engineer Signature: Ben
Mode: TX 2480MHz	Distance: 3m
Model: 6979	
Manufacturer: Kinlan	

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	46.90	-5.89	41.01	74.00	-32.99	peak			
2	2483.500	36.29	-5.89	30.40	54.00	-23.60	AVG	150	236	
3	2500.000	40.98	-5.81	35.17	74.00	-38.83	peak			
4	2500.000	30.81	-5.81	25.00	54.00	-29.00	AVG	150	286	

Note: Average measurement with peak detection at No.2&4



Hopping mode
ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JP2018 #434

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: KARAOKE MICOPHONE

Mode: HOPPING

Model: 6979

Manufacturer: Kinlan

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2019/07/22

Time: 16:52:11

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20191068



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.83	-6.32	35.51	74.00	-38.49	peak			
2	2390.000	31.22	-6.32	24.90	54.00	-29.10	AVG	200	145	
3	2400.000	64.19	-6.27	57.92	74.00	-16.08	peak			
4	2400.000	54.17	-6.27	47.90	54.00	-6.10	AVG	200	169	
5	2483.500	41.70	-5.89	35.81	74.00	-38.19	peak			
6	2483.500	32.89	-5.89	27.00	54.00	-27.00	AVG	200	213	
7	2500.000	42.77	-5.81	36.96	74.00	-37.04	peak			
8	2500.000	33.31	-5.81	27.50	54.00	-26.50	AVG	200	296	

Note: Average measurement with peak detection at No.2&4&6&8



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: JP2018 #433

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: KARAOKE MICOPHONE

Mode: HOPPING

Model: 6979

Manufacturer: Kinlan

Polarization: Vertical

Power Source: DC 3.7V


Date: 2019/07/22

Time: 16:49:14

Engineer Signature: Ben

Distance: 3m

Note: Report NO.:ATE20191068




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.83	-6.32	35.51	74.00	-38.49	peak			
2	2390.000	32.62	-6.32	26.30	54.00	-27.70	AVG	150	136	
3	2400.000	64.19	-6.27	57.92	74.00	-16.08	peak			
4	2400.000	54.07	-6.27	47.80	54.00	-6.20	AVG	150	186	
5	2483.500	41.54	-5.89	35.65	74.00	-38.35	peak			
6	2483.500	34.39	-5.89	28.50	54.00	-25.50	AVG	150	215	
7	2500.000	42.17	-5.81	36.36	74.00	-37.64	peak			
8	2500.000	33.91	-5.81	28.10	54.00	-25.90	AVG	150	296	

Note: Average measurement with peak detection at No.2&4&6&8


13.AC POWER LINE CONDUCTED EMISSION TEST

13.1.Block Diagram of Test Setup

13.1.1.Block diagram of connection between the EUT and simulators



13.1.2.Test System Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

13.2. Test Limits

Frequency (MHz)	Limit dB(μV)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

NOTE1: The lower limit shall apply at the transition frequencies.
 NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

13.3. Configuration of EUT on Measurement

The equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

13.4. Operating Condition of EUT

13.4.1. Setup the EUT and simulator as shown as Section 13.1.

13.4.2. Turn on the power of all equipment.

13.4.3. Let the EUT work in test mode and measure it.

13.5. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Measurement. The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

13.6.Data Sample

Frequency (MHz)	Transducer value (dB)	QuasiPeak Level (dBμV)	Average Level (dBμV)	QuasiPeak Limit (dBμV)	Average Limit (dBμV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
X.XX	10.6	25.3	17.0	59.0	49.0	33.4	31.7	Pass

Frequency(MHz) = Emission frequency in MHz

Transducer value(dB) = Insertion loss of LISN + Cable Loss

Level(dBμV) = Quasi-peak Reading/Average Reading + Transducer value

Limit (dBμV) = Limit stated in standard

Margin = Limit (dBμV) - Level (dBμV)

Calculation Formula:

Margin = Limit (dBμV) - Level (dBμV)

13.7.Test Result

Pass.

Test Lab: Shielding room

Test Engineer: Ben

The frequency range from 150kHz to 30MHz is checked.

Maximizing procedure was performed on the six (6) highest emissions of the EUT. Emissions attenuated more than 20 dB below the permissible value are not reported.

All data was recorded in the Quasi-peak and average detection mode.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15 C

EUT: POP SOLO KARAOKE MICROPHONE M/N:6979
 Manufacturer: Kinlan
 Operating Condition: BT Communication
 Test Site: 1#Shielding Room
 Operator: Ben
 Test Specification: N 120V 60Hz
 Comment: Report NO.:ATE20191068
 Start of Test: 7/19/2019 / 1:53:08PM

SCAN TABLE: "V 9K-30MHz fin"

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "ZR0719-04V_fin"

7/19/2019 1:56PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.210000	39.50	10.5	63	23.7	QP	N	GND
0.595000	42.60	10.6	56	13.4	QP	N	GND
1.705000	37.70	10.7	56	18.3	QP	N	GND
3.070000	35.20	10.8	56	20.8	QP	N	GND
10.315000	31.50	10.9	60	28.5	QP	N	GND
14.680000	29.70	10.9	60	30.3	QP	N	GND

MEASUREMENT RESULT: "ZR0719-04V_fin2"

7/19/2019 1:56PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.340000	33.10	10.6	49	16.1	AV	N	GND
0.590000	38.40	10.6	46	7.6	AV	N	GND
1.020000	33.40	10.7	46	12.6	AV	N	GND
3.750000	31.30	10.8	46	14.7	AV	N	GND
11.665000	17.40	10.9	50	32.6	AV	N	GND
17.395000	11.50	10.9	50	38.5	AV	N	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 C

EUT: POP SOLO KARAOKE MICROPHONE M/N:6979
 Manufacturer: Kinlan
 Operating Condition: BT Communication
 Test Site: 1#Shielding Room
 Operator: Ben
 Test Specification: L 120V 60Hz
 Comment: Report NO.:ATE20191068
 Start of Test: 7/19/2019 / 2:02:06PM

SCAN TABLE: "V 9K-30MHz fin"

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "ZR0719-06V_fin"

7/19/2019 2:05PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.340000	42.30	10.6	59	16.9	QP	L1	GND
0.590000	47.30	10.6	56	8.7	QP	L1	GND
1.710000	42.60	10.7	56	13.4	QP	L1	GND
2.390000	40.90	10.8	56	15.1	QP	L1	GND
10.945000	39.10	10.9	60	20.9	QP	L1	GND
13.315000	34.40	10.9	60	25.6	QP	L1	GND

MEASUREMENT RESULT: "ZR0719-06V_fin2"

7/19/2019 2:05PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.340000	36.10	10.6	49	13.1	AV	L1	GND
0.590000	41.20	10.6	46	4.8	AV	L1	GND
1.025000	36.40	10.7	46	9.6	AV	L1	GND
2.390000	29.20	10.8	46	16.8	AV	L1	GND
6.840000	24.20	10.9	50	25.8	AV	L1	GND
15.385000	26.80	10.9	50	23.2	AV	L1	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 C

EUT: POP SOLO KARAOKE MICROPHONE M/N:6979
 Manufacturer: Kinlan
 Operating Condition: BT Communication
 Test Site: 2#Shielding Room
 Operator: Ben
 Test Specification: N 240V 60Hz
 Comment: Report NO.:ATE20191068
 Start of Test: 2019-7-25 / 15:49:33

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TL-0725-01V_fin"

2019-7-25 15:51

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.244000	41.50	10.9	62	20.5	QP	N	GND
0.626000	47.30	11.0	56	8.7	QP	N	GND
1.252000	43.00	11.2	56	13.0	QP	N	GND
2.710000	39.30	11.3	56	16.7	QP	N	GND
8.345000	44.80	11.5	60	15.2	QP	N	GND
12.415000	38.50	11.6	60	21.5	QP	N	GND

MEASUREMENT RESULT: "TL-0725-01V_fin2"

2019-7-25 15:51

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.304000	30.70	10.9	50	19.4	AV	N	GND
0.626000	41.70	11.0	46	4.3	AV	N	GND
2.050000	24.50	11.3	46	21.5	AV	N	GND
2.675000	27.60	11.3	46	18.4	AV	N	GND
6.705000	25.60	11.5	50	24.4	AV	N	GND
13.370000	25.60	11.6	50	24.4	AV	N	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 C

EUT: POP SOLO KARAOKE MICROPHONE M/N:6979
 Manufacturer: Kinlan
 Operating Condition: BT Communication
 Test Site: 2#Shielding Room
 Operator: Ben
 Test Specification: L 240V 60Hz
 Comment: Report NO.:ATE20191068
 Start of Test: 2019-7-25 / 15:51:55

SCAN TABLE: "V 150K-30MHz fin"

Short Description:		_SUB_STD_VTERM2 1.70					
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
150.0 kHz	30.0 MHz	4.5 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008	
Average							



MEASUREMENT RESULT: "TL-0725-02V_fin"

2019-7-25 15:53

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.314000	38.80	10.9	60	21.1	QP	L1	GND
0.626000	40.80	11.0	56	15.2	QP	L1	GND
1.252000	36.30	11.2	56	19.7	QP	L1	GND
4.315000	34.40	11.4	56	21.6	QP	L1	GND
10.055000	42.70	11.6	60	17.3	QP	L1	GND
12.950000	35.30	11.6	60	24.7	QP	L1	GND

MEASUREMENT RESULT: "TL-0725-02V_fin2"

2019-7-25 15:53

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.288000	27.40	10.9	51	23.2	AV	L1	GND
0.658000	37.60	11.1	46	8.4	AV	L1	GND
2.010000	28.50	11.3	46	17.5	AV	L1	GND
4.420000	29.10	11.4	46	16.9	AV	L1	GND
9.065000	27.20	11.6	50	22.8	AV	L1	GND
14.830000	17.40	11.6	50	32.6	AV	L1	GND


14. ANTENNA REQUIREMENT

14.1. The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

14.2. Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Max Antenna gain of EUT is -0.58dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



***** End of Test Report *****