


承认书项目表

NO.	内容 (Contents)	页数 (Number of Page)	页码 (Page Code)
1	承认书封面 (Spec Cover)	1	1
2	承认书项目表 (Spec Item)	1	2
3	工程成品图 (Drawing)	1	3
4	电性测试报告 (Test Reports)	1	4
5	S 参数测试 (S Parameter)	1	5
6	增益测试 (Gain Test)	1	6
7			
8			
9			
10	-	-	-
11	-	-	-
12	-	-	-

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			



60±3mm

3	MX2458N-A01	FPC	FPC 37*10*0.1mm	1
2	R-CB-113B	Coaxial Cable	O.D. 1.13mm Black	1
1	Cl-113	Connector	Mini Connector	1
No.	Part Number	Name	Material	Q'ty

东莞市速波电子有限公司

TITLE:WIFI ANTENNA			
PART NO.:NB3710IPX4-081-LX60		DWG NAME:	
APPROVED BY	CHECKED BY	DESIGNED BY	Tolerance
jeff 2014-03-18	leon 2014-03-18	YD 2014-03-18	UNIT'S: mm SCALE: 1/1 REVISION: A

电性测试报告


Test Reports

Sample Photo	
	
A. Electrical Characteristics	
Frequency	2400 ~ 2500 MHz
S.W.R.	≤ 2.0 @ 2400 ~ 2500 MHz
Antenna Gain	3.43dBi
Impedance	50 Ohm Nominal
Return Loss	-10 dB Max
Radiation	Omni-directional
Cable Loss	2 dB / m Max @ 5000 MHz
Polarization	Linear, Vertical
Admitted Power	1 W
Connector	4代IPEX
Physical Properties	
Antenna Material	FPC
Cable Type	O.D. 0.81mm // 60 mm
Operating Temp.	-10 ~ +60 °C
Storage Temp.	-10 ~ +70 °C

S 参数测试


S Parameter Test

Agilent E5071C




1 Active Ch/Trace 2 Response 3 Stimulus 4 Mkr/Analysis 5 Instr State

Tr1 S44 Log Mag 10.00dB/ Ref 0.000dB



Tr2 S44 SWR 500.0m/ Ref 1.000



1 Start 2 GHz

IFBW 70 kHz

Stop 6 GHz

Off

Hold Stop ExtRef Ready Svc 2013-08-06 10:07

Trigger

Hold

Single

Continuous

Hold

All Channels

Continuous

Disp Channels

Trigger Source

Internal

Trigger Event

On Sweep

Trigger Scope

All Channel




Restart

Tel:0769-33691210 Fax:0769-82381572

增益测试

Gain Test

*Antenna
Radiation
Pattern
VS
Gain*



OTA TEST RESULT

Client	Zhongshan Dashan Photographic Equipment Co.,Ltd.	Test Date	2022/11/1
Product Name	NB3710IPX4-081-LX60	Model	/
Temperature	19℃-21℃	Humidity	70%
Frequency (MHz)	Efficiency (%)	Gain (dBi)	
2400	62.33%	3.19	
2410	61.50%	3.21	
2420	60.28%	3.23	
2430	63.42%	3.16	
2440	64.53%	3.28	
2450	65.50%	3.31	
2460	64.38%	3.43	
2470	64.56%	3.24	
2480	63.56%	3.32	
2490	60.56%	3.14	
2500	62.12%	3.21	