



TEST REPORT

Report Reference No...... : **TRE1712015305** R/C.....: 47178

FCC ID..... : **2A0OFS201**

Applicant's name..... : **Shenzhen Two Monkey technology co. Ltd.**

Address..... : Room 612,Building D,SDG Information Port,No.2 Kefeng Road,Nanshan District, Shenzhen,Guangdong,China

Manufacturer..... : Shenzhen Two Monkey technology co. Ltd.

Address..... : Room 612,Building D,SDG Information Port,No.2 Kefeng Road,Nanshan District, Shenzhen,Guangdong,China

Test item description : **Mobile terminal**

Trade Mark : DOSMONO

Model/Type reference..... : DOSMONO S201

Listed Model(s) : -

Standard : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**

Date of receipt of test sample..... : Dec.15,2017

Date of testing..... : Dec.16,2017 - Jan.02,2018

Date of issue..... : Jan.03,2018

Result..... : **PASS**

Compiled by
(position+printedname+signature)....: File administrators Candy Liu *Candy Liu*

Supervised by
(position+printedname+signature)....: Project Engineer : Edward Pan *Edward Pan*

Approved by
(Position+Printed name+Signature): RF Manager Hans Hu *Hans Hu*

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

1.	<u>TEST STANDARDS AND REPORT VERSION</u>	3
1.1.	Test Standards	3
1.2.	Report version	3
2.	<u>TEST DESCRIPTION</u>	4
3.	<u>SUMMARY</u>	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
4.	<u>TEST ENVIRONMENT</u>	7
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
5.	<u>TEST CONDITIONS AND RESULTS</u>	11
5.1.	Antenna requirement	11
5.2.	Conducted Emissions (AC Main)	12
5.3.	Conducted Peak Output Power	15
5.4.	20 dB Bandwidth	19
5.5.	Carrier Frequencies Separation	23
5.6.	Hopping Channel Number	25
5.7.	Dwell Time	27
5.8.	Pseudorandom Frequency Hopping Sequence	34
5.9.	Restricted band (radiated)	35
5.10.	Band edge and Spurious Emissions (conducted)	40
5.11.	Spurious Emissions (radiated)	56
6.	<u>TEST SETUP PHOTOS</u>	60
7.	<u>EXTERANAL AND INTERNAL PHOTOS</u>	61

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

1.2. Report version

Version No.	Date of issue	Description
00	Jan.03,2018	Original

2. TEST DESCRIPTION

Test Item	Section in CFR 47	Result	Test Engineer
Antenna Requirement	15.203/15.247 (c)	PASS	Zhaohui.ouyang
AC Power Line Conducted Emissions	15.207	PASS	Zhaohui.ouyang
Conducted Peak Output Power	15.247 (b)(1)	PASS	Zhaohui.ouyang
20 dB Bandwidth	15.247 (a)(1)	PASS	Zhaohui.ouyang
Carrier Frequencies Separation	15.247 (a)(1)	PASS	Zhaohui.ouyang
Hopping Channel Number	15.247 (a)(1)	PASS	Zhaohui.ouyang
Dwell Time	15.247 (a)(1)	PASS	Zhaohui.ouyang
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	PASS	Zhaohui.ouyang
Restricted band	15.247(d)/15.205	PASS	Zhaohui.ouyang
Radiated Emissions	15.247(d)/15.209	PASS	Zhaohui.ouyang

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	Shenzhen Two Monkey technology co. Ltd.
Address:	Room 612,Building D,SDG Information Port,No.2 Kefeng Road,Nanshan District, Shenzhen,Guangdong,China
Manufacturer:	Shenzhen Two Monkey technology co. Ltd.
Address:	Room 612,Building D,SDG Information Port,No.2 Kefeng Road,Nanshan District, Shenzhen,Guangdong,China

3.2. Product Description

Name of EUT:	Mobile terminal
Trade Mark:	DOSMONO
Model No.:	DOSMONO S201
Listed Model(s):	-
IMEI 1:	866811030873643
IMEI 2:	866811030875648
Power supply:	DC 4.35V
Adapter information:	Input: 100-240Va.c., 50/60Hz, 0.25A Output: 5Vd.c.,1000mA
Hardware version:	S630-BW-V1.3
Software version:	S630-BW- V1.1.5
Bluetooth	
Version:	Supported BT4.0+EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PIFA antenna
Antenna gain:	1.0dBi

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

Channel	Frequency (MHz)
00	2402
01	2403
⋮	⋮
39	2441
⋮	⋮
77	2479
78	2480

➤ TEST MODE

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit
For AC power line conducted emissions:
The EUT was set to connect with the Bluetooth instrument under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data recorded in the report.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

/	Manufacturer:	/
	Model No.:	/
/	Manufacturer:	/
	Model No.:	/

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.39 dB	(1)
Radiated Emissions 30~1000MHz	4.24 dB	(1)
Radiated Emissions 1~18GHz	5.16 dB	(1)
Radiated Emissions 18~40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.5. Equipments Used during the Test

Conducted Emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	EMI Test Receiver	R&S	ESCI	101247	11/11/2017	11/10/2018
2	Artificial Mains	SCHWARZBECK	NNLK 8121	573	11/11/2017	11/10/2018
3	2-Line V-Network	R&S	ESH3-Z5	100049	11/11/2017	11/10/2018
4	Pulse Limiter	R&S	ESH3-Z2	101488	11/11/2017	11/10/2018
5	RF Connection Cable	HUBER+SUHNER	EF400	N/A	11/21/2017	11/20/2018
6	Test Software	R&S	ES-K1	N/A	N/A	N/A

Radiated Emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	EMI Test Receiver	R&S	ESCI	101247	11/11/2017	11/10/2018
2	Loop Antenna	R&S	HFH2-Z2	100020	11/20/2017	11/19/2018
3	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	538	4/5/2017	4/4/2018
4	Preamplifier	SCHWARZBECK	BBV 9743	9743-0022	10/18/2017	10/17/2018
5	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	11/21/2017	11/20/2018
6	EMI Test Software	R&S	ESK1	N/A	N/A	N/A
7	Spectrum Analyzer	R&S	FSP40	100597	11/11/2017	11/10/2018
8	Horn Antenna	SCHWARZBECK	9120D	1011	3/27/2017	3/26/2018
9	Horn Antenna	SCHWARZBECK	BBHA9170	25841	3/27/2017	3/26/2018
10	Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-248	10/18/2017	10/17/2018
11	High pass filter	Compliance Direction systems	BSU-6	34202	11/11/2017	11/10/2018
12	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	11/21/2017	11/20/2018
13	EMI Test Software	Audix	E3	N/A	N/A	N/A
14	Turntable	MATURO	TT2.0	/	N/A	N/A
15	Antenna Mast	MATURO	TAM-4.0-P	/	N/A	N/A

RF Conducted Test						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Spectrum Analyzer	R&S	FSV40	100048	11/11/2017	11/10/2018
2	EXA Signal Analyzer	Agilent	N9020A	184247	9/22/2017	9/21/2018
3	Power Meter	Agilent	U2021XA	178231	9/22/2017	9/21/2018
4	OSP	R&S	OSP120	101317	N/A	N/A

The Cal.Interval was one year.

5. TEST CONDITIONS AND RESULTS

5.1. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Test Result:

Passed **Not Applicable**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. Conducted Emissions (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE


1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Passed Not Applicable

Note:

- 1) Transd= Cable lose + Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit - Level



MEASUREMENT RESULT: "GM1712265030_fin"

26/12/2017 11:28


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	47.10	10.0	66	18.9	QP	L1	GND
0.177000	47.70	10.0	65	16.9	QP	L1	GND
0.181500	46.70	10.0	64	17.7	QP	L1	GND
0.460500	46.60	9.9	57	10.1	QP	L1	GND
1.351500	40.40	10.1	56	15.6	QP	L1	GND
1.500000	38.30	10.1	56	17.7	QP	L1	GND
4.186500	16.80	10.1	56	39.2	QP	L1	GND

MEASUREMENT RESULT: "GM1712265030_fin2"

26/12/2017 11:28

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.177000	33.50	10.0	55	21.1	AV	L1	GND
0.321000	30.10	9.9	50	19.6	AV	L1	GND
0.460500	37.50	9.9	47	9.2	AV	L1	GND
1.243500	29.00	10.1	46	17.0	AV	L1	GND
1.491000	30.10	10.1	46	15.9	AV	L1	GND
3.286500	23.20	10.1	46	22.8	AV	L1	GND
23.127000	25.80	10.7	50	24.2	AV	L1	GND

Test Line: N



MEASUREMENT RESULT: "GM1712265029_fin"

26/12/2017 11:21

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.172500	44.40	10.0	65	20.4	QP	N	GND
0.181500	45.20	10.0	64	19.2	QP	N	GND
0.208500	40.60	9.9	63	22.7	QP	N	GND
0.460500	39.40	9.9	57	17.3	QP	N	GND
1.270500	30.10	10.1	56	25.9	QP	N	GND
4.816500	28.50	10.2	56	27.5	QP	N	GND

MEASUREMENT RESULT: "GM1712265029_fin2"

26/12/2017 11:21

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.186000	29.10	10.0	54	25.1	AV	N	GND
0.393000	30.30	9.9	48	17.7	AV	N	GND
0.469500	33.30	9.9	47	13.2	AV	N	GND
1.405500	27.10	10.1	46	18.9	AV	N	GND
2.152500	25.70	10.1	46	20.3	AV	N	GND
2.184000	25.50	10.1	46	20.5	AV	N	GND


5.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW \geq the 20 dB bandwidth of the emission being measured, VBW \geq RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 3.3




TEST RESULTS

Passed Not Applicable

Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK	00	2.85	≤ 30.00	Pass
	39	2.77		
	78	4.58		
$\pi/4$ DQPSK	00	1.94	≤ 21.00	Pass
	39	2.06		
	78	3.80		
8DPSK	00	2.09	≤ 21.00	Pass
	39	2.45		
	78	3.91		

Modulation Type: GFSK	
CH00	<p>Spectrum plot for CH00. The plot shows a signal centered at 2.402 GHz with a peak level of 2.85 dBm. The span is 5.0 MHz. The plot includes parameters: Ref Level 20.00 dBm, Att 30 dB, Offset 0.50 dB, RBW 1 MHz, Mode Auto Sweep, and M1[1] at 2.40184080 GHz.</p>
CH39	<p>Spectrum plot for CH39. The plot shows a signal centered at 2.441 GHz with a peak level of 2.77 dBm. The span is 5.0 MHz. The plot includes parameters: Ref Level 20.00 dBm, Att 30 dB, Offset 1.00 dB, RBW 1 MHz, Mode Auto Sweep, and M1[1] at 2.44118810 GHz.</p>
CH78	<p>Spectrum plot for CH78. The plot shows a signal centered at 2.48 GHz with a peak level of 4.58 dBm. The span is 5.0 MHz. The plot includes parameters: Ref Level 20.00 dBm, Att 30 dB, Offset 0.50 dB, RBW 1 MHz, Mode Auto Sweep, and M1[1] at 2.47986250 GHz.</p>

Modulation Type: $\pi/4$ QPSK	
CH00	<p>Spectrum plot for CH00. The plot shows a signal centered at 2.402 GHz. The peak level is 1.94 dBm. The plot includes a grid and various measurement parameters: Ref Level 20.00 dBm, Att 30 dB, Offset 0.50 dB, RBW 2 MHz, Mode Auto Sweep, Span 5.0 MHz, and 691 pts.</p>
CH39	<p>Spectrum plot for CH39. The plot shows a signal centered at 2.441 GHz. The peak level is 2.06 dBm. The plot includes a grid and various measurement parameters: Ref Level 20.00 dBm, Att 30 dB, Offset 1.00 dB, RBW 2 MHz, Mode Auto Sweep, Span 5.0 MHz, and 691 pts.</p>
CH78	<p>Spectrum plot for CH78. The plot shows a signal centered at 2.48 GHz. The peak level is 3.80 dBm. The plot includes a grid and various measurement parameters: Ref Level 20.00 dBm, Att 30 dB, Offset 0.50 dB, RBW 2 MHz, Mode Auto Sweep, Span 5.0 MHz, and 691 pts.</p>


Modulation Type: 8DPSK	
CH00	
CH39	
CH78	

5.4. 20 dB Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

 Passed Not Applicable

Modulation type	Channel	20 dB Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.93	-	Pass
	39	0.93		
	78	0.93		
$\pi/4$ DQPSK	00	1.30	-	Pass
	39	1.31		
	78	1.30		
8DPSK	00	1.29	-	Pass
	39	1.29		
	78	1.29		

Modulation Type:		GFSK																												
CH00	<table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.4015475 GHz</td> <td>-23.95 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.40206 GHz</td> <td>-3.29 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>927.5 kHz</td> <td>-0.49 dB</td> <td></td> <td></td> </tr> </tbody> </table>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.4015475 GHz	-23.95 dBm			M2	1		2.40206 GHz	-3.29 dBm			D3	M1	1	927.5 kHz	-0.49 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.4015475 GHz	-23.95 dBm																										
M2	1		2.40206 GHz	-3.29 dBm																										
D3	M1	1	927.5 kHz	-0.49 dB																										
CH39	<table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.4405475 GHz</td> <td>-25.70 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.44106 GHz</td> <td>-4.82 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>927.5 kHz</td> <td>-0.08 dB</td> <td></td> <td></td> </tr> </tbody> </table>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.4405475 GHz	-25.70 dBm			M2	1		2.44106 GHz	-4.82 dBm			D3	M1	1	927.5 kHz	-0.08 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.4405475 GHz	-25.70 dBm																										
M2	1		2.44106 GHz	-4.82 dBm																										
D3	M1	1	927.5 kHz	-0.08 dB																										
CH78	<table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.4795475 GHz</td> <td>-21.53 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.48006 GHz</td> <td>-1.09 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>927.5 kHz</td> <td>-0.73 dB</td> <td></td> <td></td> </tr> </tbody> </table>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.4795475 GHz	-21.53 dBm			M2	1		2.48006 GHz	-1.09 dBm			D3	M1	1	927.5 kHz	-0.73 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.4795475 GHz	-21.53 dBm																										
M2	1		2.48006 GHz	-1.09 dBm																										
D3	M1	1	927.5 kHz	-0.73 dB																										

Modulation Type:		$\pi/4$ DQPSK																												
CH00	<p>Marker</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.40136 GHz</td> <td>-22.08 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.402165 GHz</td> <td>-2.02 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.295 MHz</td> <td>-0.23 dB</td> <td></td> <td></td> </tr> </tbody> </table>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40136 GHz	-22.08 dBm			M2	1		2.402165 GHz	-2.02 dBm			D3	M1	1	1.295 MHz	-0.23 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.40136 GHz	-22.08 dBm																										
M2	1		2.402165 GHz	-2.02 dBm																										
D3	M1	1	1.295 MHz	-0.23 dB																										
CH39	<p>Marker</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.4403475 GHz</td> <td>-23.49 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.441165 GHz</td> <td>-3.28 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.3075 MHz</td> <td>-0.05 dB</td> <td></td> <td></td> </tr> </tbody> </table>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.4403475 GHz	-23.49 dBm			M2	1		2.441165 GHz	-3.28 dBm			D3	M1	1	1.3075 MHz	-0.05 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.4403475 GHz	-23.49 dBm																										
M2	1		2.441165 GHz	-3.28 dBm																										
D3	M1	1	1.3075 MHz	-0.05 dB																										
CH78	<p>Marker</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.479355 GHz</td> <td>-20.11 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.480165 GHz</td> <td>0.03 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.3 MHz</td> <td>-0.24 dB</td> <td></td> <td></td> </tr> </tbody> </table>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.479355 GHz	-20.11 dBm			M2	1		2.480165 GHz	0.03 dBm			D3	M1	1	1.3 MHz	-0.24 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.479355 GHz	-20.11 dBm																										
M2	1		2.480165 GHz	0.03 dBm																										
D3	M1	1	1.3 MHz	-0.24 dB																										

Modulation Type:		8DPSK																												
CH00	<p>Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT</p> <p>1Pk View</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.401355 GHz</td> <td>-21.74 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4021625 GHz</td> <td>-1.36 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.29 MHz</td> <td>0.24 dB</td> <td></td> <td></td> </tr> </tbody> </table> <p>CF 2.402 GHz 1001 pts Span 2.5 MHz</p>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.401355 GHz	-21.74 dBm			M2	1		2.4021625 GHz	-1.36 dBm			D3	M1	1	1.29 MHz	0.24 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.401355 GHz	-21.74 dBm																										
M2	1		2.4021625 GHz	-1.36 dBm																										
D3	M1	1	1.29 MHz	0.24 dB																										
CH39	<p>Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT</p> <p>1Pk View</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.440355 GHz</td> <td>-22.82 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4411625 GHz</td> <td>-2.62 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.2925 MHz</td> <td>0.12 dB</td> <td></td> <td></td> </tr> </tbody> </table> <p>CF 2.441 GHz 1001 pts Span 2.5 MHz</p>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.440355 GHz	-22.82 dBm			M2	1		2.4411625 GHz	-2.62 dBm			D3	M1	1	1.2925 MHz	0.12 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.440355 GHz	-22.82 dBm																										
M2	1		2.4411625 GHz	-2.62 dBm																										
D3	M1	1	1.2925 MHz	0.12 dB																										
CH78	<p>Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT</p> <p>1Pk View</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.479355 GHz</td> <td>-19.86 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4801625 GHz</td> <td>0.57 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.29 MHz</td> <td>0.19 dB</td> <td></td> <td></td> </tr> </tbody> </table> <p>CF 2.48 GHz 1001 pts Span 2.5 MHz</p>		Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.479355 GHz	-19.86 dBm			M2	1		2.4801625 GHz	0.57 dBm			D3	M1	1	1.29 MHz	0.19 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1	1		2.479355 GHz	-19.86 dBm																										
M2	1		2.4801625 GHz	0.57 dBm																										
D3	M1	1	1.29 MHz	0.19 dB																										


5.5. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels
RBW \geq 1% of the span, VBW \geq RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable




Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz) *	Result
GFSK	39	1.00	≥ 0.930	Pass
$\pi/4$ DQPSK	39	1.00	≥ 0.878	Pass
8DPSK	39	1.00	≥ 0.864	Pass

Note:

*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the section 5.4.

$\pi/4$ DQPSK limit = $2/3$ * The maximum 20 dB Bandwidth for $\pi/4$ DQPSK modulation on the section 5.4.

8DPSK limit = $2/3$ * The maximum 20 dB Bandwidth for 8DPSK modulation on the section 5.4


GFSK	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz</p> <p>Alt 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT</p> <p>1Pk View</p> <p>M1[1] -1.62 dBm 2.44116522 GHz D1[1] -0.02 dB 1.00000 MHz</p> <p>Start 2.44 GHz 691 pts Stop 2.443 GHz</p>
$\pi/4$ DQPSK	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz</p> <p>Alt 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT</p> <p>1Pk View</p> <p>M1[1] -3.34 dBm 2.44116522 GHz D1[1] -0.03 dB 1.00000 MHz</p> <p>Start 2.44 GHz 691 pts Stop 2.443 GHz</p>
8DPSK	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz</p> <p>Alt 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT</p> <p>1Pk View</p> <p>M1[1] -5.56 dBm 2.44116522 GHz D1[1] 0.06 dB 1.00000 MHz</p> <p>Start 2.44 GHz 691 pts Stop 2.443 GHz</p>

5.6. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
 Span = the frequency band of operation
 RBW \geq 1% of the span, VBW \geq RBW
 Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.




TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable

Modulation type	Channel number	Limit	Result
GFSK	79	≥ 15.00	Pass
$\pi/4$ DQPSK	79		
8DPSK	79		


<p>GFSK</p>	
<p>$\pi/4$DQPSK</p>	
<p>8DPSK</p>	

5.7. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW \geq RBW
Sweep = as necessary to capture the entire dwell time per hopping channel,
Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:




Please refer to the clause 3.3

TEST RESULTS




Passed Not Applicable

Modulation type	Channel	Burst Width [ms/hop/ch]	Total Hops[hop*ch]	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.37	314.00	0.12	≤ 0.40	Pass
	DH3	1.63	153.00	0.25		
	DH5	2.87	103.00	0.30		
$\pi/4$ DQPSK	2DH1	0.38	314.00	0.12	≤ 0.40	Pass
	2DH3	1.63	153.00	0.25		
	2DH5	2.88	101.00	0.29		
8DPSK	3DH1	0.38	315.00	0.12	≤ 0.40	Pass
	3DH3	1.63	154.00	0.25		
	3DH5	2.88	103.00	0.30		




Modulation Type: GFSK	
DH1	<p>Spectrum</p> <p>Ref Level 20.00 dBm RBW 1 MHz</p> <p>Att 30 dB SWT 10 ms VBW 3 MHz</p> <p>SGL TRG:VID</p> <p>IAP Clw</p> <p>M1[1] -32.74 dBm -1.25 μs</p> <p>D1[1] -14.41 dB 370.00 μs</p> <p>TRG -23.700 dBm</p> <p>CF 2.441 GHz 8001 pts 1.0 ms/pt</p>
	<p>Spectrum</p> <p>Ref Level 20.00 dBm RBW 500 kHz</p> <p>Att 30 dB SWT 31.6 s VBW 3 MHz</p> <p>SGL TRG:VID</p> <p>IAP Clw</p> <p>TRG -5.700 dBm</p> <p>CF 2.441 GHz 30001 pts 3.16 s/pt</p>
DH3	<p>Spectrum</p> <p>Ref Level 20.00 dBm RBW 1 MHz</p> <p>Att 30 dB SWT 10 ms VBW 3 MHz</p> <p>SGL TRG:VID</p> <p>IAP Clw</p> <p>M1[1] -21.79 dBm 0.00000000 s</p> <p>D1[1] 9.00 dB 1.62500 ms</p> <p>TRG -23.700 dBm</p> <p>CF 2.441 GHz 8001 pts 1.0 ms/pt</p>

	
DH5	
	

Modulation Type: $\pi/4$ DQPSK	
2DH1	
2DH3	

	
2DH5	
	

Modulation Type: 8DPSK	
3DH1	
3DH2	
3DH3	

	
3DH5	
	

5.8. Pseudorandom Frequency Hopping Sequence


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo-randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally on the average by each transmitter. The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.


5.9. Restricted band (radiated)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
 RBW=1 MHz, VBW=3 MHz Peak detector for Peak value
 RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

TEST MODE:



Please refer to the clause 3.3



TEST RESULTS



Passed **Not Applicable**



Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor
- 2) Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.
- 3) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.










5.10. Band edge and Spurious Emissions (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
RBW = 100 kHz, VBW \geq RBW, scan up through 10th harmonic.
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS


Passed Not Applicable

Test Item:	Band edge	Modulation type:	GFSK																																																
<p>CH00 No hopping mode</p>	 <table border="1" data-bbox="687 607 1334 719"> <thead> <tr> <th>Marker</th> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td></td> <td>2.40191 GHz</td> <td>2.00 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td></td> <td>2.4 GHz</td> <td>-45.37 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td></td> <td>2.39 GHz</td> <td>-49.73 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td></td> <td>2.31 GHz</td> <td>-59.78 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td></td> <td>2.399355 GHz</td> <td>-35.78 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1			2.40191 GHz	2.00 dBm			M2	1			2.4 GHz	-45.37 dBm			M3	1			2.39 GHz	-49.73 dBm			M4	1			2.31 GHz	-59.78 dBm			M5	1			2.399355 GHz	-35.78 dBm		
Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result																																												
M1	1			2.40191 GHz	2.00 dBm																																														
M2	1			2.4 GHz	-45.37 dBm																																														
M3	1			2.39 GHz	-49.73 dBm																																														
M4	1			2.31 GHz	-59.78 dBm																																														
M5	1			2.399355 GHz	-35.78 dBm																																														
<p>CH00 Hopping mode</p>	 <table border="1" data-bbox="687 1133 1334 1245"> <thead> <tr> <th>Marker</th> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td></td> <td>2.40493 GHz</td> <td>1.69 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td></td> <td>2.4 GHz</td> <td>-56.08 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td></td> <td>2.39 GHz</td> <td>-60.35 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td></td> <td>2.31 GHz</td> <td>-59.61 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td></td> <td>2.39729 GHz</td> <td>-51.45 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1			2.40493 GHz	1.69 dBm			M2	1			2.4 GHz	-56.08 dBm			M3	1			2.39 GHz	-60.35 dBm			M4	1			2.31 GHz	-59.61 dBm			M5	1			2.39729 GHz	-51.45 dBm		
Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result																																												
M1	1			2.40493 GHz	1.69 dBm																																														
M2	1			2.4 GHz	-56.08 dBm																																														
M3	1			2.39 GHz	-60.35 dBm																																														
M4	1			2.31 GHz	-59.61 dBm																																														
M5	1			2.39729 GHz	-51.45 dBm																																														


CH78
No hopping mode






CH78
Hopping mode







Test Item:	Band edge	Modulation type:	$\pi/4$ DQPSK																																										
<p>CH00</p> <p>No hopping mode</p>	 <table border="1" data-bbox="687 611 1334 719"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.40218 GHz</td> <td>0.61 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-49.63 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-59.42 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-59.29 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.39963 GHz</td> <td>-35.71 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40218 GHz	0.61 dBm			M2	1		2.4 GHz	-49.63 dBm			M3	1		2.39 GHz	-59.42 dBm			M4	1		2.31 GHz	-59.29 dBm			M5	1		2.39963 GHz	-35.71 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40218 GHz	0.61 dBm																																									
M2	1		2.4 GHz	-49.63 dBm																																									
M3	1		2.39 GHz	-59.42 dBm																																									
M4	1		2.31 GHz	-59.29 dBm																																									
M5	1		2.39963 GHz	-35.71 dBm																																									
<p>CH00</p> <p>Hopping mode</p>	 <table border="1" data-bbox="687 1133 1334 1240"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.40218 GHz</td> <td>-2.81 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-58.25 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-60.53 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-59.56 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.340978 GHz</td> <td>-57.59 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40218 GHz	-2.81 dBm			M2	1		2.4 GHz	-58.25 dBm			M3	1		2.39 GHz	-60.53 dBm			M4	1		2.31 GHz	-59.56 dBm			M5	1		2.340978 GHz	-57.59 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40218 GHz	-2.81 dBm																																									
M2	1		2.4 GHz	-58.25 dBm																																									
M3	1		2.39 GHz	-60.53 dBm																																									
M4	1		2.31 GHz	-59.56 dBm																																									
M5	1		2.340978 GHz	-57.59 dBm																																									




Test Item:	Band edge	Modulation type:	8DPSK																																										
<p>CH00 No hopping mode</p>		 <table border="1" data-bbox="686 616 1332 728"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td></td> <td>1</td> <td>2.40218 GHz</td> <td>0.67 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td></td> <td>1</td> <td>2.4 GHz</td> <td>-48.23 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td></td> <td>1</td> <td>2.39 GHz</td> <td>-60.43 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td></td> <td>1</td> <td>2.31 GHz</td> <td>-60.16 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td></td> <td>1</td> <td>2.398942 GHz</td> <td>-49.59 dBm</td> <td></td> <td></td> </tr> </tbody> </table>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.40218 GHz	0.67 dBm			M2		1	2.4 GHz	-48.23 dBm			M3		1	2.39 GHz	-60.43 dBm			M4		1	2.31 GHz	-60.16 dBm			M5		1	2.398942 GHz	-49.59 dBm			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.40218 GHz	0.67 dBm																																									
M2		1	2.4 GHz	-48.23 dBm																																									
M3		1	2.39 GHz	-60.43 dBm																																									
M4		1	2.31 GHz	-60.16 dBm																																									
M5		1	2.398942 GHz	-49.59 dBm																																									
<p>CH00 Hopping mode</p>		 <table border="1" data-bbox="686 1142 1332 1254"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td></td> <td>1</td> <td>2.40493 GHz</td> <td>-3.75 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td></td> <td>1</td> <td>2.4 GHz</td> <td>-57.31 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td></td> <td>1</td> <td>2.39 GHz</td> <td>-59.71 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td></td> <td>1</td> <td>2.31 GHz</td> <td>-59.44 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td></td> <td>1</td> <td>2.325558 GHz</td> <td>-57.40 dBm</td> <td></td> <td></td> </tr> </tbody> </table>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.40493 GHz	-3.75 dBm			M2		1	2.4 GHz	-57.31 dBm			M3		1	2.39 GHz	-59.71 dBm			M4		1	2.31 GHz	-59.44 dBm			M5		1	2.325558 GHz	-57.40 dBm			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.40493 GHz	-3.75 dBm																																									
M2		1	2.4 GHz	-57.31 dBm																																									
M3		1	2.39 GHz	-59.71 dBm																																									
M4		1	2.31 GHz	-59.44 dBm																																									
M5		1	2.325558 GHz	-57.40 dBm																																									
<p>CH78 No hopping mode</p>		 <table border="1" data-bbox="686 1691 1332 1780"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td></td> <td>1</td> <td>2.480149 GHz</td> <td>2.70 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td></td> <td>1</td> <td>2.4825 GHz</td> <td>-58.88 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td></td> <td>1</td> <td>2.5 GHz</td> <td>-62.28 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td></td> <td>1</td> <td>2.4838029 GHz</td> <td>-55.65 dBm</td> <td></td> <td></td> </tr> </tbody> </table>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.480149 GHz	2.70 dBm			M2		1	2.4825 GHz	-58.88 dBm			M3		1	2.5 GHz	-62.28 dBm			M4		1	2.4838029 GHz	-55.65 dBm										
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.480149 GHz	2.70 dBm																																									
M2		1	2.4825 GHz	-58.88 dBm																																									
M3		1	2.5 GHz	-62.28 dBm																																									
M4		1	2.4838029 GHz	-55.65 dBm																																									

CH78
Hoppig mode





Test Item:	SE	Modulation type:	GFSK
reference level CH00	 <p>Spectrum plot showing a peak at 2.4020430 GHz with a level of 1.53 dBm. The plot includes parameters: Ref Level 20.50 dBm, Att 30 dB, Offset 0.50 dB, RBW 100 kHz, Mode Auto FFT, Span 30.0 MHz, and 691 pts.</p>		
CH00	 <p>Spectrum plot showing a peak at 751.8340 MHz with a level of -56.50 dBm. The plot includes parameters: Ref Level 20.00 dBm, Att 30 dB, Offset 0.50 dB, RBW 100 kHz, Mode Auto Sweep, Start 30.0 MHz, Stop 1.0 GHz, and 30001 pts.</p>		
CH00	 <p>Spectrum plot showing a peak at 7.205833 GHz with a level of -36.02 dBm. The plot includes parameters: Ref Level 20.00 dBm, Att 30 dB, Offset 0.50 dB, RBW 1 MHz, Mode Auto Sweep, Start 1.0 GHz, Stop 26.0 GHz, and 30001 pts.</p>		


reference level CH39





CH39



reference level CH78




CH78





Test Item:	SE	Modulation type:	$\pi/4$ DQPSK
reference level CH00			
CH00			
CH00			


reference level CH39





CH39



reference level CH78




CH78





Test Item:	SE	Modulation type:	8DPSK
reference level CH00			
CH00			
CH00			


reference level CH39





CH39



reference level CH78



CH78



5.11. Spurious Emissions (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30 MHz ~ 88 MHz	40.00	Quasi-peak
88 MHz ~ 216 MHz	43.50	Quasi-peak
216 MHz ~ 960 MHz	46.00	Quasi-peak
960 MHz ~ 1 GHz	54.00	Quasi-peak
Above 1 GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- Below 30 MHz



- 30 MHz ~1000 MHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10:2013.
2. The EUT is placed on a turn table with 0.8 meter above ground for below 1GHz, 1.5 meter above ground for above 1GHz.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
 - RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
 - If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
 - RBW=1 MHz, VBW=3 MHz Peak detector for Peak value
 - RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable

Note:


- 1) Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3) Below 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation High channel which it was worst case, so only the worst case's data on the test report.
- 4) Above 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report
- 5) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.

➤ 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

➤ 30 MHz ~ 1 GHz

Polarization: Vertical




MEASUREMENT RESULT: "GM1712216104_red"

12/21/2017 10:22PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	21.00	-8.8	40.0	19.0	QP	100.0	212.00	VERTICAL
55.220000	20.20	-9.2	40.0	19.8	QP	100.0	147.00	VERTICAL
105.660000	19.00	-10.5	43.5	24.5	QP	100.0	159.00	VERTICAL
299.660000	22.50	-7.3	46.0	23.5	QP	100.0	159.00	VERTICAL
555.740000	29.70	-0.6	46.0	16.3	QP	100.0	132.00	VERTICAL
932.100000	38.20	7.1	46.0	7.8	QP	100.0	332.00	VERTICAL

Polarization: Horizontal



MEASUREMENT RESULT: "GM1712216103_red"

12/21/2017 10:19PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	21.60	-8.8	40.0	18.4	QP	300.0	338.00	HORIZONTAL
55.220000	20.80	-9.2	40.0	19.2	QP	100.0	357.00	HORIZONTAL
109.540000	19.20	-10.8	43.5	24.3	QP	100.0	254.00	HORIZONTAL
299.660000	22.80	-7.3	46.0	23.2	QP	100.0	309.00	HORIZONTAL
540.220000	29.60	-1.0	46.0	16.4	QP	300.0	314.00	HORIZONTAL
947.620000	38.50	7.2	46.0	7.5	QP	100.0	0.00	HORIZONTAL

➤ 1 GHz ~ 25 GHz

CH00									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1525.86	32.80	25.56	5.36	36.62	27.10	74.00	-46.90	Vertical	Peak
3709.69	32.62	29.33	8.40	38.25	32.10	74.00	-41.90	Vertical	Peak
4809.50	31.57	31.58	9.55	36.93	35.77	74.00	-38.23	Vertical	Peak
7209.02	34.17	36.21	11.87	35.07	47.18	74.00	-26.82	Vertical	Peak
1889.63	32.96	25.31	6.10	37.21	27.16	74.00	-46.84	Horizontal	Peak
3766.79	33.75	29.50	8.46	38.24	33.47	74.00	-40.53	Horizontal	Peak
4809.50	36.27	31.58	9.55	36.93	40.47	74.00	-33.53	Horizontal	Peak
7209.02	36.16	36.21	11.87	35.07	49.17	74.00	-24.83	Horizontal	Peak

CH39									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1746.25	40.41	25.29	5.86	37.03	34.53	74.00	-39.47	Vertical	Peak
3625.67	34.30	29.30	8.30	38.26	33.64	74.00	-40.36	Vertical	Peak
4883.52	36.19	31.43	9.59	36.73	40.48	74.00	-33.52	Vertical	Peak
7319.96	35.65	36.30	11.99	34.92	49.02	74.00	-24.98	Vertical	Peak
1764.12	35.30	25.33	5.89	37.06	29.46	74.00	-44.54	Horizontal	Peak
3681.47	32.23	29.30	8.36	38.25	31.64	74.00	-42.36	Horizontal	Peak
5138.58	31.29	31.74	9.78	36.26	36.55	74.00	-37.45	Horizontal	Peak
7099.75	29.53	35.60	11.85	34.93	42.05	74.00	-31.95	Horizontal	Peak

CH78									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1353.80	33.44	26.04	4.92	36.49	27.91	74.00	-46.09	Vertical	Peak
1750.70	33.89	25.30	5.86	37.04	28.01	74.00	-45.99	Vertical	Peak
3579.82	32.80	29.24	8.24	38.30	31.98	74.00	-42.02	Vertical	Peak
4958.68	45.35	31.46	9.64	36.52	49.93	74.00	-24.07	Vertical	Peak
1593.34	33.80	24.96	5.55	36.71	27.60	74.00	-46.40	Horizontal	Peak
3963.52	32.74	29.70	8.73	38.13	33.04	74.00	-40.96	Horizontal	Peak
4958.68	46.27	31.46	9.64	36.52	50.85	74.00	-23.15	Horizontal	Peak
7451.57	36.64	36.20	12.24	34.86	50.22	74.00	-23.78	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.


6. TEST SETUP PHOTOS

Conducted Emissions



Radiated Emissions





7. EXTERANAL AND INTERNAL PHOTOS

Reference to the test report No.: TRE1712015301.

-----End of Report-----