



# Shenzhen HTT Technology Co., Ltd.

## TEST REPORT

### FCC Rules and Regulations Part PART 15.249

Report Reference No.....: **HTT202405518F01**

FCC ID.....: **2A00M-GT850**

Compiled by  
( position+printed name+signature.. File administrators


*Heber He*

Supervised by  
( position+printed name+signature.. Project Engineer

*Bruce Zhu*

Approved by  
( position+printed name+signature.. RF Manager

*Kevin Han*



Date of issue..... May. 29, 2024

**Testing Laboratory Name ..... Shenzhen HTT Technology Co.,Ltd.**

Address..... 1F, Building B, Huafeng International Robotics Industrial Park,  
Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an  
District, Shenzhen, Guangdong, China

**Applicant's name ..... Shenzhen OUNI Technology Co., Ltd**

Address..... Floor 9, Area C, Building 8, Evergrande Fashion Huigu Building, beside  
Fulong Road, Dalang Street, Longhua District, Shenzhen, Guangdong.

Standard ..... **FCC Rules and Regulations Part PART 15.249**

**Shenzhen HTT Technology Co.,Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HTT Technology Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HTT Technology Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description ..... DONGEL**

Trade Mark ..... N/A

Manufacturer ..... Shenzhen OUNI Technology Co., Ltd

Model/Type reference..... GT807

Listed Models ..... B2, B3, B5, B7, B100, B130, GT801, GT802, GT803, GT805, GT806,  
GT808, GT809, GT810, GT811, GT812, GT813, GT815, GT816,  
GT818, GT819, GT820, GT821, GT822, GT823, GT825, GT826,  
GT828, GT829, GT830, GT831, GT832, GT833, GT835, GT836,  
GT838, GT839, GT850, GT851, GT852, GT853, GT855, GT856,  
GT858, GT859, GT860, GT861, GT862, GT863, GT865, GT866,  
GT868, GT869, GT880, GT881, GT882, GT883, GT885, GT886,  
GT888, GT889, GT890

Modulation ..... GFSK

Frequency..... 2402-2480MHz

Ratings..... DC 5.0V

Result..... **PASS**

# TEST REPORT

Equipment under Test : DONGEL

Model /Type : **GT807**

Listed Models : B2, B3, B5, B7, B100, B130, GT801, GT802, GT803, GT805, GT806, GT808, GT809, GT810, GT811, GT812, GT813, GT815, GT816, GT818, GT819, GT820, GT821, GT822, GT823, GT825, GT826, GT828, GT829, GT830, GT831, GT832, GT833, GT835, GT836, GT838, GT839, GT850, GT851, GT852, GT853, GT855, GT856, GT858, GT859, GT860, GT861, GT862, GT863, GT865, GT866, GT868, GT869, GT880, GT881, GT882, GT883, GT885, GT886, GT888, GT889, GT890

**Applicant** : **Shenzhen OUNI Technology Co., Ltd**

Address : Floor 9, Area C, Building 8, Evergrande Fashion Huigu Building, beside Fulong Road, Dalang Street, Longhua District, Shenzhen, Guangdong.

**Manufacturer** : **Shenzhen OUNI Technology Co., Ltd**

Address : Floor 9, Area C, Building 8, Evergrande Fashion Huigu Building, beside Fulong Road, Dalang Street, Longhua District, Shenzhen, Guangdong.

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



# Contents

- 1. TEST STANDARDS ..... 5**
  
- 2. SUMMARY ..... 6**
  - 2.1. General Remarks ..... 6
  - 2.2. Product Description ..... 6
  - 2.3. Equipment Under Test ..... 6
  - 2.4. Short description of the Equipment under Test (EUT) ..... 6
  - 2.5. EUT operation mode ..... 6
  - 2.6. Block Diagram of Test Setup ..... 7
  - 2.7. Modifications ..... 7
  
- 3. TEST ENVIRONMENT ..... 8**
  - 3.1. Address of the test laboratory ..... 8
  - 3.2. Test Facility ..... 8
  - 3.3. Environmental conditions ..... 8
  - 3.4. Summary of measurement results ..... 9
  - 3.5. Statement of the measurement uncertainty ..... 9
  - 3.6. Equipments Used during the Test ..... 9
  
- 4. TEST CONDITIONS AND RESULTS ..... 11**
  - 4.1. AC Power Conducted Emission ..... 11
  - 4.2. Radiated Emission and Band Edges ..... 14
  - 4.3. 20dB Bandwidth Measurement ..... 21
  - 4.4. Antenna Requirement ..... 23
  
- 5. TEST SETUP PHOTOS OF THE EUT ..... 24**
  
- 6. TEST PHOTOS OF THE EUT ..... 24**

## **1. TEST STANDARDS**

The tests were performed according to following standards:

**FCC Rules Part 15.249:** Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

**ANSI C63.10:2013 :** American National Standard for Testing Unlicensed Wireless Devices

**ANSI C63.4: 2014:** –American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz  
Range of 9 kHz to 40GHz

## 2. SUMMARY

### 2.1. General Remarks

Date of receipt of test sample	:	May. 23, 2024
Testing commenced on	:	May. 23, 2024
Testing concluded on	:	May. 29, 2024

### 2.2. Product Description

Name of EUT	DONGEL
Model Number	GT807
List Model:	B2, B3, B5, B7, B100, B130, GT801, GT802, GT803, GT805, GT806, GT808, GT809, GT810, GT811, GT812, GT813, GT815, GT816, GT818, GT819, GT820, GT821, GT822, GT823, GT825, GT826, GT828, GT829, GT830, GT831, GT832, GT833, GT835, GT836, GT838, GT839, GT850, GT851, GT852, GT853, GT855, GT856, GT858, GT859, GT860, GT861, GT862, GT863, GT865, GT866, GT868, GT869, GT880, GT881, GT882, GT883, GT885, GT886, GT888, GT889, GT890
Power Rating	DC 5.0V
Sample ID:	HTT202405518-1#(Engineer sample) HTT202405518-2#(Normal sample)
Operation frequency	2402-2480MHz
Modulation	GFSK
Antenna Type	Chip antenna
Antenna Gain	0.00 dBi

### 2.3. Equipment Under Test

#### Power supply system utilised

Power supply voltage	:	<input type="radio"/> 230V / 50 Hz	<input type="radio"/> 120V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 5.0V

### 2.4. Short description of the Equipment under Test (EUT)

This is a DONGEL

For more details, refer to the user's manual of the EUT.

### 2.5. EUT operation mode

The Applicant use Key to control the EUT for staying in continuous transmitting and receiving mode for testing .There is 40 channels provided to the EUT. Channel Low, Mid and High was selected to test.


Channel	Frequency(MHz)	Channel	Frequency(MHz)
0	2402	20	2442
1	2404	21	2444

2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
<b>19</b>	<b>2440</b>	<b>39</b>	<b>2480</b>

Test frequency:

Channel	Frequency (MHz)
Low	2402
Mid	2440
High	2480

## 2.6. Block Diagram of Test Setup



## 2.7. Modifications

No modifications were implemented to meet testing criteria.

### 3. TEST ENVIRONMENT

#### 3.1. Address of the test laboratory

**Shenzhen HTT Technology Co.,Ltd.**

1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 779513 Designation Number: CN1319**

Shenzhen HTT Technology Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA-Lab Cert. No.: 6435.01**

Shenzhen HTT Technology Co.,Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

#### 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	23 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar



### 3.4. Summary of measurement results

FCC PART 15.249		
FCC Part 15.249(a)	Field Strength of Fundamental	PASS
FCC Part 15.209	Spurious Emission	PASS
FCC Part 15.209	Band edge	PASS
FCC Part 15.215(c)	20dB bandwidth	PASS
FCC Part 15.207	Conducted Emission	PASS
FCC Part 15.203	Antenna Requirement	PASS

### 3.5. Statement of the measurement uncertainty

#### Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.66dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	=	3.45dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	=	4.06dB, k=2

### 3.6. Equipments Used during the Test

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	Shenzhen C.R.T technology co., LTD	9*6*6	HTT-E028	Aug. 10 2021	Aug. 09 2024
2	Control Room	Shenzhen C.R.T technology co., LTD	4.8*3.5*3.0	HTT-E030	Aug. 10 2021	Aug. 09 2024
3	EMI Test Receiver	Rohde&Schwar	ESC17	HTT-E022	Apr. 26 2024	Apr. 25 2025
4	Spectrum Analyzer	Rohde&Schwar	FSP	HTT-E037	Apr. 26 2024	Apr. 25 2025
5	Coaxial Cable	ZDecl	ZT26-NJ-NJ-0.6M	HTT-E018	Apr. 26 2024	Apr. 25 2025
6	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-2M	HTT-E019	Apr. 26 2024	Apr. 25 2025
7	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-0.6M	HTT-E020	Apr. 26 2024	Apr. 25 2025
8	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-8.5M	HTT-E021	Apr. 26 2024	Apr. 25 2025
9	Composite logarithmic antenna	Schwarzbeck	VULB 9168	HTT-E017	May. 21 2024	May. 20 2025
10	Horn Antenna	Schwarzbeck	BBHA9120D	HTT-E016	May. 20 2024	May. 19 2025
11	Loop Antenna	Zhinan	ZN30900C	HTT-E039	Apr. 26 2024	Apr. 25 2025
12	Horn Antenna	Beijing Hangwei Dayang	OBH100400	HTT-E040	Apr. 26 2024	Apr. 25 2025
13	low frequency Amplifier	Sonoma Instrument	310	HTT-E015	Apr. 26 2024	Apr. 25 2025
14	high-frequency Amplifier	HP	8449B	HTT-E014	Apr. 26 2024	Apr. 25 2025
15	Variable frequency power supply	Shenzhen Anbiao Instrument Co., Ltd	ANB-10VA	HTT-082	Apr. 26 2024	Apr. 25 2025
16	EMI Test Receiver	Rohde & Schwarz	ESCS30	HTT-E004	Apr. 26 2024	Apr. 25 2025
17	Artificial Mains	Rohde & Schwarz	ESH3-Z5	HTT-E006	May. 23 2024	May. 22 2025
18	Artificial Mains	Rohde & Schwarz	ENV-216	HTT-E038	May. 23 2024	May. 22 2025
19	Cable Line	Robinson	Z302S-NJ-BNCJ-1.5M	HTT-E001	Apr. 26 2024	Apr. 25 2025
20	Attenuator	Robinson	6810.17A	HTT-E007	Apr. 26 2024	Apr. 25 2025
21	Variable frequency power supply	Shenzhen Yanghong Electric Co., Ltd	YF-650 (5KVA)	HTT-E032	Apr. 26 2024	Apr. 25 2025


22	Control Room	Shenzhen C.R.T technology co., LTD	8*4*3.5	HTT-E029	Aug. 10 2021	Aug. 09 2024
23	DC power supply	Agilent	E3632A	HTT-E023	Apr. 26 2024	Apr. 25 2025
24	EMI Test Receiver	Agilent	N9020A	HTT-E024	Apr. 26 2024	Apr. 25 2025
25	Analog signal generator	Agilent	N5181A	HTT-E025	Apr. 26 2024	Apr. 25 2025
26	Vector signal generator	Agilent	N5182A	HTT-E026	Apr. 26 2024	Apr. 25 2025
27	Power sensor	Keysight	U2021XA	HTT-E027	Apr. 26 2024	Apr. 25 2025
28	Temperature and humidity meter	Shenzhen Anbiao Instrument Co., Ltd	TH10R	HTT-074	Apr. 28 2024	Apr. 27 2025
29	Radiated Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
30	Conducted Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
31	RF Test Software	panshanrf	TST	N/A	N/A	N/A

Note: The Cal.Interval was one year.

## 4. TEST CONDITIONS AND RESULTS

### 4.1. AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

#### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


\* Decreases with the logarithm of the frequency.

#### TEST RESULTS

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.


Measurement data:

Line:



No. Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	0.1686	16.29	10.18	26.47	65.03	-38.56	QP
2	0.1686	4.55	10.18	14.73	55.03	-40.30	AVG
3	0.1884	26.56	10.20	36.76	64.11	-27.35	QP
4	0.1884	10.59	10.20	20.79	54.11	-33.32	AVG
5	0.2460	19.94	10.22	30.16	61.89	-31.73	QP
6	0.2460	5.44	10.22	15.66	51.89	-36.23	AVG
7	2.5343	14.39	10.46	24.85	56.00	-31.15	QP
8	2.5343	6.18	10.46	16.64	46.00	-29.36	AVG
9	16.4794	34.05	11.12	45.17	60.00	-14.83	QP
10	16.4794	27.05	11.12	38.17	50.00	-11.83	AVG
11	18.8002	33.96	11.23	45.19	60.00	-14.81	QP
12 *	18.8002	27.40	11.23	38.63	50.00	-11.37	AVG

Neutral:



No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1536	25.84	10.16	36.00	65.80	-29.80	QP
2		0.1536	5.10	10.16	15.26	55.80	-40.54	AVG
3		0.2748	16.37	10.23	26.60	60.97	-34.37	QP
4		0.2748	7.20	10.23	17.43	50.97	-33.54	AVG
5		0.5068	10.26	10.28	20.54	56.00	-35.46	QP
6		0.5068	2.55	10.28	12.83	46.00	-33.17	AVG
7		2.0440	15.60	10.40	26.00	56.00	-30.00	QP
8		2.0440	7.13	10.40	17.53	46.00	-28.47	AVG
9		17.2103	32.87	11.22	44.09	60.00	-15.91	QP
10		17.2103	25.01	11.22	36.23	50.00	-13.77	AVG
11		18.7354	33.72	11.27	44.99	60.00	-15.01	QP
12	*	18.7354	27.48	11.27	38.75	50.00	-11.25	AVG


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Los


## 4.2. Radiated Emission and Band Edges

### TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



**TEST PROCEDURE**

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 26MHz and maximum operation frequency was 1910MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

**FS = RA + AF + CL - AG**

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

**RADIATION LIMIT**

According 15.249, the field strength of emissions from intentional radiators operated within 2400MHz-2483.5 MHz shall not exceed 94dBµV/m (50mV/m):

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

**TEST RESULTS**


Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. Both modes of GFSK were tested at Low, Middle, and High channel and recorded worst mode at GFSK
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

**For 30MHz-1GHz**







For 1GHz to 25GHz

Frequency(MHz):			2403		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2403.00	89.06	PK	114	24.94	89.26	27.5	5	32.7	-0.2
2403.00	77.64	AV	94	16.36	77.84	27.5	5	32.7	-0.2
4806.00	59.94	PK	74	14.06	54.24	31	6.5	31.8	5.7
4806.00	43.75	AV	54	10.25	38.05	31	6.5	31.8	5.7
7209.00	54.97	PK	74	19.03	42.32	36	8.15	31.5	12.65
7209.00	43.94	AV	54	10.06	31.29	36	8.15	31.5	12.65

Frequency(MHz):			2403		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2403.00	88.40	PK	114	25.60	88.60	27.5	5	32.7	-0.2
2403.00	76.37	AV	94	17.63	76.57	27.5	5	32.7	-0.2
4806.00	58.82	PK	74	15.18	53.12	31	6.5	31.8	5.7
4806.00	45.42	AV	54	8.58	39.72	31	6.5	31.8	5.7
7209.00	54.36	PK	74	19.64	41.71	36	8.15	31.5	12.65
7209.00	44.05	AV	54	9.95	31.40	36	8.15	31.5	12.65

Frequency(MHz):			2441		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2441.00	85.81	PK	114	28.19	85.76	27.55	5.1	32.6	0.05
2441.00	75.08	AV	94	18.92	75.03	27.55	5.1	32.6	0.05
4882.00	60.24	PK	74	13.76	54.08	31.2	6.61	31.65	6.16
4882.00	44.21	AV	54	9.79	38.05	31.2	6.61	31.65	6.16
7323.00	53.08	PK	74	20.92	40.13	36.2	8.23	31.48	12.95
7323.00	46.03	AV	54	7.97	33.08	36.2	8.23	31.48	12.95

Frequency(MHz):			2441		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2441.00	89.15	PK	114	24.85	89.10	27.55	5.1	32.6	0.05
2441.00	76.70	AV	94	17.30	76.65	27.55	5.1	32.6	0.05
4882.00	62.05	PK	74	11.95	55.89	31.2	6.61	31.65	6.16
4882.00	44.30	AV	54	9.70	38.14	31.2	6.61	31.65	6.16
7323.00	54.53	PK	74	19.47	41.58	36.2	8.23	31.48	12.95
7323.00	44.08	AV	54	9.92	31.13	36.2	8.23	31.48	12.95

Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2480.00	90.21	PK	114	23.79	89.97	27.6	5.14	32.5	0.24
2480.00	46.48	AV	94	47.52	46.24	27.6	5.14	32.5	0.24
4960.00	62.29	PK	74	11.71	55.63	31.4	6.76	31.5	6.66
4960.00	43.11	AV	54	10.89	36.45	31.4	6.76	31.5	6.66
7440.00	54.27	PK	74	19.73	40.97	36.4	8.35	31.45	13.3
7440.00	47.23	AV	54	6.77	33.93	36.4	8.35	31.45	13.3

Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2480.00	90.43	PK	114	23.57	90.19	27.6	5.14	32.5	0.24
2480.00	76.74	AV	94	17.26	76.50	27.6	5.14	32.5	0.24
4960.00	63.02	PK	74	10.98	56.36	31.4	6.76	31.5	6.66
4960.00	44.17	AV	54	9.83	37.51	31.4	6.76	31.5	6.66
7440.00	55.38	PK	74	18.62	42.08	36.4	8.35	31.45	13.3
7440.00	45.63	AV	54	8.37	32.33	36.4	8.35	31.45	13.3

**Remark:**

(1) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

(2) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed.


**Results of Band Edges Test (Radiated)**

Operation Mode: GFSK

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	59.31	PK	74	14.69	60.70	27.2	4.31	32.9	-1.39
2390.00	44.31	AV	54	9.69	45.70	27.2	4.31	32.9	-1.39
Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	59.43	PK	74	14.57	60.82	27.2	4.31	32.9	-1.39
2390.00	45.74	AV	54	8.26	47.13	27.2	4.31	32.9	-1.39
Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	55.51	PK	74	18.49	56.44	27.4	4.47	32.8	-0.93
2483.50	45.11	AV	54	8.89	46.04	27.4	4.47	32.8	-0.93
Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	54.95	PK	74	19.05	55.88	27.4	4.47	32.8	-0.93
2483.50	43.75	AV	54	10.25	44.68	27.4	4.47	32.8	-0.93

### 4.3. 20dB Bandwidth Measurement

#### TEST CONFIGURATION



#### TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30KHz RBW and 300KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

#### LIMIT


N/A

#### TEST RESULTS


Modulation	Channel	20dB bandwidth (MHz)	Result
GFSK	Low	1.0155	PASS
	Mid	1.0162	
	High	1.0162	

Note: 1.The test results including the cable lose.


GFSK



Low



Mid



High

#### **4.4. Antenna Requirement**

##### **Standard Applicable**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

##### **Antenna Information**

The maximum gain of antenna was 0.00 dBi.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen HTT Technology Co., Ltd. does not assume any responsibility.

**5. Test Setup Photos of the EUT**

Reference to the **appendix I** for details

**6. Test Photos of the EUT**

Reference to the **appendix II** for details.

.....**End of Report**.....