



MPE ESTIMATION

FCC ID: 2AOQ6LV-WR23

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

Mode	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
Ant. 1	2437	18.78	18±1(19)	79.43	0	1.0000	0.0158
Ant. 2	2412	18.25	18±1(19)	79.43	0	1.0000	0.0158
MIMO	/	/	/	/	/	/	0.0316

$$Pd = \frac{P_{out} * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2012173843-E**, antenna gain=0dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.0316 mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----