



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15B MEASUREMENT AND TEST REPORT

For

Gouldin Technologies, LLC

2150 Chenault Dr., Carrollton, Texas, 75006 United States

FCC ID: 2AOQ7-WP450V2

Report Type: Original Report	Product Type: Watchman
Test Engineer: CK Huang	<i>CK Huang</i>
Report Number: RXM190827056-00A	
Report Date: 2019-09-25 Oscar Ye	
Reviewed By: EMC Leader	<i>Oscar Ye</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
JUSTIFICATION	4
EUT EXERCISE SOFTWARE	4
SPECIAL ACCESSORIES.....	4
EQUIPMENT MODIFICATIONS	4
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF RADIATED TEST SETUP.....	6
SUMMARY OF TEST RESULTS	7
FCC §15.107 –CONDUCTED EMISSIONS	8
APPLICABLE STANDARD	8
MEASUREMENT UNCERTAINTY.....	8
EUT SETUP.....	8
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE	9
TEST EQUIPMENT LIST AND DETAILS.....	9
TEST DATA	10
FCC §15.109 - RADIATED EMISSIONS	14
APPLICABLE STANDARD	14
MEASUREMENT UNCERTAINTY.....	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	15
TEST EQUIPMENT LIST AND DETAILS.....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION (FOR ABOVE 1GHZ).....	17
TEST DATA	17

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Gouldin Technologies, LLC
Test Model	WP450
Product	Watchman
Rate Voltage	DC 12V or POE
Highest Operation Frequency	900 MHz
Dimension	156mm (L)*140mm (W)*302mm(H)

**All measurement and test data in this report was gathered from production sample serial number: 20190827056. (Assigned by the BACL. The EUT supplied by the applicant was received on 2019-08-27)*

Objective

This report is prepared on behalf of *Gouldin Technologies, LLC* in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15, Class B device.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

Test mode 1: Normal Working-Power supply by DC Source

Test mode 2: Normal Working-Power supply by POE

EUT Exercise Software

No exercise software was used to test.

Special Accessories

No special accessory was used.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
MCH	DC Power Supply	MCH-303D-II	14070562
DELL	Notebook	E6410	3094742521
NTEGEAR	POE	GS308P	4F217B5000891
NTEGEAR	POE Adapter	2ABF060R	N/A
Schneider Electric	Relay	RXM2LB2BD	N/A
WeiShi	Entrance guard	Q3	N/A
AnYong	Load	RXLG	N/A
FuShi	Switch	AR22PR-310B	N/A

External I/O Cable


Cable Description	Length (m)	From/Port	To
Power Cable	5.0	EUT	DC Power Supply
RJ45 Cable	5.0	EUT	POE
Power Cable	1.2	POE	POE Adapter
RJ45 cable	5.0	EUT	Notebook
Signal Cable	5.0	EUT	Switch
Signal Cable	5.0	EUT	Relay
Signal Cable	5.0	EUT	Entrance Guard
Power supply cable	5.0	EUT	Load

Block Diagram of Radiated Test Setup

Test Mode 1



Test Mode 2



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	Conducted Emissions	Compliant
§15.109	Radiated Emissions	Compliant

FCC §15.107 –CONDUCTED EMISSIONS

Applicable Standard

According to FCC§15.107


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Item		Measurement Uncertainty	U_{cispr}
AMN	150kHz~30MHz	3.19 dB	3.4 dB

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03 -101746-zn	2019-07-11	2020-07-10
ROHDE&SCHWARZ	LISN	ENV216	3560655016	2018-11-30	2019-11-29
Audix	Test Software	e3	V9	--	--
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-09-08	2020-09-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Over Limit Calculation

The Corrected Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for margin calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Data


Environmental Conditions

Temperature:	22.3 °C~23.5 °C
Relative Humidity:	51 %~52 %
ATM Pressure:	101.1 kPa~102 kPa

The testing was performed by CK Huang from 2019-09-20 to 2019-09-23.


Test mode 1

Line:



	Read Freq	Read Level	Read Factor	Limit Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	3.70	19.82	23.52	56.00	-32.48	Average
2	0.150	8.10	19.82	27.92	66.00	-38.08	QP
3	0.323	1.20	19.82	21.02	49.62	-28.60	Average
4	0.323	7.10	19.82	26.92	59.62	-32.70	QP
5	0.440	-2.30	19.75	17.45	47.07	-29.62	Average
6	0.440	5.40	19.75	25.15	57.07	-31.92	QP
7	0.767	-1.80	19.72	17.92	46.00	-28.08	Average
8	0.767	3.50	19.72	23.22	56.00	-32.78	QP
9	1.027	-3.20	19.82	16.62	46.00	-29.38	Average
10	1.027	1.80	19.82	21.62	56.00	-34.38	QP
11	22.416	5.90	19.82	25.72	50.00	-24.28	Average
12	22.416	10.50	19.82	30.32	60.00	-29.68	QP


Neutral:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBUV	dB	dBUV	dBUV	dB	
1	0.205	1.10	19.82	20.92	53.40	-32.48	Average
2	0.205	6.50	19.82	26.32	63.40	-37.08	QP
3	0.444	-1.60	19.75	18.15	46.98	-28.83	Average
4	0.444	3.50	19.75	23.25	56.98	-33.73	QP
5	0.767	-2.40	19.72	17.32	46.00	-28.68	Average
6	0.767	2.80	19.72	22.52	56.00	-33.48	QP
7	1.276	-1.90	19.82	17.92	46.00	-28.08	Average
8	1.276	3.00	19.82	22.82	56.00	-33.18	QP
9	11.317	0.40	19.58	19.98	50.00	-30.02	Average
10	11.317	3.70	19.58	23.28	60.00	-36.72	QP
11	22.298	6.50	19.83	26.33	50.00	-23.67	Average
12	22.298	11.10	19.83	30.93	60.00	-29.07	QP


Test mode 2

Line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.160	13.30	19.83	33.13	55.47	-22.34	Average
2	0.160	27.90	19.83	47.73	65.47	-17.74	QP
3	0.346	15.10	19.81	34.91	49.05	-14.14	Average
4	0.346	22.40	19.81	42.21	59.05	-16.84	QP
5	0.658	3.80	19.75	23.55	46.00	-22.45	Average
6	0.658	11.20	19.75	30.95	56.00	-25.05	QP
7	0.918	3.69	19.75	23.44	46.00	-22.56	Average
8	0.918	12.59	19.75	32.34	56.00	-23.66	QP
9	1.197	1.90	19.81	21.71	46.00	-24.29	Average
10	1.197	8.60	19.81	28.41	56.00	-27.59	QP
11	9.204	12.60	19.55	32.15	50.00	-17.85	Average
12	9.204	15.10	19.55	34.65	60.00	-25.35	QP

Neutral:



	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.159	13.00	19.82	32.82	55.52	-22.70	Average
2	0.159	28.90	19.82	48.72	65.52	-16.80	QP
3	0.352	17.09	19.81	36.90	48.91	-12.01	Average
4	0.352	23.09	19.81	42.90	58.91	-16.01	QP
5	0.668	2.80	19.75	22.55	46.00	-23.45	Average
6	0.668	10.60	19.75	30.35	56.00	-25.65	QP
7	0.923	3.20	19.75	22.95	46.00	-23.05	Average
8	0.923	12.10	19.75	31.85	56.00	-24.15	QP
9	10.072	13.40	19.56	32.96	50.00	-17.04	Average
10	10.072	11.00	19.56	30.56	60.00	-29.44	QP
11	12.784	0.70	19.60	20.30	50.00	-29.70	Average
12	12.784	6.10	19.60	25.70	60.00	-34.30	QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

FCC §15.109 - RADIATED EMISSIONS

Applicable Standard

FCC §15.109

Measurement Uncertainty


All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average) and system repeatability.

Item	Measurement Uncertainty	U_{cispr}
Radiated Emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6 GHz ~18 GHz	5.23dB


Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 18 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	Peak
	1MHz	3 MHz	1MHz	AVG

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz, Peak and average detection mode above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrument	Amplifier	310N	185700	2019-08-14	2020-08-13
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03 -101746-zn	2019-07-11	2020-07-10
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Champrotek	Chamber	Chamber A	T-KSEMC049	-	-
Champrotek	Chamber	Chamber B	T-KSEMC080	-	-
Audix	Test Software	e3	V9	--	--
R&S	Auto test Software	EMC32	100361	-	-
ETS	Horn Antenna	3115	6229	2016-12-12	2019-12-11
Rohde & Schwarz	EMI Receiver	ESU40	100207	2019-08-27	2020-08-26
A.H.Systems, inc	Amplifier	2641-1	491	2019-02-20	2020-02-19
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-4	004	2018-12-12	2019-12-11
MICRO-COAX	Coaxial Cable	Cable-5	005	2018-12-12	2019-12-11

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Factor & Over Limit Calculation (For Below 1GHz)

The Corrected Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for margin calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Corrected Amplitude & Margin Calculation (For Above 1GHz)

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data


Environmental Conditions

Temperature:	22.2 °C~23.5 °C
Relative Humidity:	51 %~52 %
ATM Pressure:	101.1 kPa~102.1 kPa

The testing was performed by CK Huang from 2019-09-06 to 2019-09-19.


Test mode 1

Horizontal:



	Read Freq	Read Level	Read Factor	Limit Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	71.33	50.10	-16.93	33.17	40.00	-6.83	200	14	QP
2	74.66	49.71	-17.03	32.68	40.00	-7.32	200	9	QP
3	99.88	48.03	-14.65	33.38	43.50	-10.12	200	26	Peak
4	250.30	50.96	-12.12	38.84	46.00	-7.16	100	0	Peak
5	375.94	42.88	-8.35	34.53	46.00	-11.47	100	0	Peak
6	552.88	37.43	-4.73	32.70	46.00	-13.30	200	39	Peak

Vertical:




	Read Freq	Read Level	Factor	Level	Limit	Over	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	45.54	44.35	-14.48	29.87	40.00	-10.13	172	71	Peak
2	75.45	46.17	-17.04	29.13	40.00	-10.87	172	314	Peak
3	99.53	42.13	-14.74	27.39	43.50	-16.11	200	336	Peak
4	250.30	44.94	-12.12	32.82	46.00	-13.18	172	326	Peak
5	601.43	34.13	-3.96	30.17	46.00	-15.83	200	241	Peak
6	665.80	33.44	-2.75	30.69	46.00	-15.31	200	38	Peak

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

Above 1 GHz:


Full Spectrum



Frequency (MHz)	Max Peak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1329.800000	---	29.84	54.00	24.16	200.0	V	359.0	-10.9
1329.800000	39.09	---	74.00	34.91	200.0	V	359.0	-10.9
1598.400000	---	34.59	54.00	19.41	200.0	V	2.0	-9.6
1598.400000	45.45	---	74.00	28.55	200.0	V	2.0	-9.6
1996.200000	---	31.25	54.00	22.75	100.0	V	223.0	-8.3
1996.200000	39.08	---	74.00	34.92	100.0	V	223.0	-8.3
3448.000000	---	34.48	54.00	19.52	100.0	V	0.0	-3.6
3448.000000	44.60	---	74.00	29.40	100.0	V	0.0	-3.6
13824.800000	---	44.47	54.00	9.53	200.0	H	199.0	12.3
13824.800000	54.68	---	74.00	19.32	200.0	H	199.0	12.3
17680.400000	---	45.99	54.00	8.01	100.0	H	264.0	14.0
17680.400000	56.23	---	74.00	17.77	100.0	H	264.0	14.0


Test Mode 2

Horizontal:



	Read Freq	Read Level	Factor	Limit Level	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg
1	98.49	45.90	-15.02	30.88	43.50	-12.62	200	360 Peak
2	160.35	39.51	-12.06	27.45	43.50	-16.05	200	274 Peak
3	250.30	49.91	-12.12	37.79	46.00	-8.21	100	92 Peak
4	501.18	38.49	-5.48	33.01	46.00	-12.99	100	224 Peak
5	552.88	41.94	-4.73	37.21	46.00	-8.79	200	5 Peak
6	601.43	43.92	-3.96	39.96	46.00	-6.04	100	5 Peak

Vertical:




	Read			Limit	Over	APos	TPos	
	Freq	Level	Factor	Level	Line	Limit		Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg
1	59.44	44.57	-17.52	27.05	40.00	-12.95	100	308 Peak
2	137.42	39.21	-11.63	27.58	43.50	-15.92	100	98 Peak
3	250.30	43.87	-12.12	31.75	46.00	-14.25	200	354 Peak
4	552.88	43.62	-4.73	38.89	46.00	-7.11	100	302 Peak
5	601.43	38.00	-3.96	34.04	46.00	-11.96	100	135 QP
6	649.66	43.07	-3.08	39.99	46.00	-6.01	100	142 Peak

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

Above 1 GHz:

Full Spectrum



Frequency (MHz)	Max Peak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1809.200000	---	25.80	54.00	28.20	200.0	V	198.0	-8.9
1809.200000	36.23	---	74.00	37.77	200.0	V	198.0	-8.9
4012.400000	---	32.02	54.00	21.98	200.0	V	116.0	-1.8
4012.400000	42.86	---	74.00	31.14	200.0	V	116.0	-1.8
6664.400000	---	38.09	54.00	15.91	100.0	H	155.0	4.7
6664.400000	49.37	---	74.00	24.63	100.0	H	155.0	4.7
9364.000000	---	40.36	54.00	13.64	200.0	V	140.0	7.7
9364.000000	50.71	---	74.00	23.29	200.0	V	140.0	7.7
14477.600000	56.56	---	74.00	17.44	200.0	V	246.0	12.7
14477.600000	---	45.56	54.00	8.44	200.0	V	246.0	12.7
17462.800000	---	46.07	54.00	7.93	100.0	H	193.0	14.1
17462.800000	57.32	---	74.00	16.68	100.0	H	193.0	14.1

*******END OF REPORT*******