

## RF EXPOSURE EVALUATION

### EUT Specification

EUT	Flydigi Supercharged Gaming Laptop Coolers BS1
Model	BS1
Series Model	N/A
FCC ID	2AORE-BS1
Antenna Gain	2.08dBi
Operation Frequency	2402 MHz to 2480 MHz
Modulation	GFSK
Input Rating	5V $\overline{=}$ 2A, 9V $\overline{=}$ 2A
Max. output power	1.79dBm

### Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$ = Power density in  $mW/cm^2$

$P_{out}$ =output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

$P_i=3.1416$

R= distance between observation point and center of the radiator in  $cm=20cm$

$P_d$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

**Measurement Result**

Antenna gain: 2.08dBi

BLE:

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result ( $mW/cm^2$ )	Power density Limits ( $mW/cm^2$ )
GFSK (1Mbps)	2402	0.43	0±1	1	2.08	0.000521	1
GFSK (1Mbps)	2440	1.33	1±1	2	2.08	0.000656	1
GFSK (1Mbps)	2480	1.79	2±1	3	2.08	0.000826	1

Signature:



Shawn Wen

Date: 2024-03-14

