

# FCC RF EXPOSURE EVALUATION REPORT

**APPLICANT**: Shanghai Flydigi Electronics Technology Co.,Ltd.

**PRODUCT NAME**: Flydigi Wasp One-handed Gamepad

**MODEL NAME** : FeiZhi Wasp-X

**BRAND NAME**: Flydigi

FCC ID : 2AORE-WASP-X

**STANDARD(S)** : 47CFR 2.1093

KDB 447498

**ISSUE DATE** : 2018-09-27

Reviewed by:

Gan yueming (Reviewer)

Gan Yveming

Approved by:

Peng Huarui (Supervisor)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



Tel: 86-755-36698555

Fax: 86-755-36698525





## **DIRECTORY**

1	Technical Information	-		
٠.		•		
1.1	Applicant and Manufacturer Information	3		
1.2	Equipment Under Test (EUT) Description	3		
1.3	Photographs of the EUT	4		
1.4	Identification of all used EUT	5		
1.5	Applied Reference Documents	5		
2.	Device Category and RF Exposure Limit	E		
3.	Measurement of RF Output Power	7		
4.	RF Exposure Evaluation	8		
An	Annex A General Information······			

Change History		
Issue	Date	Reason for change
1.0	2018-09-27	First edition



## 1. Technical Information

Note: Provide by manufacturer.

## 1.1 Applicant and Manufacturer Information

Applicant:	Shanghai Flydigi Electronics Technology Co.,Ltd.	
Applicant Address:	Rm1108, No.258 Guoxia Rd, Yangpu District, Shanghai	
Manufacturer:	Shanghai Flydigi Electronics Technology Co.,Ltd.	
Manufacturer Address:	Rm1108, No.258 Guoxia Rd, Yangpu District, Shanghai	

## 1.2 Equipment Under Test (EUT) Description

EUT Type:	Flydigi WASP-X Single-Handed Controller
Hardware Version:	FeiZhi Wasp-V1.1
Software Version:	FeiZhi Wasp-V1.0.1
Frequency Bands:	Bluetooth: 2402MHz-2480MHz
Modulation Mode:	BLE: GFSK
Antenna Gain:	-4.41dBi





## 1.3 Photographs of the EUT

#### 1. EUT front view



#### 2. EUT rear view







#### 1.4 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version	
1#	FeiZhi Wasp-V1.1	FeiZhi Wasp-V1.0.1	

## 1.5 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1093	Radio frequency Radiation Exposure Evaluation: portable
		devices
2	KDB 447498 D01v06	General RF Exposure Guidance



## 2. Device Category and RF Exposure Limit

Per user manual, this device is a Flydigi WASP-X Single-Handed Controller. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

#### **Portable Devices:**

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

#### **GENERAL POPULATION / UNCONTROLLED EXPOSURE**

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.





## 3. Measurement of RF Output Power

#### **Bluetooth**

Pand	Channel	Frequency	Peak Power(dBm)
Band		(MHz)	GFSK
	CH 00	2402	1.29
BLE	CH 19	2440	1.68
	CH 39	2480	2.70
Tune-up Limit			3

#### Note:

According to KDB 447498, time-averaged maximum conducted output power applies to SAR and, as required by § 2.1091(c), time-averaged effective radiated power applies to MPE.





## 4. RF Exposure Evaluation

The device only incorporates a Bluetooth transmitter, so standalone SAR evaluation is required for Bluetooth and simultaneous SAR is not required.

#### Standalone transmission SAR evaluation:

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[ $\sqrt{f(GHz)}$ ]  $\leq 3.0$ 

The maximum tune-up limit power is 2.0mW @ 2.48GHz

When Flydigi WASP-X Single-Handed Controller is used on the hand/head, so use **5mm** as the most conservative minimum test separation distance,

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[ $\sqrt{f(GHz)}$ ] =0.63 > 3.0

Therefore the standalone SAR evaluation are not required for this device.





## **Annex A General Information**

#### 1. Identification of the Responsible Testing Laboratory

Trachancation of the Responsible recting Laboratory		
Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.	
Department:	Morlab Laboratory	
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang	
	Road, Block 67, BaoAn District, ShenZhen, GuangDong	
	Province, P. R. China	
Responsible Test Lab Manager:	Mr. Su Feng	
Telephone:	+86 755 36698555	
Facsimile:	+86 755 36698525	

#### 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

 END OF REPORT	
LIND OF INEL ORG	

