

RF Exposure Report

Project Number: 4272209

Report Number: 4272209EMC05 **Revision Level:** 1

Client: Curiouser Products Inc

Equipment Under Test: Smart Mirror

Models: M1R0

FCC ID: 2AOSD-RLSYM1R0

IC ID: 23685- RLSY

Applicable Standards: FCC Part 2.1091

RSS-102

Report issued on: 7 August 2018

Test Result: Compliant

Reviewed by:



David Schramm, Operations Manager

Remarks: This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This document is issued by the Company under its General Conditions of Service accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

TABLE OF CONTENTS

1 REFERENCES	3
1.1 MODIFICATIONS REQUIRED FOR COMPLIANCE	3
2 GENERAL INFORMATION.....	4
2.1 CLIENT INFORMATION	4
2.2 TEST LABORATORY	4
2.3 GENERAL INFORMATION OF EUT	4
3 RF EXPOSURE	5
3.1 INTRODUCTION.....	5
3.2 REFERENCE LEVELS	6
4 EXPOSURE CALCULATIONS	7
4.1 5 GHz.....	7
4.2 2.4 GHz DTS	8
4.3 2.4 GHz BLUETOOTH LE.....	9
4.4 2.4 GHz BLUETOOTH CLASSIC	10
5 REVISION HISTORY	11

1 References

- 1) FCC CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091 & 2.1093)
- 2) RSS-102: Issue5 clause 2.5.2
- 3) ICNIRP Guidelines for limiting exposure to time-varying electric, magnetic and electromagnetic fields (up to 300 GHz)
- 4) Council Recommendation 1999/519/EC of 12 July 1999 on the limitations of exposure of general public to electromagnetic fields
- 5) Council Recommendation 2004/40/EC of 29 April 2004 on the limitations of exposure of workers to electromagnetic fields
- 6) AS/NZS 2772.1 Radiofrequency fields, Part 1: Maximum exposure limits - 3 kHz to 300 GHz

1.1 ***Modifications Required for Compliance***

None

2 General Information

2.1 Client Information

Name: Curiouser Products Inc
Address: 524 Broadway 11th Floor
City, State, Zip, Country: New York, NY 10013, USA

2.2 Test Laboratory

Name: SGS North America, Inc.
Address: 620 Old Peachtree Road NW, Suite 100
City, State, Zip, Country: Suwanee, GA 30024, USA

Accrediting Body: A2LA
Type of lab: Testing Laboratory
Certificate Number: 3212.01

2.3 General Information of EUT

Type of Product: Smart Mirror
Model Number: 1
Serial Number: M1R010050

Frequency Range: 2412-2462 MHz
Data Modes: 802.11b, 802.11g, 802.11n (HT20)
Antenna: Internal, PCB – Molex, P/N: 146153-0100, 3.0dB Gain.

Frequency Range: 2402-2480 MHz (Bluetooth and Bluetooth LE)
Data Modes: GFSK, EDR-2, EDR-3
Antenna: Internal, PCB – Molex, P/N: 146153-0100, 3.0dB Gain.

Frequency Range: 5150 to 5250 MHz, 5250-5350 MHz, 5470-5725 MHz, 5725-5850 MHz
Number of channels: U-NII Band 1 (Channels 36, 38, 40, 44, 46, 48)
U-NII Band 2A (Channels 52, 54, 56, 60, 62, 64)
U-NII Band 2B (Channels 100, 102, 104, 108, 110, 112, 116, 118, 120, 124, 126, 128, 132, 134, 136, 140)
U-NII Band 3 (Channels 149, 151, 153, 157, 159, 161, 165)

Modulation type: 802.11a, 802.11n (HT20/HT40)
Antenna: Internal, PCB – Molex, P/N: 146153-0100, 4.0dB Gain.

Rated Voltage: 120Vac, 60Hz
Test Voltage: 120Vac, 60Hz

3 RF Exposure

3.1 *Introduction*

This generic standard applies to low power electronic and electrical apparatus for which no dedicated product – or product family standard regarding human exposure to electromagnetic fields applies. The frequency range covered is 10 MHz to 300 GHz.

The object of this standard is to demonstrate the compliance of such apparatus with the basic restrictions on exposure of the general public to electric, magnetic and electromagnetic fields and contact current.

All electromagnetic fields

If the average power emitted by the apparatus operating in the frequency range 10 MHz to 300 GHz is less than or equal to 20 mW the apparatus is deemed to comply with the basic restrictions without testing.

Averaging time is 6 minutes in the frequency range 10 MHz to 10 GHz. The average time is equal to $68/f \cdot 1.05$ minutes (where f is in GHz) in the frequency range 10 GHz to 300 GHz.

If the total supply power or the input power to the circuitry producing the greatest emissions in the device is less than or equal to 20 mW then it is assumed that the emitted power is less than 20 mW.

Pulse modulated electromagnetic fields with pulse duration less than 30 micro seconds for pulse of duration less than 30 microseconds at frequencies between 300 MHz and 10 GHz, there is also a basic restriction on SA. This is 2mJ kg^{-1} in any 10g of tissue in the head. For most pulses, the SAR restriction will be more stringent, but for pulses with a repetition frequency of less than 100 Hz, the SA restriction will predominate. For devices producing pulses with repetition rates below 100 Hz, the average power should be less than $20 \times \text{prf mW}$ (prf in Hz).

Calculations are made using the following equation:

$$P_d = \frac{P_t G_t}{4\pi r^2}$$

Where

P_d = Power Density (W/m^2)

P_t = Power Transmitted (W)

G_t = Gain of Transmitting antenna

r = Distance from Antenna (meters)

3.2 Reference Levels

CFR 47 Part 1.1310

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

RSS-102:issue 5, 2.5.2 Exemption Limits for Routine Evaluation — RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- Below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W(adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- ✓ at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} \times f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W(adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

4 Exposure calculations

The EUT has no configuration that allows for simultaneous transmission.

4.1 5 GHz

Frequency Range:	5150-5850 MHz
Average Power at the antenna:	22.2 dBm
Average Power at the antenna:	0.17 Watts
Antenna gain:	4 dBi
Distance of interest:	20 cm
Frequency of operation:	5190 MHz

Estimated RF Power Density: 0.8293 W/m²

	Uncontrolled Environment
Limit of Maximum Permissible Exposure (MPE)	10 W/m ²
Distance to Compliance From Centre of Antenna	2.27 inches 5.76 cm
In Compliance at distance of interest?	Yes

4.2 2.4 GHz DTS

Frequency Range:	2400-2483.5 MHz
Average Power at the antenna:	16.9 dBm
Average Power at the antenna:	0.05 Watts
Antenna gain:	3 dBi
Distance of interest:	20 cm
Frequency of operation:	2412 MHz

Estimated RF Power Density: 0.1944 W/m²

	Uncontrolled Environment
Limit of Maximum Permissible Exposure (MPE)	10 W/m ²
Distance to Compliance From Centre of Antenna	1.1 inches 2.79 cm
In Compliance at distance of interest?	Yes

4.3 2.4 GHz Bluetooth LE

Frequency Range:	2400-2483.5 MHz
Average Power at the antenna:	0.1 dBm
Average Power at the antenna:	0.00 Watts
Antenna gain:	3 dBi
Distance of interest:	20 cm
Frequency of operation:	2480 MHz

Estimated RF Power Density: 0.0041 W/m²

	Uncontrolled Environment
Limit of Maximum Permissible Exposure (MPE)	10 W/m ²
Distance to Compliance From Centre of Antenna	0.16 inches 0.4 cm
In Compliance at distance of interest?	Yes

4.4 2.4 GHz Bluetooth Classic

Frequency Range:	2400-2483.5 MHz
Average Power at the antenna:	9.1 dBm
Average Power at the antenna:	0.01 Watts
Antenna gain:	3 dBi
Distance of interest:	20 cm
Frequency of operation:	2480 MHz

Estimated RF Power Density: 0.0323 W/m²

	Uncontrolled Environment
Limit of Maximum Permissible Exposure (MPE)	10 W/m ²
Distance to Compliance From Centre of Antenna	0.45 inches 1.14 cm
In Compliance at distance of interest?	Yes

5 Revision History

Revision Level	Description of changes	Revision Date
0	Initial release	7 June 2018
1	Corrected channels and frequencies on Page 4. Corrected applicant address. Added Bluetooth MPE calculations.	7 August 2018