

TEST REPORT

Product Name : Bluetooth mesh smart plug
Brand Mark : N/A
Model No. : YX-WS01C
Extension Model : YX-WS01B , YX-WS02A , YX-WS02B
FCC ID : 2AOT8-YXWS01X
Report Number : BLA-EMC-202211-A4303
Date of Sample Receipt : 2022/11/14
Date of Test : 2022/11/14 to 2022/11/24
Date of Issue : 2022/11/24
Test Standard : 47 CFR Part 15, Part1.1307
47 CFR Part 15, Part2.1093
KDB447498D04 General RF Exposure
Guidance v01
Test Result : Pass

Prepared for:

Shenzhen Yexiang Intelligent Technology Co., Ltd.
**5th Floor, Office Building, Yiyuantong Industrial Park, No.6 Zhonghao
Avenue, Xiangjiao Community, Bantian Street, Longgang District,
SHENZHEN Guangdong**

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
**Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China**
TEL: +86-755-23059481

Compiled by: *charlie*

Review by: *Sueels*

Approved by: *Bluezhong*

Date: 2022/11/24



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/11/24	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY	4
2 GENERAL INFORMATION	5
3 GENERAL DESCRIPTION OF E.U.T.	5
4 LABORATORY LOCATION	6
5 RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
<i>Standard Requirement</i>	7
<i>Limits</i>	7

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	PASS

BlueAsia

2 GENERAL INFORMATION

Applicant	Shenzhen Yexiang Intelligent Technology Co., Ltd.
Address	5th Floor, Office Building, Yiyuantong Industrial Park, No.6 Zhonghao Avenue, Xiangjiao Community, Bantian Street, Longgang District, SHENZHEN Guangdong
Manufacturer	Shenzhen Yexiang Intelligent Technology Co., Ltd.
Address	5th Floor, Office Building, Yiyuantong Industrial Park, No.6 Zhonghao Avenue, Xiangjiao Community, Bantian Street, Longgang District, SHENZHEN Guangdong
Factory	Shenzhen Yexiang Intelligent Technology Co., Ltd.
Address	5th Floor, Office Building, Yiyuantong Industrial Park, No.6 Zhonghao Avenue, Xiangjiao Community, Bantian Street, Longgang District, SHENZHEN Guangdong
Product Name	Bluetooth mesh smart plug
Test Model No.	YX-WS01C
Extension Model	YX-WS01B , YX-WS02A , YX-WS02B
Remark	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.0
Software Version	V1.0
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	-3.78dBi (Provided by the customer)

4 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

BlueAsia

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 RF EXPOSURE COMPLIANCE REQUIREMENT

Standard Requirement

According to KDB447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
300	39	65	88	110	129	148	166	184	201	217	
450	22	44	67	89	112	135	158	180	203	226	
835	9	25	44	66	90	116	145	175	207	240	
1900	3	12	26	44	66	92	122	157	195	236	
2450	3	10	22	38	59	83	111	143	179	219	
3600	2	8	18	32	49	71	96	125	158	195	
5800	1	6	14	25	40	58	80	106	136	169	

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$EIRP = p_t \times g_t = (EXd)^2/30$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10((dBuV/m)/20)/106$

d = measurement distance in meters (m)---3m

$$S_{opt} = (EXd)^2/30 \times g_t$$

$$\text{Ant gain} = -3.78 \text{ dBi}$$

$$\text{Max Output power} = 0.407 \text{ dBm @ BR@ 2402 MHz}$$

$$\text{ERP} = 0.407 \text{ dBm} + (-3.78 \text{ dBi}) - 2.15 = -5.523 \text{ dBm}$$

So

worse case:

$$10^{-0.0407} = 1.09 \text{ mW} < 2.72 \text{ mW}$$

Then SAR evaluation is not required

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.