



FCC TEST REPORT

**Test report
On Behalf of
Shenzhen SEI Robotics Co., Ltd.
For
SEI400DN
Model No.: SN8BABX(X=A TO Z)**

FCC ID: 2AOVU-SN8BABX

Prepared for : **Shenzhen SEI Robotics Co., Ltd.**
501, Block A, Productivity Building #5 Hi-tech Middle 2nd Road, Nanshan District,
Shenzhen, China

Prepared By : **Shenzhen HUAKE Testing Technology Co., Ltd.**
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: **May 9, 2019~ May 15, 2019**

Date of Report: **May 16, 2019**

Report Number: **HK1905151042-E1**



TEST RESULT CERTIFICATION

Applicant's name: **Shenzhen SEI Robotics Co., Ltd.**
 Address.....: 501, Block A, Productivity Building #5 Hi-tech Middle 2nd Road,
 Nanshan District, Shenzhen, China
Manufacture's Name: **Shenzhen SEI Robotics Co., Ltd.**
 Address.....: 501, Block A, Productivity Building #5 Hi-tech Middle 2nd Road,
 Nanshan District, Shenzhen, China


Product description

Trade Mark: SEI
 Product name.....: SEI400DN
 Model and/or type reference ..: SN8BABX(X=A TO Z)


Standards: FCC Rules and Regulations Part 15 Subpart C Section 15.247
 ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.


Date of Test:
 Date (s) of performance of tests: May 9, 2019~ May 15, 2019
 Date of Issue.....: May 16, 2019
 Test Result: **Pass**

Testing Engineer : 

 (Gary Qian)

Technical Manager : 

 (Eden Hu)

Authorized Signatory : 

 (Jason Zhou)



Revision History

Revision	Issue Date	Revisions	Revised By
00	May 16, 2019	Initial Issue	Jason Zhou



TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. DESCRIPTION OF DEVICE (EUT)	5
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS	6
1.3. EXTERNAL I/O CABLE	6
1.4. DESCRIPTION OF TEST FACILITY	6
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
1.6. MEASUREMENT UNCERTAINTY	7
1.7. DESCRIPTION OF TEST MODES	8
2. TEST METHODOLOGY	9
2.1. EUT CONFIGURATION	9
2.2. EUT EXERCISE	9
2.3. GENERAL TEST PROCEDURES	9
3. SYSTEM TEST CONFIGURATION	10
3.1. JUSTIFICATION	10
3.2. EUT EXERCISE SOFTWARE	10
3.3. SPECIAL ACCESSORIES	10
3.4. BLOCK DIAGRAM/SCHEMATICS	10
3.5. EQUIPMENT MODIFICATIONS	10
3.6. TEST SETUP	10
4. SUMMARY OF TEST RESULTS	11
5. TEST RESULT	12
5.1. ON TIME AND DUTY CYCLE	12
5.2. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT	14
5.3. POWER SPECTRAL DENSITY MEASUREMENT	16
5.5. RADIATED EMISSIONS MEASUREMENT	28
5.6. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST	41
5.7. POWER LINE CONDUCTED EMISSIONS	58
5.8. BAND-EDGE MEASUREMENTS FOR RADIATED EMISSIONS	61
5.9. ANTENNA REQUIREMENTS	66
6. LIST OF MEASURING EQUIPMENTS	68
7. TEST SETUP PHOTOGRAPHS OF EUT	69
8. EXTERIOR PHOTOGRAPHS OF THE EUT	69
9. INTERIOR PHOTOGRAPHS OF THE EUT	69



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: SEI400DN
Model Number	: SN8BABX(X=A TO Z)
Model Declaration	: PCB board, structure and internal of these model(s) are the same, : Only models name is different for these models.
Test Model	: SN8BABH
Power Supply	: DC 5V by adapter
Hardware version	: SMB.195.04
Software version	: Android 9.0
Bluetooth Version	: V4.2
Channel Number	: 79 Channels for Bluetooth V3.0(DSS) : 40 Channels for Bluetooth V4.2(DTS)
Modulation Technology	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V3.0(DSS) : GFSK for Bluetooth V4.2(DTS)
Data Rates	: Bluetooth V3.0(DSS): 1~3Mbps : Bluetooth V4.2(DTS): 1Mbps
WLAN	: Supported IEEE 802.11a/b/g/n/ac IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz / 5180-5240MHz / 5745-5825MHz
WLAN FCC Operation Frequency	: IEEE 802.11n HT40:2422-2452MHz / 5190-5230MHz / 5755-5795MHz IEEE 802.11a: 5180-5240MHz / 5745-5825MHz IEEE 802.11ac VHT20: 5180-5240MHz / 5745-5825MHz IEEE 802.11ac VHT40: 5190-5230MHz / 5755-5795MHz IEEE 802.11ac VHT80: 5210MHz / 5775MHz
WLAN Channel Number	: 11 Channels for 2412-2462MHz(IEEE 802.11b/g/n HT20) 7 Channels for 2422-2452MHz(IEEE 802.11n HT40) 4 Channels for 5180-5240MHz (IEEE 802.11a/ac VHT20/n HT20) 2 Channels for 5190-5230MHz (IEEE 802.11ac VHT40/n HT40) 1 Channels for 5210MHz (IEEE 802.11ac VHT80) 5 Channels for 5745-5825MHz(IEEE 802.11a/ac VHT20/n HT20) 2 Channels for 5755-5795MHz(IEEE 802.11ac VHT40/n HT40) 1 Channels for 5775MHz(IEEE 802.11ac VHT80)
WLAN Modulation Technology	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Type And Gain	: Three Antennas: Internal Antenna 0: 2.5 dBi(Max.), for TX/RX (WLAN 2.4G Band), 3.3 dBi(Max.), for TX/RX (WLAN 5G Band) Internal Antenna 1: 4.07 dBi(Max.), for TX/RX (WLAN 2.4G Band), 2.8 dBi(Max.), for TX/RX (WLAN 5G Band) Internal Antenna 2: 3.10 dBi(Max.), for TX/RX (Bluetooth),



802.11n/ac support 2T2R.[Antenna 0 and Antenna 1]

Directional Gain : 6.37 dBi for MIMO(2.4G Band)
: 6.1 dBi for MIMO(5G Band)

Note: Antenna position refer to EUT Photos.

1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
Aohai	Adapter	A18A-050100U-US2	N/A	N/A

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
USB Port	1	1m, unshielded
HDMI Port	1	N/A

1.4. Description of Test Facility

Designation Number: CN1229

Test Firm Registration Number: 616276

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the HUAK quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.



1.6. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty :	9KHz~30MHz	$\pm 3.08\text{dB}$	(1)
	30MHz~1000MHz	$\pm 4.42\text{dB}$	(1)
	1GHz~40GHz	$\pm 4.06\text{dB}$	(1)
Conduction Uncertainty :	150kHz~30MHz	$\pm 2.23\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



1.7. Description of Test Modes

The EUT has been tested under operating condition.

AC power line conducted emission pre-test at both at AC 120V/60Hz and AC 240V/50Hz modes, recorded worst case.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, that was determined to be **802.11n HT40 mode(Middle Channel, Chain 0+Chain 1)**.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be **802.11n HT40 mode(Middle Channel, Chain 0+Chain 1)**.

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

IEEE 802.11b Mode: 1 Mbps, DSSS.

IEEE 802.11g Mode: 6 Mbps, OFDM.

IEEE 802.11n Mode HT20: MCS0, OFDM.

IEEE 802.11n Mode HT40: MCS0, OFDM.

Antenna & Bandwidth

Antenna	Antenna 0		Antenna 1		Simultaneously
Bandwidth Mode	20MHz	40MHz	20MHz	40MHz	/
IEEE 802.11b	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11g	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11n	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Channel List & Frequency

IEEE 802.11b/g/n HT20

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2412~2462MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	--	--

IEEE 802.11n HT40

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2422~2452MHz	1	--	7	2442
	2	--	8	2447
	3	2422	9	2452
	4	2427	10	--
	5	2432	11	--
	6	2437	--	--



2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen HUAK Testing Technology Co., Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB 558074 D01 DTS Meas Guidance v05r02 and KDB 662911 D01 Multiple Transmitter Output v02r01 are required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013



3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (MPTool) provided by application.

3.3. Special Accessories

No.	Equipment	Manufacturer	Model No.	Serial No.	Length	shielded/ unshielded	Notes
1	TV	AOC	280LM000 03	JVVGJA000307	/	/	/

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen HUAK Testing Technology Co., Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.



4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C		
FCC Rules	Description of Test	Result
/	Duty Cycle	Compliant
§15.247(b)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	6dB Bandwidth	Compliant
§15.247(a)	Occupied Bandwidth	Compliant
§15.209, §15.247(d)	Radiated and Conducted Spurious Emissions	Compliant
§15.205	Emissions at Restricted Band	Compliant
§15.207(a)	Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant
§15.247(i)§2.1093	RF Exposure	Compliant

5. TEST RESULT

5.1. On Time and Duty Cycle

5.1.1. Standard Applicable

None; for reporting purpose only.


5.1.2. Measuring Instruments and Setting

Please refer to equipment's list in this report. The following table is the setting of the spectrum analyzer.

5.1.3. Test Procedures

1. Set the centre frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=10MHz, VBW=10MHz, Sweep time=5ms;
3. Detector = peak;
4. Trace mode = Single hold.

5.1.4. Test Setup Layout



5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.6. Test result

Mode	On Time Points	Total Sweep points	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (KHz)
IEEE 802.11b	7972	8001	99.64	0.02	0.01
IEEE 802.11g	7845	8001	98.05	0.09	0.01
IEEE 802.11n HT20	7835	8001	97.93	0.09	0.01
IEEE 802.11n HT40	7831	8001	97.88	-0.09	0.01

Remark:


1. Measured duty cycle for WLAN at antenna 0 and antenna 1 port, the two antenna ports results were same, just recorded results at antenna 0;




On Time and Duty Cycle



IEEE 802.11b



IEEE 802.11g



IEEE 802.11n HT20



IEEE 802.11n HT40

5.2. Maximum Conducted Output Power Measurement

5.2.1. Standard Applicable

According to §15.247(b): For systems using digital modulation in the 2400-2483.5 MHz and 5725-5850 MHz band, the limit for maximum peak conducted output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter peak output power.

5.2.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the power meter.

5.2.3. Test Procedures

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2 the maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

According to KDB558074 D01 DTS Measurement Guidance Section 9.2 Maximum average conducted output power, 9.2.3.1 Method AVGPM (Measurement using an RF average power meter)

(a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.


- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

(b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

(c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

(d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle to the measurement result.

5.2.4. Test Setup Layout



5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



5.2.6. Test Result of Maximum Conducted Output Power

Temperature	25.1 °C	Humidity	52.4%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)			Limits (dBm)	Verdict
			Antenna 0	Antenna 1	Sum		
IEEE 802.11b	1	2412	18.97	20.89	-/-	29.63	PASS
	6	2437	19.87	20.17	-/-		
	11	2462	18.93	19.99	-/-		
IEEE 802.11g	1	2412	19.97	20.14	-/-	29.63	PASS
	6	2437	18.66	19.38	-/-		
	11	2462	17.77	19.52	-/-		
IEEE 802.11n HT20	1	2412	18.26	18.12	21.20	29.63	PASS
	6	2437	17.64	18.27	20.98		
	11	2462	17.15	18.13	20.68		
IEEE 802.11n HT40	3	2422	18.51	18.66	21.59	29.63	PASS
	6	2437	19.02	18.19	21.63		
	9	2452	17.52	18.62	21.11		

Test Mode	Channel	Frequency (MHz)	Measured Average Output Power (dBm)			Limits (dBm)	Verdict
			Antenna 0	Antenna 1	Sum		
IEEE 802.11b	1	2412	15.68	17.82	-/-	29.63	PASS
	6	2437	16.99	17.42	-/-		
	11	2462	15.99	17.45	-/-		
IEEE 802.11g	1	2412	12.68	13.42	-/-	29.63	PASS
	6	2437	11.42	12.09	-/-		
	11	2462	10.61	12.35	-/-		
IEEE 802.11n HT20	1	2412	10.99	11.17	14.09	29.63	PASS
	6	2437	10.49	11.04	13.79		
	11	2462	9.94	10.91	13.46		
IEEE 802.11n HT40	3	2422	9.80	11.30	13.63	29.63	PASS
	6	2437	10.69	11.37	14.05		
	9	2452	8.77	11.25	13.19		

Remark:

1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. “-/-“ means no need measured or sum as cannot work at MIMO mode;
5. Average power is for report only;



5.3. Power Spectral Density Measurement

5.3.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


5.3.2. Measuring Instruments and Setting

Please refer to equipment’s list in this report. The following table is the setting of Spectrum Analyzer.

5.3.3. Test Procedures

1. The transmitter was connected directly to a Spectrum Analyzer.
2. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
3. Set the RBW = 3 KHz~100 KHz.
4. Set the VBW $\geq 3 \times$ RBW
5. Set the span to 1.5 times the DTS channel bandwidth.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.6. Test Result of Power Spectral Density

Temperature	25.1℃	Humidity	52.4%
Test Engineer	Gary Qian	Configurations	IEEE 802.11b/g/n



Test Mode	Channel	Frequency (MHz)	Measured Peak Power Spectral Density (dBm/3KHz)			Convert Factor	Report Peak Power Spectral Density	Directional Gain	Limits (dBm/3KHz)	Verdict
			Antenna 0	Antenna 1	Sum					
IEEE 802.11b	1	2412	-5.47	-6.84	-/-	0.00	-5.47	-/-	8.00	PASS
	6	2437	-5.99	-7.05	-/-	0.00	-5.99	-/-		
	11	2462	-7.64	-7.16	-/-	0.00	-7.16	-/-		
IEEE 802.11g	1	2412	-12.52	-14.64	-/-	0.00	-12.52	-/-	8.00	PASS
	6	2437	-13.77	-15.57	-/-	0.00	-13.77	-/-		
	11	2462	-14.29	-15.68	-/-	0.00	-14.29	-/-		
IEEE 802.11n HT20	1	2412	-15.14	-14.38	-11.73	0.00	-11.73	6.37	8.00	PASS
	6	2437	-15.97	-14.06	-11.90	0.00	-11.90	6.37		
	11	2462	-16.64	-14.45	-12.40	0.00	-12.40	6.37		
IEEE 802.11n HT40	3	2422	-14.95	-17.35	-12.97	0.00	-12.97	6.37	8.00	PASS
	6	2437	-15.48	-18.16	-13.61	0.00	-13.61	6.37		
	9	2452	-17.43	-17.47	-14.44	0.00	-14.44	6.37		

Remark:

1. Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. Please refer to following plots;
5. For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain;

$$\text{Directional gain} = 10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})/N_{ANT}] \text{ dBi, where antenna gains given by } G1, G2, \dots, GN \text{ dBi, } N_{ANT} \text{ is the antennas total Number.}$$
6. “-/-“ means no need measured or sum as cannot work at MIMO mode;



Power Spectral Density


Antenna 0
IEEE 802.11b

Antenna 0
IEEE 802.11g



Channel 1 / 2412 MHz

Channel 1 / 2412 MHz



Channel 6 / 2437 MHz

Channel 6 / 2437 MHz



Channel 11 / 2462 MHz


Channel 11 / 2462 MHz



Power Spectral Density


Antenna 0

IEEE 802.11n HT20




Antenna 0


IEEE 802.11n HT40




Channel 1 / 2412 MHz




Channel 3 / 2422 MHz



Channel 6 / 2437 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz

Channel 9 / 2452 MHz




Power Spectral Density


Antenna 1
IEEE 802.11b



Antenna 1
IEEE 802.11g




Channel 1 / 2412 MHz



Channel 1 / 2412 MHz



Channel 6 / 2437 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz


Channel 11 / 2462 MHz



Power Spectral Density


Antenna 1

IEEE 802.11n HT20




Antenna 1


IEEE 802.11n HT40




Channel 1 / 2412 MHz



Channel 3 / 2422 MHz



Channel 6 / 2437 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz

Channel 9 / 2452 MHz



5.4. 6 dB Spectrum Bandwidth Measurement

5.4.1. Standard Applicable

According to §15.247(a) (2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

5.4.2. Measuring Instruments and Setting


Please refer to equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> RBW
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

5.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to KDB558074.
3. Measured the spectrum width with power higher than 6dB below carrier.

5.4.4. Test Setup Layout



5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.6. Test Result of 6dB Spectrum Bandwidth

Temperature	25.1°C	Humidity	52.4%
Test Engineer	Gary Qian	Configurations	IEEE 802.11b/g/n



Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Limits (MHz)	Verdict
			Antenna 0	Antenna 1		
IEEE 802.11b	1	2412	9.07	9.10	0.500	PASS
	6	2437	9.15	9.10		
	11	2462	9.01	8.62		
IEEE 802.11g	1	2412	16.37	16.35	0.500	PASS
	6	2437	16.35	16.35		
	11	2462	16.02	16.36		
IEEE 802.11n HT20	1	2412	17.04	17.11	0.500	PASS
	6	2437	16.70	16.84		
	11	2462	16.98	17.04		
IEEE 802.11n HT40	3	2422	36.38	36.12	0.500	PASS
	6	2437	36.36	36.13		
	9	2452	36.35	36.16		


Remark:

1. Measured 6dB Bandwidth at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. Please refer to following plots;




6 dB Bandwidth


Antenna 0
IEEE 802.11b




Antenna 0
IEEE 802.11g




Channel 1 / 2412 MHz




Channel 1 / 2412 MHz



Channel 6 / 2437 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz


Channel 11 / 2462 MHz



6 dB Bandwidth


Antenna 0

IEEE 802.11n HT20




Antenna 0


IEEE 802.11n HT40




Channel 1 / 2412 MHz




Channel 3 / 2422 MHz



Channel 6 / 2437 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz

Channel 9 / 2452 MHz




6 dB Bandwidth


Antenna 1 IEEE 802.11b




Antenna 1 IEEE 802.11g




Channel 1 / 2412 MHz




Channel 1 / 2412 MHz



Channel 6 / 2437 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz


Channel 11 / 2462 MHz



6 dB Bandwidth


Antenna 1

IEEE 802.11n HT20




Antenna 1


IEEE 802.11n HT40




Channel 1 / 2412 MHz




Channel 3 / 2422 MHz



Channel 6 / 2437 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz

Channel 9 / 2452 MHz



5.5. Radiated Emissions Measurement

5.5.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

5.5.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 ^m carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP



5.5.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.5 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

Premeasurement:


- The antenna is moved spherical over the EUT in different polarizations of the antenna.

Final measurement:


- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

5.5.4. Test Setup Layout


For radiated emissions below 30MHz



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log(\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);
 Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



5.5.6. Results of Radiated Emissions (9 KHz~30MHz)

Temperature	24.5°C	Humidity	56.2%
Test Engineer	Gary Qian	Configurations	IEEE 802.11b/g/n
Test Date	May 13, 2019		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


5.5.7. Results of Radiated Emissions (30MHz~1GHz)

Temperature	24.5°C	Humidity	56.2%
Test Engineer	Gary Qian	Configurations	802.11n HT40 Middle Channel, Chain 0+Chain 1
Test Date	May 13, 2019		

The Worst Test result for 802.11n HT40 (Middle Channel) @Chain 0+Chain 1




Vertical



NO.	Freq. [MHz]	Result Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	30.970	36.41	-16.19	40	3.59	100	258	Vertical
2	62.010	36.65	-16.16	40	3.35	100	177	Vertical
3	131.850	36.23	-19.15	43.5	7.27	100	2	Vertical
4	314.695	27.41	-12.41	46.5	19.09	100	281	Vertical
5	445.160	34.68	-9.15	46.5	11.82	100	72	Vertical
6	556.225	36.18	-6.68	46.5	10.32	100	281	Vertical



Horizontal



NO.	Freq. [MHz]	Result Level [dBuV/m]	Factor [dB/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	68.315	25.46	-17.78	40	14.54	300	349	Horizontal
2	109.540	35.27	-16.01	43.5	8.23	300	355	Horizontal
3	157.555	25.95	-18.78	43.5	17.55	100	349	Horizontal
4	250.190	35.54	-13.87	46.5	10.96	100	263	Horizontal
5	445.160	37.85	-9.15	46.5	8.65	300	107	Horizontal
6	651.770	38.24	-4.95	46.5	8.26	100	303	Horizontal

Note:

- 1). Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11n HT40 (Low Channel) @ Chain 0+Chain 1
- 2). Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3). Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



5.5.8. Results for Radiated Emissions (Above 1GHz)

*IEEE 802.11b**Antenna 0**Channel 1 / 2412 MHz*

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	58.98	33.06	35.04	3.94	60.94	74.00	13.06	Peak	Horizontal
4824.00	41.68	33.06	35.04	3.94	43.64	54.00	10.36	Average	Horizontal
4824.00	56.94	33.06	35.04	3.94	58.90	74.00	15.10	Peak	Vertical
4824.00	41.43	33.06	35.04	3.94	43.39	54.00	10.61	Average	Vertical

Channel 6 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	56.74	33.16	35.15	3.96	58.71	74.00	15.29	Peak	Horizontal
4874.00	42.64	33.16	35.15	3.96	44.61	54.00	9.39	Average	Horizontal
4874.00	57.80	33.16	35.15	3.96	59.77	74.00	14.23	Peak	Vertical
4874.00	45.25	33.16	35.15	3.96	47.22	54.00	6.78	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	58.45	33.26	35.14	3.98	60.55	74.00	13.45	Peak	Horizontal
4924.00	41.48	33.26	35.14	3.98	43.58	54.00	10.42	Average	Horizontal
4924.00	59.01	33.26	35.14	3.98	61.11	74.00	12.89	Peak	Vertical
4924.00	39.92	33.26	35.14	3.98	42.02	54.00	11.98	Average	Vertical

*IEEE 802.11g**Antenna 0**Channel 1 / 2412 MHz*

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	59.14	33.06	35.04	3.94	61.10	74.00	12.90	Peak	Horizontal
4824.00	45.53	33.06	35.04	3.94	47.49	54.00	6.51	Average	Horizontal
4824.00	58.18	33.06	35.04	3.94	60.14	74.00	13.86	Peak	Vertical
4824.00	42.89	33.06	35.04	3.94	44.85	54.00	9.15	Average	Vertical

*Channel 6 / 2437 MHz*

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	58.17	33.16	35.15	3.96	60.14	74.00	13.86	Peak	Horizontal
4874.00	40.22	33.16	35.15	3.96	42.19	54.00	11.81	Average	Horizontal
4874.00	57.11	33.16	35.15	3.96	59.08	74.00	14.92	Peak	Vertical
4874.00	44.59	33.16	35.15	3.96	46.56	54.00	7.44	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	56.10	33.26	35.14	3.98	58.20	74.00	15.80	Peak	Horizontal
4924.00	42.68	33.26	35.14	3.98	44.78	54.00	9.22	Average	Horizontal
4924.00	57.33	33.26	35.14	3.98	59.43	74.00	14.57	Peak	Vertical
4924.00	45.75	33.26	35.14	3.98	47.85	54.00	6.15	Average	Vertical

*IEEE 802.11n HT20**Combined Antenna 0 and Antenna 1**Channel 1 / 2412 MHz*

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	59.02	33.06	35.04	3.94	60.98	74.00	13.02	Peak	Horizontal
4824.00	43.42	33.06	35.04	3.94	45.38	54.00	8.62	Average	Horizontal
4824.00	59.87	33.06	35.04	3.94	61.83	74.00	12.17	Peak	Vertical
4824.00	45.77	33.06	35.04	3.94	47.73	54.00	6.27	Average	Vertical

Channel 6 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	58.74	33.16	35.15	3.96	60.71	74.00	13.29	Peak	Horizontal
4874.00	44.61	33.16	35.15	3.96	46.58	54.00	7.42	Average	Horizontal
4874.00	57.00	33.16	35.15	3.96	58.97	74.00	15.03	Peak	Vertical
4874.00	45.61	33.16	35.15	3.96	47.58	54.00	6.42	Average	Vertical



Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	59.26	33.26	35.14	3.98	61.36	74.00	12.64	Peak	Horizontal
4924.00	44.46	33.26	35.14	3.98	46.56	54.00	7.44	Average	Horizontal
4924.00	57.13	33.26	35.14	3.98	59.23	74.00	14.77	Peak	Vertical
4924.00	45.48	33.26	35.14	3.98	47.58	54.00	6.42	Average	Vertical

IEEE 802.11n HT40

Combined Antenna 0 and Antenna 1

Channel 3 / 2422 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4844.00	59.14	33.06	35.04	3.94	61.10	74.00	12.90	Peak	Horizontal
4844.00	45.56	33.06	35.04	3.94	47.52	54.00	6.48	Average	Horizontal
4844.00	58.68	33.06	35.04	3.94	60.64	74.00	13.36	Peak	Vertical
4844.00	45.91	33.06	35.04	3.94	47.87	54.00	6.13	Average	Vertical

Channel 6 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	56.47	33.16	35.15	3.96	58.44	74.00	15.56	Peak	Horizontal
4874.00	41.88	33.16	35.15	3.96	43.85	54.00	10.15	Average	Horizontal
4874.00	57.94	33.16	35.15	3.96	59.91	74.00	14.09	Peak	Vertical
4874.00	44.56	33.16	35.15	3.96	46.53	54.00	7.47	Average	Vertical

Channel 9 / 2452 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4904.00	57.20	33.26	35.14	3.98	59.30	74.00	14.70	Peak	Horizontal
4904.00	44.84	33.26	35.14	3.98	46.94	54.00	7.06	Average	Horizontal
4904.00	56.78	33.26	35.14	3.98	58.88	74.00	15.12	Peak	Vertical
4904.00	40.52	33.26	35.14	3.98	42.62	54.00	11.38	Average	Vertical

Notes:

1. Measuring frequencies from 9 KHz - 10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9 KHz ~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20;



- 13.5Mbps at IEEE 802.11n HT40;*
- 5. Pre-scan at Antenna 0 and Antenna 1 for IEEE 802.11b and IEEE 802.11g mode, pre-scan at Antenna 0, Antenna 1 and Combined Antenna 0 and Antenna 1 for IEEE 802.11n mode, recorded worst case;*



5.6. Conducted Spurious Emissions and Band Edges Test

5.6.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.6.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Detector	Peak
Attenuation	Auto
RB / VB (Emission in restricted band)	100KHz/300KHz
RB / VB (Emission in non-restricted band)	100KHz/300KHz

5.6.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9 KHz to 26.5GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

5.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 5.4.4.

5.6.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.6.6. Test Results of Conducted Spurious Emissions

Temperature	24.5°C	Humidity	56.2%
Test Engineer	Gary Qian	Configurations	IEEE 802.11b/g/n



Test Mode	Channel	Frequency (MHz)	Measured Frequency Range	Spurious RF Conducted Emission (dBc)			Limits (dBc)	Verdict
				Antenna 0	Antenna 1	Antenna 2		
IEEE 802.11b	1	2412	9 KHz – 26.5 GHz	<-20	<-20	<-20	-20	PASS
	6	2437	9 KHz – 26.5 GHz	<-20	<-20	<-20		
	11	2462	9 KHz – 26.5 GHz	<-20	<-20	<-20		
IEEE 802.11g	1	2412	9 KHz – 26.5 GHz	<-20	<-20	<-20	-20	PASS
	6	2437	9 KHz – 26.5 GHz	<-20	<-20	<-20		
	11	2462	9 KHz – 26.5 GHz	<-20	<-20	<-20		
IEEE 802.11n HT20	1	2412	9 KHz – 26.5 GHz	<-20	<-20	<-20	-20	PASS
	6	2437	9 KHz – 26.5 GHz	<-20	<-20	<-20		
	11	2462	9 KHz – 26.5 GHz	<-20	<-20	<-20		
IEEE 802.11n HT40	3	2422	9 KHz – 26.5 GHz	<-20	<-20	<-20	-20	PASS
	6	2437	9 KHz – 26.5 GHz	<-20	<-20	<-20		
	9	2452	9 KHz – 26.5 GHz	<-20	<-20	<-20		

Remark:

1. Measured RF conducted spurious emission at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. “---“means that the fundamental frequency not for 15.209 limits requirement.
5. Not recorded emission values from 9 KHz to 30 MHz as emission level at least 20 dBc lower than limit;
6. Please refer to following plots;



RF Conducted Spurious Emissions

<p style="text-align: center;">Antenna 0 IEEE 802.11b Channel 1 / 2412 MHz</p>	<p style="text-align: center;">Antenna 0 IEEE 802.11g Channel 1 / 2412 MHz</p>
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 2.41200000 GHz Mkr1 2.412 995 GHz 3.895 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 2.41200000 GHz Mkr1 2.404 515 GHz 1.459 dBm</p>
2392 MHz – 2432 MHz	
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 5.01500000 GHz Mkr1 4.825 1 GHz -43.129 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 5.01500000 GHz Mkr1 6.282 2 GHz -43.230 dBm</p>
30 MHz – 10 GHz	
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 18.00000000 GHz Mkr1 25.968 0 GHz -37.930 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 18.00000000 GHz Mkr1 25.996 0 GHz -38.208 dBm</p>
10 GHz – 26 GHz	



RF Conducted Spurious Emissions

<p style="text-align: center;">Antenna 0 IEEE 802.11b Channel 6 / 2437 MHz</p>	<p style="text-align: center;">Antenna 0 IEEE 802.11g Channel 6 / 2437 MHz</p>
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 2.43700000 GHz Mkr1 2.435 995 GHz -8.143 dBm Center 2.43700 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms (8001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 2.43700000 GHz Mkr1 2.439 490 GHz -0.044 dBm Center 2.43700 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms (8001 pts)</p>
2417 MHz – 2457 MHz	2417 MHz – 2457 MHz
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 5.01500000 GHz Mkr1 1.958 2 GHz -38.628 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 17.33 ms (20001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 5.01500000 GHz Mkr1 1.970 2 GHz -41.846 dBm Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 17.33 ms (20001 pts)</p>
30 MHz – 10 GHz	30 MHz – 10 GHz
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 18.00000000 GHz Mkr1 25.600 8 GHz -38.598 dBm Start 10.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 40.00 ms (20001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 18.00000000 GHz Mkr1 25.545 6 GHz -38.229 dBm Start 10.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 40.00 ms (20001 pts)</p>
10 GHz – 26 GHz	10 GHz – 26 GHz



RF Conducted Spurious Emissions

Antenna 0


IEEE 802.11b

Channel 11 / 2462 MHz

Antenna 0


IEEE 802.11g

Channel 11 / 2462 MHz




2442 MHz – 2482 MHz

2442 MHz – 2482 MHz



30 MHz – 10 GHz

30 MHz – 10 GHz



10 GHz – 26 GHz

10 GHz – 26 GHz



RF Conducted Spurious Emissions

<p style="text-align: center;">Antenna 0</p> <p style="text-align: center;">IEEE 802.11n HT20</p> <p style="text-align: center;">Channel 1 / 2412 MHz</p>	<p style="text-align: center;">Antenna 0</p> <p style="text-align: center;">IEEE 802.11n HT40</p> <p style="text-align: center;">Channel 3 / 2422 MHz</p>																												
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 2.41200000 GHz</p> <p>Mkr1 2.418 250 GHz -0.008 dBm</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.392000000 GHz</p> <p>Stop Freq 2.432000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Center 2.41200 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Sweep 4.267 ms (8001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 2.42200000 GHz</p> <p>Mkr1 2.405 74 GHz -1.389 dBm</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.382000000 GHz</p> <p>Stop Freq 2.462000000 GHz</p> <p>CF Step 8.000000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Center 2.42200 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Sweep 8.000 ms (8001 pts)</p>																												
2392 MHz – 2432 MHz	2382 MHz – 2462 MHz																												
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 5.015000000 GHz</p> <p>Mkr1 6.128 2 GHz -43.039 dBm</p> <p>Center Freq 5.015000000 GHz</p> <p>Start Freq 30.000000 MHz</p> <p>Stop Freq 10.000000000 GHz</p> <p>CF Step 997.000000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Start 30 MHz</p> <p>#Res BW 1.0 MHz</p> <p>#VBW 3.0 MHz</p> <p>Sweep 17.33 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>Mkrs</th> <th>Marker</th> <th>Freq</th> <th>Value</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>f</td> <td>6.128 2 GHz</td> <td></td> <td></td> <td>-43.039 dBm</td> </tr> </tbody> </table>	Mkrs	Marker	Freq	Value	Function	Function Width	Function Value	1	N	f	6.128 2 GHz			-43.039 dBm	<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 5.015000000 GHz</p> <p>Mkr1 6.904 8 GHz -41.997 dBm</p> <p>Center Freq 5.015000000 GHz</p> <p>Start Freq 30.000000 MHz</p> <p>Stop Freq 10.000000000 GHz</p> <p>CF Step 997.000000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Start 30 MHz</p> <p>#Res BW 1.0 MHz</p> <p>#VBW 3.0 MHz</p> <p>Sweep 17.33 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>Mkrs</th> <th>Marker</th> <th>Freq</th> <th>Value</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>f</td> <td>6.904 8 GHz</td> <td></td> <td></td> <td>-41.997 dBm</td> </tr> </tbody> </table>	Mkrs	Marker	Freq	Value	Function	Function Width	Function Value	1	N	f	6.904 8 GHz			-41.997 dBm
Mkrs	Marker	Freq	Value	Function	Function Width	Function Value																							
1	N	f	6.128 2 GHz			-43.039 dBm																							
Mkrs	Marker	Freq	Value	Function	Function Width	Function Value																							
1	N	f	6.904 8 GHz			-41.997 dBm																							
30 MHz – 10 GHz	30 MHz – 10 GHz																												
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 18.000000000 GHz</p> <p>Mkr1 25.601 6 GHz -38.826 dBm</p> <p>Center Freq 18.000000000 GHz</p> <p>Start Freq 10.000000000 GHz</p> <p>Stop Freq 26.000000000 GHz</p> <p>CF Step 1.600000000 GHz</p> <p>Freq Offset 0 Hz</p> <p>Start 10.000 GHz</p> <p>#Res BW 1.0 MHz</p> <p>#VBW 3.0 MHz</p> <p>Sweep 40.00 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>Mkrs</th> <th>Marker</th> <th>Freq</th> <th>Value</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>f</td> <td>25.601 6 GHz</td> <td></td> <td></td> <td>-38.826 dBm</td> </tr> </tbody> </table>	Mkrs	Marker	Freq	Value	Function	Function Width	Function Value	1	N	f	25.601 6 GHz			-38.826 dBm	<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 18.000000000 GHz</p> <p>Mkr1 25.582 4 GHz -38.378 dBm</p> <p>Center Freq 18.000000000 GHz</p> <p>Start Freq 10.000000000 GHz</p> <p>Stop Freq 26.000000000 GHz</p> <p>CF Step 1.600000000 GHz</p> <p>Freq Offset 0 Hz</p> <p>Start 10.000 GHz</p> <p>#Res BW 1.0 MHz</p> <p>#VBW 3.0 MHz</p> <p>Sweep 40.00 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>Mkrs</th> <th>Marker</th> <th>Freq</th> <th>Value</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>f</td> <td>25.582 4 GHz</td> <td></td> <td></td> <td>-38.378 dBm</td> </tr> </tbody> </table>	Mkrs	Marker	Freq	Value	Function	Function Width	Function Value	1	N	f	25.582 4 GHz			-38.378 dBm
Mkrs	Marker	Freq	Value	Function	Function Width	Function Value																							
1	N	f	25.601 6 GHz			-38.826 dBm																							
Mkrs	Marker	Freq	Value	Function	Function Width	Function Value																							
1	N	f	25.582 4 GHz			-38.378 dBm																							
10 GHz – 26 GHz	10 GHz – 26 GHz																												



RF Conducted Spurious Emissions

Antenna 0



IEEE 802.11n HT20

Channel 6 / 2437 MHz

Antenna 0

IEEE 802.11n HT40

Channel 6 / 2437 MHz




2417 MHz – 2457 MHz

2397 MHz – 2477 MHz



30 MHz – 10 GHz

30 MHz – 10 GHz



10 GHz – 26 GHz

10 GHz – 26 GHz



RF Conducted Spurious Emissions

Antenna 0



IEEE 802.11n HT20

Channel 11 / 2462 MHz

Antenna 0


IEEE 802.11n HT40

Channel 9 / 2452 MHz





2442 MHz – 2482 MHz

2412 MHz – 2492 MHz



30 MHz – 10 GHz

30 MHz – 10 GHz



10 GHz – 26 GHz

10 GHz – 26 GHz



RF Conducted Spurious Emissions

<p style="text-align: center;">Antenna 1 IEEE 802.11b Channel 1 / 2412 MHz</p>	<p style="text-align: center;">Antenna 1 IEEE 802.11g Channel 1 / 2412 MHz</p>
	
2392 MHz – 2432 MHz	2392 MHz – 2432 MHz
	
30 MHz – 10 GHz	30 MHz – 10 GHz
	
10 GHz – 26 GHz	10 GHz – 26 GHz



RF Conducted Spurious Emissions

<p style="text-align: center;">Antenna 1 IEEE 802.11b Channel 6 / 2437 MHz</p>	<p style="text-align: center;">Antenna 1 IEEE 802.11g Channel 6 / 2437 MHz</p>
<p>Center Freq 2.437000000 GHz Mkr1 2.437 990 GHz 8.361 dBm Center Freq 2.437000000 GHz Start Freq 2.417000000 GHz Stop Freq 2.457000000 GHz CF Step 4.000000 MHz Freq Offset 0 Hz Center 2.43700 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms (8001 pts)</p>	<p>Center Freq 2.437000000 GHz Mkr1 2.444 490 GHz 0.863 dBm Center Freq 2.437000000 GHz Start Freq 2.417000000 GHz Stop Freq 2.457000000 GHz CF Step 4.000000 MHz Freq Offset 0 Hz Center 2.43700 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms (8001 pts)</p>
2417 MHz – 2457 MHz	2417 MHz – 2457 MHz
<p>Center Freq 5.015000000 GHz Mkr1 4.874 9 GHz -40.635 dBm Center Freq 5.015000000 GHz Start Freq 30.000000 MHz Stop Freq 10.000000000 GHz CF Step 997.000000 MHz Freq Offset 0 Hz Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 17.33 ms (20001 pts)</p>	<p>Center Freq 5.015000000 GHz Mkr1 6.724 9 GHz -42.798 dBm Center Freq 5.015000000 GHz Start Freq 30.000000 MHz Stop Freq 10.000000000 GHz CF Step 997.000000 MHz Freq Offset 0 Hz Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 17.33 ms (20001 pts)</p>
30 MHz – 10 GHz	30 MHz – 10 GHz
<p>Center Freq 18.000000000 GHz Mkr1 25.567 2 GHz -38.384 dBm Center Freq 18.000000000 GHz Start Freq 10.000000000 GHz Stop Freq 26.000000000 GHz CF Step 1.600000000 GHz Freq Offset 0 Hz Start 10.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 40.00 ms (20001 pts)</p>	<p>Center Freq 18.000000000 GHz Mkr1 25.976 0 GHz -37.762 dBm Center Freq 18.000000000 GHz Start Freq 10.000000000 GHz Stop Freq 26.000000000 GHz CF Step 1.600000000 GHz Freq Offset 0 Hz Start 10.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 40.00 ms (20001 pts)</p>
10 GHz – 26 GHz	10 GHz – 26 GHz



RF Conducted Spurious Emissions

<p style="text-align: center;">Antenna 1 IEEE 802.11b Channel 11 / 2462 MHz</p>	<p style="text-align: center;">Antenna 1 IEEE 802.11g Channel 11 / 2462 MHz</p>
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 2.46200000 GHz Mkr1 2.462 990 GHz -8.840 dBm Span 40.00 MHz</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 2.46200000 GHz Mkr1 2.484 490 GHz -0.438 dBm Span 40.00 MHz</p>
2442 MHz – 2482 MHz	2442 MHz – 2482 MHz
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 5.015000000 GHz Mkr1 4.924 3 GHz -39.870 dBm Sweep 17.33 ms (20001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 5.015000000 GHz Mkr1 5.443 7 GHz -42.574 dBm Sweep 17.33 ms (20001 pts)</p>
30 MHz – 10 GHz	30 MHz – 10 GHz
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 18.000000000 GHz Mkr1 25.992 0 GHz -38.164 dBm Sweep 40.00 ms (20001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 18.000000000 GHz Mkr1 25.988 4 GHz -38.829 dBm Sweep 40.00 ms (20001 pts)</p>
10 GHz – 26 GHz	10 GHz – 26 GHz



RF Conducted Spurious Emissions

<p style="text-align: center;">Antenna 1</p> <p style="text-align: center;">IEEE 802.11n HT20</p> <p style="text-align: center;">Channel 1 / 2412 MHz</p>	<p style="text-align: center;">Antenna 1</p> <p style="text-align: center;">IEEE 802.11n HT40</p> <p style="text-align: center;">Channel 3 / 2422 MHz</p>																												
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 2.41200000 GHz</p> <p>Mkr1 2.406980 GHz 0.084 dBm</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.38200000 GHz</p> <p>Stop Freq 2.43200000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Center 2.41200 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Sweep 4.267 ms (8001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 2.42200000 GHz</p> <p>Mkr1 2.40575 GHz -2.404 dBm</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.38200000 GHz</p> <p>Stop Freq 2.46200000 GHz</p> <p>CF Step 8.000000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Center 2.42200 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Sweep 8.000 ms (8001 pts)</p>																												
2392 MHz – 2432 MHz	2382 MHz – 2462 MHz																												
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 5.01500000 GHz</p> <p>Mkr1 5.8988 GHz -42.882 dBm</p> <p>Center Freq 5.01500000 GHz</p> <p>Start Freq 30.000000 MHz</p> <p>Stop Freq 10.00000000 GHz</p> <p>CF Step 997.000000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Start 30 MHz</p> <p>#Res BW 1.0 MHz</p> <p>#VBW 3.0 MHz</p> <p>Sweep 17.33 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>INDEX</th> <th>FREQ (GHz)</th> <th>AMPL (dBm)</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>5.8988 GHz</td> <td>-42.882 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	INDEX	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	5.8988 GHz	-42.882 dBm				<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 5.01500000 GHz</p> <p>Mkr1 6.4223 GHz -42.879 dBm</p> <p>Center Freq 5.01500000 GHz</p> <p>Start Freq 30.000000 MHz</p> <p>Stop Freq 10.00000000 GHz</p> <p>CF Step 997.000000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Start 30 MHz</p> <p>#Res BW 1.0 MHz</p> <p>#VBW 3.0 MHz</p> <p>Sweep 17.33 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>INDEX</th> <th>FREQ (GHz)</th> <th>AMPL (dBm)</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>6.4223 GHz</td> <td>-42.879 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	INDEX	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	6.4223 GHz	-42.879 dBm			
MKR	INDEX	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																							
1	N	5.8988 GHz	-42.882 dBm																										
MKR	INDEX	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																							
1	N	6.4223 GHz	-42.879 dBm																										
30 MHz – 10 GHz	30 MHz – 10 GHz																												
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 18.00000000 GHz</p> <p>Mkr1 25.9944 GHz -38.339 dBm</p> <p>Center Freq 18.00000000 GHz</p> <p>Start Freq 10.00000000 GHz</p> <p>Stop Freq 26.00000000 GHz</p> <p>CF Step 1.60000000 GHz</p> <p>Freq Offset 0 Hz</p> <p>Start 10.000 GHz</p> <p>#Res BW 1.0 MHz</p> <p>#VBW 3.0 MHz</p> <p>Sweep 40.00 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>INDEX</th> <th>FREQ (GHz)</th> <th>AMPL (dBm)</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>25.9944 GHz</td> <td>-38.339 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	INDEX	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	25.9944 GHz	-38.339 dBm				<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 18.00000000 GHz</p> <p>Mkr1 25.9856 GHz -38.330 dBm</p> <p>Center Freq 18.00000000 GHz</p> <p>Start Freq 10.00000000 GHz</p> <p>Stop Freq 26.00000000 GHz</p> <p>CF Step 1.60000000 GHz</p> <p>Freq Offset 0 Hz</p> <p>Start 10.000 GHz</p> <p>#Res BW 1.0 MHz</p> <p>#VBW 3.0 MHz</p> <p>Sweep 40.00 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>INDEX</th> <th>FREQ (GHz)</th> <th>AMPL (dBm)</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>25.9856 GHz</td> <td>-38.330 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	INDEX	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	25.9856 GHz	-38.330 dBm			
MKR	INDEX	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																							
1	N	25.9944 GHz	-38.339 dBm																										
MKR	INDEX	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																							
1	N	25.9856 GHz	-38.330 dBm																										
10 GHz – 26 GHz	10 GHz – 26 GHz																												



RF Conducted Spurious Emissions

Antenna 1 IEEE 802.11n HT20 Channel 6 / 2437 MHz	Antenna 1 IEEE 802.11n HT40 Channel 6 / 2437 MHz
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 2.43700000 GHz Mkr1 2.442 000 GHz -0.221 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 2.43700000 GHz Mkr1 2.434 49 GHz -2.297 dBm</p>
2417 MHz – 2457 MHz	2397 MHz – 2477 MHz
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 5.01500000 GHz Mkr1 6.274 7 GHz -42.739 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 5.01500000 GHz Mkr1 6.382 4 GHz -42.840 dBm</p>
30 MHz – 10 GHz	30 MHz – 10 GHz
<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 18.00000000 GHz Mkr1 25.809 6 GHz -37.859 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep 54 Center Freq 18.00000000 GHz Mkr1 25.987 2 GHz -38.517 dBm</p>
10 GHz – 26 GHz	10 GHz – 26 GHz



RF Conducted Spurious Emissions



<p style="text-align: center;">Antenna 1</p> <p style="text-align: center;">IEEE 802.11n HT20</p> <p style="text-align: center;">Channel 11 / 2462 MHz</p>	<p style="text-align: center;">Antenna 1</p> <p style="text-align: center;">IEEE 802.11n HT40</p> <p style="text-align: center;">Channel 9 / 2452 MHz</p>
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 2.46200000 GHz</p> <p>Mkr1 2.456 985 GHz -0.144 dBm</p> <p>Center Freq: 2.46200000 GHz Start Freq: 2.44200000 GHz Stop Freq: 2.48200000 GHz CF Step: 4.000000 MHz Freq Offset: 0 Hz</p> <p>Center 2.46200 GHz #VBW 300 kHz Span 40.000 MHz #Res BW 100 kHz Sweep 4.267 ms (8001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 2.45200000 GHz</p> <p>Mkr1 2.454 52 GHz -2.550 dBm</p> <p>Center Freq: 2.45200000 GHz Start Freq: 2.41200000 GHz Stop Freq: 2.49200000 GHz CF Step: 8.000000 MHz Freq Offset: 0 Hz</p> <p>Center 2.45200 GHz #VBW 300 kHz Span 80.000 MHz #Res BW 100 kHz Sweep 8.000 ms (8001 pts)</p>
2442 MHz – 2482 MHz	2412 MHz – 2492 MHz
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 5.01500000 GHz</p> <p>Mkr1 5.849 5 GHz -42.673 dBm</p> <p>Center Freq: 5.01500000 GHz Start Freq: 30.000000 MHz Stop Freq: 10.00000000 GHz CF Step: 997.000000 MHz Freq Offset: 0 Hz</p> <p>Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 17.33 ms (20001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 5.01500000 GHz</p> <p>Mkr1 5.857 5 GHz -43.049 dBm</p> <p>Center Freq: 5.01500000 GHz Start Freq: 30.000000 MHz Stop Freq: 10.00000000 GHz CF Step: 997.000000 MHz Freq Offset: 0 Hz</p> <p>Start 30 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 17.33 ms (20001 pts)</p>
30 MHz – 10 GHz	30 MHz – 10 GHz
<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 18.00000000 GHz</p> <p>Mkr1 25.599 6 GHz -38.260 dBm</p> <p>Center Freq: 18.00000000 GHz Start Freq: 10.00000000 GHz Stop Freq: 26.00000000 GHz CF Step: 1.60000000 GHz Freq Offset: 0 Hz</p> <p>Start 10.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 40.00 ms (20001 pts)</p>	<p>Agilent Spectrum Analyzer - Sweep 54</p> <p>Center Freq 18.00000000 GHz</p> <p>Mkr1 25.984 0 GHz -37.732 dBm</p> <p>Center Freq: 18.00000000 GHz Start Freq: 10.00000000 GHz Stop Freq: 26.00000000 GHz CF Step: 1.60000000 GHz Freq Offset: 0 Hz</p> <p>Start 10.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 40.00 ms (20001 pts)</p>
10 GHz – 26 GHz	10 GHz – 26 GHz



Band-edge Measurements for Conducted Emissions


Antenna 0
IEEE 802.11b

Antenna 0
IEEE 802.11g



Channel 1 / 2412 MHz

Channel 1 / 2412 MHz



Channel 11 / 2462 MHz

Channel 11 / 2462 MHz





Band-edge Measurements for Conducted Emissions

Antenna 1

IEEE 802.11b



Antenna 1

IEEE 802.11g



Channel 1 / 2412 MHz

Channel 1 / 2412 MHz




Channel 11 / 2462 MHz

Channel 11 / 2462 MHz




Band-edge Measurements for Conducted Emissions Combine Antenna 0 and Antenna 1

IEEE 802.11n HT20




IEEE 802.11n HT40



Channel 1 / 2412 MHz



Channel 3 / 2422 MHz



Channel 11 / 2462 MHz

Channel 9 / 2452 MHz

5.7. Power line conducted emissions


5.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency

5.7.2 Block Diagram of Test Setup



5.7.3 Test Results


Temperature	24.5°C	Humidity	56.2%
Test Engineer	Gary Qian	Configurations	802.11n HT20 Low Channel, Chain 0+Chain 1
Test Date	May 13, 2019		

The Worst Test result for 802.11n HT20 (High Channel) @Chain 0+Chain 1




AC Conducted Emission of power adapter @ AC 120V/60Hz @ IEEE 802.11n HT20 (worst case)

Line



Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.208500	40.70	10.7	63	22.6	QP	N	GND
0.501000	40.60	10.0	56	15.4	QP	N	GND
1.014000	32.80	9.8	56	23.2	QP	N	GND
2.251500	28.40	9.8	56	27.6	QP	N	GND
10.734000	36.00	9.9	60	24.0	QP	N	GND
17.826000	35.80	10.2	60	24.2	QP	N	GND
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.307500	24.80	10.2	50	25.2	AV	N	GND
0.501000	30.00	10.0	46	16.0	AV	N	GND
0.933000	23.10	9.8	46	22.9	AV	N	GND
3.732000	20.90	9.8	46	25.1	AV	N	GND
10.959000	25.30	9.9	50	24.7	AV	N	GND
17.488500	24.80	10.2	50	25.2	AV	N	GND



Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.181500	42.30	10.4	64	22.1	QP	L1	GND
0.496500	40.10	10.0	56	16.0	QP	L1	GND
0.910500	32.90	9.9	56	23.1	QP	L1	GND
4.713000	26.60	9.8	56	29.4	QP	L1	GND
10.585500	35.30	9.9	60	24.7	QP	L1	GND
15.594000	31.90	10.0	60	28.1	QP	L1	GND
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.195000	28.50	10.6	54	25.3	AV	L1	GND
0.519000	27.40	10.0	46	18.6	AV	L1	GND
0.910500	25.10	9.9	46	20.9	AV	L1	GND
2.512500	22.30	9.8	46	23.7	AV	L1	GND
10.504500	26.00	9.9	50	24.0	AV	L1	GND
17.817000	25.60	10.2	50	24.4	AV	L1	GND

***Note: Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11n HT40).


5.8. Band-edge measurements for radiated emissions

5.8.1 Standard Applicable


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.8.2 Test Setup Layout

For Radiated



For Conducted



5.8.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.8.4. Test Procedures

Radiated Method:

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.



3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed..
5. The distance between test antenna and EUT was 3 meter:
6. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Conducted Method:

According to KDB 558074 D01 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to an EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=1/B for AV detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies \leq 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies $>$ 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the result ant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.77 = \text{EIRP} + 95.23$$

Where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Per KDB662911 D01 section b) In cases where a combination of conducted measurements and cabinet radiated measurements are permitted to demonstrate compliance with absolute radiated out-of-band and spurious limits (e.g., KDB Publications 558074 for DTS and 789033 for U-NII), the conducted measurements must be combined with directional gain to compute the radiated levels of the out-of-band and spurious emissions as described in this section.
13. Compare the resultant electric field strength level to the applicable regulatory limit.
14. Perform radiated spurious emission test duress until all measured frequencies were complete.



5.8.5 Test Results

Antenna 0

IEEE 802.11b										
Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2390.00	53.84	29.99	30.21	8.35	61.97	74	-12.03	Peak	Horizontal
1	2390.00	39.25	29.99	30.21	8.35	47.38	54	-6.62	AV ^[1]	Horizontal
2	2390.00	57.22	29.99	30.21	8.35	65.35	74	-8.65	Peak	Vertical
2	2390.00	36.96	29.99	30.21	8.35	45.09	54	-8.91	AV ^[1]	Vertical
3	2483.50	53.98	30.25	30.25	8.5	62.48	74	-11.52	Peak	Horizontal
3	2483.50	25.22	30.25	30.25	8.5	33.72	54	-20.28	AV ^[1]	Horizontal
4	2483.50	52.52	30.25	30.25	8.5	61.02	74	-12.98	Peak	Vertical
4	2483.50	25.16	30.25	30.25	8.5	33.66	54	-20.34	AV ^[1]	Vertical
5	2489.67	54.75	30.25	30.25	8.5	63.25	74	-10.75	Peak	Horizontal
5	2486.15	33.99	30.25	30.25	8.5	42.49	54	-11.51	AV ^[1]	Horizontal
6	2499.54	51.92	30.25	30.25	8.5	60.42	74	-13.58	Peak	Vertical
6	2499.71	39.81	30.25	30.25	8.5	48.31	54	-5.69	AV ^[1]	Vertical

IEEE 802.11g										
Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2390.00	57.36	29.99	30.21	8.35	65.49	74	-8.51	Peak	Horizontal
1	2390.00	39.46	29.99	30.21	8.35	47.59	54	-6.41	AV ^[1]	Horizontal
2	2390.00	61.20	29.99	30.21	8.35	69.33	74	-4.67	Peak	Vertical
2	2390.00	38.11	29.99	30.21	8.35	46.24	54	-7.76	AV ^[1]	Vertical
3	2483.50	58.28	30.25	30.25	8.5	66.78	74	-7.22	Peak	Horizontal
3	2483.50	27.61	30.25	30.25	8.5	36.11	54	-17.89	AV ^[1]	Horizontal
4	2483.50	51.71	30.25	30.25	8.5	60.21	74	-13.79	Peak	Vertical
4	2483.50	26.85	30.25	30.25	8.5	35.35	54	-18.65	AV ^[1]	Vertical
5	2487.70	60.20	30.25	30.25	8.5	68.70	74	-5.30	Peak	Horizontal
5	2488.56	39.06	30.25	30.25	8.5	47.56	54	-6.44	AV ^[1]	Horizontal
6	2495.95	51.67	30.25	30.25	8.5	60.17	74	-13.83	Peak	Vertical
6	2498.55	41.15	30.25	30.25	8.5	49.65	54	-4.35	AV ^[1]	Vertical



Antenna 1

IEEE 802.11b										
Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Detector	Polarization
1	2390.00	53.14	29.99	30.21	8.35	61.27	74	-12.73	Peak	Horizontal
1	2390.00	37.78	29.99	30.21	8.35	45.91	54	-8.09	AV ^[1]	Horizontal
2	2390.00	55.29	29.99	30.21	8.35	63.42	74	-10.58	Peak	Vertical
2	2390.00	39.07	29.99	30.21	8.35	47.20	54	-6.80	AV ^[1]	Vertical
3	2483.50	54.67	30.25	30.25	8.5	63.17	74	-10.83	Peak	Horizontal
3	2483.50	27.58	30.25	30.25	8.5	36.08	54	-17.92	AV ^[1]	Horizontal
4	2483.50	49.85	30.25	30.25	8.5	58.35	74	-15.65	Peak	Vertical
4	2483.50	24.81	30.25	30.25	8.5	33.31	54	-20.69	AV ^[1]	Vertical
5	2483.68	55.10	30.25	30.25	8.5	63.60	74	-10.40	Peak	Horizontal
5	2484.03	38.18	30.25	30.25	8.5	46.68	54	-7.32	AV ^[1]	Horizontal
6	2495.99	50.81	30.25	30.25	8.5	59.31	74	-14.69	Peak	Vertical
6	2497.38	37.15	30.25	30.25	8.5	45.65	54	-8.35	AV ^[1]	Vertical

IEEE 802.11g										
Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Detector	Polarization
1	2390.00	56.66	29.99	30.21	8.35	64.79	74	-9.21	Peak	Horizontal
1	2390.00	41.70	29.99	30.21	8.35	49.83	54	-4.17	AV ^[1]	Horizontal
2	2390.00	59.67	29.99	30.21	8.35	67.80	74	-6.20	Peak	Vertical
2	2390.00	42.45	29.99	30.21	8.35	50.58	54	-3.42	AV ^[1]	Vertical
3	2483.50	55.81	30.25	30.25	8.5	64.31	74	-9.69	Peak	Horizontal
3	2483.50	28.60	30.25	30.25	8.5	37.10	54	-16.90	AV ^[1]	Horizontal
4	2483.50	54.39	30.25	30.25	8.5	62.89	74	-11.11	Peak	Vertical
4	2483.50	29.31	30.25	30.25	8.5	37.81	54	-16.19	AV ^[1]	Vertical
5	2487.93	57.64	30.25	30.25	8.5	66.14	74	-7.86	Peak	Horizontal
5	2491.26	35.96	30.25	30.25	8.5	44.46	54	-9.54	AV ^[1]	Horizontal
6	2495.55	51.04	30.25	30.25	8.5	59.54	74	-14.46	Peak	Vertical
6	2496.02	36.98	30.25	30.25	8.5	45.48	54	-8.52	AV ^[1]	Vertical



Antenna 0 and 1

IEEE 802.11n HT20										
Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Detector	Polarization
1	2390.00	53.70	29.99	30.21	8.35	61.83	74	-12.17	Peak	Horizontal
1	2390.00	39.53	29.99	30.21	8.35	47.66	54	-6.34	AV ^[1]	Horizontal
2	2390.00	56.01	29.99	30.21	8.35	64.14	74	-9.86	Peak	Vertical
2	2390.00	36.50	29.99	30.21	8.35	44.63	54	-9.37	AV ^[1]	Vertical
3	2483.50	55.86	30.25	30.25	8.5	64.36	74	-9.64	Peak	Horizontal
3	2483.50	29.29	30.25	30.25	8.5	37.79	54	-16.21	AV ^[1]	Horizontal
4	2483.50	49.92	30.25	30.25	8.5	58.42	74	-15.58	Peak	Vertical
4	2483.50	24.66	30.25	30.25	8.5	33.16	54	-20.84	AV ^[1]	Vertical
5	2487.27	57.80	30.25	30.25	8.5	66.30	74	-7.70	Peak	Horizontal
5	2488.08	35.78	30.25	30.25	8.5	44.28	54	-9.72	AV ^[1]	Horizontal
6	2499.97	49.57	30.25	30.25	8.5	58.07	74	-15.93	Peak	Vertical
6	2495.52	38.96	30.25	30.25	8.5	47.46	54	-6.54	AV ^[1]	Vertical

IEEE 802.11n HT40										
Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Detector	Polarization
1	2390.00	57.37	29.99	30.21	8.35	65.50	74	-8.50	Peak	Horizontal
1	2390.00	37.82	29.99	30.21	8.35	45.95	54	-8.05	AV ^[1]	Horizontal
2	2390.00	61.06	29.99	30.21	8.35	69.19	74	-4.81	Peak	Vertical
2	2390.00	40.64	29.99	30.21	8.35	48.77	54	-5.23	AV ^[1]	Vertical
3	2483.50	59.57	30.25	30.25	8.5	68.07	74	-5.93	Peak	Horizontal
3	2483.50	31.41	30.25	30.25	8.5	39.91	54	-14.09	AV ^[1]	Horizontal
4	2483.50	52.97	30.25	30.25	8.5	61.47	74	-12.53	Peak	Vertical
4	2483.50	26.53	30.25	30.25	8.5	35.03	54	-18.97	AV ^[1]	Vertical
5	2486.12	59.66	30.25	30.25	8.5	68.16	74	-5.84	Peak	Horizontal
5	2489.59	36.75	30.25	30.25	8.5	45.25	54	-8.75	AV ^[1]	Horizontal
6	2495.14	53.00	30.25	30.25	8.5	61.50	74	-12.50	Peak	Vertical
6	2499.34	41.75	30.25	30.25	8.5	50.25	54	-3.75	AV ^[1]	Vertical

REMARKS:

1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. The other emission levels were very low against the limit.
3. Over Limit=Emission Level - Limit.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak;



5.9. Antenna Requirements

5.9.1. Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

5.9.2. Antenna Connected Construction

5.9.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.9.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting refer to section 1.1 of this report, and the antenna is a Internal antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

5.9.2.3. Results: Compliance.

Measurement

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Conducted power refers ANSI C63.10:2013 Output power test procedure for DTS devices.

Radiated power refers to ANSI C63.10:2013 Radiated emissions tests.

Measurement parameters

Measurement parameter	
Detector:	Peak
Sweep Time:	Auto
Resolution bandwidth:	1MHz
Video bandwidth:	3MHz
Trace-Mode:	Max hold

Note: The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal WLAN devices, the IEEE 802.11b mode is used.



Limits

FCC	ISED
Antenna Gain	
6 dBi	

Antenna 0

T _{nom}	V _{nom}	Lowest Channel 2412 MHz	Middle Channel 2437 MHz	Highest Channel 2462 MHz
Conducted power [dBm] Measured with DSSS modulation		18.97	19.87	18.93
Radiated power [dBm] Measured with DSSS modulation		17.76	19.52	19.1
Gain [dBi] Calculated		-1.21	-0.35	0.17
Measurement uncertainty			± 1.6 dB (cond.) / ± 3.8 dB (rad.)	

Antenna 1

T _{nom}	V _{nom}	Lowest Channel 2412 MHz	Middle Channel 2437 MHz	Highest Channel 2462 MHz
Conducted power [dBm] Measured with DSSS modulation		20.89	20.17	19.99
Radiated power [dBm] Measured with DSSS modulation		20.15	18.82	19.34
Gain [dBi] Calculated		-0.74	-1.35	-0.65
Measurement uncertainty			± 1.6 dB (cond.) / ± 3.8 dB (rad.)	



6. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 27, 2018	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 27, 2018	1 Year
4.	Spectrum analyzer	R&S	FSP40	HKE-025	Dec. 27, 2018	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 27, 2018	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 27, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 27, 2018	1 Year
10.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Dec. 27, 2018	1 Year
11.	Broadband Horn Antenna	Schwarzbeck	BBHA 9170	HKE-017	Dec. 27, 2018	1 Year
12.	Pre-amplifier	EMCI	EMC051845 SE	HKE-015	Dec. 27, 2018	1 Year
13.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 27, 2018	1 Year
14.	EMI Test Software EZ-EMC	Tonscend	JS1120-B	HKE-083	Dec. 27, 2018	N/A
15.	Power Sensor	Agilent	E9300A	HKE-086	Dec. 27, 2018	1 Year
16.	Signal generator	Agilent	N5182A	HKE-029	Dec. 27, 2018	1 Year
17.	Signal Generator	Agilent	83630A	HKE-028	Dec. 27, 2018	1 Year
18.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 27, 2018	3 Year
19.	Horn Antenna	ETS	3117	HKE-040	Dec. 27, 2018	1 Year
20.	RF Cable(below 1GHz)	HUBER+SUHNER	RG214	HKE-055	Dec. 27, 2018	1 Year
21.	RF Cable(above 1GHz)	HUBER+SUHNER	RG214	HKE-056	Dec. 27, 2018	1 Year



7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----