

# FCC REPORT

**Applicant:** Green Start Industries LLC

**Address of Applicant:** 3305 Fairmount Ave Ocean NJ USA

**Equipment Under Test (EUT)**

Product Name: keyless transmitter

Model No.: 2AOVX-4B

**FCC ID:** 2AOVX-K2

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.231(a)

**Date of sample receipt:** 06 Sep., 2018

**Date of Test:** 06 Sep., to 13 Sep., 2018

**Date of report issue:** 13 Sep., 2018

**Test Result:** PASS\*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	13 Sep., 2018	Original

**Prepared By:** Zora Lee **Date:** 13 Sep., 2018  
**Test Engineer**

**Check By:** Wimer Zhang **Date:** 13 Sep., 2018  
**Project Engineer**

## 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 TEST SUMMARY.....</b>	<b>4</b>
<b>5 GENERAL INFORMATION.....</b>	<b>5</b>
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE .....	5
5.4 DESCRIPTION OF SUPPORT UNITS.....	5
5.5 LABORATORY FACILITY.....	6
5.6 LABORATORY LOCATION .....	6
5.7 MEASUREMENT UNCERTAINTY.....	6
5.8 TEST INSTRUMENTS LIST.....	7
<b>6 TEST RESULTS AND MEASUREMENT DATA.....</b>	<b>8</b>
6.1 ANTENNA REQUIREMENT .....	8
6.2 RADIATED EMISSION .....	9
6.2.1 Field Strength Of The Fundamental Signal.....	11
6.2.2 Spurious Emissions .....	15
6.3 20DB BANDWIDTH.....	20
6.4 DURATION TIME.....	22
<b>7 TEST SETUP PHOTOS.....</b>	<b>24</b>
<b>8 EUT CONSTRUCTIONAL PHOTOS.....</b>	<b>25</b>

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
Field strength of the fundamental signal	15.231 (b)	Pass
Spurious emissions	15.231 (b)/15.209	Pass
20dB Bandwidth	15.231 (c)	Pass
Dwell time	15.231 (a1)	Pass
Conducted Emission	15.207	N/A
<p><i>Remarks:</i>  <i>N/A: The EUT not applicable of the test item.</i>  <i>Pass: The EUT complies with the essential requirements in the standard.</i>  <b>TEST ACCORDING TO ANSI C63.4:2014 AND ANSI C63.10:2013.</b></p>		

## 5 General Information

### 5.1 Client Information

Applicant:	Green Start Industries LLC
Address of Applicant:	3305 Fairmount Ave Ocean NJ USA
Manufacturer:	Green Start Industries LLC
Address of Manufacturer:	3305 Fairmount Ave Ocean NJ USA

### 5.2 General Description of E.U.T.

Product Name:	keyless transmitter
Model No.:	2AOVX-4B
Operation Frequency:	313.85MHz
Channel numbers:	1
Modulation type:	FSK
Antenna Type:	PCB antenna
Antenna gain:	0 dBi
Power supply:	DC 3V (CR2025 battery)

### 5.3 Test mode

Transmitting mode:	Keep the EUT in transmitting mode with modulation (new battery used)		
<b>Pre-Test Mode:</b>			
CCIS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:			
Axis	X	Y	Z
Field Strength(dBuV/m)	74.86	73.25	72.41
<b>Final Test Mode:</b>			
According to ANSI C63.4 standards, the test results are both the "worst case" and "worst setup": X axis (see the test setup photo)			

### 5.4 Description of Support Units

N/A
-----

## 5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

## 5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,

Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

## 5.7 Measurement Uncertainty


Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±2.22 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±2.76 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.28 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.72 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±2.88 dB (k=2)

## 5.8 Test Instruments list

<b>Radiated Emission:</b>					
<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Date (mm-dd-yy)</b>	<b>Cal. Due date (mm-dd-yy)</b>
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-16-2018	03-15-2019
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-16-2018	03-15-2019
Loop Antenna	SCHWARZBECK	FMZB 1519 B	00044	04-28-2018	04-27-2019
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2017	11-20-2018
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2018	03-06-2019
Pre-amplifier	CD	PAP-1G18	11804	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2017	11-20-2018
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-07-2018	03-06-2019
Simulated Station	Anritsu	MT8820C	6201026545	03-07-2018	03-06-2019
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2018	03-06-2019
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2018	03-06-2019
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2018	03-06-2019

## 6 Test results and Measurement Data



### 6.1 Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203
<p>15.203 requirement:          An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
<b>E.U.T Antenna:</b>	
<p>The EUT make use of an PCB antenna, The typical gain of the antenna is 0 dBi.</p>	
	




## 6.2 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.231(b) and 15.209				
Test Method:	ANSI C63.4:2014 ; ANSI C63.10:2013				
Test Frequency Range:	30MHz to 5000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	313.85MHz	75.55		Average Value	
		95.55		Peak Value	
Limit: (Spurious Emissions)	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
Or The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level whichever limit permits higher field strength.					
Test Procedure:	<p>a. The EUT was placed on the top of a rotating table 0.8m(below 1GHz) /1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p>				

<p>Test setup:</p>	<p>Below 1GHz</p>  <p>Above 1GHz</p> 
<p>Test Instruments:</p>	<p>Refer to section 5.7 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Pass</p>


## 6.2.1 Field Strength Of The Fundamental Signal

Peak value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor(dB)	Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Polarization
313.85	38.41	13.89	2.98	0.00	55.28	75.55	-20.27	Vertical
313.85	57.99	13.89	2.98	0.00	74.86	75.55	-0.69	Horizontal



**Test Plots:**

<b>Product Name:</b>	Keyless transmitter	<b>Product Model:</b>	2AOVX-4B
<b>Test By:</b>	Zora	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	313.85 MHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Huni: 57%




Remark : X

	Read Freq	Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	313.896	38.41	13.89	2.98	0.00	55.28	-----	-----	

*Remark:*

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.*

<b>Product Name:</b>	Keyless transmitter	<b>Product Model:</b>	2AOVX-4B
<b>Test By:</b>	Zora	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	313.85 MHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Huni: 57%



Remark : X

	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	313.892	57.99	13.89	2.98	0.00	74.86	-----

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

## 6.2.2 Spurious Emissions

Below 1GHz (30MHz-1000MHz)							
Peak value							
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	AV Limit (dBuV/m)	polarization
629.477	17.68	19.56	3.89	0.00	41.13	55.55	Vertical
942.131	26.71	22.38	4.13	0.00	53.22	55.55	Vertical
629.477	17.70	19.56	3.89	0.00	41.15	55.55	Horizontal
942.131	26.75	22.38	4.13	0.00	53.26	55.55	Horizontal

**Test Plots:**

<b>Product Name:</b>	Keyless transmitter	<b>Product Model:</b>	2AOVX-4B
<b>Test By:</b>	Zora	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Humi: 57%



Remark :


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	48.332	17.41	13.97	1.27	0.00	32.65	40.00	-7.35	QP
2	56.197	19.48	13.01	1.36	0.00	33.85	40.00	-6.15	QP
3	90.537	18.56	10.10	2.03	0.00	30.69	43.50	-12.81	QP
4	121.123	17.17	10.03	2.18	0.00	29.38	43.50	-14.12	QP
5	629.477	17.68	19.56	3.89	0.00	41.13			Peak
6 *	942.131	26.71	22.38	4.13	0.00	53.22			Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.



<b>Product Name:</b>	Keyless transmitter	<b>Product Model:</b>	2AOVX-4B
<b>Test By:</b>	Zora	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Huni: 57%




Remark :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	46.016	17.65	13.78	1.28	0.00	32.71	40.00	-7.29	QP
2	57.392	17.70	12.81	1.37	0.00	31.88	40.00	-8.12	QP
3	90.537	18.60	10.10	2.03	0.00	30.73	43.50	-12.77	QP
4	104.170	16.59	11.96	1.99	0.00	30.54	43.50	-12.96	QP
5	629.477	17.70	19.56	3.89	0.00	41.15			Peak
6 *	942.131	26.75	22.38	4.13	0.00	53.26			Peak

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

<b>Product Name:</b>	Keyless transmitter	<b>Product Model:</b>	2AOVX-4B
<b>Test By:</b>	Zora	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	1 GHz ~ 5 GHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Huni: 57%




Remark :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1254.743	45.77	24.50	3.40	41.05	35.07	74.00	-38.93	Peak
2	1569.320	46.75	25.39	3.81	41.03	37.14	74.00	-36.86	Peak
3	1882.328	46.14	26.15	4.21	41.40	37.55	74.00	-36.45	Peak
4	2196.829	46.33	26.91	4.50	41.68	38.75	74.00	-35.25	Peak
5	2510.793	45.48	27.63	4.84	41.90	38.90	74.00	-35.10	Peak
6	2823.811	46.35	28.27	5.16	41.64	41.03	74.00	-32.97	Peak
7	3140.275	46.85	28.69	5.40	41.44	42.42	74.00	-31.58	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

<b>Product Name:</b>	Keyless transmitter	<b>Product Model:</b>	2AOVX-4B
<b>Test By:</b>	Zora	<b>Test mode:</b>	Tx mode
<b>Test Frequency:</b>	1 GHz ~ 5 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Huni: 57%




Remark :

	Read Freq	Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1254.743	45.80	24.50	3.40	41.05	35.10	74.00	-38.90	Peak
2	1569.320	45.32	25.39	3.81	41.03	35.71	74.00	-38.29	Peak
3	1882.328	45.96	26.15	4.21	41.40	37.37	74.00	-36.63	Peak
4	2196.829	46.22	26.91	4.50	41.68	38.64	74.00	-35.36	Peak
5	2510.793	46.57	27.63	4.84	41.90	39.99	74.00	-34.01	Peak
6	2823.811	45.85	28.27	5.16	41.64	40.53	74.00	-33.47	Peak
7	3140.275	45.97	28.69	5.40	41.44	41.54	74.00	-32.46	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 6.3 20dB Bandwidth


Test Requirement:	FCC Part15 C Section 15.231 (c)
Test Method:	ANSI C63.4:2014
Receiver setup:	RBW=1kHz, VBW=3kHz, detector: Peak
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Procedure:	<ol style="list-style-type: none"> <li>1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT.</li> <li>2. Set the EUT to proper test channel.</li> <li>3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points.</li> <li>4. Read 20dB bandwidth.</li> </ol>
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

### Measurement Data


20dB bandwidth (MHz)	Limit (MHz)	Results
0.097	0.7846	Passed

Note: Limit= Fundamental frequency×0.25%=313.85×0.25%=0.7846MHz

Test plot as follows:



## 6.4 Duration Time

Test Requirement:	FCC Part15 C Section 15.231 (a1)
Test Method:	ANSI C63.10: 2013
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector: Peak
Limit:	Not more than 5 seconds
Test mode:	Transmitting mode
Test Procedure:	<ol style="list-style-type: none"> <li>1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT.</li> <li>2. Set the EUT to proper test channel.</li> <li>3. Single scan the transmission, and read the transmission time.</li> </ol>
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

### Measurement Data

Duration time (second)	Limit (second)	Result
0.352	<5.0	Pass

Test plot as follows:

