

## FCC RF Exposure

EUT Description:Bluetooth headset

Model No.: YYK-Q71,YYK-Q72,YYK-710,YYK-890,YYK-Q86,YYK-Q69,YYK-Q92,YYK-780,YYK-770,YYK-790,YYK-599,YYK-Q15,YYK-Q16,YYK-Q17,YYK-Q18,YYK-Q19,YYK-Q20,YYK-Q21,YYK-Q22,YYK-Q23,YYK-Q24,YYK-Q26,YYK-Q27,YYK-Q28,YYK-Q29,YYK-Q30,YYK-Q31,YYK-Q32,YYK-Q33,YYK-Q34

FCC ID: 2AOZM-YYKSQ71

Equipment type: Portable Device

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numericasimulation, is not required when the corresponding SAR Test Exclusion Thresholocondition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR testexclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distancecm})] \cdot [f(\text{GHz})] < 3.0$  for 1-g SAR, and  $s 7.5$  for 10-g extremity SAR, where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Channel(MHz)	Output power ( dBm/ mW )	Min. distance(mm)	Calc. thresholds	Limit (mW/cm2)	Result
2402	4.277/2.677	5	0.8298	3.0	Pass
2441	5.342/3.421	5	1.0690	3.0	Pass
2480	5.455/3.512	5	1.1061	3.0	Pass

Conclusion: No SAR is required