

# TEST REPORT

**Applicant:** SKY RICH STAR LIMITED

**Address of Applicant:** Unit E, 10/F, Worldwide Centre, 123 Tung Chau Street, Tai Kok Tsui Kowloon, Hong Kong, China

**Manufacturer/Factory:** 1. Zhongshan Quaxin Lighting Electrical Co., Ltd.  
2. Solana Smart Lighting Co., Ltd.

**Address of Manufacturer/Factory:** 1. Hong Ji Street, Shalang, Long Ping Cun, West District, Zhongshan Guangdong 528411 China  
2. No.268 Moo 7, Huasamrong Sub-district, Plaengyao District, Chachoengsao Province, Thailand 24190

**Equipment Under Test (EUT)**

Product Name: Solar LED Light

Model No.: SR74FA02C-08, SR74FA02\*-##(Where "#" is used to denote numbers or blank for commercial purpose; Where "\*" is used to denote letters or blank for commercial purpose.)

**FCC ID:** 2AP2L-SR74FA02

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.249

**Date of sample receipt:** March 29, 2022

**Date of Test:** March 30, 2022-April 07, 2022

**Date of report issued:** April 07, 2022

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




**Robinson Luo**  
**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

Version No.	Date	Description
00	April 07, 2022	Original

**Prepared By:**




**Date:**

April 07, 2022

**Project Engineer**

**Check By:**



**Date:**

April 07, 2022

**Reviewer**

## 3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
4.1 MEASUREMENT UNCERTAINTY .....	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT .....	5
5.2 TEST MODE .....	6
5.3 DESCRIPTION OF SUPPORT UNITS .....	6
5.4 DEVIATION FROM STANDARDS.....	6
5.5 ABNORMALITIES FROM STANDARD CONDITIONS .....	6
5.6 TEST FACILITY.....	6
5.7 TEST LOCATION .....	6
5.8 ADDITIONAL INSTRUCTIONS.....	6
6 TEST INSTRUMENTS LIST .....	7
7 TEST RESULTS AND MEASUREMENT DATA.....	9
7.1 ANTENNA REQUIREMENT .....	9
7.2 RADIATED EMISSION METHOD .....	10
7.2.1 Field Strength of The Fundamental Signal .....	12
7.2.2 Spurious emissions.....	14
7.2.3 Bandedge emissions.....	26
7.3 20dB OCCUPY BANDWIDTH .....	30
8 TEST SETUP PHOTO .....	32
9 EUT CONSTRUCTIONAL DETAILS .....	32

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10: 2013.
2. Pass: The EUT complies with the essential requirements in the standard.

### 4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz-30MHz	3.1dB	(1)
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.



## 5 General Information

### 5.1 General Description of EUT

Product Name:	Solar LED Light
Model No.:	SR74FA02C-08, SR74FA02*-##(Where "#" is used to denote numbers or blank for commercial purpose; Where "*" is used to denote letters or blank for commercial purpose.)
Test Model No:	SR74FA02C-08
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color and model name for commercial purpose.	
Serial No.:	QXSR74FA02C
Test sample(s) ID:	GTS202203000346-1
Sample(s) Status	Engineered sample
Operation Frequency:	2420MHz, 2450MHz, 2470MHz
Channel numbers:	3
Modulation type:	GFSK
Antenna Type:	Integral antenna
Antenna gain:	3dBi(Declared by applicant)
Power supply:	DC 3.7V, 2000mAh, 7.4Wh Li-ion Battery The battery is charged by solar panel

The test frequencies are below:

Channel	Frequency
The lowest channel	2420MHz
The middle channel	2450MHz
The Highest channel	2470MHz

## 5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

### Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	75.33	76.39	74.27

## 5.3 Description of Support Units

None.
-------

## 5.4 Deviation from Standards

None.
-------

## 5.5 Abnormalities from Standard Conditions

None.
-------

## 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **IC —Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

## 5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

## 5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

## 6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 24 2021	June. 23 2022
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 24 2021	June. 23 2022
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 24 2021	June. 23 2022
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 24 2021	June. 23 2022
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 24 2021	June. 23 2022
9	Coaxial Cable	GTS	N/A	GTS211	June. 24 2021	June. 23 2022
10	Coaxial cable	GTS	N/A	GTS210	June. 24 2021	June. 23 2022
11	Coaxial Cable	GTS	N/A	GTS212	June. 24 2021	June. 23 2022
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 24 2021	June. 23 2022
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 24 2021	June. 23 2022
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 24 2021	June. 23 2022
15	Band filter	Amindeon	82346	GTS219	June. 24 2021	June. 23 2022
16	Power Meter	Anritsu	ML2495A	GTS540	June. 24 2021	June. 23 2022
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 24 2021	June. 23 2022
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 24 2021	June. 23 2022
19	Splitter	Agilent	11636B	GTS237	June. 24 2021	June. 23 2022
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 24 2021	June. 23 2022
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 17 2021	Oct. 16 2022
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 17 2021	Oct. 16 2022
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 17 2021	Oct. 16 2022
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 24 2021	June. 23 2022



<b>RF Conducted Test:</b>						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 24 2021	June. 23 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 24 2021	June. 23 2022
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 24 2021	June. 23 2022
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 24 2021	June. 23 2022
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 24 2021	June. 23 2022
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 24 2021	June. 23 2022
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 24 2021	June. 23 2022
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 24 2021	June. 23 2022

<b>General used equipment:</b>						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 24 2021	June. 23 2022
2	Barometer	ChangChun	DYM3	GTS255	June. 24 2021	June. 23 2022






## 7 Test results and Measurement Data

### 7.1 Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203
<b>15.203 requirement:</b> An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
<b>15.247(c) (1)(i) requirement:</b> (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
<b>EUT Antenna:</b>	
<i>The antenna is integral antenna, the best case gain of the are antennas 3dBi, reference to the appendix II for details</i>	

## 7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	2400MHz-2483.5MHz	94.00		Average Value	
		114.00		Peak Value	
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)		Remark	
	0.009MHz-0.490MHz	2400/F(kHz) @300m		Quasi-peak Value	
	0.490MHz-1.705MHz	24000/F(kHz) @30m		Quasi-peak Value	
	1.705MHz-30.0MHz	30 @30m		Quasi-peak Value	
	30MHz-88MHz	100 @3m		Quasi-peak Value	
	88MHz-216MHz	150 @3m		Quasi-peak Value	
	216MHz-960MHz	200 @3m		Quasi-peak Value	
	960MHz-1GHz	500 @3m		Quasi-peak Value	
	Above 1GHz	500 @3m		Average Value	
	5000 @3m		Peak Value		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz				
	 <p>The diagram illustrates the test setup for radiated emissions from 9kHz to 30MHz. It shows an Equipment Under Test (EUT) placed on a turn table at a height of less than 80cm. A test antenna is positioned at a distance of 3m from the EUT. A receiver is connected to the test antenna and is positioned at a height of 1m. The setup is shown in a cross-sectional view with a ground plane at the bottom.</p>				
	For radiated emissions from 30MHz to 1GHz				

	 <p>For radiated emissions above 1GHz</p> 						
<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>						
<p>Test Instruments:</p>	<p>Refer to section 6.0 for details</p>						
<p>Test mode:</p>	<p>Refer to section 5.2 for details</p>						
<p>Test environment:</p>	<table border="1"> <tr> <td>Temp.:</td> <td>25 °C</td> <td>Humid.:</td> <td>52%</td> <td>Press.:</td> <td>1012mbar</td> </tr> </table>	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar		
<p>Test voltage:</p>	<p>DC 3.7V</p>						
<p>Test results:</p>	<p>Pass</p>						



**Measurement data:**

**7.2.1 Field Strength of The Fundamental Signal**

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2420.00	83.75	27.43	2.93	38.88	75.23	114.00	-38.77	Vertical
2420.00	79.75	27.43	2.93	38.88	71.23	114.00	-42.77	Horizontal
2450.00	84.86	27.55	2.96	38.98	76.39	114.00	-37.61	Vertical
2450.00	78.70	27.55	2.96	38.98	70.23	114.00	-43.77	Horizontal
2470.00	83.69	27.64	2.99	39.05	75.27	114.00	-38.73	Vertical
2470.00	77.76	27.64	2.99	39.05	69.34	114.00	-44.66	Horizontal


**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2420.00	79.91	27.43	2.93	38.88	71.39	94.00	-22.61	Vertical
2420.00	76.26	27.43	2.93	38.88	67.74	94.00	-26.26	Horizontal
2450.00	81.02	27.55	2.96	38.98	72.55	94.00	-21.45	Vertical
2450.00	75.94	27.55	2.96	38.98	67.47	94.00	-26.53	Horizontal
2470.00	80.40	27.64	2.99	39.05	71.98	94.00	-22.02	Vertical
2470.00	74.89	27.64	2.99	39.05	66.47	94.00	-27.53	Horizontal


Note: For fundamental frequency , RBW>20dB BW, VBW>=RBW, PK detector for PK value, RMS detector for AV value

Test plot as follows:

Only show the worst case: 2440MHz, Vertical



PK detector is for PK value



RMS detector is for AV value


## 7.2.2 Spurious emissions

### ■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


### ■ Below 1GHz

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------






Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
33.917	41.14	12.43	0.60	35.28	18.89	40.00	-21.11	QP
39.576	39.59	13.20	0.66	35.64	17.81	40.00	-22.19	QP
54.071	39.65	12.64	0.81	36.24	16.86	40.00	-23.14	QP
406.088	35.77	14.86	2.88	37.52	15.99	46.00	-30.01	QP
830.400	33.32	22.45	4.58	37.61	22.74	46.00	-23.26	QP
968.934	32.35	23.99	5.11	37.54	23.91	54.00	-30.09	QP

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
33.445	41.53	12.40	0.59	35.25	19.27	40.00	-20.73	QP
40.988	38.44	13.20	0.67	35.72	16.59	40.00	-23.41	QP
47.326	38.71	13.00	0.74	36.05	16.40	40.00	-23.60	QP
422.058	39.69	15.26	2.96	37.52	20.39	46.00	-25.61	QP
603.539	33.37	19.30	3.73	37.54	18.86	46.00	-27.14	QP
912.862	35.29	23.21	4.90	37.59	25.81	46.00	-20.19	QP


Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
33.917	41.14	12.43	0.60	35.28	18.89	40.00	-21.11	QP
52.208	38.91	12.82	0.79	36.21	16.31	40.00	-23.69	QP
69.114	40.76	10.75	0.93	36.43	16.01	40.00	-23.99	QP
165.487	36.02	12.59	1.66	37.16	13.11	43.50	-30.39	QP
467.235	35.08	16.22	3.17	37.51	16.96	46.00	-29.04	QP
919.287	34.64	23.35	4.93	37.58	25.34	46.00	-20.66	QP




Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
45.535	40.03	12.97	0.72	35.96	17.76	40.00	-22.24	QP
52.575	38.75	12.79	0.79	36.22	16.11	40.00	-23.89	QP
163.755	36.63	12.64	1.65	37.15	13.77	43.50	-29.73	QP
250.301	37.71	10.74	2.12	37.38	13.19	46.00	-32.81	QP
519.065	34.41	17.07	3.39	37.52	17.35	46.00	-28.65	QP
857.025	34.74	22.64	4.68	37.61	24.45	46.00	-21.55	QP


Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
33.917	41.14	12.43	0.60	35.28	18.89	40.00	-21.11	QP
40.559	41.20	13.23	0.67	35.70	19.40	40.00	-20.60	QP
54.071	38.65	12.64	0.81	36.24	15.86	40.00	-24.14	QP
95.762	40.34	8.83	1.16	36.69	13.64	43.50	-29.86	QP
355.427	35.04	13.69	2.64	37.48	13.89	46.00	-32.11	QP
836.244	35.63	22.49	4.60	37.61	25.11	46.00	-20.89	QP

■ Above 1GHz


Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4840.000	46.37	31.26	4.65	37.66	44.62	74.00	-29.38	Peak
7260.000	36.95	36.30	6.55	37.80	42.00	74.00	-32.00	Peak
9680.000	36.60	38.00	8.00	37.94	44.66	74.00	-29.34	Peak




Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4840.000	44.73	31.26	4.65	37.66	42.98	74.00	-31.02	Peak
7260.000	35.53	36.30	6.55	37.80	40.58	74.00	-33.42	Peak
9680.000	35.43	38.00	8.00	37.94	43.49	74.00	-30.51	Peak

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4900.000	49.09	31.35	4.71	37.60	47.55	74.00	-26.45	Peak
7350.000	35.06	36.48	6.67	37.76	40.45	74.00	-33.55	Peak
9800.000	37.38	38.17	8.05	37.96	45.64	74.00	-28.36	Peak


Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4900.000	46.02	31.35	4.71	37.60	44.48	74.00	-29.52	Peak
7350.000	34.64	36.48	6.67	37.76	40.03	74.00	-33.97	Peak
9800.000	35.03	38.17	8.05	37.96	43.29	74.00	-30.71	Peak




Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4940.000	45.89	31.41	4.77	37.56	44.51	74.00	-29.49	Peak
7410.000	35.82	36.62	6.73	37.74	41.43	74.00	-32.57	Peak
9880.000	36.90	38.23	8.07	37.98	45.22	74.00	-28.78	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4940.000	45.95	31.41	4.77	37.56	44.57	74.00	-29.43	Peak
7410.000	35.82	36.62	6.73	37.74	41.43	74.00	-32.57	Peak
9880.000	35.13	38.23	8.07	37.98	43.45	74.00	-30.55	Peak


**Remarks:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

### 7.2.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.


Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	30.84	27.14	2.81	38.64	22.15	54.00	-31.85	Average
2310.000	42.73	27.14	2.81	38.64	34.04	74.00	-39.96	Peak
2390.000	30.98	27.37	2.91	38.84	22.42	54.00	-31.58	Average
2390.000	52.51	27.37	2.91	38.84	43.95	74.00	-30.05	Peak
2400.000	30.89	27.41	2.91	38.86	22.35	54.00	-31.65	Average
2400.000	56.33	27.41	2.91	38.86	47.79	74.00	-26.21	Peak




Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	30.84	27.14	2.81	38.64	22.15	54.00	-31.85	Average
2310.000	42.48	27.14	2.81	38.64	33.79	74.00	-40.21	Peak
2390.000	30.95	27.37	2.91	38.84	22.39	54.00	-31.61	Average
2390.000	43.82	27.37	2.91	38.84	35.26	74.00	-38.74	Peak
2400.000	30.73	27.41	2.91	38.86	22.19	54.00	-31.81	Average
2400.000	48.20	27.41	2.91	38.86	39.66	74.00	-34.34	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	30.83	27.66	2.99	39.06	22.42	54.00	-31.58	Average
2483.500	59.00	27.66	2.99	39.06	50.59	74.00	-23.41	Peak
2500.000	31.04	27.70	3.01	39.10	22.65	54.00	-31.35	Average
2500.000	50.11	27.70	3.01	39.10	41.72	74.00	-32.28	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	29.91	27.66	2.99	39.06	21.50	54.00	-32.50	Average
2483.500	51.69	27.66	2.99	39.06	43.28	74.00	-30.72	Peak
2500.000	30.23	27.70	3.01	39.10	21.84	54.00	-32.16	Average
2500.000	42.04	27.70	3.01	39.10	33.65	74.00	-40.35	Peak

**Remark:**

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*




### 7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

### Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	7.276	Pass
Middle	6.249	Pass
Highest	4.160	Pass


Test plot as follows:



Lowest channel



Middle channel



Highest channel

## 8 Test Setup Photo

Reference to the **appendix I** for details.

## 9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----