


Human Exposure Report

Application No.: SZEM1907016873CR
Applicant: Shenzhen Esorun Technology Co., LTD
Address of Applicant: 10F, Mingzhuo Building, Mingzhuoxing Industrial Park, Guangming Street, Guangming District, Shenzhen, China
Manufacturer: Shenzhen Esorun Technology Co., Ltd
Address of Manufacturer: 10F, Mingzhuo Building, Mingzhuoxing Industrial Park, Guangming Street, Guangming District, Shenzhen, China
Factory: Shenzhen Yostand Technology Co., LTD
Address of Factory: 10F, Mingzhou Building, Mingzhuoxing Industrial Park, Guangming Street, Guangming District
Equipment Under Test (EUT):
EUT Name: Qi wireless charger
Model No.: Super Z
Trade mark: ESORUN
FCC ID: 2AP2N-SUPER-Z-P
Standards: 47 CFR PART 1, Subpart I, Section 1.1310
 47 CRF PART 2, Subpart J, Section 2.1091
Date of Receipt: 2019-07-29
Date of Test: 2019-08-03 to 2019-09-04
Date of Issue: 2019-09-06

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above



Keny Xu
EMC Laboratory Manager



<i>Revision Record</i>				
Version	Chapter	Date	Modifier	Remark
01		2019-09-06		Original

Authorized for issue by:			
			
		<hr/> Bill Chen /Project Engineer	
			
		<hr/> Eric Fu /Reviewer	



2 Contents

1	COVER PAGE	1
2	CONTENTS	3
3	GENERAL INFORMATION	4
3.1	DETAILS OF E.U.T.	4
3.2	DESCRIPTION OF SUPPORT UNITS	4
3.3	TEST LOCATION	5
3.4	TEST FACILITY.....	5
3.5	DEVIATION FROM STANDARDS.....	5
3.6	ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4	EQUIPMENTS USED DURING TEST	6
5	TEST RESULTS	7
5.1	RF EXPOSURE TEST	7
5.1.1	<i>E.U.T. Operation</i>	7
6	PHOTOGRAPHS- RF EXPOSURE SETUP	9



3 General Information

3.1 Details of E.U.T.

Power supply: Input:DC 5V/2A;9V/1.67A; 12V/1.67A
Wireless Output:DC 5V/1A;9V/1.12A;9V/1.67A
Wireless output: 5W,10W,15W

Cable: USB cable:96cm unshielded

Operation frequency: 111.86-146.63kHz

Antenna Type: Loop Antenna

Modulation Type: Load Modulation

Antenna Gain: 0dBi

Remark: This device has been tested the worst status of full load and the device has been tested with load at 5W,10W, 15W.The worst case 15W is reported only.

3.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	SAMSUNG	EP-TA200	R37J8YA7W71DK3
iPhone 8	Apple	A1863	F4GVQ656JC6D
SAMSUNG Galaxy S8	SAMSUNG	SM-G9500	R28J9140LPB
XIAOMI MI 9	XIAOMI	M1902F1A	22006/K9SH01862



3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.



4 Equipments Used during Test

Item	Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
1	Electric Field Probe (100KHz-3GHz)	WANDEL & GOLTERMAN N	EMR-20	EMC0907	2019-05-21	2020-05-20
2	EMF Tester	Narda	ELT-400	SZE039-4	2019-07-08	2020-07-07



5 Test Results

5.1 RF Exposure test

Test Requirement: 47 CFR PART 1, Subpart I, Section 1.1310

Measurement Distance: 15cm

Limit:

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 *=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

5.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C Humidity: 52% RH Atmospheric Pressure: 1015 mbar

EUT Operation:

This device has been tested the worst status of full load and the device has been tested with mobile phone at zero charge, intermediate charge, and full charge.



5.1.2 Measurement Data

Output Voltage=DC 12V; The max output power =15W

Magnetic Field Emissions


Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (A/m)	50% Limit (A/m)
122 kHz	15	Side 1	0.1446	0.815
		Side 2	0.1121	0.815
		Side 3	0.1559	0.815
		Side 4	0.1015	0.815
		Top	0.0824	0.815

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result(A/m)			50%Limit (A/m)
			zero charge	intermediate charge	full charge	
122 kHz	15	Side 1	0.1543	0.1397	0.1251	0.815
		Side 2	0.1231	0.1108	0.0979	0.815
		Side 3	0.1663	0.1554	0.1417	0.815
		Side 4	0.1119	0.0972	0.0838	0.815
		Top	0.0942	0.0803	0.0668	0.815



6 Photographs- RF exposure setup



- End of the Report -

