

# FCC ID: 2AP2P-13713847177

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

**MAX OUTPUT POWER**

WIFI:

Test Channel	Frequency (MHz)	Power Setting	Average Output Power (dBm)	Maximum Output Power (dBm)	LIMIT (dBm)	Verdict
<b>802.11b</b>						
1	2412	Default	13.2	13.2	30	PASS
6	2437	Default	13.9	13.9	30	PASS
11	2462	Default	13.7	13.7	30	PASS
<b>802.11g</b>						
1	2412	Default	13.3	13.3	30	PASS
6	2437	Default	13.8	13.8	30	PASS
11	2462	Default	13.5	13.5	30	PASS
<b>802.11n HT20</b>						
1	2412	Default	13.3	13.3	30	PASS
6	2437	Default	13.6	13.6	30	PASS
11	2462	Default	13.7	13.7	30	PASS
<b>802.11n HT40</b>						
3	2422	Default	14.3	14.3	30	PASS
6	2437	Default	14.1	14.1	30	PASS
9	2452	Default	13.9	13.9	30	PASS

## Measurement Result

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz, 2422-2452MHz for 802.11n(HT40);

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: External Antenna

Antenna gain: 5dBi,

R=20cm

802.11b/g/n:

Freq. (MHz)	modulation	(dBm)	power (dBm)	tune-up power		Gain		(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
				(dBm)	(mW)	(dBi)	Numeric		
2412	802.11b	13.2	14±1	15	31.623	5.00	3.16	0.0199	1
2437		13.9	14±1	15	31.623	5.00	3.16	0.0199	1
2462		13.7	14±1	15	31.623	5.00	3.16	0.0199	1
2412	802.11g	13.3	14±1	15	31.623	5.00	3.16	0.0199	1
2437		13.8	14±1	15	31.623	5.00	3.16	0.0199	1
2462		13.5	14±1	15	31.623	5.00	3.16	0.0199	1
2412	802.11n H20	13.3	14±1	15	31.623	5.00	3.16	0.0199	1
2437		13.6	14±1	15	31.623	5.00	3.16	0.0199	1
2462		13.7	14±1	15	31.623	5.00	3.16	0.0199	1
2422	802.11n H40	14.3	14±1	15	31.623	5.00	3.16	0.0199	1
2437		14.1	14±1	15	31.623	5.00	3.16	0.0199	1
2452		13.9	14±1	15	31.623	5.00	3.16	0.0199	1

### Conclusion:

For the max result : 0.0199≤ 1.0, compliance with FCC's RF Exposure.

*Jason chen*

**Signature:**

**Date:** 2018-12-19

**NAME AND TITLE** (Please print or type): Jason Chen/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.