

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

|                     |                                     |
|---------------------|-------------------------------------|
| Product Description | Smart Watch                         |
| Test Model          | G16PRO                              |
| Series Model        | G16, G25, G25T, G25PRO, G27, G27PRO |
| FCC ID              | 2AP4R-G16PRO                        |

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

BLE 1M:

$$P_t = -0.979 \text{ dBm} = 0.80 \text{ mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.80 \text{ mW}/5 \text{ mm}) \cdot [\sqrt{2.480 \text{ GHz}}] = 0.25 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

BLE 2M:

$$P_t = -0.962 \text{ dBm} = 0.80 \text{ mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.80 \text{ mW}/5 \text{ mm}) \cdot [\sqrt{2.480 \text{ GHz}}] = 0.25 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.