



FCC RADIO TEST REPORT

FCC ID : 2AP4W-VLITE
Equipment : mPERS
Brand Name : Belle
Model Name : Belle X VZW
Marketing Name : Belle X
Applicant : Freeus, LLC
640 W 1100 S Suite 4, Ogden, Utah, United States 84404
Manufacturer : Wistron Corporation
21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist, New Taipei City 221, Taiwan R.O.C
Standard : FCC Part 15 Subpart C §15.247

The product was received on Sep. 20, 2019 and testing was started from Sep. 23, 2019 and completed on Oct. 14, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report..... 3

Summary of Test Result..... 4

1 General Description 5

 1.1 Product Feature of Equipment Under Test..... 5

 1.2 Modification of EUT 5

 1.3 Testing Location 5

 1.4 Applicable Standards..... 5

2 Test Configuration of Equipment Under Test 6

 2.1 Carrier Frequency and Channel 6

 2.2 Test Mode..... 6

 2.3 Connection Diagram of Test System..... 7

 2.4 Support Unit used in test configuration and system 7

 2.5 EUT Operation Test Setup 8

 2.6 Measurement Results Explanation Example..... 8

3 Test Result 9

 3.1 6dB and 99% Bandwidth Measurement 9

 3.2 Output Power Measurement..... 11

 3.3 Power Spectral Density Measurement 12

 3.4 Conducted Band Edges and Spurious Emission Measurement 14

 3.5 Radiated Band Edges and Spurious Emission Measurement 24

 3.6 AC Conducted Emission Measurement..... 28

 3.7 Antenna Requirements 30

4 List of Measuring Equipment..... 31

5 Uncertainty of Evaluation 32

Appendix A. Conducted Test Results

Appendix B. AC Conducted Emission Test Result

Appendix C. Radiated Spurious Emission

Appendix D. Radiated Spurious Emission Plots

Appendix E. Duty Cycle Plots

Appendix F. Setup Photographs



History of this test report

Report No.	Version	Description	Issued Date
FR982310-02	01	Initial issue of report	Nov. 05, 2019



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 1.38 dB at 240.060 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 14.52 dB at 0.152 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang
Report Producer: Tina Chuang



1 General Description

1.1 Product Feature of Equipment Under Test

LTE, Wi-Fi 2.4GHz 802.11b/g/n, and GNSS

Product Specification subjective to this standard	
Antenna Type	WWAN: LDS Antenna WLAN: LDS Antenna GPS / Glonass: LDS Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	CO05-HY	TH05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		


2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WLAN Tx + Cradle (Black) with Notebook
Remark: For radiation emission, the tests were performed with Cradle (Black).	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
2.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
4.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m



2.5 EUT Operation Test Setup

The RF test items, utility “QRCT V4.0-00113” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission


Test Engineer :	Shiming Liu and Hank Hsu	Temperature :	21~25°C
		Relative Humidity :	51~54%

Number of TX = 1, Ant. 1 (Measured)


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----

WLAN 802.11b Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






WLAN 802.11b Channel 06

100kHz PSD reference Level


Mid Channel Plot




Date: 3.OCT.2019 09:50:44

Spurious Emission 30MHz~3GHz

Spurious Emission 2GHz~25GHz



Date: 3.OCT.2019 09:53:01




Date: 3.OCT.2019 09:54:55




WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 3.OCT.2019 09:59:12

High Channel Plot




Date: 3.OCT.2019 10:00:20

Spurious Emission 30MHz~3GHz



Date: 3.OCT.2019 10:01:52

Spurious Emission 2GHz~25GHz




Date: 3.OCT.2019 10:03:10




WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 3.OCT.2019 10:14:54

Low Channel Plot




Date: 3.OCT.2019 10:16:34

Spurious Emission 30MHz~3GHz



Date: 3.OCT.2019 10:17:40

Spurious Emission 2GHz~25GHz




Date: 3.OCT.2019 10:20:42



WLAN 802.11g Channel 06

100kHz PSD reference Level


Mid Channel Plot




Date: 3.OCT.2019 10:28:21

Spurious Emission 30MHz~3GHz

Spurious Emission 2GHz~25GHz



Date: 3.OCT.2019 10:30:15




Date: 3.OCT.2019 10:31:34




WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 3.OCT.2019 10:44:31

High Channel Plot




Date: 3.OCT.2019 10:47:42

Spurious Emission 30MHz~3GHz




Date: 3.OCT.2019 10:48:33

Spurious Emission 2GHz~25GHz



Date: 3.OCT.2019 10:49:55






WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level


Mid Channel Plot




Date: 3.OCT.2019 11:10:18

Spurious Emission 30MHz~3GHz

Spurious Emission 2GHz~25GHz



Date: 3.OCT.2019 11:12:51




Date: 3.OCT.2019 11:14:12




WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 3.OCT.2019 11:31:29

High Channel Plot




Date: 3.OCT.2019 11:32:52

Spurious Emission 30MHz~3GHz



Date: 3.OCT.2019 11:34:34

Spurious Emission 2GHz~25GHz



Date: 3.OCT.2019 11:35:34



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.




3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Sensor	DARE	RPR3006W	16I00054S NO12	10MHz~6GHz	Dec. 27, 2018	Sep. 23, 2019 ~Oct. 03, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9kHz~30GHz	Nov. 15, 2018	Sep. 23, 2019 ~Oct. 03, 2019	Nov. 14, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1208382	N/A	Mar. 27, 2019	Sep. 23, 2019 ~Oct. 03, 2019	Mar. 26, 2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Sep. 24, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Sep. 24, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Sep. 24, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Sep. 24, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Sep. 24, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Sep. 24, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Sep. 24, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Filter	Microwave	H3G018G1	SN477219	3GHz High Pass Filter	Nov. 02, 2018	Oct. 04, 2019~ Oct. 14, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
Filter	Wainwright	WLKS1200-8 SS	SN3	1.2G Low Pass	Aug. 22, 2019	Oct. 04, 2019~ Oct. 14, 2019	Aug. 21, 2020	Radiation (03CH07-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	35419 & 03	30MHz~1GHz	Apr. 30, 2019	Oct. 04, 2019~ Oct. 14, 2019	Apr. 29, 2020	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Dec. 02, 2018	Oct. 04, 2019~ Oct. 14, 2019	Dec. 03, 2019	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY5329005 3	20Hz~26.5GHz	Jan. 23, 2019	Oct. 04, 2019~ Oct. 14, 2019	Jan. 22, 2020	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz~18GHz	Apr. 24, 2019	Oct. 04, 2019~ Oct. 14, 2019	Apr. 23, 2020	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	May 20, 2019	Oct. 04, 2019~ Oct. 14, 2019	May 19, 2020	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A0236 2	1GHz~26.5GHz	Nov. 02, 2018	Oct. 04, 2019~ Oct. 14, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4, MY28655/4	9kHz~30MHz	Feb. 26, 2019	Oct. 04, 2019~ Oct. 14, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4, MY24971/4, MY15682/4	30MHz~1GHz	Feb. 26, 2019	Oct. 04, 2019~ Oct. 14, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4, MY24971/4, MY15682/4	1GHz~18GHz	Feb. 26, 2019	Oct. 04, 2019~ Oct. 14, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2858/2	18GHz~40GHz	Feb. 26, 2019	Oct. 04, 2019~ Oct. 14, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Oct. 04, 2019~ Oct. 14, 2019	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Oct. 04, 2019~ Oct. 14, 2019	N/A	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8-24	8050400465 6H	N/A	N/A	Oct. 04, 2019~ Oct. 14, 2019	N/A	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu/Hank Hsu	Temperature:	21~25	°C
Test Date:	2019/9/23 ~ 2019/10/3	Relative Humidity:	51~54	%
TX Tool	QRCT	TX Tool Version	4.0.00113	

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	13.25	-	8.04	-	0.50	Pass
11b	1Mbps	1	6	2437	13.25	-	8.04	-	0.50	Pass
11b	1Mbps	1	11	2462	13.25	-	7.06	-	0.50	Pass
11g	6Mbps	1	1	2412	16.40	-	15.30	-	0.50	Pass
11g	6Mbps	1	6	2437	16.40	-	15.14	-	0.50	Pass
11g	6Mbps	1	11	2462	16.40	-	15.16	-	0.50	Pass
HT20	MCS0	1	1	2412	17.55	-	15.12	-	0.50	Pass
HT20	MCS0	1	6	2437	17.55	-	15.14	-	0.50	Pass
HT20	MCS0	1	11	2462	17.50	-	15.12	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	1.40	-	-	30.00	-	-4.60	-	-3.20	-	36.00	-	Pass
11b	1Mbps	1	6	2437	1.10	-		30.00	-	-4.60	-	-3.50	-	36.00	-	Pass
11b	1Mbps	1	11	2462	1.00	-		30.00	-	-4.60	-	-3.60	-	36.00	-	Pass
11g	6Mbps	1	1	2412	1.10	-		30.00	-	-4.60	-	-3.50	-	36.00	-	Pass
11g	6Mbps	1	6	2437	1.30	-		30.00	-	-4.60	-	-3.30	-	36.00	-	Pass
11g	6Mbps	1	11	2462	0.70	-		30.00	-	-4.60	-	-3.90	-	36.00	-	Pass
HT20	MCS0	1	1	2412	0.70	-		30.00	-	-4.60	-	-3.90	-	36.00	-	Pass
HT20	MCS0	1	6	2437	0.50	-		30.00	-	-4.60	-	-4.10	-	36.00	-	Pass
HT20	MCS0	1	11	2462	0.40	-		30.00	-	-4.60	-	-4.20	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-20.61	-	-	-4.60	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-20.06	-	-	-4.60	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-20.37	-	-	-4.60	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-25.52	-	-	-4.60	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-25.57	-	-	-4.60	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-25.39	-	-	-4.60	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-25.95	-	-	-4.60	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-26.56	-	-	-4.60	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-25.60	-	-	-4.60	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	Temperature :	24~26°C
		Relative Humidity :	52~54%

EUT Information

Report NO : 982310-02
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	32.01	55.88	23.87	L1	OFF	19.4
0.152250	51.36	---	65.88	14.52	L1	OFF	19.4
0.179250	---	27.90	54.52	26.62	L1	OFF	19.4
0.179250	46.77	---	64.52	17.75	L1	OFF	19.4
0.525750	---	27.27	46.00	18.73	L1	OFF	19.4
0.525750	35.92	---	56.00	20.08	L1	OFF	19.4
3.684750	---	28.19	46.00	17.81	L1	OFF	19.5
3.684750	36.73	---	56.00	19.27	L1	OFF	19.5
9.604500	---	30.98	50.00	19.02	L1	OFF	19.6
9.604500	36.23	---	60.00	23.77	L1	OFF	19.6
21.097500	---	16.12	50.00	33.88	L1	OFF	19.7
21.097500	19.27	---	60.00	40.73	L1	OFF	19.7

EUT Information

Report NO : 982310-02
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	31.00	55.75	24.75	N	OFF	19.4
0.154500	49.48	---	65.75	16.27	N	OFF	19.4
0.188250	---	28.09	54.11	26.02	N	OFF	19.4
0.188250	44.83	---	64.11	19.28	N	OFF	19.4
0.501000	---	29.94	46.00	16.06	N	OFF	19.5
0.501000	36.62	---	56.00	19.38	N	OFF	19.5
3.693750	---	24.44	46.00	21.56	N	OFF	19.5
3.693750	32.80	---	56.00	23.20	N	OFF	19.5
9.384000	---	20.34	50.00	29.66	N	OFF	19.6
9.384000	25.47	---	60.00	34.53	N	OFF	19.6
21.147000	---	17.03	50.00	32.97	N	OFF	19.8
21.147000	20.12	---	60.00	39.88	N	OFF	19.8



Appendix C. Radiated Spurious Emission

Test Engineer :	Jack Hsu	Temperature :	20.8~26.1°C
		Relative Humidity :	58.0~68.0%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11b CH 01 2412MHz		2379.51	54.81	-19.19	74	40.15	31.93	17.67	34.94	357	15	P	H	
		2386.86	43.98	-10.02	54	29.18	32	17.74	34.94	357	15	A	H	
	*	2412	94.91	-	-	80.05	32.07	17.74	34.95	357	15	P	H	
	*	2412	91.05	-	-	76.19	32.07	17.74	34.95	357	15	A	H	
													H	
													H	
			2389.59	54.58	-19.42	74	39.78	32	17.74	34.94	400	146	P	V
			2389.695	43.9	-10.1	54	29.1	32	17.74	34.94	400	146	A	V
	*		2412	92.05	-	-	77.19	32.07	17.74	34.95	400	146	P	V
	*		2412	88.74	-	-	73.88	32.07	17.74	34.95	400	146	A	V
													V	
													V	
802.11b CH 06 2437MHz		2332.26	54.99	-19.01	74	40.53	31.8	17.59	34.93	357	200	P	H	
		2389.8	43.87	-10.13	54	29.08	32	17.74	34.95	357	200	A	H	
	*	2437	92.85	-	-	77.82	32.2	17.79	34.96	357	200	P	H	
	*	2437	89.99	-	-	74.96	32.2	17.79	34.96	357	200	A	H	
			2487.26	54.63	-19.37	74	39.56	32.2	17.84	34.97	357	200	P	H
			2484.32	44	-10	54	28.93	32.2	17.84	34.97	357	200	A	H
			2314.76	54.94	-19.06	74	40.48	31.8	17.59	34.93	388	143	P	V
			2389.8	43.91	-10.09	54	29.12	32	17.74	34.95	388	143	A	V
	*		2437	90.73	-	-	75.7	32.2	17.79	34.96	388	143	P	V
	*		2437	86.93	-	-	71.9	32.2	17.79	34.96	388	143	A	V
			2487.68	54.74	-19.26	74	39.67	32.2	17.84	34.97	388	143	P	V
			2485.44	44.05	-9.95	54	28.98	32.2	17.84	34.97	388	143	A	V



802.11b CH 11 2462MHz	*	2462	93.16	-	-	78.09	32.2	17.84	34.97	388	16	P	H
	*	2462	89.61	-	-	74.54	32.2	17.84	34.97	388	16	A	H
		2492.16	54.78	-19.22	74	39.72	32.2	17.84	34.98	388	16	P	H
		2495.12	44.1	-9.9	54	29.04	32.2	17.84	34.98	388	16	A	H
													H
													H
	*	2462	91.8	-	-	76.73	32.2	17.84	34.97	337	185	P	V
	*	2462	88.62	-	-	73.55	32.2	17.84	34.97	337	185	A	V
		2488.6	55.25	-18.75	74	40.18	32.2	17.84	34.97	337	185	P	V
		2487.8	44.07	-9.93	54	29	32.2	17.84	34.97	337	185	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	43.42	-30.58	74	56.96	34.1	11.39	59.03	100	0	P	H
													H
													H
													H
		4824	43.54	-30.46	74	57.08	34.1	11.39	59.03	100	0	P	V
													V
													V
802.11b CH 06 2437MHz		4874	43.1	-30.9	74	56.47	34.13	11.42	58.92	100	0	P	H
		7311	43.38	-30.62	74	52.01	35.7	13.97	58.3	100	0	P	H
													H
													H
		4874	43.63	-30.37	74	32.64	-500	10.99	-500	100	0	P	V
		7311	43.67	-30.33	74	30.17	-500	13.5	-500	100	0	P	V
													V
802.11b CH 11 2462MHz		4924	43.46	-30.54	74	56.65	34.17	11.45	58.81	100	0	P	H
		7386	44.53	-29.47	74	53.31	35.5	14.07	58.35	100	0	P	H
													H
													H
		4924	43.05	-30.95	74	56.24	34.17	11.45	58.81	100	0	P	V
		7386	44.69	-29.31	74	53.47	35.5	14.07	58.35	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11g CH 01 2412MHz		2383.29	54.97	-19.03	74	40.24	31.93	17.74	34.94	358	16	P	H	
		2389.905	45	-9	54	30.21	32	17.74	34.95	358	16	A	H	
	*	2412	94.46	-	-	79.6	32.07	17.74	34.95	358	16	P	H	
	*	2412	86.96	-	-	72.1	32.07	17.74	34.95	358	16	A	H	
													H	
													H	
			2388.225	54.82	-19.18	74	40.02	32	17.74	34.94	400	149	P	V
			2355.885	44.93	-9.07	54	30.34	31.87	17.66	34.94	400	149	A	V
	*		2412	92.54	-	-	77.68	32.07	17.74	34.95	400	149	P	V
	*		2412	84.37	-	-	69.51	32.07	17.74	34.95	400	149	A	V
													V	
													V	
802.11g CH 06 2437MHz		2370.06	54.48	-19.52	74	39.82	31.93	17.67	34.94	356	199	P	H	
		2386.02	44.83	-9.17	54	30.03	32	17.74	34.94	356	199	A	H	
	*	2437	93.11	-	-	78.08	32.2	17.79	34.96	356	199	P	H	
	*	2437	85.09	-	-	70.06	32.2	17.79	34.96	356	199	A	H	
			2490.41	55.12	-18.88	74	40.05	32.2	17.84	34.97	356	199	P	H
			2493.7	45.03	-8.97	54	29.97	32.2	17.84	34.98	356	199	A	H
			2316.58	55.2	-18.8	74	40.74	31.8	17.59	34.93	392	135	P	V
			2383.36	44.77	-9.23	54	30.04	31.93	17.74	34.94	392	135	A	V
	*		2437	90.8	-	-	75.77	32.2	17.79	34.96	392	135	P	V
	*		2437	83.4	-	-	68.37	32.2	17.79	34.96	392	135	A	V
			2496.71	54.78	-19.22	74	39.72	32.2	17.84	34.98	392	135	P	V
			2495.38	44.95	-9.05	54	29.89	32.2	17.84	34.98	392	135	A	V



802.11g CH 11 2462MHz	*	2462	93.02	-	-	77.95	32.2	17.84	34.97	391	10	P	H
	*	2462	84.73	-	-	69.66	32.2	17.84	34.97	391	10	A	H
		2490	54.85	-19.15	74	39.78	32.2	17.84	34.97	391	10	P	H
		2499.28	45.12	-8.88	54	30.06	32.2	17.84	34.98	391	10	A	H
													H
													H
	*	2462	89.71	-	-	74.64	32.2	17.84	34.97	392	256	P	V
	*	2462	80.83	-	-	65.76	32.2	17.84	34.97	392	256	A	V
		2486.6	54.69	-19.31	74	39.62	32.2	17.84	34.97	392	256	P	V
		2495.72	45.02	-8.98	54	29.96	32.2	17.84	34.98	392	256	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11g CH 01 2412MHz		4824	44	-30	74	57.54	34.1	11.39	59.03	100	0	P	H	
													H	
													H	
													H	
			4824	43.41	-30.59	74	56.95	34.1	11.39	59.03	100	0	P	V
														V
														V
802.11g CH 06 2437MHz		4874	43.55	-30.45	74	56.92	34.13	11.42	58.92	100	0	P	H	
		7311	44.5	-29.5	74	53.13	35.7	13.97	58.3	100	0	P	H	
													H	
													H	
			4874	43.93	-30.07	74	57.3	34.13	11.42	58.92	100	0	P	V
			7311	44.83	-29.17	74	53.46	35.7	13.97	58.3	100	0	P	V
														V
802.11g CH 11 2462MHz		4924	43.96	-30.04	74	57.15	34.17	11.45	58.81	100	0	P	H	
		7386	45.45	-28.55	74	54.23	35.5	14.07	58.35	100	0	P	H	
													H	
													H	
			4924	43.86	-30.14	74	57.05	34.17	11.45	58.81	100	0	P	V
			7386	44.81	-29.19	74	53.59	35.5	14.07	58.35	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11n HT20 CH 01 2412MHz		2314.83	55.36	-18.64	74	40.9	31.8	17.59	34.93	358	19	P	H	
		2384.76	44.96	-9.04	54	30.23	31.93	17.74	34.94	358	19	A	H	
	*	2412	95.06	-	-	80.2	32.07	17.74	34.95	358	19	P	H	
	*	2412	87.02	-	-	72.16	32.07	17.74	34.95	358	19	A	H	
													H	
														H
			2375.31	54.94	-19.06	74	40.28	31.93	17.67	34.94	400	145	P	V
			2389.695	45.06	-8.94	54	30.26	32	17.74	34.94	400	145	A	V
		*	2412	91.07	-	-	76.21	32.07	17.74	34.95	400	145	P	V
		*	2412	83.68	-	-	68.82	32.07	17.74	34.95	400	145	A	V
													V	
													V	
802.11n HT20 CH 06 2437MHz		2316.16	54.74	-19.26	74	40.28	31.8	17.59	34.93	358	199	P	H	
		2389.94	44.9	-9.1	54	30.11	32	17.74	34.95	358	199	A	H	
		*	2437	92.49	-	-	77.46	32.2	17.79	34.96	358	199	P	H
		*	2437	84.59	-	-	69.56	32.2	17.79	34.96	358	199	A	H
			2489.78	54.13	-19.87	74	39.06	32.2	17.84	34.97	358	199	P	H
			2490.41	45.05	-8.95	54	29.98	32.2	17.84	34.97	358	199	A	H
			2385.18	54.59	-19.41	74	39.86	31.93	17.74	34.94	390	142	P	V
			2388.68	44.95	-9.05	54	30.15	32	17.74	34.94	390	142	A	V
		*	2437	90.61	-	-	75.58	32.2	17.79	34.96	390	142	P	V
		*	2437	83.42	-	-	68.39	32.2	17.79	34.96	390	142	A	V
		2496.08	54.13	-19.87	74	39.07	32.2	17.84	34.98	390	142	P	V	
		2486.07	45.27	-8.73	54	30.2	32.2	17.84	34.97	390	142	A	V	



802.11n HT20 CH 11 2462MHz	*	2462	93.05	-	-	77.98	32.2	17.84	34.97	388	17	P	H
	*	2462	85.29	-	-	70.22	32.2	17.84	34.97	388	17	A	H
		2489.84	55.17	-18.83	74	40.1	32.2	17.84	34.97	388	17	P	H
		2494.04	45.13	-8.87	54	30.07	32.2	17.84	34.98	388	17	A	H
													H
													H
	*	2462	90.87	-	-	75.8	32.2	17.84	34.97	338	135	P	V
	*	2462	83.72	-	-	68.65	32.2	17.84	34.97	338	135	A	V
		2492.2	54.59	-19.41	74	39.53	32.2	17.84	34.98	338	135	P	V
		2497.72	45.09	-8.91	54	30.03	32.2	17.84	34.98	338	135	A	V
													V
												V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11n HT20 CH 01 2412MHz		4824	44.41	-29.59	74	57.95	34.1	11.39	59.03	100	0	P	H	
													H	
													H	
													H	
			4824	44.86	-29.14	74	58.4	34.1	11.39	59.03	100	0	P	V
														V
														V
802.11n HT20 CH 06 2437MHz		4874	43.92	-30.08	74	57.29	34.13	11.42	58.92	100	0	P	H	
													H	
			7311	45.15	-28.85	74	53.78	35.7	13.97	58.3	100	0	P	H
														H
			4874	43.81	-30.19	74	57.18	34.13	11.42	58.92	100	0	P	V
			7311	44.75	-29.25	74	53.38	35.7	13.97	58.3	100	0	P	V
														V
802.11n HT20 CH 11 2462MHz		4924	43.66	-30.34	74	56.85	34.17	11.45	58.81	100	0	P	H	
													H	
			7386	44.58	-29.42	74	53.36	35.5	14.07	58.35	100	0	P	H
														H
			4924	44.38	-29.62	74	57.57	34.17	11.45	58.81	100	0	P	V
			7386	45.46	-28.54	74	54.24	35.5	14.07	58.35	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots





Test Engineer :	Jack Hsu	Temperature :	20.8~26.1°C
		Relative Humidity :	58.0~68.0%

Note symbol





-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz
WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 1</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HE_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 1</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_S4 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 1</p>	 <p>Site : 03CH07-HY Condition : AVG_S4 3m HE_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 1</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 982310-02 Mode : 1</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 982310-02 Mode : 1</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 982310-02 Mode : 1</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 982310-02 Mode : 1</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 <p>Site : site Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 982310-02 Mode : 2</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 982310-02 Mode : 2</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 2</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 2</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Project : Peak Mode : 2</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 2</p>	<p>Left blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	<p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 982310-02 Mode : 2</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 982310-02 Mode : 2</p>
Avg.	<p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 2</p>	<p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 2</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 2</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 2</p>	<p>Left blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 982310-02 : 3</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 982310-02 : 3</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak Mode : 982310-02 : 3</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak Mode : 982310-02 : 3</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 3</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 3</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 3</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 3</p>







2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 4</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HE_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 4</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HE_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 4</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HE_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 4</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 4</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 4</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 4</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 4</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 5</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 5</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 5</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 5</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : S</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : S</p>	<p>Left blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 5</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 5</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 5</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 5</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Vertical	Fundamental
<p>Peak</p>	 <p>Date: 2019-10-04</p> <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : S</p>	<p>Left Blank</p>
<p>Avg.</p>	 <p>Date: 2019-10-04</p> <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : S</p>	<p>Left Blank</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 6</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 6</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Project : 982310-02 Mode : 6</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Project : 982310-02 Mode : 6</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 6</p>	 <p>Site : site Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 6</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 6</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 6</p>







2.4GHz 2400~2483.5MHz





WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 7</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HE_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 7</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_S4 3m HE_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 7</p>	 <p>Site : 03CH07-HY Condition : AVG_S4 3m HE_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 7</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 7</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 7</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 7</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 7</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 8</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 8</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 8</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 8</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Fundamental
<p>Peak</p>	 <p>Date: 2019-10-04</p> <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 8</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Date: 2019-10-04</p> <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 8</p>	<p>Left blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 8</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 8</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 8</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 8</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 <p>Date: 2019-10-04</p> <p>Level (dBm/1m)</p> <p>Frequency (MHz)</p> <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 8</p>	Left Blank
Avg.	 <p>Date: 2019-10-04</p> <p>Level (dBm/1m)</p> <p>Frequency (MHz)</p> <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 8</p>	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 9</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 982310-02 Mode : 9</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Project : 982310-02 Mode : 9</p>	 <p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Project : 982310-02 Mode : 9</p>



WIFI	2.4GHz 2400~2483.5MHz Fundamental @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 982310-02</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 982310-02</p>
	<p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 9</p>	<p>Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 982310-02 Mode : 9</p>



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 1</p>	<p>Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 1</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 2</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 2</p>





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 3</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 3</p>



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 4</p>	 <p>Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 4</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 5</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 5</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 6</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 6</p>



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 7</p>	<p>Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 7</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 8</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 8</p>





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 982310-02 Mode : 9</p>	<p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 982310-02 Mode : 9</p>



2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)


WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT20 LF	
1	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH07-HY Condition : QP 3m LF-ANT-35419(G) HORIZONTAL Detector : Peak Project : 982310-02 Mode : 10</p>	 <p>Site : 03CH07-HY Condition : QP 3m LF-ANT-35419(G) VERTICAL Detector : Peak Project : 982310-02 Mode : 10</p>



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
802.11b	100.00	-	-	10Hz	0.00
802.11g	92.36	1390	0.72	1kHz	0.35
2.4GHz 802.11n HT20	92.20	1300	0.77	1kHz	0.35


802.11b



Date: 23.SEP.2019 23:10:40




802.11g



Date: 23.SEP.2019 23:16:49

802.11n HT20



Date: 23.SEP.2019 23:20:57