



RF TEST REPORT

Applicant Mobike Information Technology Limited
FCC ID 2AP7UMCA5A15
Product Mobike Lock
Brand mobike
Model MCA5A15
Report No. R1805A0244-R1
Issue Date July 3, 2018

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 24E (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Jiangpeng Lan

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1.	Test Laboratory	4
1.1.	Notes of the test report.....	4
1.2.	Test facility.....	4
1.3.	Testing Location	5
2.	General Description of Equipment under Test.....	6
3.	Applied Standards.....	7
4.	Test Configuration.....	8
5.	Test Case Results.....	9
5.1.	RF Power Output.....	9
5.2.	Effective Isotropic Radiated Power	11
5.3.	Occupied Bandwidth	14
5.4.	Band Edge Compliance.....	18
5.5.	Peak-to-Average Power Ratio (PAPR)	27
5.6.	Frequency Stability.....	29
5.7.	Spurious Emissions at Antenna Terminals	32
5.8.	Radiates Spurious Emission	42
6.	Main Test Instruments	49
	ANNEX A: EUT Appearance and Test Setup.....	50
A.1	EUT Appearance	50
A.2	Test Setup.....	51



Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Isotropic Radiated power	24.232(c)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	2.1051 /24.238(a)	PASS
5	Peak-to-Average Power Ratio	24.232/KDB 971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 24.235	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 24.238(a)	PASS
8	Radiates Spurious Emission	2.1053 / 24.238(a)	PASS

Date of Testing: May 24, 2018 ~ June 29, 2018

Note: PASS: The EUT complies with the essential requirements in the standard.
FAIL: The EUT does not comply with the essential requirements in the standard.



1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com



2. General Description of Equipment under Test

Client Information

Applicant	Mobike Information Technology Limited
Applicant address	Section 4, Room 112, Block C, Nangang Industrial Develop area, economic and technological development zone, Tianjin, PRC.
Manufacturer	Mobike Information Technology Limited
Manufacturer address	Section 4, Room 112, Block C, Nangang Industrial Develop area, economic and technological development zone, Tianjin, PRC.

General information

EUT Description					
Model	MCA5A15				
IMEI	866425030269767				
Hardware Version	A15				
Software Version	MSL_MC_A_A5_A15_522				
Power Supply	Battery				
Antenna Type	Internal Antenna				
Test Mode(s)	LTE Band 2;				
Test Modulation	QPSK,16QAM				
LTE Category	M1				
Maximum E.I.R.P	LTE Band 2:	21.62dBm			
Rated Power Supply Voltage	3.7V				
Extreme Voltage	Minimum: 3.5V Maximum: 4.2V				
Extreme Temperature	Lowest: -20°C Highest: +55°C				
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)		
	LTE Band 2	1850 ~ 1910	1930 ~ 1990		
EUT Accessory					
Battery	Manufacturer: LIFUN TECHNOLOGY Co., LTD Model: S20-875771				
Note: The information of the EUT is declared by the manufacturer.					



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR47 Part 2 (2017)

FCC CFR 47 Part 24E (2017)

ANSI/TIA-603-E (2016)

KDB 971168 D01 Power Meas License Digital Systems v03r01



4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal position) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below for LTE Band 2:

Test items	Bandwidth (MHz)						Modulation		RB			Test Channel		
	1.4	3	5	10	15	20	QPSK	16QAM	1	50%	100%	L	M	H
RF power output	O	O	O	O	O	O	O	O	O	O	O	O	O	O
Effective Isotropic Radiated power	O	O	O	O	O	O	O	O	-	-	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	O	O	-	-	O	-	O	-
Band Edge Compliance	O	O	O	O	O	O	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	O	O	-	-	O	-	O	-
Frequency Stability	O	O	O	O	O	O	O	O	-	-	O	O	-	O
Conducted Spurious Emissions	O	O	O	O	O	O	O	-	O	-	-	O	O	O
Radiates Spurious Emission	O	-	-	O	-	O	O	-	O	-	-	O	O	O
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.													

5. Test Case Results

5.1. RF Power Output


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.



Test Results

LTE Band2	Channel/ Frequency(MHz)	Index	RB# RBstart	Conducted Power (dBm)	
				QPSK	16QAM
1.4MHz	18607/1850.7	0	1#0	22.70	21.25
		0	6#0	20.48	20.65
	18900/1880	0	1#0	22.55	21.13
		0	6#0	20.44	20.08
	19193/1909.3	0	1#5	22.02	21.58
		0	6#0	20.50	19.93
3MHz	18615/1851.5	0	1#0	22.51	22.18
		0	6#0	20.38	20.18
	18900/1880	0	1#0	22.58	21.43
		0	6#0	20.47	20.23
	19185/1908.5	1	1#5	22.03	22.00
		1	6#0	20.26	19.70
5MHz	18625/1852.5	3	1#0	22.68	22.78
		0	6#0	21.41	19.94
	18900/1880	0	1#0	22.85	22.76
		0	6#0	21.63	20.61
	19175/1907.5	0	1#5	21.52	22.37
		3	6#0	21.30	20.49
10MHz	18650/1855	3	1#0	22.52	22.25
		0	4#0	22.73	22.00
	18900/1880	0	1#0	22.77	21.70
		0	4#0	22.58	21.82
	19150/1905	4	1#5	22.43	22.40
		7	4#2	22.69	21.87
15MHz	18675/1857.5	3	1#0	22.66	22.53
		0	6#0	22.56	22.79
	18900/1880	0	1#0	22.47	22.59
		0	6#0	22.58	22.47
	19125/1902.5	8	1#5	22.21	22.28
		11	6#0	22.36	22.51
20MHz	18700/1860	3	1#0	22.90	22.81
		0	6#0	22.87	22.88
	18900/1880	0	1#0	22.57	22.50
		0	6#0	22.64	22.59
	19100/1900	12	1#5	22.40	22.31
		15	6#0	22.37	22.45



5.2. Effective Isotropic Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Methods of Measurement

The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI/TIA-603-E (2016).

- a) Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.
 - b) Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).
 - c) Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.
 - d) Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading.
$$\text{LOSS} = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$$
 - e) Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation:
$$\text{ERP (dBm)} = \text{LVL (dBm)} + \text{LOSS (dB)}$$
 - f) The maximum ERP is the maximum value determined in the preceding step.
 - g) When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g.transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:
$$\text{ERP (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBd)}$$
where: dBd refers to gain relative to an ideal dipole.
- $$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15 \text{ (dB.)}$$

The RB allocation refers to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 24.232(c) Mobile and portable stations are limited to 2 watts EIRP.

Rule Part 24.232(e) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Limit	$\leq 2 \text{ W}$ (33 dBm)
-------	-----------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19 \text{ dB}$

**Test Results:**

The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.

LTE Band 2							
bandwidth	Frequency (MHz)	Polarization	RB	Index	EIRP (dBm)	Limit (dBm)	Conclusion
1.4 MHz (QPSK)	1850.7	Horizontal	1#0	0	20.43	33	Pass
	1880	Horizontal	1#2	0	20.50	33	Pass
	1909.3	Horizontal	1#5	0	20.68	33	Pass
3 MHz (QPSK)	1851.5	Horizontal	1#0	0	20.75	33	Pass
	1880	Horizontal	1#5	0	20.80	33	Pass
	1908.5	Horizontal	1#5	1	20.53	33	Pass
5 MHz (QPSK)	1852.5	Horizontal	1#0	0	20.74	33	Pass
	1880	Horizontal	1#5	1	20.84	33	Pass
	1907.5	Horizontal	1#5	3	20.83	33	Pass
10 MHz (QPSK)	1855	Horizontal	4#0	0	20.95	33	Pass
	1880	Horizontal	4#2	3	21.15	33	Pass
	1905	Horizontal	4#2	7	20.39	33	Pass
15 MHz (QPSK)	1857.5	Horizontal	1#0	0	20.61	33	Pass
	1880	Horizontal	1#5	5	21.09	33	Pass
	1902.5	Horizontal	1#5	11	20.69	33	Pass
20 MHz (QPSK)	1860	Horizontal	6#0	0	20.84	33	Pass
	1880	Horizontal	6#0	7	21.04	33	Pass
	1900	Horizontal	6#0	15	21.62	33	Pass
1.4 MHz (16QAM)	1850.7	Horizontal	1#0	0	20.12	33	Pass
	1880	Horizontal	1#2	0	20.27	33	Pass
	1909.3	Horizontal	1#5	0	20.28	33	Pass
3 MHz (16QAM)	1851.5	Horizontal	1#0	0	20.36	33	Pass
	1880	Horizontal	1#5	0	20.59	33	Pass
	1908.5	Horizontal	1#5	1	20.16	33	Pass
5 MHz (16QAM)	1852.5	Horizontal	1#0	0	20.34	33	Pass
	1880	Horizontal	1#5	1	20.56	33	Pass
	1907.5	Horizontal	1#5	3	20.61	33	Pass
10 MHz (16QAM)	1855	Horizontal	4#0	0	20.78	33	Pass
	1880	Horizontal	4#2	3	21.01	33	Pass
	1905	Horizontal	4#2	7	20.29	33	Pass
15 MHz (16QAM)	1857.5	Horizontal	1#0	0	20.33	33	Pass
	1880	Horizontal	1#5	5	20.89	33	Pass
	1902.5	Horizontal	1#5	11	20.58	33	Pass
20 MHz (16QAM)	1860	Horizontal	6#0	0	20.67	33	Pass
	1880	Horizontal	6#0	7	20.87	33	Pass
	1900	Horizontal	6#0	15	21.57	33	Pass

5.3.Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 51kHz, VBW is set to 160kHz for LTE Band 2.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

**Test Result**


Mode	Bandwidth	Modulation	Channel/ Frequency(MHz)	RB	Index	Bandwidth(MHz)	
						99% Power	-26dBc
LTE Band 2	1.4MHz	QPSK	18900/1880	6#0	0	1.1079	1.36
		16QAM	18900/1880	6#0	0	0.95056	1.265
	3MHz	QPSK	18900/1880	6#0	0	1.1772	1.966
		16QAM	18900/1880	6#0	0	0.97937	1.314
	5MHz	QPSK	18900/1880	6#0	0	1.1528	2.017
		16QAM	18900/1880	6#0	0	1.0718	1.631
	10MHz	QPSK	18900/1880	6#0	0	1.093	1.737
		16QAM	18900/1880	6#0	0	1.2187	2.081
	15MHz	QPSK	18900/1880	6#0	0	1.2206	2.031
		16QAM	18900/1880	6#0	0	1.0527	1.746
	20MHz	QPSK	18900/1880	6#0	0	1.2351	1.866
		16QAM	18900/1880	6#0	0	1.1205	1.815



LTE Band 2 1.4MHz QPSK CH-Middle



LTE Band 2 3MHz QPSK CH-Middle



LTE Band 2 5MHz QPSK CH-Middle



LTE Band 2 10MHz QPSK CH-Middle



LTE Band 2 15MHz QPSK CH-Middle




LTE Band 2 20MHz QPSK CH-Middle







LTE Band 2 1.4MHz 16QAM CH-Middle



LTE Band 2 3MHz 16QAM CH-Middle



LTE Band 2 5MHz 16QAM CH-Middle



LTE Band 2 10MHz 16QAM CH-Middle



LTE Band 2 15MHz 16QAM CH-Middle



LTE Band 2 20MHz 16QAM CH-Middle



5.4. Band Edge Compliance

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The Average detector is used and RBW is set to 51kHz, VBW is set to 160kHz for LTE Band 2 (1.4MHz/3MHz/5MHz/10MHz/15MHz/20MHz).

Spectrum analyzer plots are included on the following pages.

Test Setup




Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------


Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684$ dB.

**Test Result:**



LTE Band 2 3MHz QPSK 100%RB CH-Low



LTE Band 2 3MHz QPSK 100%RB CH-High




LTE Band 2 5MHz QPSK 1RB CH-Low




LTE Band 2 5MHz QPSK 1RB CH-High



LTE Band 2 5MHz QPSK 100%RB CH-Low




LTE Band 2 5MHz QPSK 100%RB CH-High






LTE Band 2 10MHz QPSK 1RB CH-Low



LTE Band 2 10MHz QPSK 1RB CH-High




LTE Band 2 10MHz QPSK 100%RB CH-Low




LTE Band 2 10MHz QPSK 100%RB CH-High



LTE Band 2 15MHz QPSK 1RB CH-Low



LTE Band 2 15MHz QPSK 1RB CH-High





LTE Band 2 15MHz QPSK 100%RB CH-Low




LTE Band 2 15MHz QPSK 100%RB CH-High



LTE Band 2 20MHz QPSK 1RB CH-Low




LTE Band 2 20MHz QPSK 1RB CH-High



LTE Band 2 20MHz QPSK 100%RB CH-Low



LTE Band 2 20MHz QPSK 100%RB CH-High






LTE Band 2 1.4MHz 16QAM 1RB CH-Low




LTE Band 2 1.4MHz 16QAM 1RB CH-High




LTE Band 2 1.4MHz 16QAM 100%RB CH-Low




LTE Band 2 1.4MHz 16QAM 100%RB CH-High



LTE Band 2 3MHz 16QAM 1RB CH-Low




LTE Band 2 3MHz 16QAM 1RB CH-High






LTE Band 2 3MHz 16QAM 100%RB CH-Low



LTE Band 2 3MHz 16QAM 100%RB CH-High



LTE Band 2 5MHz 16QAM 1RB CH-Low




LTE Band 2 5MHz 16QAM 1RB CH-High



LTE Band 2 5MHz 16QAM 100%RB CH-Low




LTE Band 2 5MHz 16QAM 100%RB CH-High







LTE Band 2 10MHz 16QAM 1RB CH-Low




LTE Band 2 10MHz 16QAM 1RB CH-High




LTE Band 2 10MHz 16QAM 100%RB CH-Low




LTE Band 2 10MHz 16QAM 100%RB CH-High



LTE Band 2 15MHz 16QAM 1RB CH-Low



LTE Band 2 15MHz 16QAM 1RB CH-High





LTE Band 2 15MHz 16QAM 100%RB CH-Low




LTE Band 2 15MHz 16QAM 100%RB CH-High




LTE Band 2 20MHz 16QAM 1RB CH-Low




LTE Band 2 20MHz 16QAM 1RB CH-High



LTE Band 2 20MHz 16QAM 100%RB CH-Low



LTE Band 2 20MHz 16QAM 100%RB CH-High



5.5. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as PPK. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

Test Setup



Limits

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB in 24.232(d).

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

**Test Results**

Mode	Bandwidth	Modulation	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)		
				Peak(dBm)	Avg(dBm)	PAPR(dB)
LTE Band 2	1.4MHz	QPSK	18900/1880	28.76	22.55	6.21
		16QAM	18900/1880	27.18	21.13	6.05
	3MHz	QPSK	18900/1880	28.64	22.58	6.06
		16QAM	18900/1880	27.78	21.43	6.35
	5MHz	QPSK	18900/1880	29.01	22.85	6.16
		16QAM	18900/1880	29.01	22.76	6.25
	10MHz	QPSK	18900/1880	29.07	22.77	6.30
		16QAM	18900/1880	27.83	21.70	6.13
	15MHz	QPSK	18900/1880	28.71	22.47	6.24
		16QAM	18900/1880	28.92	22.59	6.33
	20MHz	QPSK	18900/1880	28.74	22.57	6.17
		16QAM	18900/1880	28.84	22.50	6.34

5.6. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +55°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a "call mode". These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +55°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.5 V and 4.2 V, with a nominal voltage of 3.7V.

Test setup



**Limits**

No specific frequency stability requirements in part 24.235

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.

**Test Result**

LTE Band 2					
(QPSK, 20MHz BANDWIDTH)					
Condition		1850	1910	Delta(Hz)	Frequency Stability(ppm)
Temperature	Voltage	F low@-13dBm(MHz)	F high@-13dBm(MHz)		
Normal (25°C)	Normal	1851.2788	1908.7258	-3.95	-0.00210
Extreme (55°C)		1851.2783	1908.7253	-4.21	-0.00224
Extreme (50°C)		1851.2868	1908.7338	1.40	0.00075
Extreme (40°C)		1851.2822	1908.7292	-2.39	-0.00127
Extreme (30°C)		1851.2829	1908.7299	1.40	0.00075
Extreme (20°C)		1851.2832	1908.7302	-1.34	-0.00071
Extreme (10C)		1851.2797	1908.7267	-0.40	-0.00021
Extreme (0°C)		1851.2856	1908.7326	0.37	0.00020
Extreme (-10°C)		1851.2793	1908.7263	-1.36	-0.00072
Extreme (-20°C)		1851.2834	1908.7304	-3.48	-0.00185
Extreme (-30°C)		1851.2781	1908.7252	-3.26	-0.00173
25°C	LV	1851.2832	1908.7302	-3.19	-0.00170
	HV	1851.2781	1908.7251	1.85	0.00099
(16QAM, 20MHz BANDWIDTH)					
Condition		1850	1910	Delta(Hz)	Frequency Stability(ppm)
Temperature	Voltage	F low@-13dBm(MHz)	F high@-13dBm(MHz)		
Normal (25°C)	Normal	1851.2742	1908.7212	-1.90	-0.00101
Extreme (55°C)		1851.2747	1908.7217	3.06	0.00163
Extreme (50°C)		1851.2662	1908.7132	-2.58	-0.00137
Extreme (40°C)		1851.2708	1908.7178	-1.15	-0.00061
Extreme (30°C)		1851.2701	1908.7171	-3.73	-0.00198
Extreme (20°C)		1851.2698	1908.7168	-2.97	-0.00158
Extreme (10C)		1851.2733	1908.7203	-0.74	-0.00039
Extreme (0°C)		1851.2674	1908.7144	1.31	0.00070
Extreme (-10°C)		1851.2737	1908.7207	-3.74	-0.00199
Extreme (-20°C)		1851.2696	1908.7166	-2.49	-0.00132
Extreme (-30°C)		1851.2753	1908.7222	2.31	0.00123
25°C	LV	1851.2698	1908.7168	-5.76	-0.00307
	HV	1851.2749	1908.7219	1.27	0.00067

5.7. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement


The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used.

RBW is set to 100kHz, VBW is set to 300kHz for 30MHz~1GHz

RBW is set to 1MHz, VBW is set to 3MHz for above 1GHz, Sweep is set to ATUO.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 24.238(a) specifies that "on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB."

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-20GHz	1.407 dB



Test Result


Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.







LTE Band 2 1.4MHz CH-High 30MHz~1GHz




LTE Band 2 3MHz CH-Low 30MHz~1GHz




LTE Band 2 1.4MHz CH-High 1GHz~3GHz




LTE Band 2 3MHz CH-Low 1GHz~3GHz



LTE Band 2 1.4MHz CH-High 3GHz~20GHz




LTE Band 2 3MHz CH-Low 3GHz~20GHz







LTE Band 2 3MHz CH-Middle 30MHz~1GHz




LTE Band 2 3MHz CH-High 30MHz~1GHz




LTE Band 2 3MHz CH-Middle 1GHz~3GHz




LTE Band 2 3MHz CH-High 1GHz~3GHz



LTE Band 2 3MHz CH-Middle 3GHz~20GHz




LTE Band 2 3MHz CH-High 3GHz~20GHz







LTE Band 2 5MHz CH-Low 30MHz~1GHz




LTE Band 2 5MHz CH-Middle 30MHz~1GHz




LTE Band 2 5MHz CH-Low 1GHz~3GHz




LTE Band 2 5MHz CH-Middle 1GHz~3GHz



LTE Band 2 5MHz CH-Low 3GHz~20GHz




LTE Band 2 5MHz CH-Middle 3GHz~20GHz







LTE Band 2 5MHz CH-High 30MHz~1GHz




LTE Band 2 10MHz CH-Low 30MHz~1GHz




LTE Band 2 5MHz CH-High 1GHz~3GHz




LTE Band 2 10MHz CH-Low 1GHz~3GHz



LTE Band 2 5MHz CH-High 3GHz~20GHz




LTE Band 2 10MHz CH-Low 3GHz~20GHz







LTE Band 2 10MHz CH-Middle 30MHz~1GHz




LTE Band 2 10MHz CH-High 30MHz~1GHz




LTE Band 2 10MHz CH-Middle 1GHz~3GHz




LTE Band 2 10MHz CH-High 1GHz~3GHz



LTE Band 2 10MHz CH-Middle 3GHz~20GHz




LTE Band 2 10MHz CH-High 3GHz~20GHz







LTE Band 2 15MHz CH-Low 30MHz~1GHz




LTE Band 2 15MHz CH-Middle 30MHz~1GHz




LTE Band 2 15MHz CH-Low 1GHz~3GHz




LTE Band 2 15MHz CH-Middle 1GHz~3GHz



LTE Band 2 15MHz CH-Low 3GHz~20GHz




LTE Band 2 15MHz CH-Middle 3GHz~20GHz







LTE Band 2 15MHz CH-High 30MHz~1GHz




LTE Band 2 20MHz CH-Low 30MHz~1GHz




LTE Band 2 15MHz CH-High 1GHz~3GHz




LTE Band 2 20MHz CH-Low 1GHz~3GHz



LTE Band 2 15MHz CH-High 3GHz~20GHz




LTE Band 2 20MHz CH-Low 3GHz~20GHz







LTE Band 2 20MHz CH-Middle 30MHz~1GHz




LTE Band 2 20MHz CH-High 30MHz~1GHz




LTE Band 2 20MHz CH-Middle 1GHz~3GHz




LTE Band 2 20MHz CH-High 1GHz~3GHz



LTE Band 2 20MHz CH-Middle 3GHz~20GHz



LTE Band 2 20MHz CH-High 3GHz~20GHz





5.8.Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI/TIA-603-E (2016).
2. The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz,VBW=3MHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:

$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$

The measurement results are amend as described below:


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$

8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup

30MHz~~~1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

Limits

Rule Part 24.238(a) specifies that "on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB."

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.



Test Result

Sweep the whole frequency band through the range from 30MHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

LTE Band 2 1.4MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3700.5	-45.35	5.1	11.05	Horizontal	-39.4	-13.0	26.4	135
3	5550.8	-58.93	5.42	12.65	Horizontal	-51.7	-13.0	38.7	225
4	7402.8	-53.35	6.7	13.85	Horizontal	-46.2	-13.0	33.2	0
5	9253.5	-51.84	7.01	14.75	Horizontal	-44.1	-13.0	31.1	0
6	11104.2	-52.37	7.48	15.95	Horizontal	-43.9	-13.0	30.9	45
7	12954.9	-51.44	7.51	16.55	Horizontal	-42.4	-13.0	29.4	315
8	14805.6	-45.51	8.24	15.35	Horizontal	-38.4	-13.0	25.4	90
9	16656.3	-46.74	8.41	14.95	Horizontal	-40.2	-13.0	27.2	0
10	18507.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3759.0	-36.55	5.10	11.05	Horizontal	-30.6	-13.0	17.6	225
3	5638.9	-58.83	5.42	12.65	Horizontal	-51.6	-13.0	38.6	315
4	7520.0	-53.95	6.70	13.85	Horizontal	-46.8	-13.0	33.8	0
5	9400.0	-51.64	7.01	14.75	Horizontal	-43.9	-13.0	30.9	45
6	11280.0	-51.77	7.48	15.95	Horizontal	-43.3	-13.0	30.3	90
7	13160.0	-51.24	7.51	16.55	Horizontal	-42.2	-13.0	29.2	315
8	15040.0	-47.71	8.24	15.35	Horizontal	-40.6	-13.0	27.6	315
9	16920.0	-46.54	8.41	14.95	Horizontal	-40.0	-13.0	27.0	0
10	18800.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 2 1.4MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3817.5	-40.35	5.10	11.05	Horizontal	-34.4	-13.0	21.4	0
3	5726.6	-59.63	5.42	12.65	Horizontal	-52.4	-13.0	39.4	135
4	7637.2	-55.25	6.70	13.85	Horizontal	-48.1	-13.0	35.1	270
5	9546.5	-53.84	7.01	14.75	Horizontal	-46.1	-13.0	33.1	135
6	11455.8	-50.47	7.48	15.95	Horizontal	-42.0	-13.0	29.0	135
7	13365.1	-51.44	7.51	16.55	Horizontal	-42.4	-13.0	29.4	225
8	15274.4	-48.71	8.24	15.35	Horizontal	-41.6	-13.0	28.6	0
9	17183.7	-45.94	8.41	14.95	Horizontal	-39.4	-13.0	26.4	225
10	19093.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 10MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3710.0	-44.55	5.10	11.05	Horizontal	-38.6	-13.0	25.6	135
3	5565.0	-59.43	5.42	12.65	Horizontal	-52.2	-13.0	39.2	135
4	7420.0	-53.85	6.70	13.85	Horizontal	-46.7	-13.0	33.7	315
5	9275.0	-52.04	7.01	14.75	Horizontal	-44.3	-13.0	31.3	180
6	11130.0	-51.07	7.48	15.95	Horizontal	-42.6	-13.0	29.6	45
7	12985.0	-51.64	7.51	16.55	Horizontal	-42.6	-13.0	29.6	135
8	14840.0	-46.11	8.24	15.35	Horizontal	-39.0	-13.0	26.0	0
9	16695.0	-46.54	8.41	14.95	Horizontal	-40.0	-13.0	27.0	225
10	18550.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 2 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.0	-38.75	5.10	11.05	Horizontal	-32.8	-13.0	19.8	135
3	5640.0	-57.93	5.42	12.65	Horizontal	-50.7	-13.0	37.7	270
4	7520.0	-52.75	6.70	13.85	Horizontal	-45.6	-13.0	32.6	180
5	9400.0	-51.64	7.01	14.75	Horizontal	-43.9	-13.0	30.9	180
6	11280.0	-51.67	7.48	15.95	Horizontal	-43.2	-13.0	30.2	270
7	13160.0	-49.64	7.51	16.55	Horizontal	-40.6	-13.0	27.6	315
8	15040.0	-47.91	8.24	15.35	Horizontal	-40.8	-13.0	27.8	225
9	16920.0	-46.74	8.41	14.95	Horizontal	-40.2	-13.0	27.2	180
10	18800.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 10MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3810.0	-39.45	5.10	11.05	Horizontal	-33.5	-13.0	20.5	0
3	5715.0	-59.63	5.42	12.65	Horizontal	-52.4	-13.0	39.4	135
4	7620.0	-54.55	6.70	13.85	Horizontal	-47.4	-13.0	34.4	315
5	9525.0	-53.84	7.01	14.75	Horizontal	-46.1	-13.0	33.1	180
6	11430.0	-52.37	7.48	15.95	Horizontal	-43.9	-13.0	30.9	270
7	13335.0	-50.64	7.51	16.55	Horizontal	-41.6	-13.0	28.6	270
8	15240.0	-47.81	8.24	15.35	Horizontal	-40.7	-13.0	27.7	0
9	17145.0	-45.64	8.41	14.95	Horizontal	-39.1	-13.0	26.1	45
10	19050.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 2 20MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3720.0	-47.45	5.10	11.05	Horizontal	-41.5	-13.0	28.5	0
3	5580.0	-59.83	5.42	12.65	Horizontal	-52.6	-13.0	39.6	45
4	7440.0	-53.15	6.70	13.85	Horizontal	-46.0	-13.0	33.0	180
5	9300.0	-50.74	7.01	14.75	Horizontal	-43.0	-13.0	30.0	225
6	11160.0	-52.47	7.48	15.95	Horizontal	-44.0	-13.0	31.0	135
7	13020.0	-52.04	7.51	16.55	Horizontal	-43.0	-13.0	30.0	315
8	14880.0	-46.71	8.24	15.35	Horizontal	-39.6	-13.0	26.6	90
9	16740.0	-46.64	8.41	14.95	Horizontal	-40.1	-13.0	27.1	180
10	18600.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 20MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.0	-44.45	5.10	11.05	Horizontal	-38.5	-13.0	25.5	135
3	5640.0	-58.93	5.42	12.65	Horizontal	-51.7	-13.0	38.7	135
4	7520.0	-53.95	6.70	13.85	Horizontal	-46.8	-13.0	33.8	315
5	9400.0	-52.84	7.01	14.75	Horizontal	-45.1	-13.0	32.1	225
6	11280.0	-52.17	7.48	15.95	Horizontal	-43.7	-13.0	30.7	90
7	13160.0	-52.04	7.51	16.55	Horizontal	-43.0	-13.0	30.0	180
8	15040.0	-48.31	8.24	15.35	Horizontal	-41.2	-13.0	28.2	0
9	16920.0	-46.74	8.41	14.95	Horizontal	-40.2	-13.0	27.2	45
10	18800.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 2 20MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3800.0	-37.25	5.10	11.05	Horizontal	-31.3	-13.0	18.3	225
3	5700.0	-59.53	5.42	12.65	Horizontal	-52.3	-13.0	39.3	90
4	7600.0	-54.55	6.70	13.85	Horizontal	-47.4	-13.0	34.4	180
5	9500.0	-54.34	7.01	14.75	Horizontal	-46.6	-13.0	33.6	0
6	11400.0	-50.97	7.48	15.95	Horizontal	-42.5	-13.0	29.5	45
7	13300.0	-50.64	7.51	16.55	Horizontal	-41.6	-13.0	28.6	315
8	15200.0	-47.61	8.24	15.35	Horizontal	-40.5	-13.0	27.5	90
9	17100.0	-47.84	8.41	14.95	Horizontal	-41.3	28.3	69.6	180
10	19000.0	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.




6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMU200	118133	2018-05-13	2019-05-12
Base Station Simulator	R&S	CMW500	113645	2018-05-13	2019-05-12
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	NA	NA
Spectrum Analyzer	Agilent	N9010A	MY47191109	2018-05-20	2019-05-19
Universal Radio Communication Tester	Agilent	E5515C	MY48367192	2018-05-20	2019-05-19
Signal Analyzer	R&S	FSV30	100815	2017-12-17	2018-12-16
EMI Test Receiver	R&S	ESCI	100948	2018-05-20	2019-05-19
Signal generator	R&S	SMB 100A	102594	2018-05-13	2019-05-12
Signal generator	R&S	SMR27	100365	2018-05-14	2019-05-13
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2014-12-06	2019-12-05
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2014-12-06	2019-12-05
Climatic Chamber	Re Ce	PT-30B	20101891	2015-07-18	2018-07-17
Horn Antenna	ETS-Lindgren	3160-09	00102644	2015-01-30	2020-01-29
RF Cable	Agilent	SMA 15cm	0001	2018-02-03	2018-08-02
Preamplifier	R&S	SCU18	102327	2018-06-18	2019-06-17
Software	R&S	EMC32	V 8.52.0	NA	NA
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2018-05-07	2019-05-06

*****END OF REPORT *****

ANNEX A: EUT Appearance and Test Setup


A.1 EUT Appearance



a: EUT

Picture 1 EUT and Accessory

A.2 Test Setup



Picture 2: Radiated Spurious Emissions Test setup