

RADIO TEST REPORT

FCC ID: 2APA5-HPBU01

Product : RF transceiver module

Trade Mark : N/A

Model Name : HPBU01-TR-915

Serial Model : N/A

Report No. : SER180315013001E

Prepared for

BuildingLink

85 5th Ave 3rd Fl New York, NY 10003, USA

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen 518126 P.R. China

Tel.: +86-755-6115 9388 Fax.: +86-755-6115 6599

Website: <http://www.ntek.org.cn>



TEST RESULT CERTIFICATION

Applicant's name : BuildingLink

Address : 85 5th Ave 3rd FI New York, NY 10003, USA

Manufacturer's Name : Hope Microelectronics Co., Ltd.

Address : 2/F Building 3, Pingshan Private Enterprise Science & Technology Park, Nanshan District, Shenzhen 518057, China

Product description

Product name..... : RF transceiver module

Model and/or type reference : HPBU01-TR-915

Serial Model : N/A

Rating(s)..... : DC 3.3V

Standards : FCC Part15.249: 2018

Test procedure ANSI C63.10-2013

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test..... :

Date (s) of performance of tests..... : 15 Mar. 2018 ~ 26 Mar. 2018

Date of Issue..... : 26 Mar. 2018

Test Result..... : **Pass**

Testing Engineer : *Lake Xie*
(Lake Xie)

Technical Manager : *Jason chen*
(Jason Chen)

Authorized Signatory : *Sam. chen*
(Sam Chen)

Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . ANTENNA REQUIREMENT	13
3.1 STANDARD REQUIREMENT	13
3.2 EUT ANTENNA	13
3.3 CONDUCTED EMISSION MEASUREMENT	14
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.3.2 TEST PROCEDURE	15
3.3.3 DEVIATION FROM TEST STANDARD	15
3.3.4 TEST SETUP	15
3.2.5 TEST RESULT	16
3.4 RADIATED EMISSION MEASUREMENT	20
3.4.1 RADIATED EMISSION LIMITS	20
3.4.2 TEST PROCEDURE	21
3.4.3 DEVIATION FROM TEST STANDARD	21
3.4.4 TEST RESULTS (BELOW 30MHZ)	24
3.4.5 TEST RESULTS (BELOW 1000 MHZ)	25
3.4.6 TEST RESULTS (ABOVE 1000 MHZ)	27
3.4.7 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	28
4 . FREQUENCY TOLERANCE	29
4.1 FREQUENCY TOLERANCE LIMITS	29
4.2TEST PROCEDURE	29
4.3 TEST SETUP	29
4.4 TEST RESULTS	29
5. BANDWIDTH TEST	30
5.1 TEST PROCEDURE	30
5.1 DEVIATION FROM STANDARD	30
5.1 TEST SETUP	30
6. TEST RESULTS	31

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.249)			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	Pass	
15.203	Antenna Requirement	Pass	
15.249 15.209	Radiated Spurious Emission	Pass	
15.249(2)	Frequency Tolerance	Pass	
15.249(a)	Fundamental Measurement	Pass	
15.205	Band Edge Emission	Pass	
15.249	Occupied Bandwidth	Pass	

1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd
 Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.
 FCC FRN Registration No.:463705; IC Registration No.:9270A-1
 CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	RF transceiver module
Trade Mark	N/A
Model Name	HPBU01-TR-915
Serial Model	N/A
Model Difference	N/A
Product Description	The EUT is a RF transceiver module
	Operation Frequency: 915MHz
	Modulation Type: FSK
	Antenna Designation: PCB Antenna
	Antenna Gain(Peak) 1.7 dBi
Based on the application, features, or specification exhibited in User's Manual. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.
Adapter	N/A
Battery	N/A
HW Version	V1.0
SW Version	HPBU01_V0.1

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency(MHz)
01	915

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	1.7	Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	CH01

For Radiated Spurious Emission	
Pretest Mode	Description
Mode 1	CH01


For Conducted Emission	
Final Test Mode	Description
Mode 1	CH01

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Mode



Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	RF transceiver module	N/A	HPBU01-TR-915	N/A	EUT
E-2	DC Power	N/A	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS
Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2017.06.06	2018.06.05	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2017.11.10	2018.11.09	1 year
3	EMI Test Receiver	Agilent	N9038A	MY53227146	2017.06.06	2018.06.05	1 year
4	Test Receiver	R&S	ESPI	101318	2017.06.06	2018.06.05	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2017.04.09	2018.04.08	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2017.06.06	2018.06.05	1 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2017.04.09	2018.04.08	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2017.07.06	2018.07.05	1 year
9	Amplifier	EMC	EMC051835SE	980246	2017.08.09	2018.08.08	1 year
10	Amplifier	MITEQ	TTA1840-35-HG	177156	2017.06.06	2018.06.05	1 year
11	Loop Antenna	ARA	PLA-1030/B	1029	2017.06.06	2018.06.05	1 year
12	Power Meter	DARE	RPR3006W	15I00041S NO84	2017.08.07	2018.08.06	1 year
13	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
14	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
15	High Test Cable(1G-40 GHz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
16	High Test Cable(1G-40 GHz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
 And this temporary antenna connector is listed within the instrument list

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2017.06.06	2018.06.05	1 year
2	LISN	R&S	ENV216	101313	2017.04.19	2018.04.18	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2017.06.06	2018.06.05	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2017.06.06	2018.06.05	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is permanent attached PCB antenna (Gain:1.7dBi). It comply with the standard requirement.

3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR
0.50 -5.0			56.00	46.00	CISPR
5.0 -30.0			60.00	50.00	CISPR

0.15 -0.5			66 - 56 *	56 - 46 *	LP002.
0.50 -5.0			56.00	46.00	LP002.
5.0 -30.0			60.00	50.00	LP002.

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.3.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



- Note: 1.Support units were connected to second LISN.**
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes


3.2.5 TEST RESULT

EUT :	RF transceiver module	Model Name. :	HPBU01-TR-915
Temperature :	25 °C	Relative Humidity :	55%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 3.3V from DC Power AC 120V/60Hz	Test Mode :	Model 2

Frequency (MHz)	Reading Level (dB μ V)	Correct Factor (dB)	Measure-ment (dB μ V)	Limits (dB μ V)	Margin (dB)	Remark
0.1660	44.62	9.82	54.44	65.15	-10.71	QP
0.1660	31.68	9.82	41.50	55.15	-13.65	AVG
0.4500	41.09	9.83	50.92	56.87	-5.95	QP
0.4500	30.63	9.83	40.46	46.87	-6.41	AVG
0.4780	39.33	9.83	49.16	56.37	-7.21	QP
0.4780	14.22	9.83	24.05	46.37	-22.32	AVG
0.5460	38.09	9.83	47.92	56.00	-8.08	QP
0.5460	31.65	9.83	41.48	46.00	-4.52	AVG
0.6900	38.05	9.83	47.88	56.00	-8.12	QP
0.6900	26.51	9.83	36.34	46.00	-9.66	AVG
2.2220	36.67	9.88	46.55	56.00	-9.45	QP
2.2220	25.45	9.88	35.33	46.00	-10.67	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	RF transceiver module	Model Name. :	HPBU01-TR-915
Temperature :	25 °C	Relative Humidity :	55%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 3.3V from DC Power AC 120V/60Hz	Test Mode :	Model 2

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1660	44.47	9.92	54.39	65.15	-10.76	QP
0.1660	34.86	9.92	44.78	55.15	-10.37	AVG
0.4460	41.81	9.93	51.74	56.95	-5.21	QP
0.4460	33.12	9.93	43.05	46.95	-3.90	AVG
0.5180	38.78	9.93	48.71	56.00	-7.29	QP
0.5180	29.22	9.93	39.15	46.00	-6.85	AVG
0.5460	37.37	9.93	47.30	56.00	-8.70	QP
0.5460	31.29	9.93	41.22	46.00	-4.78	AVG
0.9220	37.83	9.93	47.76	56.00	-8.24	QP
0.9220	31.90	9.93	41.83	46.00	-4.17	AVG
2.4740	39.29	9.94	49.23	56.00	-6.77	QP
2.4740	30.28	9.94	40.22	46.00	-5.78	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	RF transceiver module	Model Name. :	HPBU01-TR-915
Temperature :	25 °C	Relative Humidity :	55%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 3.3V from DC Power AC 240V/60Hz	Test Mode :	Model 2

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2060	38.13	9.82	47.95	63.36	-15.41	QP
0.2060	31.46	9.82	41.28	53.36	-12.08	AVG
0.3180	39.69	9.82	49.51	59.76	-10.25	QP
0.3180	20.64	9.82	30.46	49.76	-19.30	AVG
0.4305	38.51	9.83	48.34	57.24	-8.90	QP
0.4305	23.30	9.83	33.13	47.24	-14.11	AVG
0.8740	37.33	9.89	47.22	56.00	-8.78	QP
0.8740	18.47	9.89	28.36	46.00	-17.64	AVG
1.6460	35.86	9.88	45.74	56.00	-10.26	QP
1.6460	11.17	9.88	21.05	46.00	-24.95	AVG
4.9299	39.02	10.06	49.08	56.00	-6.92	QP
4.9299	27.07	10.06	37.13	46.00	-8.87	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	RF transceiver module	Model Name. :	HPBU01-TR-915
Temperature :	25 °C	Relative Humidity :	55%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 3.3V from DC Power AC 240V/60Hz	Test Mode :	Model 2

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2860	38.92	9.92	48.84	60.64	-11.80	QP
0.2860	35.83	9.92	45.75	50.64	-4.89	AVG
0.5660	38.17	9.93	48.10	56.00	-7.90	QP
0.5660	29.15	9.93	39.08	46.00	-6.92	AVG
1.9460	39.54	9.94	49.48	56.00	-6.52	QP
1.9460	25.80	9.94	35.74	46.00	-10.26	AVG
2.3380	39.56	9.94	49.50	56.00	-6.50	QP
2.3380	31.27	9.94	41.21	46.00	-4.79	AVG
2.9900	40.95	9.95	50.90	56.00	-5.10	QP
2.9900	26.41	9.95	36.36	46.00	-9.64	AVG
3.3340	41.71	9.95	51.66	56.00	-4.34	QP
3.3340	30.87	9.95	40.82	46.00	-5.18	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
Frequency (MHz)	Limit (dBuV)	
30~88	40	3
88~216	43.5	3
216~960	46	3
960 -10000	54.00	3
*902 - 928	94.00	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).
- (3) *Note: This is the limit for the fundamental frequency.

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.249)

Frequency of Emission (MHz)	Field Strength of fundamental ((millivolts /meter)	Field Strength of Harmonics (microvolts/meter)
902-928	50	500

Notes:

- (1) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.4.3 DEVIATION FROM TEST STANDARD

No deviation


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.4.4 TEST RESULTS (BELOW 30MHz)

EUT :	RF transceiver module	Model Name. :	HPBU01-TR-915
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log(\text{specific distance}/\text{test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.4.5 TEST RESULTS (BELOW 1000 MHz)

EUT :	RF transceiver module	Model Name :	HPBU01-TR-915
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	Model 1	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type
35.2511	6.90	18.80	25.70	40.00	-14.30	QP
65.1145	12.52	8.08	20.60	40.00	-19.40	QP
113.3161	15.69	10.11	25.80	43.50	-17.70	QP
174.4241	12.96	12.63	25.59	43.50	-17.91	QP
203.5226	14.15	13.85	28.00	43.50	-15.50	QP
914.3320	64.05	25.06	89.11	94.00	-4.89	QP

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	RF transceiver module	Model Name :	HPBU01-TR-915
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	Model 1	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type
37.2854	5.97	17.83	23.80	40.00	-16.20	QP
106.0126	11.90	10.35	22.25	43.50	-21.25	QP
191.7450	17.22	13.08	30.30	43.50	-13.20	QP
419.1080	5.30	16.59	21.89	46.00	-24.11	QP
679.9600	14.42	21.08	35.50	46.00	-10.50	QP
914.6500	65.03	25.07	90.10	94.00	-3.90	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



3.4.6 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	RF transceiver module	Model Name :	HPBU01-TR-915
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	Model 1	Test By:	Lake Xie

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
915 MHz-Above 1G									
2745	44.25	4.65	32.25	44.30	36.85	74	-37.15	Pk	Vertical
2745	35.11	4.65	32.25	44.30	27.71	54	-26.29	AV	Vertical
3660	35.16	7.10	39.68	44.43	37.51	74	-36.49	Pk	Vertical
3660	24.68	7.10	39.68	44.43	27.03	54	-26.97	AV	Vertical
2745	42.67	4.65	32.25	44.20	35.37	74	-38.63	Pk	Horizontal
2745	33.55	4.65	32.25	44.20	26.25	54	-27.75	AV	Horizontal
3660	38.65	7.10	39.75	44.43	41.07	74	-32.93	Pk	Horizontal
3660	26.74	7.10	39.75	44.43	29.16	54	-24.84	AV	Horizontal

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3)All other emissions more than 20dB below the limit.

3.4.7 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

EUT :	RF transceiver module	Model Name :	HPBU01-TR-915
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	Model 1	Test By:	Lake Xie

Frequency	Reading Level	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	Type	
915MHz							
844.81	7.36	28.87	36.23	46	-9.77	QP	Vertical
848.65	8.26	28.97	37.23	46	-8.77	QP	Horizontal
902.00	6.25	29.49	35.74	46	-10.26	QP	Vertical
902.00	6.35	29.49	35.84	46	-10.16	QP	Horizontal
928.00	5.98	30.54	36.52	46	-9.48	QP	Vertical
928.00	6.21	30.54	36.75	46	-9.25	QP	Horizontal
935.42	7.99	31.05	39.04	46	-6.96	QP	Vertical
945.52	8.32	31.29	39.61	46	-6.39	QP	Horizontal

4. FREQUENCY TOLERANCE

4.1 FREQUENCY TOLERANCE LIMITS

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.001\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

4.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 10KHz, VBW \geq RBW, Sweep time = Auto.

4.3 TEST SETUP



4.4 TEST RESULTS

EUT :	RF transceiver module	Model Name :	HPBU01-TR-915
Temperature :	26 °C	Relative Humidity :	53%
Pressure :	1020 hPa	Test Power :	DC 3.3V
Test Mode :	Model 1		

915MHz

Voltage (V)	Frequency(MHz)	Reading(MHz)	Frequency Tolerance	LIMIT
2.8	915	915.004	0.000437%	$\pm 0.001\%$
3.3	915	915.002	0.000219%	$\pm 0.001\%$
3.8	915	915.005	0.000546%	$\pm 0.001\%$

Temperature (°C)	Frequency(MHz)	Reading(MHz)	Frequency Tolerance	LIMIT
-20	915	915.003	0.000328%	$\pm 0.001\%$
-10	915	915.005	0.000546%	$\pm 0.001\%$
0	915	915.001	0.000109%	$\pm 0.001\%$
10	915	915.003	0.000328%	$\pm 0.001\%$
20	915	915.002	0.000219%	$\pm 0.001\%$
30	915	915.005	0.000546%	$\pm 0.001\%$
40	915	915.007	0.000765%	$\pm 0.001\%$
50	915	915.002	0.000219%	$\pm 0.001\%$

5. BANDWIDTH TEST

5.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW \geq RBW, Sweep time = Auto.

5.1 DEVIATION FROM STANDARD

No deviation.

5.1 TEST SETUP



6. TEST RESULTS

EUT :	RF transceiver module	Model Name :	HPBU01-TR-915
Temperature :	26 °C	Relative Humidity :	53%
Pressure :	1020 hPa	Test Power :	DC 3.3V
Test Mode :	Model 1		

Test Channel	Frequency (MHz)	6 dB Bandwidth (KHz)
CH01	915	210.087

