

# EMF TEST REPORT

**Test Report No.** : OT-228-RWD-009  
**Reception No.** : 2207002095  
**Applicant** : CHIPSEN. Co., Ltd  
**Address** : B1 C-17, 15, Gyeongin-ro 53-gil, Guro-gu, Seoul, South Korea  
**Manufacturer** : CHIPSEN. Co., Ltd  
**Address** : B1 C-17, 15, Gyeongin-ro 53-gil, Guro-gu, Seoul, South Korea  
**Type of Equipment** : Wireless Communication Module  
**FCC ID.** : 2APB6-BOT-CDA110  
**Model Name** : BoT-cDA110  
**Multiple Model Name** : BoT-cDA110SC, BoT-cDA110SU, BoT-cDA110DC, BoT-cDA110DU, BoT-cDA110DS  
**Serial number** : N/A  
**Total page of Report** : 8 pages (including this page)  
**Date of Incoming** : July 11, 2022  
**Date of issue** : August 09, 2022

## SUMMARY


The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.





Tested by  
 Soon-Ki, Choi / Engineer  
 ONETECH Corp.

Reviewed by  
 Tae-Ho, Kim / General Manager  
 ONETECH Corp.

Approved by  
 Ki-Hong, Nam / General Manager  
 ONETECH Corp.

## CONTENTS

	<b>PAGE</b>
<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
<b>2.1 PRODUCT DESCRIPTION.....</b>	<b>5</b>
<b>2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....</b>	<b>6</b>
<b>3. EUT MODIFICATIONS.....</b>	<b>6</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>7</b>
<b>4.1 RF EXPOSURE CALCULATION .....</b>	<b>7</b>
<b>4.2 EUT DESCRIPTION.....</b>	<b>7</b>
<b>4.3 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH .....</b>	<b>8</b>
<b>4.4 CALCULATED MPE SAFE DISTANCE FOR BLUETOOTH LE .....</b>	<b>8</b>

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-228-RWD-009	August 09, 2022	Initial Release	All

### 1. VERIFICATION OF COMPLIANCE

Applicant : CHIPSEN. Co., Ltd  
 Address : B1 C-17, 15, Gyeongin-ro 53-gil, Guro-gu, Seoul, South Korea  
 Contact Person : Young Min Park / Senior Engineer  
 Telephone No. : 070-8708-5990  
 FCC ID : 2APB6-BOT-CDA110  
 Model Name : BoT-cDA110  
 Brand Name : N/A  
 Serial Number : N/A  
 Date : August 09, 2022

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Wireless Communication Module
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2020
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The CHIPSEN. Co., Ltd, Model BoT-cDA110 (referred to as the EUT in this report) is a Wireless Communication Module. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Wireless Communication Module		
Temperature Range	-30 °C ~ 85 °C		
Operating Frequency	2 402 MHz ~ 2 480 MHz		
MAX. RF OUTPUT POWER	Bluetooth	1 Mbps	5.09 dBm
		2 Mbps	2.04 dBm
		3 Mbps	-4.84 dBm
	Bluetooth LE	1 Mbps	5.30 dBm
		2 Mbps	5.32 dBm
Number of Channel	Bluetooth	79 Channels	
	Bluetooth LE	40 Channels	
Modulation Type	Bluetooth	GFSK for 1 Mbps, $\pi/4$ -DQPSK for 2 Mbps, 8-DPSK for 3 Mbps	
	Bluetooth LE	GFSK	
Antenna Type	Chip Antenna		
Antenna Gain	5.53 dBi		
List of each Osc. or crystal Freq.(Freq. $\geq$ 1 MHz)	24 MHz		
Rated Supply Voltage	DC 3.3 V		

**2.2 Alternative type(s)/model(s); also covered by this test report.**

-. The following lists consist of the added model and their differences.

Model Name	Differences	Tested
BoT-cDA110	Basic Model	<input checked="" type="checkbox"/>
BoT-cDA110SC	This model is derived for Marketing purpose. It is identical to the basic model except for the model name.	<input type="checkbox"/>
BoT-cDA110SU		<input type="checkbox"/>
BoT-cDA110DC		<input type="checkbox"/>
BoT-cDA110DU		<input type="checkbox"/>
BoT-cDA110DS		<input type="checkbox"/>

Note: 1. Applicant consigns only basic model to test. Therefore this test report just guarantees the units, which have been tested.

2. The Applicant/manufacturer is responsible for the compliance of all variants.

**3. EUT MODIFICATIONS**

-. None

## 4. MAXIMUM PERMISSIBLE EXPOSURE

### 4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are  $f/1500 \text{ mW/cm}^2$  for the frequency range between 300 MHz and 1 500 MHz and  $1.0 \text{ mW/cm}^2$  for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a  $1 \text{ mW/cm}^2$  exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in  $\text{mW/cm}^2$ , Z = Impedance of free space,  $377 \Omega$

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using  $P (\text{mW}) = P (\text{W}) / 1 000$ ,  $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in  $\text{mW/cm}^2$

### 4.2 EUT Description

Kind of EUT	Wireless Communication Module
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

### 4.3 Calculated MPE Safe Distance for Bluetooth

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	5.09 ± 1.0	6.09	4.06	5.53	3.57	1.07	0.002 9	1
	2 Mbps	2.04 ± 1.0	3.04	2.01			0.76	0.001 4	1
	3 Mbps	-4.84 ± 1.0	-3.84	0.41			0.34	0.000 3	1

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(4.06 * 3.57)/1.00} = 1.07 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 4.06 * 3.57 / (4 * \pi * 20^2) = 0.002 9$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

### 4.4 Calculated MPE Safe Distance for Bluetooth LE

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
2 402 ~ 2 480	1 Mbps	5.30 ± 1.0	6.30	4.27	5.53	3.57	1.10	0.003 0	1
	2 Mbps	5.32 ± 1.0	6.32	4.29			1.10	0.003 0	1

According to above table, for 2 402 ~ 2480 MHz Band(1 Mbps), safe distance,

$$D = 0.282 * \sqrt{(4.27 * 3.57)/1.00} = 1.10 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 4.27 * 3.57 / (4 * \pi * 20^2) = 0.003 0$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna