# RF EXPOSURE REPORT



Report No.: 18070268-FCC-H Supersede Report No.: N/A

Applicant	cant Shenzhen Kesi E-commerce Co.,Ltd		
Product Name	Bluetooth headset		
Model No.	S3		
Serial No.	S4, S5, S6, S7, S8, S9, S10, N3, N4, N5, N6, N7, N8, N9		
Test Standard	FCC 2.1093:2017		
Test Date	March 12 to March 29, 2018		
Issue Date	March 29, 2018		
Test Result	Test Result Pass Fail		
Equipment compl	Equipment complied with the specification		
Equipment did not comply with the specification			
Agron Liang David Huang			
Aaron Lia Test Engir			

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

#### Issued by:

#### SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report	18070268-FCC-H
Page	2 of 8

#### **Laboratories Introduction**

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

#### **Accreditations for Conformity Assessment**

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety



Test Report	18070268-FCC-H
Page	3 of 8

This page has been left blank intentionally.



Test Report	18070268-FCC-H
Page	4 of 8

# **CONTENTS**

1.	REPORT REVISION HISTORY	. 5
2.	CUSTOMER INFORMATION	.5
3.	TEST SITE INFORMATION	. 5
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION	. 6
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES	.7
5.1	RF EXPOSURE	.7
5.2	TEST RESULT	.8



Test Report	18070268-FCC-H
Page	5 of 8

# 1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070268-FCC-H	NONE	Original	March 29, 2018

# 2. Customer information

Applicant Name	Shenzhen Kesi E-commerce Co.,Ltd	
Applicant Add	5A-079, Trading Square,No.2, Huanan City, Pinghu Street, Longgang	
	District, Shenzhen, China	
Manufacturer	Dongguan Shenyao Electronic Technology Co. ,Ltd.	
Manufacturer Add	Shangbaotan Industrial Park, Shipai Town, Dongguan City, China	

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES	
	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park	
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China	
	518108	
FCC Test Site No.	535293	
IC Test Site No.	4842E-1	
Test Software	Radiated Emission Program-To Shenzhen v2.0	



Test Report	18070268-FCC-H
Page	6 of 8

### 4. Equipment under Test (EUT) Information

Main Model: S3

Serial Model: S4, S5, S6, S7, S8, S9, S10, N3, N4, N5, N6, N7, N8, N9

Date EUT received: March 11, 2018

Test Date(s): March 12 to March 29, 2018

Antenna Gain: Bluetooth: 0.6dBi

Antenna Type: Internal Antenna

Type of Modulation: Bluetooth: GFSK,  $\pi$  /4DQPSK, 8DPSK

RF Operating Frequency (ies): Bluetooth: 2402-2480 MHz

Number of Channels: Bluetooth: 79CH

Port: Pls refer to the user's manual

Battery

Input Power: Spec: 3.7V, 98mA

Trade Name: WRZ, AILIHEN, COOSII

FCC ID: 2APBQ-S3



Test Report	18070268-FCC-H
Page	7 of 8

# 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

#### 5.1 RF Exposure

#### Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f_{(GHz)}}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR,  $^{16}$  where

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result =  $P\sqrt{F}/D$ 

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



Test Report	18070268-FCC-H
Page	8 of 8

#### 5.2 Test Result

#### Bluetooth Mode:

		Freque	Conducted	Tune Up	Max Tune	Max Tune		
Modulation	СН	ncy	Power	Power	Up Power	Up Power	Result	Limit
		(MHz)	(dBm)	(dBm)	(dBm)	(mW)		
GFSK	Low	2402	1.337	1±1	2	1.585	0.49	3
	Mid	2441	1.477	1±1	2	1.585	0.50	3
	High	2480	1.469	1±1	2	1.585	0.50	3
π /4 DQPSK	Low	2402	1.482	1±1	2	1.585	0.49	3
	Mid	2441	1.428	1±1	2	1.585	0.50	3
	High	2480	1.423	1±1	2	1.585	0.50	3
8-DPSK	Low	2402	1.479	1±1	2	1.585	0.49	3
	Mid	2441	1.332	1±1	2	1.585	0.50	3
	High	2480	1.295	1±1	2	1.585	0.50	3

Result: Compliance

No SAR measurement is required.