

<b>Prüfbericht-Nr.:</b> Test report no.:	<b>CN23WNQ4 001</b>	<b>Auftrags-Nr.:</b> Order no.:	<b>168454514</b>	Seite 1 von 22 Page 1 of 22
<b>Kunden-Referenz-Nr.:</b> Client reference no.:	N/A	<b>Auftragsdatum:</b> Order date:	2023-11-08	
<b>Auftraggeber:</b> Client:	<b>ARKON ELECTRONICS (HUIZHOU) CO., LIMITED</b> NO.4 Taihao Road, High-tech Industrial Park, Sandong Town, Huicheng District, Huizhou, Guangdong, China			
<b>Prüfgegenstand:</b> Test item:	Foldable Bluetooth Stereo Noise Reduction Headphone			
<b>Bezeichnung / Typ-Nr.:</b> Identification / Type no.:	BN982, APOLLO MAX, ANC033 (Trademark: ARKON, ARTISTE, DAYSNEW, Reeder, ReeDer, REEDER, Avantree)			
<b>Auftrags-Inhalt:</b> Order content:	Test Report			
<b>Prüfgrundlage:</b> Test specification:	FCC CFR Title 47, Part 15, Subpart C, Section 15.247			
<b>Wareneingangsdatum:</b> Date of sample receipt:	2023-11-01	Please refer to Photo Document		
<b>Prüfmuster-Nr.:</b> Test sample no.:	HS231102-001-002 HS231102-001-003			
<b>Prüfzeitraum:</b> Testing period:	2023-11-07 - 2023-11-23			
<b>Ort der Prüfung:</b> Place of testing:	Hwa-Hsing (Dongguan) Testing Co., Ltd.			
<b>Prüflaboratorium:</b> Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
<b>Prüfergebnis*:</b> Test result*:	Pass			
<b>geprüft von:</b> tested by:	<u>X Breeze Jiang</u>	<b>genehmigt von:</b> authorized by:	<u>X Bell Hu</u>	
<b>Datum:</b> Date: 2023-12-27	Signed by: Breeze Jiang	<b>Ausstellungsdatum:</b> Issue date: 2023-12-27	Signed by: Bell Hu	
<b>Stellung / Position:</b>	Sachverständige(r)/Expert	<b>Stellung / Position:</b>	Sachverständige(r)/Expert	
<b>Sonstiges / Other:</b>	FCC ID: 2APBSBN982-001R			
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
<p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b></p> <p><i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>				

v05

Prüfbericht-Nr.: CN23WNQ4 001  
Test report no.:

Seite 2 von 22  
Page 2 of 22

**Anmerkungen**  
*Remarks*

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

## ***Test Summary***

**5.1.1 ANTENNA REQUIREMENT**

*RESULT: Pass*

**5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER**

*RESULT: Pass*

**5.1.3 CONDUCTED POWER SPECTRAL DENSITY**

*RESULT: Pass*

**5.1.4 6dB BANDWIDTH**

*RESULT: Pass*

**5.1.5 99% BANDWIDTH**

*RESULT: Pass*

**5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH**

*RESULT: Pass*

**5.1.7 RADIATED SPURIOUS EMISSION**

*RESULT: Pass*

**5.1.8 CONDUCTED EMISSION ON AC MAINS**

*RESULT: Pass*

## Contents

<b>1</b>	<b>GENERAL REMARKS .....</b>	<b>5</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>5</b>
<b>2</b>	<b>TEST SITES.....</b>	<b>6</b>
<b>2.1</b>	<b>TEST FACILITIES.....</b>	<b>6</b>
<b>2.2</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS .....</b>	<b>6</b>
<b>2.3</b>	<b>TRACEABILITY.....</b>	<b>7</b>
<b>2.4</b>	<b>CALIBRATION .....</b>	<b>7</b>
<b>2.5</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>7</b>
<b>2.6</b>	<b>LOCATION OF ORIGINAL DATA .....</b>	<b>7</b>
<b>2.7</b>	<b>STATUS OF FACILITY USED FOR TESTING.....</b>	<b>8</b>
<b>3</b>	<b>GENERAL PRODUCT INFORMATION.....</b>	<b>9</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>9</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>9</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES .....</b>	<b>10</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS.....</b>	<b>10</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS.....</b>	<b>10</b>
<b>4</b>	<b>TEST SET-UP AND OPERATION MODES .....</b>	<b>11</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION.....</b>	<b>11</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>11</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....</b>	<b>11</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....</b>	<b>11</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>12</b>
<b>5</b>	<b>TEST RESULTS.....</b>	<b>14</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES.....</b>	<b>14</b>
<b>5.1.1</b>	<i>Antenna Requirement.....</i>	<b>14</b>
<b>5.1.2</b>	<i>Maximum Peak Conducted Output Power.....</i>	<b>15</b>
<b>5.1.3</b>	<i>Conducted Power Spectral Density.....</i>	<b>16</b>
<b>5.1.4</b>	<i>6dB Bandwidth .....</i>	<b>17</b>
<b>5.1.5</b>	<i>99% Bandwidth .....</i>	<b>18</b>
<b>5.1.6</b>	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth .....</i>	<b>19</b>
<b>5.1.7</b>	<i>Radiated Spurious Emission.....</i>	<b>20</b>
<b>5.1.8</b>	<i>Conducted Emission.....</i>	<b>21</b>
<b>6</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP.....</b>	<b>22</b>
<b>7</b>	<b>LIST OF TABLES .....</b>	<b>22</b>

# 1 General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of Bluetooth Low Energy

Appendix B: Photographs of the Test Set-up

## 2 Test Sites

### 2.1 Test Facilities

**Hwa-Hsing (Dongguan) Testing Co., Ltd.**

No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China

FCC Accreditation Designation No.: 915896

### 2.2 List of Test and Measurement Instruments

**Table 1: List of Test and Measurement Equipment**

<b>Radiated emission below 30MHz:</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
EMI Test Receiver	Rohde&Schwarz	ESPI 7	101978	2023-12-27
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	HS-2018037	2026-03-12**
Test software	FARAD	FARAD	EZ_EMCV1.1.4. 2	N/A
Loop Antenna	EMCI	HLA 6121	45745	2024-08-18
Preamplifier	EMCI	EMC001340	980201	2024-08-18
<b>Frequency Range below 1GHz:</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
EMI Test Receiver	Rohde&Schwarz	ESPI 7	101978	2023-12-27
Broadband antenna	Schwarzbeck	VULB 9168	00937	2024-08-18
Signal Amplifier	Com-power	PAM-103	18020051	2024-08-06
Attenuator	Rohde&Schwarz	TS2GA-6dB	18101101	N/A
Test software	FARAD	FARAD	EZ_EMCV1.1.4. 2	N/A
<b>Frequency Range 1-18GHz:</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
Horn Antenna	Schwarzbeck	BBHA 9170	979	2024-05-03*
Broadband Coaxial Preamplifier	Schwarzbeck	BBV 9718	25	2024-08-06
Spectrum	Rohde&Schwarz	FSV40-N	101783	2023-12-27
<b>AC Line Conducted Emission</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Until</b>
EMI Test Receiver(10kHz~7GHz)	R&S	ESR 7	100962	2023-12-27
2 Line V-Network LISN	R&S	ENV216	3560.6550.15	2023-12-27
Test software	FARAD	EZ EMC V1.1.4.2	N/A	N/A

RF Conducted test system				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Spectrum	Keysight	N9020A	MY51240612	2024-08-06
Power Meter 10Hz~18GHz	Tonscend	JS0806-2	188060126	2024-08-06
Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101783	2023-12-27
Signal generator	Keysight	E4421	GB40051020	2024-03-15
Universal Switch Control Unit	Rohde&Schwarz	CMW500	12010002k50	2023-12-27
Humidity tester	Jingchuang	GSP-8A	CMA22B000592	2024-01-15
Test Software	Tonscend	JS0806-2	NA	NA

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

**Table 2: Measurement Uncertainty**

Parameter	Uncertainty
Radio Frequency	$\pm 1.06 \times 10^{-8}$
RF Power (conducted)	$\pm 1.371$ dB
Radiated Emission of Transmitter, valid up to 26.5 GHz	$\pm 3.294$ dB
Radiated Emission of Receiver, valid up to 26.5 GHz	$\pm 3.294$ dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	$\pm 2.66$ dB
Temperature	$\pm 1$ °C
Humidity	$\pm 5$ %
Voltage (DC)	$\pm 1$ %
Voltage (AC, <10kHz)	$\pm 2$ %

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

## 2.7 Status of Facility Used for Testing

The **Hwa-Hsing (Dongguan) Testing Co., Ltd.** Test facility located at No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.



## 3 General Product Information

### 3.1 Product Function and Intended Use

The EUT is a Foldable Bluetooth Stereo Noise Reduction Headphone, which supports Bluetooth low energy wireless technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

### 3.2 Ratings and System Details

**Table 3: Technical Specification of EUT**

General Information of EUT	Value
Kind of Equipment:	Foldable Bluetooth Stereo Noise Reduction Headphone
Type Designation:	BN982, APOLLO MAX, ANC033
Trademark:	ARKON, ARTISTE, DAYSNEW, Reeder, ReeDer, REEDER, Avantree
FCC ID:	2APBSBN982-001R
Operating Voltage:	DC 5V From USB port; or DC 3.7V from Battery
Operating Temperature Range:	+0 °C ~ +40 °C
Technical Specification of Bluetooth LE	
Frequency Range:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Channel Number:	40 channels
Channel Separation:	2 MHz
Data rate:	1Mbps
Antenna Type:	PCB Layout Antenna
Antenna Gain:	1.89 dBi (Provided by the Client)

**Table 4: RF Channel and Frequency of Bluetooth Low Energy**

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
<b>00</b>	<b>2402.00</b>	10	2422.00	20	2442.00	30	2462.00
01	2404.00	11	2424.00	21	2444.00	31	2464.00
02	2406.00	12	2426.00	22	2446.00	32	2466.00
03	2408.00	13	2428.00	23	2448.00	33	2468.00
04	2410.00	14	2430.00	24	2450.00	34	2470.00
05	2412.00	15	2432.00	25	2452.00	35	2472.00
06	2414.00	16	2434.00	26	2454.00	36	2474.00
07	2416.00	17	2436.00	27	2456.00	37	2476.00
08	2418.00	18	2438.00	28	2458.00	38	2478.00
09	2420.00	<b>19</b>	<b>2440.00</b>	29	2460.00	<b>39</b>	<b>2480.00</b>

Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2480 MHz for Bluetooth LE.

### 3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth LE transmitting mode
  - 1) Low Channel
  - 2) Middle Channel
  - 3) High Channel
- B. On, Normal Operating Mode
- C. Charging
- D. Off

### 3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

### 3.5 Submitted Documents

- Bill of Material
- PCB Layout
- Photo Document
- Circuit Diagram
- Instruction Manual
- Rating Label

## 4 Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

**Radio Spectrum:** The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013.

According to clause 3.1, all tests were performed on model BN982 in this report.

### 4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Remark
Laptop	Lenovo	ThinkPad X280	SL10P97665	SL10P97665
Mobile Phone	Samsung	Samsung Galaxy S4	N/A	N/A
Adapter	UGREEN	CD231	N/A	AC input: 100-240V, 50/60Hz, 800mA max DC output: 5V/3A

### 4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

## 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



## 5 Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**RESULT:**

**Pass**

**Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has a PCB Layout Antenna, the gain of antenna is 1.89 dBi, which that permanent attachment and no consideration of replacement.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

## 5.1.2 Maximum Peak Conducted Output Power

**RESULT:**
**Pass**
**Test Specification**

Test standard : FCC Part 15.247(b)(3)  
 Basic standard : ANSI C63.10: 2013  
 Limits : 1.0 Watts  
 Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2023-11-12 to 2023-11-22  
 Input voltage : DC 3.7V from fully battery  
 Operation mode : A  
 Test channel : Low / Middle / High  
 Ambient temperature : 24.3 °C  
 Relative humidity : 56 %  
 Atmospheric pressure : 101 kPa

**Table 6: Test Result of Maximum Peak Conducted Output Power**

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
Bluetooth LE (1 Mbps)	2402	2.64	0.0018	< 1.0
	2440	1.83	0.0015	
	2480	1.84	0.0015	
<b>Max. Measured Value</b>		2.64	0.0018	

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): 1.89 dBi

### 5.1.3 Conducted Power Spectral Density

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(e)
Basic standard	:	ANSI C63.10: 2013
Limits	:	< 8 dBm / 3kHz
Kind of test site	:	Shielded Room

**Test Setup**

Date of testing	:	2023-11-14
Input voltage	:	DC 3.7V from fully battery
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.3 °C
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.



### 5.1.4 6dB Bandwidth

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(a)(2)
Basic standard	:	ANSI C63.10: 2013
Limits	:	> 500 KHz
Kind of test site	:	Shielded Room

**Test Setup**

Date of testing	:	2023-11-22
Input voltage	:	DC 3.7V from fully battery
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.3 °C
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: **CN23WNQ4 001**  
Test Report No.:Seite 18 von 22  
Page 18 of 22

### 5.1.5 99% Bandwidth

**RESULT:****Pass****Test Specification**

Test standard : RSS-Gen Clause 6.7  
Basic standard : ANSI C63.10: 2013  
Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2023-11-22  
Input voltage : DC 3.7V from fully battery  
Operation mode : A  
Test channel : Low / Middle / High  
Ambient temperature : 24.3 °C  
Relative humidity : 56 %  
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A.

## 5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(d)
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2023-11-22
Input voltage	: DC 3.7V from fully battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24.3 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix A.

## 5.1.7 Radiated Spurious Emission

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d)
Kind of test site	:	3m Semi-anechoic Chamber

**Test Setup**

Date of testing	:	2023-11-20
Input voltage	:	DC 3.7V from fully battery
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

**Remark:**

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN23WNQ4 001  
Test Report No.:Seite 21 von 22  
Page 21 of 22

### 5.1.8 Conducted Emission on AC Mains

**RESULT:****Pass****Test Specification**

Test standard : FCC Part 15.207(a)

Basic standard : ANSI C63.10:2013

Frequency range : 0.15 – 30MHz

Classification : Class B

Limits : FCC Part 15.207(a)

Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2023-11-23

Input voltage : DC 5V by Adapter (Adapter input AC 120V/60Hz)

Operation mode : C

Earthing : Not connected

Ambient temperature : 22 °C

Relative humidity : 64 %

Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A.

## 6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

## 7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: Technical Specification of EUT.....	9
Table 4: RF Channel and Frequency of Bluetooth Low Energy.....	10
Table 5: List of Accessories and Auxiliary Equipment.....	11
Table 6: Test Result of Maximum Peak Conducted Output Power.....	15