




TEST REPORT

FCC ID	2APD3TS100	
Test Report No	TCT221216E026	
Date of issue	Jan. 09, 2023	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name	SHEN ZHEN TOMSTAR TECHNOLOGY CO., LTD.	
Address	Room 2110-2116, huafeng international building, NO.4018 BaoAn Blvd, Shenzhen, China.	
Manufacturer's name ...	SHEN ZHEN TOMSTAR TECHNOLOGY CO., LTD.	
Address	Room 2110-2116, huafeng international building, NO.4018 BaoAn Blvd, Shenzhen, China.	
Standard(s)	FCC CFR Title 47 Part 15 Subpart C Section 15.247 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013	
Product Name	Smart Watch	
Trade Mark	N/A	
Model/Type reference	TS100, RY67, TS38 pro, TS38max, TS38E, TS82, TS93, TS99, TS85, TS83, TS96, TS57, TS76E, TS63, TS59, TS89	
Rating(s)	Rechargeable Li-ion Battery DC 3.7V	
Date of receipt of test item	Dec. 16, 2022	
Date (s) of performance of test	Dec. 15, 2022 - Jan. 09, 2023	
Tested by (+signature) ...	Ronaldo LUO	
Check by (+signature)	Beryl ZHAO	
Approved by (+signature):	Tomsin	



General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Operation Frequency	3
2. Test Result Summary	4
3. General Information.....	5
3.1. Test environment and mode.....	5
3.2. Description of Support Units.....	5
4. Facilities and Accreditations	6
4.1. Facilities	6
4.2. Location	6
4.3. Measurement Uncertainty.....	6
5. Test Results and Measurement Data	7
5.1. Antenna requirement	7
5.2. Conducted Emission.....	8
5.3. Conducted Output Power	12
5.4. Emission Bandwidth	13
5.5. Power Spectral Density.....	14
5.6. Conducted Band Edge and Spurious Emission Measurement	15
5.7. Radiated Spurious Emission Measurement.....	17
Appendix A: Test Result of Conducted Test	
Appendix B: Photographs of Test Setup	
Appendix C: Photographs of EUT	

1. General Product Information

1.1. EUT description

Product Name.....:	Smart Watch
Model/Type reference.....:	TS100
Sample Number.....:	TCT221216E026-0101
Bluetooth Version	5.1
Operation Frequency	2402MHz~2480MHz
Channel Separation.....:	2MHz
Data Rate.....:	LE 1M PHY, LE 2M PHY
Number of Channel	40
Modulation Type	GFSK
Antenna Type.....:	Monopole Antenna
Antenna Gain.....:	0dBi
Rating(s).....:	Rechargeable Li-ion Battery DC 3.7V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

No.	Model No.	Tested with
1	TS100	<input checked="" type="checkbox"/>
Other models	RY67, TS38 pro, TS38max, TS38E, TS82, TS93, TS99, TS85, TS83, TS96, TS57, TS76E, TS63, TS59, TS89	<input type="checkbox"/>

Note: TS100 is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names. So the test data of TS100 can represent the remaining models.

1.3. Operation Frequency

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
...
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Remark: Channel 0, 19 & 39 have been tested.

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3)	PASS
6dB Emission Bandwidth	§15.247 (a)(2)	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d)	PASS
Spurious Emission	§15.205/§15.209	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.
5. After pre-testing the two earphones, the two earphones are left and right ears respectively; we found that the left earphone is the worst case, so the results are recorded in this report.

3. General Information

3.1. Test environment and mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	24.0 °C	25.0 °C
Humidity:	52 % RH	55 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar
Test Software:		
Software Information:	RTLBTAPP	
Power Level:	5	
Test Mode:		
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations with Fully-charged battery.	
The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case(Z axis) are shown in Test Results of the following pages.		

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339


4.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
E.U.T Antenna:	Monopole Antenna
<p>The antenna is Monopole Antenna which permanently attached, and the best case gain of the antenna is 0dBi.</p>	
	

5.2. Conducted Emission

5.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Charging + Transmitting Mode														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Result:	PASS														


5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI3	100898	Jul. 03, 2023
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Feb. 24, 2023
Line-5	TCT	CE-05	/	Jul. 03, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1545	23.78	10.12	33.90	65.75	-31.85	QP	P	
2	0.1545	8.36	10.12	18.48	55.75	-37.27	AVG	P	
3	0.2445	19.31	10.17	29.48	61.94	-32.46	QP	P	
4	0.2445	5.24	10.17	15.41	51.94	-36.53	AVG	P	
5	0.6270	18.48	10.26	28.74	56.00	-27.26	QP	P	
6 *	0.6270	18.31	10.26	28.57	46.00	-17.43	AVG	P	
7	0.9465	-0.01	10.26	10.25	46.00	-35.75	AVG	P	
8	0.9510	12.88	10.26	23.14	56.00	-32.86	QP	P	
9	1.8330	3.52	10.29	13.81	46.00	-32.19	AVG	P	
10	1.8555	15.05	10.29	25.34	56.00	-30.66	QP	P	
11	11.7915	17.12	10.24	27.36	60.00	-32.64	QP	P	
12	12.0300	4.97	10.21	15.18	50.00	-34.82	AVG	P	

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1545	24.23	10.20	34.43	65.75	-31.32	QP	P	
2	0.1556	5.86	10.20	16.06	55.70	-39.64	AVG	P	
3 *	0.6270	20.92	10.24	31.16	56.00	-24.84	QP	P	
4	0.6270	10.66	10.24	20.90	46.00	-25.10	AVG	P	
5	0.9420	13.82	10.25	24.07	56.00	-31.93	QP	P	
6	0.9420	-1.37	10.25	8.88	46.00	-37.12	AVG	P	
7	1.6575	-1.46	10.24	8.78	46.00	-37.22	AVG	P	
8	1.6980	14.50	10.24	24.74	56.00	-31.26	QP	P	
9	2.7239	-0.96	10.27	9.31	46.00	-36.69	AVG	P	
10	2.7420	13.68	10.27	23.95	56.00	-32.05	QP	P	
11	11.8005	15.60	10.21	25.81	60.00	-34.19	QP	P	
12	11.8860	7.05	10.21	17.26	50.00	-32.74	AVG	P	

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)


Q.P. =Quasi-Peak

AVG =average

** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*

5.4. Emission Bandwidth

5.4.1. Test Specification


Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB 558074 D01 v05r02
Limit:	>500kHz
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Refer to item 3.1
Test Procedure:	<ol style="list-style-type: none"> 1. Set to the maximum power setting and enable the EUT transmit continuously. 2. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 3. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

Name	Manufacturer	Model No.	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.6. Conducted Band Edge and Spurious Emission Measurement

5.6.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB 558074 D01 v05r02
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Refer to item 3.1
Test Procedure:	<ol style="list-style-type: none"> 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS


5.6.2. Test Instruments

Name	Manufacturer	Model No.	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/


5.7. Radiated Spurious Emission Measurement

5.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209					
Test Method:	ANSI C63.10: 2013					
Frequency Range:	9 kHz to 25 GHz					
Measurement Distance:	3 m					
Antenna Polarization:	Horizontal & Vertical					
Operation mode:	Refer to item 3.1					
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark	
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
		Peak	1MHz	10Hz	Average Value	
Limit:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)			
	0.009-0.490	2400/F(KHz)	300			
	0.490-1.705	24000/F(KHz)	30			
	1.705-30	30	30			
	30-88	100	3			
	88-216	150	3			
	216-960	200	3			
	Above 960	500	3			
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector		
	Above 1GHz	500	3	Average		
	5000	3	Peak			
Test setup:	For radiated emissions below 30MHz					
	<p>Distance = 3m</p> <p>0.8m</p> <p>Turn table</p> <p>1m</p> <p>Ground Plane</p> <p>Computer</p> <p>Pre-Amplifier</p> <p>Receiver</p>					
	30MHz to 1GHz					



Above 1GHz



Test Procedure:

1. For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final

	<p>measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>4. Use the following spectrum analyzer settings:</p> <p>(1) Span shall wide enough to fully capture the emission being measured;</p> <p>(2) Set RBW=120 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;</p> <p>(3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement.</p> <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
Test mode:	Refer to section 4.1 for details
Test results:	PASS


5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESIB7	100197	Jul. 03, 2023
Spectrum Analyzer	R&S	FSQ40	200061	Jul. 03, 2023
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Feb. 24, 2023
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Feb. 24, 2023
Pre-amplifier	HP	8447D	2727A05017	Jul. 03, 2023
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 11, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 05, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 05, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Apr. 10, 2023
Antenna Mast	Keleto	RE-AM	/	/
Coaxial cable	SKET	RC-18G-N-M	/	Feb. 24, 2024
Coaxial cable	SKET	RC_40G-K-M	/	Feb. 24, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.7.3. Test Data


Please refer to following diagram for individual
Below 1GHz

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	30.2111	33.09	-15.71	17.38	40.00	-22.62	QP	P
2	45.8553	27.89	-13.41	14.48	40.00	-25.52	QP	P
3	148.9625	44.74	-27.26	17.48	43.50	-26.02	QP	P
4	282.9852	45.99	-26.55	19.44	46.00	-26.56	QP	P
5	437.1199	46.85	-25.64	21.21	46.00	-24.79	QP	P
6 *	922.5157	49.61	-24.33	25.28	46.00	-20.72	QP	P

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	30.4238	39.09	-18.04	21.05	40.00	-18.95	QP	P
2	52.7600	34.04	-16.75	17.29	40.00	-22.71	QP	P
3	84.4054	44.19	-27.86	16.33	40.00	-23.67	QP	P
4	159.7844	44.51	-27.20	17.31	43.50	-26.19	QP	P
5	435.5898	45.02	-25.64	19.38	46.00	-26.62	QP	P
6	593.0497	48.09	-25.16	22.93	46.00	-23.07	QP	P

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low), and the worst case Mode (Lowest channel) was submitted only.

3. Freq. = Emission frequency in MHz

Measurement (dBuV/m) = Reading level (dBuV) + Corr. Factor (dB)

Correction Factor = Antenna Factor + Cable loss – Pre-amplifier

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Measurement (dBuV/m) – Limits (dBuV/m)

Any value more than 10dB below limit have not been specifically reported

* is meaning the worst frequency has been tested in the test frequency range

Test Result of Radiated Spurious at Band edges

Lowest channel 2402:

1Mbps

Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	38.91	-5.05	33.86	74.00	-40.14	peak	P
2	2390.000	39.76	-4.97	34.79	74.00	-39.21	peak	P
3 *	2400.000	57.94	-4.96	52.98	74.00	-21.02	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	37.37	-5.05	32.32	74.00	-41.68	peak	P
2	2390.000	37.13	-4.97	32.16	74.00	-41.84	peak	P
3 *	2400.000	57.45	-4.96	52.49	74.00	-21.51	peak	P

2Mbps

Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	38.51	-5.05	33.46	74.00	-40.54	peak	P
2	2390.000	38.45	-4.97	33.48	74.00	-40.52	peak	P
3 *	2400.000	57.42	-4.96	52.46	74.00	-21.54	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	35.84	-5.05	30.79	74.00	-43.21	peak	P
2	2390.000	36.49	-4.97	31.52	74.00	-42.48	peak	P
3 *	2400.000	55.98	-4.96	51.02	74.00	-22.98	peak	P

Highest channel 2480:

1Mbps

Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2483.500	44.57	-4.89	39.68	74.00	-34.32	peak	P
2	2500.000	40.03	-4.87	35.16	74.00	-38.84	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2483.500	44.44	-6.29	38.15	74.00	-35.85	peak	P
2	2500.000	40.53	-6.27	34.26	74.00	-39.74	peak	P

2Mbps

Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2483.500	46.75	-4.89	41.86	74.00	-32.14	peak	P
2	2500.000	38.36	-4.87	33.49	74.00	-40.51	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2483.500	44.35	-4.89	39.46	74.00	-34.54	peak	P
2	2500.000	35.85	-4.87	30.98	74.00	-43.02	peak	P

Above 1GHz

1Mbps

Low channel: 2402 MHz

Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3516.973	66.13	-29.92	36.21	74.00	-37.79	peak	P
2	5240.789	66.82	-28.03	38.79	74.00	-35.21	peak	P
3	8507.077	68.76	-25.79	42.97	74.00	-31.03	peak	P
4	10652.230	67.37	-25.13	42.24	74.00	-31.76	peak	P
5	12255.224	67.66	-22.91	44.75	74.00	-29.25	peak	P
6 *	16490.649	67.99	-20.68	47.31	74.00	-26.69	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	4580.374	63.30	-29.90	33.40	74.00	-40.60	peak	P
2	6507.536	65.98	-26.08	39.90	74.00	-34.10	peak	P
3	8443.386	66.62	-25.83	40.79	74.00	-33.21	peak	P
4	10083.014	68.70	-24.74	43.96	74.00	-30.04	peak	P
5	12717.119	67.85	-22.45	45.40	74.00	-28.60	peak	P
6 *	15217.425	70.62	-21.45	49.17	74.00	-24.83	peak	P

Middle channel: 2440 MHz

Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	4112.248	65.10	-30.47	34.63	74.00	-39.37	peak	P
2	5694.073	67.49	-27.26	40.23	74.00	-33.77	peak	P
3	8620.940	67.85	-25.69	42.16	74.00	-31.84	peak	P
4	10710.890	67.63	-25.00	42.63	74.00	-31.37	peak	P
5	12505.705	67.72	-22.79	44.93	74.00	-29.07	peak	P
6 *	14668.956	69.25	-21.54	47.71	74.00	-26.29	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3374.572	64.54	-29.89	34.65	74.00	-39.35	peak	P
2	4359.491	64.11	-30.29	33.82	74.00	-40.18	peak	P
3	6309.358	64.36	-26.31	38.05	74.00	-35.95	peak	P
4	8736.326	66.38	-25.58	40.80	74.00	-33.20	peak	P
5	9898.209	66.43	-24.58	41.85	74.00	-32.15	peak	P
6 *	16725.865	69.29	-19.81	49.48	74.00	-24.52	peak	P

High channel: 2480 MHz
Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	6447.624	68.89	-26.14	42.75	74.00	-31.25	peak	P
2	8315.028	70.39	-25.92	44.47	74.00	-29.53	peak	P
3	10596.954	69.48	-25.23	44.25	74.00	-29.75	peak	P
4	12244.602	67.80	-22.93	44.87	74.00	-29.13	peak	P
5	15800.096	68.76	-21.90	46.86	74.00	-27.14	peak	P
6 *	16988.970	67.58	-18.82	48.76	74.00	-25.24	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5030.044	64.31	-28.37	35.94	74.00	-38.06	peak	P
2	6367.985	67.54	-26.24	41.30	74.00	-32.70	peak	P
3	7773.486	69.61	-26.20	43.41	74.00	-30.59	peak	P
4	9685.947	69.49	-24.52	44.97	74.00	-29.03	peak	P
5	12831.579	70.06	-22.27	47.79	74.00	-26.21	peak	P
6 *	16301.090	69.45	-20.95	48.50	74.00	-25.50	peak	P

2Mbps

Low channel: 2402 MHz
Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3344.470	65.37	-29.90	35.47	74.00	-38.53	peak	P
2	4953.576	64.58	-28.58	36.00	74.00	-38.00	peak	P
3	6358.789	67.61	-26.25	41.36	74.00	-32.64	peak	P
4	7062.213	65.72	-25.73	39.99	74.00	-34.01	peak	P
5	8409.289	67.37	-25.85	41.52	74.00	-32.48	peak	P
6 *	14563.341	70.47	-21.86	48.61	74.00	-25.39	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3453.511	63.07	-29.90	33.17	74.00	-40.83	peak	P
2	5469.841	63.98	-27.67	36.31	74.00	-37.69	peak	P
3	6989.109	68.23	-25.66	42.57	74.00	-31.43	peak	P
4	10801.047	69.55	-24.82	44.73	74.00	-29.27	peak	P
5	12954.555	68.91	-22.07	46.84	74.00	-27.16	peak	P
6 *	15573.397	69.39	-22.48	46.91	74.00	-27.09	peak	P

Middle channel: 2440 MHz

Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2891.926	68.32	-30.15	38.17	74.00	-35.83	peak	P
2	3502.771	67.85	-29.90	37.95	74.00	-36.05	peak	P
3	7080.608	70.55	-25.75	44.80	74.00	-29.20	peak	P
4	10083.014	72.20	-24.74	47.46	74.00	-26.54	peak	P
5	14370.993	71.51	-21.98	49.53	74.00	-24.47	peak	P
6 *	17984.399	70.73	-18.72	52.01	74.00	-21.99	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	1050.060	68.75	-29.65	39.10	74.00	-34.90	peak	P
2	2891.926	68.32	-30.15	38.17	74.00	-35.83	peak	P
3	5720.466	64.23	-27.21	37.02	74.00	-36.98	peak	P
4	8499.703	71.95	-25.79	46.16	74.00	-27.84	peak	P
5	14370.993	71.51	-21.98	49.53	74.00	-24.47	peak	P
6 *	17984.399	70.73	-18.72	52.01	74.00	-21.99	peak	P

High channel: 2480 MHz

Horizontal:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2891.926	68.32	-30.15	38.17	74.00	-35.83	peak	P
2	3565.076	66.73	-29.99	36.74	74.00	-37.26	peak	P
3	6682.902	70.62	-25.92	44.70	74.00	-29.30	peak	P
4	8680.950	70.11	-25.63	44.48	74.00	-29.52	peak	P
5	15235.029	71.24	-21.52	49.72	74.00	-24.28	peak	P
6 *	17984.399	70.23	-18.72	51.51	74.00	-22.49	peak	P

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2891.926	68.32	-30.15	38.17	74.00	-35.83	peak	P
2	3502.771	66.85	-29.90	36.95	74.00	-37.05	peak	P
3	6682.902	68.62	-25.92	42.70	74.00	-31.30	peak	P
4	8680.950	68.61	-25.63	42.98	74.00	-31.02	peak	P
5	11053.709	70.65	-24.43	46.22	74.00	-27.78	peak	P
6 *	14370.993	71.51	-21.98	49.53	74.00	-24.47	peak	P

Note:


1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Appendix A: Test Result of Conducted Test


Maximum Conducted Output Power

Condition	Antenna	Rate	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1Mbps	2402	-3.87	0.41	1000	Pass
NVNT	ANT1	1Mbps	2440.00	2.69	1.86	1000	Pass
NVNT	ANT1	1Mbps	2480	3.96	2.49	1000	Pass
NVNT	ANT1	2Mbps	2402	-3.97	0.40	1000	Pass
NVNT	ANT1	2Mbps	2440.00	2.69	1.86	1000	Pass
NVNT	ANT1	2Mbps	2480	4.00	2.51	1000	Pass


Peak_Output_Power_BLE_1Mbps_2402




Peak_Output_Power_BLE_1Mbps_2440




Peak Output Power_BLE_1Mbps_2480




Peak Output Power_BLE_2Mbps_2402



Peak Output Power_BLE_2Mbps_2440




Peak Output Power_BLE_2Mbps_2480




-6dB Bandwidth

Condition	Antenna	Rate	Frequency (MHz)	-6dB BW(kHz)	limit(kHz)	Result
NVNT	ANT1	1Mbps	2402	670.04	500	Pass
NVNT	ANT1	1Mbps	2440.00	669.24	500	Pass
NVNT	ANT1	1Mbps	2480	670.04	500	Pass
NVNT	ANT1	2Mbps	2402	1176.59	500	Pass
NVNT	ANT1	2Mbps	2440.00	1171.00	500	Pass
NVNT	ANT1	2Mbps	2480	1173.69	500	Pass


-6dB Bandwidth BLE 1Mbps 2402




-6dB Bandwidth BLE 1Mbps 2440





-6dB Bandwidth_BLE_1Mbps_2480





-6dB Bandwidth_BLE_2Mbps_2402









Occupied Channel Bandwidth

Condition	Antenna	Rate	Frequency (MHz)	99% BW (MHz)
NVNT	ANT1	1Mbps	2402	1.042
NVNT	ANT1	1Mbps	2440.00	1.040
NVNT	ANT1	1Mbps	2480	1.040
NVNT	ANT1	2Mbps	2402	2.065
NVNT	ANT1	2Mbps	2440.00	2.059
NVNT	ANT1	2Mbps	2480	2.061











Maximum Power Spectral Density Level

Condition	Antenna	Rate	Frequency (MHz)	Power Spectral Density(dBm)	Limit(dBm/3kHz)	Result
NVNT	ANT1	1Mbps	2402	-20.40	8	Pass
NVNT	ANT1	1Mbps	2440.00	-13.78	8	Pass
NVNT	ANT1	1Mbps	2480	-12.35	8	Pass
NVNT	ANT1	2Mbps	2402	-22.83	8	Pass
NVNT	ANT1	2Mbps	2440.00	-16.34	8	Pass
NVNT	ANT1	2Mbps	2480	-14.76	8	Pass







Bandedge

Condition	Antenna	Rate	TX_Frequency (MHz)	Max. Mark Frequency (MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	1Mbps	2402	2386.66	-47.90	-24.46	Pass
NVNT	ANT1	1Mbps	2480	2489.00	-48.01	-16.51	Pass
NVNT	ANT1	2Mbps	2402	2399.97	-36.59	-25.21	Pass
NVNT	ANT1	2Mbps	2480	2490.88	-48.63	-17.14	Pass


1_Reference_Level_BLE_1Mbps_2402




2_Bandedge_BLE_1Mbps_2402




1_Reference_Level_BLE_1Mbps_2480




2_Bandedge_BLE_1Mbps_2480



1_Reference_Level_BLE_2Mbps_2402




2_Bandedge_BLE_2Mbps_2402



1_Reference_Level_BLE_2Mbps_2480




2_Bandedge_BLE_2Mbps_2480




Spurious Emission

Condition	Antenna	Rate	TX_Frequency(MHz)	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1Mbps	2402	-36.69	-24.46	Pass
NVNT	ANT1	1Mbps	2440.00	-35.95	-17.75	Pass
NVNT	ANT1	1Mbps	2480	-36.35	-16.51	Pass
NVNT	ANT1	2Mbps	2402	-35.82	-25.21	Pass
NVNT	ANT1	2Mbps	2440.00	-36.15	-18.44	Pass
NVNT	ANT1	2Mbps	2480	-36.05	-17.14	Pass


1 Reference_Level_BLE_1Mbps_2402




2 Spurious Emission_BLE_1Mbps_2402




1_Reference_Level_BLE_1Mbps_2440




2_Spurious Emission_BLE_1Mbps_2440



1_Reference_Level_BLE_1Mbps_2480




2_Spurious_Emission_BLE_1Mbps_2480



1_Reference_Level_BLE_2Mbps_2402




2_Spurious Emission_BLE_2Mbps_2402



1_Reference_Level_BLE_2Mbps_2440




2_Spurious Emission_BLE_2Mbps_2440





1_Reference_Level_BLE_2Mbps_2480




2_Spurious Emission_BLE_2Mbps_2480




Appendix B: Photographs of Test Setup Radiated Emission



Conducted Emission




**Appendix C: Photographs of EUT
External Photos**














Internal Photos







*******END OF REPORT*******