

10623-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	7.25	73.11	20.09	0.46	130.0	± 9.6 %
		Y	7.10	72.60	19.72		130.0	
		Z	6.63	71.30	19.02		130.0	
10624-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	7.72	74.03	20.65	0.46	130.0	± 9.6 %
		Y	7.42	73.09	20.05		130.0	
		Z	7.58	73.78	20.36		130.0	
10625-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	10.18	79.67	23.30	0.46	130.0	± 9.6 %
		Y	9.57	78.23	22.53		130.0	
		Z	11.95	83.13	24.58		130.0	
10626-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	6.70	70.29	18.53	0.46	130.0	± 9.6 %
		Y	6.59	69.94	18.23		130.0	
		Z	6.69	70.46	18.54		130.0	
10627-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	8.60	75.50	21.17	0.46	130.0	± 9.6 %
		Y	8.25	74.56	20.59		130.0	
		Z	9.42	77.64	22.06		130.0	
10628-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	7.02	71.22	18.91	0.46	130.0	± 9.6 %
		Y	6.93	70.92	18.65		130.0	
		Z	6.94	71.13	18.77		130.0	
10629-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	8.10	74.24	20.50	0.46	130.0	± 9.6 %
		Y	7.84	73.49	20.01		130.0	
		Z	7.41	72.40	19.44		130.0	
10630-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	56.46	115.95	35.95	0.46	130.0	± 9.6 %
		Y	59.83	117.06	36.16		130.0	
		Z	57.52	115.75	35.56		130.0	
10631-AAB	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	20.91	95.04	29.34	0.46	130.0	± 9.6 %
		Y	16.92	90.27	27.42		130.0	
		Z	9.74	78.33	22.36		130.0	
10632-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	8.62	75.79	21.44	0.46	130.0	± 9.6 %
		Y	8.27	74.81	20.84		130.0	
		Z	9.19	77.33	22.04		130.0	
10633-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	9.22	77.24	21.98	0.46	130.0	± 9.6 %
		Y	8.73	75.99	21.26		130.0	
		Z	7.59	73.09	19.81		130.0	
10634-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	7.28	71.94	19.34	0.46	130.0	± 9.6 %
		Y	7.19	71.65	19.09		130.0	
		Z	7.97	74.33	20.52		130.0	
10635-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	6.73	69.99	18.12	0.46	130.0	± 9.6 %
		Y	6.70	69.90	17.97		130.0	
		Z	6.72	70.22	18.17		130.0	
10636-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	8.31	74.19	20.53	0.46	130.0	± 9.6 %
		Y	8.03	73.37	20.00		130.0	
		Z	8.09	73.61	20.11		130.0	
10637-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	12.10	82.45	24.39	0.46	130.0	± 9.6 %
		Y	11.52	81.29	23.76		130.0	
		Z	9.45	76.85	21.65		130.0	
10638-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	9.54	77.03	21.86	0.46	130.0	± 9.6 %
		Y	9.15	76.06	21.28		130.0	
		Z	9.77	77.57	21.97		130.0	

10639-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	8.41	74.14	20.46	0.46	130.0	± 9.6 %
		Y	8.18	73.51	20.02		130.0	
		Z	7.96	73.01	19.77		130.0	
10640-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	7.70	71.87	19.13	0.46	130.0	± 9.6 %
		Y	7.59	71.60	18.90		130.0	
		Z	10.04	78.18	22.25		130.0	
10641-AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	8.69	74.71	20.77	0.46	130.0	± 9.6 %
		Y	8.24	73.45	20.00		130.0	
		Z	8.46	74.17	20.36		130.0	
10642-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	8.18	73.36	20.17	0.46	130.0	± 9.6 %
		Y	7.94	72.66	19.69		130.0	
		Z	8.42	74.20	20.51		130.0	
10643-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	8.20	73.71	20.29	0.46	130.0	± 9.6 %
		Y	7.97	73.03	19.83		130.0	
		Z	7.82	72.74	19.67		130.0	
10644-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	16.21	88.92	27.10	0.46	130.0	± 9.6 %
		Y	14.24	85.93	25.76		130.0	
		Z	10.50	79.18	22.77		130.0	
10645-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	14.11	85.32	25.61	0.46	130.0	± 9.6 %
		Y	12.55	82.61	24.32		130.0	
		Z	9.49	76.17	21.23		130.0	
10646-AAF	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	59.89	132.23	44.21	9.30	60.0	± 9.6 %
		Y	66.17	134.23	44.31		60.0	
		Z	35.09	116.44	38.91		60.0	
10647-AAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	71.49	137.63	45.87	9.30	60.0	± 9.6 %
		Y	78.02	139.24	45.83		60.0	
		Z	39.53	120.17	40.16		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	1.03	67.02	12.57	0.00	150.0	± 9.6 %
		Y	1.06	67.17	12.86		150.0	
		Z	0.97	66.67	12.05		150.0	
10652-AAD	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	5.27	71.86	19.06	2.23	80.0	± 9.6 %
		Y	5.23	71.82	19.01		80.0	
		Z	5.33	71.84	18.78		80.0	
10653-AAD	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	5.85	71.50	19.40	2.23	80.0	± 9.6 %
		Y	5.80	71.45	19.32		80.0	
		Z	5.89	71.41	19.14		80.0	
10654-AAD	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	5.72	71.13	19.40	2.23	80.0	± 9.6 %
		Y	5.67	71.08	19.31		80.0	
		Z	5.79	71.05	19.16		80.0	
10655-AAE	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	5.82	71.33	19.52	2.23	80.0	± 9.6 %
		Y	5.77	71.27	19.43		80.0	
		Z	5.88	71.16	19.25		80.0	
10658-AAA	Pulse Waveform (200Hz, 10%)	X	10.37	82.93	21.06	10.00	50.0	± 9.6 %
		Y	11.27	84.88	21.48		50.0	
		Z	10.75	83.25	22.31		50.0	
10659-AAA	Pulse Waveform (200Hz, 20%)	X	9.52	82.62	19.51	6.99	60.0	± 9.6 %
		Y	11.30	85.59	20.35		60.0	
		Z	9.95	83.49	20.89		60.0	

10660-AAA	Pulse Waveform (200Hz, 40%)	X	8.99	83.77	18.32	3.98	80.0	± 9.6 %
		Y	13.99	89.75	20.15		80.0	
		Z	10.20	86.38	20.25		80.0	
10661-AAA	Pulse Waveform (200Hz, 60%)	X	100.00	84.64	10.47	2.22	100.0	± 9.6 %
		Y	100.00	85.27	11.37		100.0	
		Z	100.00	86.26	11.61		100.0	
10662-AAA	Pulse Waveform (200Hz, 80%)	X	100.00	99.15	17.30	0.97	120.0	± 9.6 %
		Y	100.00	104.58	19.59		120.0	
		Z	100.00	106.03	20.55		120.0	
10670-AAA	Bluetooth Low Energy	X	6.83	82.91	17.22	2.19	100.0	± 9.6 %
		Y	13.56	91.41	19.91		100.0	
		Z	9.06	87.64	19.73		100.0	

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.