



TEST REPORT

APPLICANT : Hot Pepper, Inc.
PRODUCT NAME : 4G Smart Phone
MODEL NAME : H5
BRAND NAME : Hot Pepper
FCC ID : 2APD4-P26A
STANDARD(S) : 47 CFR Part 15 Subpart B
TEST DATE : 2018-04-01 to 2018-05-04
ISSUE DATE : 2018-05-17

Tested by: Wu Junke
Wu Junke(Test Engineer)
Approved by: Andy Yeh
Andy Yeh(Technical Director)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information..... 3
 - 1.1. Applicant and Manufacturer Information..... 3
 - 1.2. Equipment Under Test (EUT) Description 3
- 2. Test Results 5
 - 2.1. Applied Reference Documents 5
 - 2.2. EUT Setup and Operating Conditions..... 6
- 3. 47 CFR Part 15B Requirements 8
 - 3.1. Conducted Emission 8
 - 3.2. Radiated Disturbance..... 12
- Annex A Photographs of Test Setup..... 17
- Annex B Test Uncertainty..... 19
- Annex C Testing Laboratory Information..... 20

Change History		
Issue	Date	Reason for change
1.0	2018-05-17	First edition



1. Technical Information

Note: Provide by applicant

1.1. Applicant and Manufacturer Information

Applicant:	Hot Pepper, Inc.
Applicant Address:	5151 California Ave., Suite 100, Irvine 92617, USA
Manufacturer:	Hot Pepper, Inc.
Manufacturer Address:	5151 California Ave., Suite 100, Irvine 92617, USA

1.2. Equipment Under Test (EUT) Description

EUT Type:	4G Smart Phone
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	T169-LK-V1.2
Software Version:	HOTPEPPER_SW01_20180320
Tx Frequency:	GSM850: 824.2MHz ~ 848.8MHz GSM1900: 1850.2MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1712.4 MHz ~ 1752.6 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 17: 704 MHz ~ 716 MHz Bluetooth: 2402 MHz ~ 2480 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz; 802.11a/n:5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz;5725MHz ~ 5875 MHz;
Rx Frequency:	GSM850: 869 MHz ~ 894 MHz GSM1900: 1930 MHz ~ 1990 MHz WCDMA Band II: 1930 MHz ~ 1990 MHz WCDMA Band IV: 2112.4 MHz ~ 2152.6 MHz WCDMA Band V: 869 MHz ~ 894 MHz LTE Band 2: 1930 MHz ~ 1990 MHz LTE Band 4: 2110 MHz ~ 2155 MHz LTE Band 12: 729 MHz ~ 746 MHz LTE Band 17: 734 MHz ~ 746 MHz Bluetooth: 2402 MHz ~ 2480 MHz



	802.11b/g/n: 2412 MHz ~ 2462 MHz; 802.11a/n:5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725MHz ~ 5875 MHz; GPS:1575.42MHz	
Ancillary Equipment:	Battery	
	Brand Name:	Hot Pepper
	Model No.:	BL9503
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	2800mA
	Rated Voltage:	3.85V
	Charge Limit:	4.3V
	AC Adapter	
	Brand Name:	Hot Pepper
	Model No.:	TPA_46050150UU
	Serial No.:	(N/A, marked #1 by test site)
	Rated Input:	~ 100-240V, 50/60Hz,0.3A
	Rated Output:	≐5V,1.5A

Note:

1. The 4G Smart Phone supports GSM850MHz, 1900MHz, WCDMA Band II, Band IV, Band V ,LTE Band 2/4/12/17, GPS, 5.8GHz WIFI, ISM 2.4GHz Bluetooth band and WIFI (802.11a/b/g/n) band.
2. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer.



2. Test Results

2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result
1	15.107	Conducted Emission	2018.05.04	Wu Junke	PASS
2	15.109	Radiated Emission	2018.04.01	Wu Junke	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.



2.2. EUT Setup and Operating Conditions

Test Item	
Radiated Emission	
Mode 1	: GSM Link (850,900) + Bluetooth Idle + WLAN Idle + Earphone + Battery + USB Cable (Charging from Adapter) + Adapter + SIM Card
Mode 2	: GSM Link (850,900)+ Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable (Charging from Adapter) + Adapter + SIM Card
Mode 3	: WCDMA Link (Band II, Band IV, Band V) + Bluetooth Idle + WLAN Idle + Earphone + Battery + USB Cable (Charging from Adapter) + Adapter + SIM Card
Mode 4	: WCDMA Link (Band II, Band IV, Band V)+ Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable (Charging from Adapter) + Adapter + SIM Card
Mode 5	: LTE Link (Band 2/4/12/17) + Bluetooth Idle + WLAN Idle + Earphone + Battery + USB Cable(Charging from Adapter) + Adapter + SIM Card
Mode 6	: LTE Link (Band 2/4/12/17) + Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable(Charging from Adapter) + Adapter + SIM Card
Mode 7	: GSM/WCDMA/LTE Band Idle + Bluetooth Idle + WLAN Idle + PC + T-Flash Card + Earphone + Battery + USB Cable + SIM Card
Conducted Emission	
Mode 1	: GSM Link (850,900) + Bluetooth Idle + WLAN Idle + Earphone + Battery + USB Cable (Charging from Adapter) + Adapter + SIM Card
Mode 2	: GSM Link (850,900)+ Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable (Charging from Adapter) + Adapter + SIM Card
Mode 3	: WCDMA Link (Band II, Band IV, Band V) + Bluetooth Idle + WLAN Idle + Earphone + Battery + USB Cable (Charging from Adapter) + Adapter + SIM Card
Mode 4	: WCDMA Link (Band II, Band IV, Band V)+ Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable (Charging from Adapter) + Adapter + SIM Card
Mode 5	: LTE Link (Band 2/4/12/17) + Bluetooth Idle + WLAN Idle + Earphone + Battery + USB Cable(Charging from Adapter) + Adapter + SIM Card
Mode 6	: LTE Link (Band 2/4/12/17) + Bluetooth Link + WLAN Link + Earphone + Battery + USB Cable(Charging from Adapter) + Adapter + SIM Card
Mode 7	: GSM/WCDMA/LTE Band Idle + Bluetooth Idle + WLAN Idle + PC + T-Flash Card + Earphone + Battery + USB Cable + SIM Card
Remark: The above test modes in boldface were the worst cases of conducted emission, radiated emission tests; only the test data of these modes was reported.	



During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

3. 47 CFR Part 15B Requirements

3.1. Conducted Emission

3.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- a) The limit subjects to the Class B digital device.
- b) The lower limit shall apply at the band edges.
- c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2. Test Setup

Please refer to Annex A for the photographs of the Test Configuration.






The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity is maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.


3.1.3. Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

A. Test Plot and Suspicious Points:



NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.5650	40.04	33.58	56.00	46.00	Line	PASS
2	1.1799	37.20	28.29	56.00	46.00		PASS
3	2.3099	38.05	32.00	56.00	46.00		PASS
4	3.5551	34.09	27.79	56.00	46.00		PASS
5	9.0998	28.89	22.19	60.00	50.00		PASS
6	20.554	31.95	21.11	60.00	50.00		PASS



NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2497	40.45	34.08	61.76	51.76	Neutral	PASS
2	0.5647	40.70	31.17	56.00	46.00		PASS
3	1.1299	38.67	28.65	56.00	46.00		PASS
4	2.6097	39.31	31.64	56.00	46.00		PASS
5	4.7598	34.54	24.70	56.00	46.00		PASS
6	20.064	35.84	22.67	60.00	50.00		PASS



3.2. Radiated Disturbance

3.2.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength Limitation at 3m Measurement Dist	
	(μ V/m)	(dB μ V/m)
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dB μ V/m is calculated by 20log Emission Level(μ V/m).


3.2.2. Frequency range of measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

3.2.3. Test Setup

- 1) For radiated emissions from 30MHz to1GHz



- 2) For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:


In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

3.2.4. Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions which (6GHz-30GHz) are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.



No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	33.390	38.36	35.62	N.A	N.A	40.00	N.A	V	PASS
2	49.215	38.25	34.96	N.A	N.A	40.00	N.A	V	PASS
3	94.020	34.88	N.A	N.A	N.A	43.50	N.A	V	PASS
4	198.780	38.46	N.A	N.A	N.A	43.50	N.A	V	PASS
5	2408.000	48.21	N.A	N.A	74.00	N.A	54.00	V	PASS
6	5014.720	46.51	N.A	N.A	74.00	N.A	54.00	V	PASS



No.	Fre. MHz	Pk dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	33.880	34.35	N.A	N.A	N.A	40.00	N.A	H	PASS
2	94.990	36.92	N.A	N.A	N.A	43.50	N.A	H	PASS
3	201.800	44.32	39.19	N.A	N.A	43.50	N.A	H	PASS
4	297.720	42.39	N.A	N.A	N.A	46.00	N.A	H	PASS
5	2409.067	48.14	N.A	N.A	74.00	N.A	54.00	H	PASS
6	5646.400	46.44	N.A	N.A	74.00	N.A	54.00	H	PASS

Annex A Photographs of Test Setup


1. Mains Terminal Disturbance Voltage Measurement




2. Conducted emission main's port side view



3. Radiated Field Strength Measurement(30MHz-1GHz)



4. Radiated Field Strength Measurement(above 1GHz)





Annex B Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	9kHz-150kHz	±4.1 dB
	150kHz-30MHz	±3.7dB

Uncertainty of Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	30MHz-200MHz	±5.06dB
	200MHz-1000MHz	±5.24dB
	1GHz-6GHz	±5.18dB
	6GHz-18GHz	±5.48dB



Annex C Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.	
Department:	Morlab Laboratory	
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China	
Responsible Test Lab Manager:	Mr. Su Feng	
Telephone:	+86 755 36698555	
Facsimile:	+86 755 36698525	

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

3. Accreditation Certificate

Accredited Testing Laboratory:	The FCC designation number is CN1192. (Shenzhen Morlab Communications Technology Co., Ltd.)
---------------------------------------	--

4. Test Software Utilized

Model	Version Number	Producer
MORLAB EMCR V1.2	Version 1.0	MORLAB
TS+ -[JS32-CE]	Version2.5.0.0	Tonscend

**5. Test Equipments Utilized**

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
MXE EMI Receiver	Agilent	N9038A	MY54130016	2018.05.08	2019.05.07
Receiver	KEYSIGHT	N9038A	MY56400093	2017.07.13	2018.07.12
LISN	Schwarzbeck	NSLK 8127	812744	2018.05.08	2019.05.07
Pulse Limiter (20dB)	VTSD	9561D	9537	2018.05.08	2019.05.07
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-519	2018.05.08	2019.05.07
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	1774	2017.09.13	2018.09.12
Test Antenna-Horn	Schwarz	BBHA9170	BBHA9170#773	2017.09.13	2018.09.12
Test Antenna-Horn	Schwarz	BBHA9170	BBHA9170#774	2017.09.13	2018.09.12
Semi-Anechoic Chamber	CRT	9m*6m*6m 1#	N/A	2017.11.19	2020.11.18
Semi-Anechoic Chamber	CRT	9m*6m*6m 2#	N/A	2017.01.12	2020.01.11

————— END OF REPORT —————