

Date: August 13, 2018

Federal Communications Commission  
Office of Engineering and Technology Laboratory Division  
7435 Oakland Mills Rd.  
Columbia MD 21046

Attn: Office of Engineering and Technology

HAC Attestation - FCC ID: 2APD4-A80C

To whom it may concern:

Hot Pepper, Inc. hereby declares that the MIF values detailed below are based on worst case operating modes for all air interfaces for which the HAC rating is provided based on the current methodology for determining MIF values.

Reference Test report Number(s): TA lab Test Report R1803A0143-H1V2\_P26A\_HAC TCoil

<b>SPEAG test files</b>		
UID	Communication System Name	MIF (dB)
10021 DAC	GSM-FDD(TDMA, MSK)	3.63
10011 CAB	UMTS-FDD (WCDMA)	-27.23
10188 CAD	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	-9.76
10185 CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	-9.76
10178 CAD	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	-9.76
10176 CAD	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	-9.76
10182 CAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	-9.76
10170 CAC	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	-9.76

Sincerely,



---

Hong Peow ONG  
CEO  
On behalf of Hot Pepper, Inc.