

Maximum Permissible Exposure Evaluation

FCC ID: 2APD7-SA-P202

1. Client Information

Applicant : Shenzhen Golden Vision Technology Development Co.,Ltd
Address : Bao lai industrial Park, Xinhe Rd No.66, Shang mu gu Village, Pinghu, Longgang District, Shenzhen, China
Manufacturer : Shenzhen Golden Vision Technology Development Co.,Ltd
Address : Bao lai industrial Park, Xinhe Rd No.66, Shang mu gu Village, Pinghu, Longgang District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Wi-Fi Smart Plug
Models No.	:	SA-P202, SA-P302, SA-P402, SA-P502, SA-P602, SA-P702, SA-P802, SA-P902
Model Difference	:	All these models are identical in the same PCB layout and electrical circuit, the only difference is model name for commercial.
Product Description	:	Operation Frequency: 802.11b/g/n(HT20): 2412MHz~2462MHz
		RF Output Power: 802.11b: 17.65dBm 802.11g: 16.44dBm 802.11n (HT20): 14.84dBm
		Antenna Gain: 1dBi PCB Antenna
		Modulation Type: 802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK,QPSK,16QAM, 64QAM)
Power Supply	:	AC Voltage supplied
Power Rating	:	Input: AC 100-240V, 50/60Hz, 10A
Connecting I/O Port(S)	:	Please refer to the User's Manual

TB-RF-075-1.0

MPE Calculations for WIFI

1. Antenna Gain:

PCB Antenna: 1dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
802.11b	17.65	17±1	18	1	20	0.01580
802.11g	16.44	16±1	17	1	20	0.01255
802.11n (HT20)	14.84	14±1	15	1	20	0.00792

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n:2412~2462 MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.01580\text{mW} / \text{cm}^2 < \text{limit } 1\text{mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----