

Test Report

Report No.: MTi240612025-21E2

Date of issue: 2024-07-31

Applicant: ShangXing Technology (Shenzhen) Co., Ltd.

Product: 3-in-1 magnetic wireless charging station

Model(s): X83Q, X80, X80Q, X80S, X80SQ, X80Pro, X83, X83PRO, X83S, X85, X85Q, X85Pro, X87, X87Q, X89, X89Q

FCC ID: 2APDM-X83Q

Shenzhen Microtest Co., Ltd.

[http:// Web: www.mtitest.cn](http://www.mtitest.cn)

Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Contents

1	General Description	5
1.1	Description of the EUT	5
1.2	Description of test modes	5
1.3	Description of support units	7
2	Measurement uncertainty	7
3	Test facilities and accreditations.....	8
3.1	Test laboratory	8
4	List of test equipment	9
5	Test result	10
5.2	Test setup	11
5.3	Test Procedures.....	11
5.4	Information of test equipment	12
5.5	Test results	13
	Photographs of the Test Setup.....	15
	Photographs of the EUT.....	15

Test Result Certification	
Applicant:	ShangXing Technology (Shenzhen) Co., Ltd.
Address:	Room 408, 4th Floor, Building 30. Wisdomland Business Park, Guankou 2ndroad, Nantou, Nanshan, Shenzhen, China
Manufacturer:	ShangXing Technology (Shenzhen) Co., Ltd.
Address:	Room 408, 4th Floor, Building 30. Wisdomland Business Park, Guankou 2ndroad, Nantou, Nanshan, Shenzhen, China
Product description	
Product name:	3-in-1 magnetic wireless charging station
Trademark:	N/A
Model name:	X83Q
Series Model:	X80, X80Q, X80S, X80SQ, X80Pro, X83, X83PRO, X83S, X85, X85Q, X85Pro, X87, X87Q, X89, X89Q
Standards:	47 CFR PART 1, § 1.1310
Test method:	KDB 680106 D01 Wireless Power Transfer v04
Date of Test	
Date of test:	2024-07-25 to 2024-07-29
Test result:	Pass

Test Engineer	:	<i>Letter. Lan.</i>
		(Letter Lan)
Reviewed By	:	<i>David. Lee</i>
		(David Lee)
Approved By	:	<i>Leon chen</i>
		(Leon Chen)

1 General Description

1.1 Description of the EUT

Product name:	3-in-1 magnetic wireless charging station
Model name:	X83Q
Series Model(s):	X80, X80Q, X80S, X80SQ, X80Pro, X83, X83PRO, X83S, X85, X85Q, X85Pro, X87, X87Q, X89, X89Q
Model difference:	All the models are the same circuit and module, except the model name.
Electrical rating:	Input: USB-C: DC 9V/3A, 12V/3A Output: Magnetic Wireless Charger: 5W/7.5W/10W/15W Air Pods Charger: 5W Apple Watch Charger: 3W/5W
Accessories:	N/A
Hardware version:	SXtech-X83Qi2-JXV-V1.0
Software version:	ABF4
Test sample(s) number:	MTi240612025-16S1001
RF specification	
Operating frequency range:	Transmitter1 (Phone): 115-205kHz &360kHz Transmitter2 (Air Pods): 115-205 kHz Transmitter3 (Watch): 300-350 kHz&1778kHz
Modulation type:	ASK
Antenna(s) type:	Coli

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Wireless output(5W) +Air Pods(5W) +Watch(5W)
Mode2	Wireless output (7.5W) +Air Pods(5W) +Watch(5W)
Mode3	Wireless output(10W) +Air Pods(5W) +Watch(5W)
Mode4	Wireless output(15W) +Air Pods(5W) +Watch(5W)
Mode5	Wireless output(15W) +Air Pods(5W) +Watch(3W)
Mode6	Wireless output(10W) +Air Pods(5W) +Watch(3W)
Mode7	Wireless output (7.5W) +Air Pods(5W) +Watch(3W)
Mode8	Wireless output(5W) +Air Pods(5W) +Watch(3W)
Mode9	Wireless output(5W) +Air Pods(5W)
Mode10	Wireless output (7.5W) +Air Pods(5W)
Mode11	Wireless output(10W) +Air Pods(5W)
Mode12	Wireless output(15W) +Air Pods(5W)
Mode13	Wireless output(5W) +Watch(3W)
Mode14	Wireless output (7.5W) +Watch(3W)

Mode15	Wireless output(10W) +Watch(3W)
Mode16	Wireless output(15W) +Watch(3W)
Mode17	Wireless output(5W) +Watch(5W)
Mode18	Wireless output (7.5W) +Watch(5W)
Mode19	Wireless output(10W) +Watch(5W)
Mode20	Wireless output(15W) +Watch(5W)
Mode21	Air Pods(5W) +Watch(5W)
Mode22	Air Pods(5W) +Watch(3W)
Mode23	Air Pods(5W)
Mode24	Watch(5W)
Mode25	Watch(3W)
Mode26	Wireless output(5W)
Mode27	Wireless output (7.5W)
Mode28	Wireless output(10W)
Mode29	Wireless output(15W)
Mode30	stand by

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
AC adapter(65W)	EP-TA865	/	SAMSUNG
Mobile Phone	iPhone 15	M2LQK7WHH0	Apple
Mobile phone	iPhone 12	F17DMBNE0DYM	Apple
Air Pods	MQD83CH/A	/	Apple
watch	watch S7	M0JVGQG1VP	Apple
watch	watch SE	/	Apple
Support cable list			
Description	Length (m)	From	To
/	/	/	/

2 Measurement uncertainty

Parameter	Expanded Uncertainty
Magnetic field measurements(3kHz~10MHz)	$\pm 14.8\%$
Electric field measurements(3kHz~10MHz)	$\pm 17.5\%$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3 Test facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	SPEAG	MAGPy-8H3D +ED3	3101	2024/3/12	2027/3/11

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.4	2.4.1	/	/

5 Test result

5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30


f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

5.2 Test setup




5.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

5.4 Information of test equipment

Test equipment: MAGPy-8H3D+ED3	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm ² arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)



Test probe, without the casing

5.5 Test results

Test condition 1: Mode 4 operating mode with client device (1 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	1.34	614	0.22%	0.03	1.63	1.84%
Left	0.92			0.01		
Right	0.99			0.02		
Front	0.84			0.02		
Rear	0.79			0.01		
bottom	0.69			0.02		

Test condition 2: Mode 4 operating mode with client device (50 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Z axis	1.33	614	0.22%	0.04	1.63	2.45%
Left	0.90			0.02		
Right	0.98			0.02		
Front	0.84			0.02		
Rear	0.78			0.01		
Bottom	0.68			0.02		

Test condition 3: Mode 4 operating mode with client device (99 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	1.30	614	0.21%	0.04	1.63	2.45%
Left	0.87			0.01		
Right	0.93			0.01		
Front	0.81			0.02		
Rear	0.78			0.01		
bottom	0.68			0.02		

Test condition 1: Mode 7 operating mode with client device (1 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	1.12	614	0.18%	0.02	1.63	1.84%
Left	0.84			0.01		
Right	0.77			0.02		
Front	0.69			0.03		
Rear	0.79			0.02		
bottom	0.69			0.02		

Test condition 2: Mode 7 operating mode with client device (50 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Z axis	1.10	614	0.18%	0.02	1.63	1.23%
Left	0.82			0.01		
Right	0.75			0.02		
Front	0.68			0.02		
Rear	0.77			0.02		
Bottom	0.69			0.02		

Test condition 3: Mode 7 operating mode with client device (99 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	1.08	614	0.18%	0.02	1.63	1.84%
Left	0.80			0.03		
Right	0.75			0.01		
Front	0.68			0.02		
Rear	0.76			0.02		
bottom	0.69			0.01		

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

----End of Report----