



RF TEST REPORT

Applicant MeiG Smart Technology Co., Ltd
FCC ID 2APJ4-SLM750VSA
Product SLM750VSA
Brand MEIGLink
Model SLM750VSA
Report No. R2202A0142-R1
Issue Date March 1, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2020)/ FCC CFR 47 Part 22H (2020)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the Test Report	4
1.2. Test facility	4
1.3. Testing Location	4
2. General Description of Equipment under Test	5
3. Applied Standards	6
4. Test Configuration	7
5. Test Case Results	9
5.1. RF Power Output	9
5.2. Effective Radiated Power	13
5.3. Occupied Bandwidth	18
5.4. Band Edge Compliance	26
5.5. Peak-to-Average Power Ratio (PAPR)	34
5.6. Frequency Stability	36
5.7. Spurious Emissions at Antenna Terminals	41
5.8. Radiates Spurious Emission	48
6. Main Test Instruments	54
ANNEX A: The EUT Appearance	55
ANNEX B: Test Setup Photos	56
ANNEX C: Product Change Description	57



Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Radiated Power	22.913(a)(5)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	2.1051 / 22.917(a)	PASS
5	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 22.355	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
8	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard.			
Date of Testing: September 3, 2019 ~ September 24, 2019			

SLM750VSA (Report No.: R2202A0142-R1) is a variant model of SLM750 (Report No.: R1908A0527-R1V1). Changed FCC ID and Product Applicant address and Manufacturer address. Test values partial duplicated from Original for variant. There is no test for variant in this report.

The difference between model SLM750VSA and model SLM750 is show in the below table:

	Model	SLM750VSA (Variant)	SLM750 (Original)
Hardware	PCB	Addsomebands, the related matching circuit wiring has changed	/
Software	Software Version	SLM750-V_4.0.13_EQ101	SLM750-V_2.0.2D_EQ100
RF	RF circuit	Add LTE Band7/40	/
Notes: The SLM750VSA support LTE Band 2/4/5/7/40;WCDMA B2/5;GSM 850/1900; The SLM750 support LTE Band 2/4/5/12/13/17/25/26/B41,WCDMA B2/4/5, GSM 850/1900; CDMA BC0, CDMA BC1			

The detailed product change description please refers to the *Difference Declaration Letter*.



1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

Client Information

Applicant	MeiG Smart Technology Co., Ltd
Applicant address	Floor 2, Office Building No.5, Lingxia Road, Fenghuang Community, Fuyong Street, Bao 'an District, Shenzhen
Manufacturer	MeiG Smart Technology Co., Ltd
Manufacturer address	Floor 2, Office Building No.5, Lingxia Road, Fenghuang Community, Fuyong Street, Bao 'an District, Shenzhen

General Information

EUT Description			
Model	SLM750VSA		
IMEI	863879041726491		
Hardware Version	SLM750-V_MB_V1.00		
Software Version	SLM750-V_4.0.13_EQ101		
Power Supply	External Power Supply		
Antenna Type	PCB Antenna		
Antenna Gain	1.8dBi		
Test Mode(s)	GSM 850; WCDMA Band V; LTE Band 5;		
Test Modulation	(GSM)GMSK; (WCDMA) QPSK; (LTE)QPSK 16QAM;		
HSDPA UE Category	8		
HSUPA UE Category	6		
LTE Category	4		
Maximum E.R.P.	GSM 850:	32.15dBm	
	WCDMA Band V:	23.40dBm	
	LTE Band 5:	23.22dBm	
Rated Power Supply Voltage	3.8V		
Extreme Voltage	Minimum: 3.3V Maximum: 4.2V		
Extreme Temperature	Lowest: -40°C Highest: +85°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 5	824 ~ 849	869 ~ 894
Note: The information of the EUT is declared by the manufacturer.			



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR47 Part 2 (2020)

FCC CFR 47 Part 22H (2020)

ANSI C63.26 (2015)

KDB 971168 D01 Power Meas License Digital Systems v03r01

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, vertical polarization) and the worst case was recorded.

All mode and data rates and positions were investigated. Subsequently, only the worst case emissions are reported.

The following testing in GSM /WCDMA/LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

Test items	Modes/Modulation	
	GSM 850	WCDMA Band V
RF power output	GSM	RMC HSDPA/HSUPA DC-HSDPA
Effective Radiated Power	GSM	RMC
Occupied Bandwidth	GSM	RMC
Band Edge Compliance	GSM	RMC
Peak-to-Average Power Ratio	GSM	RMC
Frequency Stability	GSM	RMC
Spurious Emissions at Antenna Terminals	GSM	RMC
Radiates Spurious Emission	GSM	RMC



Test modes are chosen as the worst case configuration below for LTE Band 5

Test items	Modes	Bandwidth (MHz)					Modulation		RB			Test Channel		
		1.4	3	5	10	15	QPSK	16QAM	1	50%	100%	L	M	H
RF power output	LTE 5	0	0	0	0	-	0	0	0	0	0	0	0	0
Effective Isotropic Radiated power	LTE 5	0	0	0	0	-	0	0	0	0	0	0	0	0
Occupied Bandwidth	LTE 5	0	0	0	0	-	0	0	-	-	0	0	0	0
Band Edge Compliance	LTE 5	0	0	0	0	-	0	0	0	-	0	0	-	0
Peak-to-Average Power Ratio	LTE 5	0	0	0	0	-	0	0	-	-	0	0	0	0
Frequency Stability	LTE 5	0	0	0	0	-	0	0	0	0	0	0	0	0
Spurious Emissions at Antenna Terminals	LTE 5	0	0	0	0	-	0	-	0	-	-	0	0	0
Radiates Spurious Emission	LTE 5	0	-	0	0	-	0	-	0	-	-	-	0	-
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.													

5. Test Case Results

5.1. RF Power Output


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

Test Results

GSM 850		Conducted Power(dBm)		
		Channel 128	Channel 190	Channel 251
		824.2 (MHz)	836.6 (MHz)	848.8 (MHz)
GSM	Results	32.29	32.32	32.34

WCDMA Band V		Conducted Power(dBm)		
		Channel 4132	Channel 4183	Channel 4233
		826.4(MHz)	836.6(MHz)	846.6(MHz)
RMC		23.61	23.63	23.75
HSDPA	Sub - Test 1	23.07	23.05	23.19
	Sub - Test 2	23.06	23.07	23.16
	Sub - Test 3	22.53	22.57	22.68
	Sub - Test 4	22.54	22.58	22.66
HSUPA	Sub - Test 1	23.03	23.04	23.14
	Sub - Test 2	22.02	22.02	22.13
	Sub - Test 3	22.49	22.50	22.62
	Sub - Test 4	21.95	21.99	22.10
	Sub - Test 5	22.96	22.97	23.08
DC-HSDPA	Sub - Test 1	22.95	22.99	23.09
	Sub - Test 2	22.94	22.98	23.08
	Sub - Test 3	22.52	22.47	22.59
	Sub - Test 4	22.51	22.46	22.58

LTE Band 5				Conducted Power(dBm)		
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20407/824.7	20525/836.5	20643/848.3
1.4MHz	QPSK	1	0	23.37	23.17	23.05
		1	2	23.19	23.30	23.15
		1	5	23.55	23.23	23.05
		3	0	21.97	22.04	21.91
		3	2	21.93	22.09	21.85
		3	3	22.16	22.23	21.89
		6	0	21.91	22.23	22.01
	16QAM	1	0	22.22	22.35	21.83
		1	2	22.46	23.11	21.72
		1	5	22.16	22.59	21.61
		3	0	21.00	21.06	21.15
		3	2	21.03	21.18	21.09
		3	3	21.02	21.25	20.95
		6	0	20.96	21.22	21.00
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20415/825.5	20525/836.5	20635/847.5
3MHz	QPSK	1	0	23.39	23.18	23.08
		1	7	23.22	23.35	23.19
		1	14	23.57	23.27	23.08
		8	0	22.00	22.09	21.95
		8	4	21.96	22.14	21.89
		8	7	22.18	22.27	21.94
		15	0	21.99	22.25	22.05
	16QAM	1	0	22.24	22.38	21.85
		1	7	22.49	23.15	21.75
		1	14	22.19	22.61	21.64
		8	0	21.03	21.11	21.19
		8	4	21.05	21.22	21.12
		8	7	21.05	21.30	20.99
		15	0	20.99	21.27	21.04
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				20425/826.5	20525/836.5	20625/846.5
5MHz	QPSK	1	0	23.38	23.14	23.06



		1	13	23.20	23.34	23.16	
		1	24	23.54	23.22	23.04	
		12	0	21.98	22.05	21.92	
		12	6	21.93	22.09	21.85	
		12	13	22.15	22.24	21.90	
		25	0	21.97	22.21	22.00	
	16QAM	1	0	22.19	22.36	21.83	
		1	13	22.47	23.12	21.73	
		1	24	22.16	22.57	21.61	
		12	0	21.00	21.09	21.16	
		12	6	21.02	21.17	21.08	
		12	13	21.03	21.26	20.96	
			25	0	20.96	21.22	21.00
	BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
20450/829					20525/836.5	20600/844	
10MHz	QPSK	1	0	23.35	23.10	23.03	
		1	25	23.19	23.30	23.14	
		1	49	23.52	23.21	23.01	
		25	0	21.95	22.00	21.88	
		25	13	21.91	22.05	21.82	
		25	25	22.12	22.19	21.86	
	16QAM	50	0	21.94	22.16	21.96	
		1	0	22.17	22.32	21.78	
		1	25	22.43	23.10	21.69	
		1	49	22.14	22.54	21.59	
		25	0	20.97	21.05	21.13	
		25	13	20.99	21.15	21.05	
		25	25	21.00	21.21	20.92	
			50	0	20.94	21.18	20.97

5.2. Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa



Methods of Measurement

The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26 (2015).

- a) Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.
- b) Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).
- c) Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.
- d) Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading. $LOSS = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$
- e) Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation: $ERP \text{ (dBm)} = LVL \text{ (dBm)} + LOSS \text{ (dB)}$
- f) The maximum ERP is the maximum value determined in the preceding step.
- g) When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g. transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:
 $EIRP \text{ (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$
where: dBd refers to gain relative to an ideal dipole.
 $EIRP \text{ (dBm)} = ERP \text{ (dBm)} + 2.15 \text{ (dB.)}$

The RB allocation refers to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 22.913(a)(5) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	$\leq 7 \text{ W}$ (38.45 dBm)
-------	--------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19 \text{ dB}$

Test Results:

The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.

GSM 850		ERP(dBm)			Limit (dBm)
		Channel 128	Channel 190	Channel 251	
		824.2 (MHz)	836.6 (MHz)	848.8 (MHz)	
GSM	Results	31.94	31.97	31.99	38.45

WCDMA Band V		ERP(dBm)			Limit (dBm)
		Channel 4132	Channel 4183	Channel 4233	
		826.4(MHz)	836.6(MHz)	846.6(MHz)	
RMC		23.26	23.28	23.40	38.45
HSDPA	Sub - Test 1	22.72	22.70	22.84	38.45
	Sub - Test 2	22.71	22.72	22.81	38.45
	Sub - Test 3	22.18	22.22	22.33	38.45
	Sub - Test 4	22.19	22.23	22.31	38.45
HSUPA	Sub - Test 1	22.68	22.69	22.79	38.45
	Sub - Test 2	21.67	21.67	21.78	38.45
	Sub - Test 3	22.14	22.15	22.27	38.45
	Sub - Test 4	21.60	21.64	21.75	38.45
	Sub - Test 5	22.61	22.62	22.73	38.45
DC-HSDPA	Sub - Test 1	22.60	22.64	22.74	38.45
	Sub - Test 2	22.59	22.63	22.73	38.45
	Sub - Test 3	22.17	22.12	22.24	38.45
	Sub - Test 4	22.16	22.11	22.23	38.45

LTE Band 5				ERP(dBm)			Limit (dBm)
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)			
				20407/824. 7	20525/836. 5	20643/848. 3	
1.4MHz	QPSK	1	0	23.02	22.82	22.7	38.45
		1	2	22.84	22.95	22.8	38.45
		1	5	23.20	22.88	22.7	38.45
		3	0	21.62	21.69	21.56	38.45
		3	2	21.58	21.74	21.5	38.45
		3	3	21.81	21.88	21.54	38.45
		6	0	21.56	21.88	21.66	38.45
	16QAM	1	0	21.87	22.00	21.48	38.45
		1	2	22.11	22.76	21.37	38.45
		1	5	21.81	22.24	21.26	38.45
		3	0	20.65	20.71	20.8	38.45
		3	2	20.68	20.83	20.74	38.45
		3	3	20.67	20.90	20.6	38.45
		6	0	20.61	20.87	20.65	38.45
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)			Limit (dBm)
3MHz	QPSK	1	0	23.04	22.83	22.73	38.45
		1	7	22.87	23.00	22.84	38.45
		1	14	23.22	22.92	22.73	38.45
		8	0	21.65	21.74	21.6	38.45
		8	4	21.61	21.79	21.54	38.45
		8	7	21.83	21.92	21.59	38.45
		15	0	21.64	21.90	21.7	38.45
	16QAM	1	0	21.89	22.03	21.5	38.45
		1	7	22.14	22.80	21.4	38.45
		1	14	21.84	22.26	21.29	38.45
		8	0	20.68	20.76	20.84	38.45
		8	4	20.70	20.87	20.77	38.45
		8	7	20.70	20.95	20.64	38.45
		15	0	20.64	20.92	20.69	38.45
BW	Modulation	RB	RB	Channel/Frequency(MHz)			Limit



		size	offset	20425/826. 5	20525/836. 5	20625/846. 5	(dBm)
5MHz	QPSK	1	0	23.03	22.79	22.71	38.45
		1	13	22.85	22.99	22.81	38.45
		1	24	23.19	22.87	22.69	38.45
		12	0	21.63	21.70	21.57	38.45
		12	6	21.58	21.74	21.5	38.45
		12	13	21.80	21.89	21.55	38.45
		25	0	21.62	21.86	21.65	38.45
	16QAM	1	0	21.84	22.01	21.48	38.45
		1	13	22.12	22.77	21.38	38.45
		1	24	21.81	22.22	21.26	38.45
		12	0	20.65	20.74	20.81	38.45
		12	6	20.67	20.82	20.73	38.45
		12	13	20.68	20.91	20.61	38.45
		25	0	20.61	20.87	20.65	38.45
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)			Limit (dBm)
				20450/829	20525/836. 5	20600/844	
10MHz	QPSK	1	0	23.00	22.75	22.68	38.45
		1	25	22.84	22.95	22.79	38.45
		1	49	23.17	22.86	22.66	38.45
		25	0	21.60	21.65	21.53	38.45
		25	13	21.56	21.70	21.47	38.45
		25	25	21.77	21.84	21.51	38.45
		50	0	21.59	21.81	21.61	38.45
	16QAM	1	0	21.82	21.97	21.43	38.45
		1	25	22.08	22.75	21.34	38.45
		1	49	21.79	22.19	21.24	38.45
		25	0	20.62	20.70	20.78	38.45
		25	13	20.64	20.80	20.7	38.45
		25	25	20.65	20.86	20.57	38.45
		50	0	20.59	20.83	20.62	38.45

5.3. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 3kHz, VBW is set to 10kHz for GSM 850,

RBW is set to 51kHz, VBW is set to 160kHz for WCDMA Band V,


RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 5 (1.4MHz),

RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 5 (3MHz/5MHz),

RBW is set to 300 kHz, VBW is set to 1 MHz for LTE Band 5 (10MHz),

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.


Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.


Test Result


Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
GSM 850 (GSM)	128	824.2	0.24535	0.3136
	190	836.6	0.24334	0.3105
	251	848.8	0.24713	0.3107
WCDMA Band V (RMC)	4132	826.4	4.1243	4.689
	4183	836.6	4.1247	4.703
	4233	846.6	4.1291	4.691


LTE Band 5						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	20407	824.7	1.1224	1.321
			20525	836.5	1.1275	1.338
			20643	848.3	1.1184	1.343
		3	20415	825.5	2.7373	3.056
			20525	836.5	2.7229	3.014
			20635	847.5	2.7405	3.047
		5	20425	826.5	4.5201	5.045
			20525	836.5	4.5304	5.002
			20625	846.5	4.4979	4.956
		10	20450	829	9.047	10.19
			20525	836.5	8.9989	10.05
			20600	844	9.0183	10.03
	16QAM	1.4	20407	824.7	1.1143	1.319
			20525	836.5	1.1139	1.343
			20643	848.3	1.1215	1.347
		3	20415	825.5	2.7352	3.042
			20525	836.5	2.7355	3.052
			20635	847.5	2.7311	3.058
		5	20425	826.5	4.5026	4.982
			20525	836.5	4.495	5.006
			20625	846.5	4.5169	4.989
		10	20450	829	9.0479	9.985
			20525	836.5	8.996	9.875
			20600	844	9.007	9.966











5.4. Band Edge Compliance


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used. RBW is set to 3kHz,VBW is set to 10kHz for GSM 850, RBW is set to 51kHz,VBW is set to 160kHz for WCDMA Band V, RBW is set to 15 kHz, VBW is set to 51 kHz for LTE Band 5 (1.4MHz), RBW is set to 30 kHz, VBW is set to 100 kHz for LTE Band 5 (3MHz), RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 5 (5MHz), RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 5 (10MHz), Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684$ dB.




Test Result:

GSM 850 CH-Low



GSM 850 CH-High




WCDMA Band V CH-Low




WCDMA Band V CH-High




LTE Band 5 QPSK 1.4MHz CH-Low 1RB




LTE Band 5 QPSK 1.4MHz CH-High 1RB




LTE Band 5 QPSK 1.4MHz CH-Low 100%RB




LTE Band 5 QPSK 1.4MHz CH-High 100%RB



LTE Band 5 QPSK 3MHz CH-Low 1RB




LTE Band 5 QPSK 3MHz CH-High 1RB







LTE Band 5 QPSK 3MHz CH-Low 100%RB




LTE Band 5 QPSK 3MHz CH-High 100%RB




LTE Band 5 QPSK 5MHz CH-Low 1RB



LTE Band 5 QPSK 5MHz CH-High 1RB




LTE Band 5 QPSK 5MHz CH-Low 100%RB




LTE Band 5 QPSK 5MHz CH-High 100%RB



LTE Band 5 QPSK 10MHz CH-Low 1RB



LTE Band 5 QPSK 10MHz CH-High 1RB




LTE Band 5 QPSK 10MHz CH-Low 100%RB




LTE Band 5 QPSK 10MHz CH-High 100%RB



LTE Band 5 16QAM 1.4MHz CH-Low 1RB




LTE Band 5 16QAM 1.4MHz CH-High 1RB







LTE Band 5 16QAM 1.4MHz CH-Low 100%RB




LTE Band 5 16QAM 1.4MHz CH-High 100%RB




LTE Band 5 16QAM 3MHz CH-Low 1RB




LTE Band 5 16QAM 3MHz CH-High 1RB




LTE Band 5 16QAM 3MHz CH-Low 100%RB




LTE Band 5 16QAM 3MHz CH-High 100%RB



LTE Band 5 16QAM 5MHz CH-Low 1RB



LTE Band 5 16QAM 5MHz CH-High 1RB




LTE Band 5 16QAM 5MHz CH-Low 100%RB




LTE Band 5 16QAM 5MHz CH-High 100%RB



LTE Band 5 16QAM 10MHz CH-Low 1RB



LTE Band 5 16QAM 10MHz CH-High 1RB





LTE Band 5 16QAM 10MHz CH-Low 100%RB



LTE Band 5 16QAM 10MHz CH-High 100%RB



5.5. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk} . And measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

Test Results

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
GSM 850 (GSM)	128	824.2	33.50	32.29	1.21	≤13	PASS
	190	836.6	33.66	32.32	1.34	≤13	PASS
	251	848.8	33.59	32.34	1.25	≤13	PASS

LTE Band 5								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	20407	824.7	27.77	23.28	4.49	≤13	PASS
		20525	836.5	26.89	23.15	3.74	≤13	PASS
		20643	848.3	27.08	23.22	3.86	≤13	PASS
	3	20415	825.5	27.73	23.19	4.54	≤13	PASS
		20525	836.5	26.87	23.21	3.66	≤13	PASS
		20635	847.5	26.94	22.97	3.97	≤13	PASS
	5	20425	826.5	27.43	22.93	4.50	≤13	PASS
		20525	836.5	26.63	22.92	3.71	≤13	PASS
		20625	846.5	27.00	22.75	4.25	≤13	PASS
	10	20450	829	27.93	23.36	4.57	≤13	PASS
		20525	836.5	26.78	22.97	3.81	≤13	PASS
		20600	844	27.24	23.05	4.19	≤13	PASS
16QAM	1.4	20407	824.7	27.94	22.59	5.35	≤13	PASS
		20525	836.5	26.73	22.01	4.72	≤13	PASS
		20643	848.3	27.03	22.36	4.67	≤13	PASS
	3	20415	825.5	27.52	22.11	5.41	≤13	PASS
		20525	836.5	27.01	22.58	4.43	≤13	PASS
		20635	847.5	26.87	21.97	4.90	≤13	PASS
	5	20425	826.5	27.25	21.76	5.49	≤13	PASS
		20525	836.5	26.62	22.14	4.48	≤13	PASS
		20625	846.5	26.90	21.72	5.18	≤13	PASS
	10	20450	829	27.49	22.14	5.35	≤13	PASS
		20525	836.5	26.90	22.54	4.36	≤13	PASS
		20600	844	27.27	22.33	4.94	≤13	PASS

5.6. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -40°C to +85°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -40°C to +85°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.3 V and 4.2 V, with a nominal voltage of 3.8V.

Test setup



**Limits**

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm
--------	----------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01$ ppm.

Test Result

GSM 850				
Condition		Freq.Error (Hz)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	GMSK	GMSK	
Normal (25°C)	Normal	13.63	0.00725	PASS
Extreme (90°C)		11.29	0.00601	PASS
Extreme (80°C)		4.20	0.00224	PASS
Extreme (70°C)		14.13	0.00752	PASS
Extreme (60°C)		6.13	0.00326	PASS
Extreme (50°C)		15.87	0.00844	PASS
Extreme (40°C)		6.13	0.00326	PASS
Extreme (30°C)		11.96	0.00636	PASS
Extreme (20°C)		4.01	0.00213	PASS
Extreme (10°C)		4.31	0.00229	PASS
Extreme (0°C)		10.50	0.00558	PASS
Extreme (-10°C)		10.47	0.00557	PASS
Extreme (-20°C)		7.55	0.00402	PASS
Extreme (-30°C)		9.23	0.00491	PASS
Extreme (-40°C)		14.52	0.00772	PASS
25°C	LV	10.74	0.00571	PASS
	HV	16.93	0.00900	PASS

WCDMA Band 5						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
Normal (25°C)	Normal	9.95	9.30	0.00529	0.00495	PASS
Extreme (90°C)		13.53	10.00	0.00720	0.00532	PASS
Extreme (80°C)		16.30	9.78	0.00867	0.00520	PASS
Extreme (70°C)		2.67	8.67	0.00142	0.00461	PASS
Extreme (60°C)		12.29	9.27	0.00654	0.00493	PASS
Extreme (50°C)		11.52	16.55	0.00613	0.00880	PASS
Extreme (40°C)		3.13	10.30	0.00167	0.00548	PASS
Extreme (30°C)		8.41	11.75	0.00447	0.00625	PASS
Extreme (20°C)		16.19	9.40	0.00861	0.00500	PASS
Extreme (10°C)		17.28	1.85	0.00919	0.00098	PASS
Extreme (0°C)		3.63	5.34	0.00193	0.00284	PASS
Extreme (-10°C)		12.89	10.40	0.00686	0.00553	PASS
Extreme (-20°C)		2.66	6.02	0.00142	0.00320	PASS
Extreme (-30°C)		8.48	5.85	0.00451	0.00311	PASS
Extreme (-40°C)		14.86	2.07	0.00790	0.00110	PASS
25°C	LV	10.07	6.55	0.00536	0.00348	PASS
	HV	12.19	9.89	0.00648	0.00526	PASS

LTE Band 5						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	13.27	11.76	0.00706	0.00626	PASS
Extreme (90°C)		11.64	13.12	0.00619	0.00698	PASS
Extreme (80°C)		5.04	6.41	0.00268	0.00341	PASS
Extreme (70°C)		16.22	14.51	0.00863	0.00772	PASS
Extreme (60°C)		4.22	11.96	0.00225	0.00636	PASS
Extreme (50°C)		3.82	15.41	0.00203	0.00820	PASS
Extreme (40°C)		6.80	2.19	0.00362	0.00117	PASS
Extreme (30°C)		7.17	9.65	0.00382	0.00513	PASS
Extreme (20°C)		13.91	12.76	0.00740	0.00679	PASS
Extreme (10°C)		7.98	14.59	0.00424	0.00776	PASS
Extreme (0°C)		4.62	11.39	0.00246	0.00606	PASS



Extreme (-10°C)		4.91	17.28	0.00261	0.00919	PASS
Extreme (-20°C)		10.44	12.99	0.00555	0.00691	PASS
Extreme (-30°C)		15.36	8.57	0.00817	0.00456	PASS
Extreme (-40°C)		16.36	2.48	0.00870	0.00132	PASS
25°C	LV	16.50	16.96	0.00878	0.00902	PASS
	HV	5.83	13.55	0.00310	0.00721	PASS

5.7. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier.

The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-18GHz	1.407 dB



Test Result


Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.






WCDMA Band V CH-Low 30MHz ~ 1GHz




Date: 6.SEP.2019 13:26:49

WCDMA Band V CH-Low 1GHz ~ 9GHz




Date: 6.SEP.2019 16:22:19

WCDMA Band V CH-Middle 30MHz ~ 1GHz




Date: 6.SEP.2019 13:27:43

WCDMA Band V CH-Middle 1GHz ~ 9GHz




Date: 6.SEP.2019 16:22:40

WCDMA Band V CH-High 30MHz ~ 1GHz



Date: 6.SEP.2019 13:28:07


WCDMA Band V CH-High 1GHz ~ 9GHz



Date: 6.SEP.2019 16:22:58




LTE Band 5 1.4MHz CH-Low 30MHz~1GHz




Date: 9.SEP.2019 20:06:11

LTE Band 5 1.4MHz CH-Low 1GHz~9GHz




Date: 9.SEP.2019 20:00:36

LTE Band 5 1.4MHz CH-Middle 30MHz~1GHz




Date: 9.SEP.2019 20:06:45

LTE Band 5 1.4MHz CH-Middle 1GHz~9GHz




Date: 9.SEP.2019 20:00:55

LTE Band 5 1.4MHz CH-High 30MHz~1GHz



Date: 9.SEP.2019 20:07:11


LTE Band 5 1.4MHz CH-High 1GHz~9GHz



Date: 9.SEP.2019 20:01:13




LTE Band 5 3MHz CH-Low 30MHz~1GHz




Date: 9.SEP.2019 20:07:57

LTE Band 5 3MHz CH-Low 1GHz~9GHz




Date: 9.SEP.2019 20:01:56

LTE Band 5 3MHz CH-Middle 30MHz~1GHz




Date: 9.SEP.2019 20:08:19

LTE Band 5 3MHz CH-Middle 1GHz~9GHz




Date: 9.SEP.2019 20:02:14

LTE Band 5 3MHz CH-High 30MHz~1GHz



Date: 9.SEP.2019 20:08:02


LTE Band 5 3MHz CH-High 1GHz~9GHz



Date: 9.SEP.2019 20:02:35




LTE Band 5 5MHz CH-Low 30MHz~1GHz




Date: 9.SEP.2019 20:08:52

LTE Band 5 5MHz CH-Low 1GHz~9GHz




Date: 9.SEP.2019 20:03:05

LTE Band 5 5MHz CH-Middle 30MHz~1GHz




Date: 9.SEP.2019 20:09:05

LTE Band 5 5MHz CH-Middle 1GHz~9GHz




Date: 9.SEP.2019 20:03:22

LTE Band 5 5MHz CH-High 30MHz~1GHz



Date: 9.SEP.2019 20:09:24


LTE Band 5 5MHz CH-High 1GHz~9GHz



Date: 9.SEP.2019 20:03:49




LTE Band 5 10MHz CH-Low 30MHz~1GHz




Date: 9.SEP.2019 20:09:45

LTE Band 5 10MHz CH-Low 1GHz~9GHz




Date: 9.SEP.2019 20:04:14

LTE Band 5 10MHz CH-Middle 30MHz~1GHz




Date: 9.SEP.2019 20:09:58

LTE Band 5 10MHz CH-Middle 1GHz~9GHz




Date: 9.SEP.2019 20:04:28

LTE Band 5 10MHz CH-High 30MHz~1GHz



Date: 9.SEP.2019 20:10:10

LTE Band 5 10MHz CH-High 1GHz~9GHz



Date: 9.SEP.2019 20:04:41

5.8. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=200Hz,VBW=600Hz for 9kHz150kHz , RBW=10kHz, VBW=30kHz 150kHz-30MHz , RBW=100kHz,VBW=300kHz for 30MHz to 1GHz and RBW=1MHz, VBW=3MHz for above 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$


The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi)

and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz





Note: Area side:2.4mX3.6m

Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

**Test Result**

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

GSM 850 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673	-61.10	2.00	10.75	Horizontal	-54.50	-13.00	41.50	135
3	2498	-56.58	2.51	11.05	Horizontal	-50.19	-13.00	37.19	90
4	3346	-53.80	4.20	11.15	Horizontal	-49.00	-13.00	36.00	315
5	4183	-53.50	5.20	11.15	Horizontal	-49.70	-13.00	36.70	225
6	5020	-55.20	5.50	11.95	Horizontal	-50.90	-13.00	37.90	180
7	5856	-52.50	5.70	13.55	Horizontal	-46.80	-13.00	33.80	135
8	6693	-52.80	6.30	13.75	Horizontal	-47.50	-13.00	34.50	45
9	7529	-59.40	6.80	13.85	Horizontal	-54.50	-13.00	41.50	135
10	8366	-55.39	6.90	14.25	Horizontal	-50.19	-13.00	37.19	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673	-65.70	2.00	10.75	Horizontal	-59.10	-13.00	46.10	180
3	2510	-64.99	2.51	11.05	Horizontal	-58.60	-13.00	45.60	90
4	3346	-63.30	4.20	11.15	Horizontal	-58.50	-13.00	45.50	45
5	4183	-59.30	5.20	11.15	Horizontal	-55.50	-13.00	42.50	315
6	5020	-58.00	5.50	11.95	Horizontal	-53.70	-13.00	40.70	0
7	5856	-60.00	5.70	13.55	Horizontal	-54.30	-13.00	41.30	45
8	6693	-58.10	6.30	13.75	Horizontal	-52.80	-13.00	39.80	135
9	8366	-55.00	6.80	13.85	Horizontal	-50.10	-13.00	37.10	90
10	3346	-55.30	6.90	14.25	Horizontal	-50.10	-13.00	37.10	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-64.74	2.00	10.75	Horizontal	-58.14	-13.00	45.14	315
3	2509.5	-61.18	2.51	11.05	Horizontal	-54.79	-13.00	41.79	90
4	3346.0	-63.46	4.20	11.15	Horizontal	-58.66	-13.00	45.66	45
5	4182.5	-62.23	5.20	11.15	Horizontal	-58.43	-13.00	45.43	225
6	5019.0	-60.64	5.50	11.95	Horizontal	-56.34	-13.00	43.34	0
7	5855.5	-61.96	5.70	13.55	Horizontal	-56.26	-13.00	43.26	270
8	6692.0	-60.24	6.30	13.75	Horizontal	-54.94	-13.00	41.94	315
9	7528.5	-56.40	6.80	13.85	Horizontal	-51.50	-13.00	38.50	45
10	8365.0	-57.10	6.90	14.25	Horizontal	-51.90	-13.00	38.90	135

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-66.03	2.00	10.75	Horizontal	-59.43	-13.00	46.43	135
3	2509.5	-60.29	2.51	11.05	Horizontal	-53.90	-13.00	40.90	45
4	3346.0	-63.47	4.20	11.15	Horizontal	-58.67	-13.00	45.67	225
5	4182.5	-57.56	5.20	11.15	Horizontal	-53.76	-13.00	40.76	135
6	5019.0	-59.86	5.50	11.95	Horizontal	-55.56	-13.00	42.56	45
7	5855.5	-61.72	5.70	13.55	Horizontal	-56.02	-13.00	43.02	270
8	6692.0	-58.86	6.30	13.75	Horizontal	-53.56	-13.00	40.56	0
9	7528.5	-56.40	6.80	13.85	Horizontal	-51.50	-13.00	38.50	90
10	8365.0	-56.88	6.90	14.25	Horizontal	-51.68	-13.00	38.68	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-66.59	2.00	10.75	Horizontal	-59.99	-13.00	46.99	0
3	2509.5	-60.92	2.51	11.05	Horizontal	-54.53	-13.00	41.53	90
4	3346.0	-64.29	4.20	11.15	Horizontal	-59.49	-13.00	46.49	225
5	4182.5	-61.97	5.20	11.15	Horizontal	-58.17	-13.00	45.17	90
6	5019.0	-57.02	5.50	11.95	Horizontal	-52.72	-13.00	39.72	315
7	5855.5	-62.28	5.70	13.55	Horizontal	-56.58	-13.00	43.58	125
8	6692.0	-59.44	6.30	13.75	Horizontal	-54.14	-13.00	41.14	90
9	7528.5	-56.40	6.80	13.85	Horizontal	-51.50	-13.00	38.50	180
10	8365.0	-56.26	6.90	14.25	Horizontal	-51.06	-13.00	38.06	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113824	2019-05-19	2020-05-18
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Key sight	N9010A	MY50210259	2019-05-19	2020-05-18
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2019-05-19	2020-05-18
Signal Analyzer	R&S	FSV30	100815	2018-12-16	2019-12-15
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-09-26	2019-09-25
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2019-11-17
Horn Antenna	R&S	HF907	100126	2018-07-07	2020-07-06
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2020-06-19
Signal generator	R&S	SMB 100A	102594	2019-05-19	2020-05-18
Climatic Chamber	ESPEC	SU-242	93000506	2017-12-17	2020-12-16
Preamplifier	R&S	SCU18	102327	2019-05-19	2020-05-18
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2019-05-20	2020-05-21
RF Cable	Agilent	SMA 15cm	0001	2019-06-14	2019-09-13
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT *****



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.



ANNEX C: Product Change Description

The Product Change Description are submitted separately.