

# RF Exposure Evaluation Report

**APPLICANT** : MeiG Smart Technology Co., Ltd  
**EQUIPMENT** : Smart Module  
**BRAND NAME** : MEIGLink  
**MODEL NAME** : SNM927  
**FCC ID** : 2APJ4-SNM927  
**STANDARD** : 47 CFR Part 2.1091  
FCC KDB 447498 D01 v06

The product evaluation date was started from Jul. 02, 2024 and completed on Jul. 02, 2024. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

**Sporton International Inc. (Kunshan)**

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China



## **Table of Contents**

<b>1. ADMINISTRATION DATA</b> .....	<b>4</b>
1.1. Testing Laboratory .....	4
<b>2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)</b> .....	<b>5</b>
<b>3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS</b> .....	<b>5</b>
<b>4. RF EXPOSURE LIMIT INTRODUCTION</b> .....	<b>7</b>
<b>5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION</b> .....	<b>8</b>
5.1. Standalone Power Density Calculation .....	8



**Revision History**

<b>REPORT NO.</b>	<b>VERSION</b>	<b>DESCRIPTION</b>	<b>ISSUED DATE</b>
FA462035	Rev. 01	Initial issue of report.	Jul. 05, 2024



## **1. Administration Data**

### **1.1. Testing Laboratory**

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Testing Laboratory</b>			
<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	SAR01-KS	CN1257	314309

<b>Applicant</b>	
<b>Company Name</b>	MeiG Smart Technology Co., Ltd
<b>Address</b>	2nd Floor,Office Building,No.5 Lingxia Road,Fenghuang,Fuyong Street,Bao'an District,Shenzhen City.

<b>Manufacturer</b>	
<b>Company Name</b>	MeiG Smart Technology Co., Ltd
<b>Address</b>	2nd Floor,Office Building,No.5 Lingxia Road,Fenghuang,Fuyong Street,Bao'an District,Shenzhen City.

## 2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Smart Module
Brand Name	MEIGLink
Model Name	SNM927
FCC ID	2APJ4-SNM927
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
Antenna Gain	WLAN2.4GHz/Bluetooth: 0.95 dBi WLAN5.2GHz: 6.84 dBi WLAN5.3GHz: 7.17 dBi WLAN5.5GHz: 6.50 dBi WLAN5.8GHz: 5.47 dBi
Antenna Type	WWAN: Glue Stick Antenna WLAN/Bluetooth: Glue Stick Antenna
HW Version	V1.00
SW Version	T02
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

## 3. Maximum RF average output tune up power among production units

### <2.4GHz WLAN >

Mode	Maximum Average Power (dBm)	
2.4GHz	802.11b	20.5
	802.11g	17.0
	802.11n-HT20	16.0
	802.11n-HT40	16.0

### <Bluetooth>

Mode	Maximum Average power(dBm)	
Bluetooth	BR/EDR	14.0
	LE	3.0



<5GHz WLAN >

Mode		Maximum Average Power (dBm)
5.2GHz	802.11a	16.0
	802.11n-HT20	16.0
	802.11n-HT40	15.0
	802.11ac-VHT20	16.0
	802.11ac-VHT40	16.0
	802.11ac-VHT80	14.0
5.3GHz	802.11a	16.0
	802.11n-HT20	15.5
	802.11n-HT40	15.0
	802.11ac-VHT20	16.0
	802.11ac-VHT40	15.5
	802.11ac-VHT80	14.0
5.5GHz	802.11a	17.0
	802.11n-HT20	15.5
	802.11n-HT40	14.5
	802.11ac-VHT20	17.0
	802.11ac-VHT40	15.5
	802.11ac-VHT80	14.0
5.8GHz	802.11a	18.0
	802.11n-HT20	16.5
	802.11n-HT40	15.0
	802.11ac-VHT20	18.0
	802.11ac-VHT40	16.5
	802.11ac-VHT80	14.0



### 4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Table with 8 columns: Band, Frequency (MHz), Antenna Gain (dBi), Maximum Power (dBm), Maximum EIRP (dBm), Average EIRP (mW), Power Density at 20cm (mW/cm^2), Limit (mW/cm^2). Rows include Bluetooth, 2.4GHz WLAN, 5.2GHz WLAN, 5.3GHz WLAN, 5.5GHz WLAN, and 5.8GHz WLAN.

Note:

- 1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. According to the EUT characteristic, WLAN (2.4GHz or 5GHz) and Bluetooth cannot transmit simultaneously.
4. According to the EUT characteristic, WLAN 2.4GHz and WLAN 5GHz cannot transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----