

Page : 1 of 9 Issued date : 2022/6/23 FCC ID : 2APLE18300408

Maximum Permissible Exposure Report

Product : All-in-one Sensor

Model Name : MS1001

FCC ID : 2APLE18300408

Test Regulation : 47 CFR FCC Part 2.1091

Received Date : 2022/3/31

Test Date : 2022/3/31 ~ 2022/4/8

Issued Date : 2022/6/23

Applicant: Arlo Technologies Inc

2200 Faraday Avenue, Suite 150, Carlsbad, CA 92008, USA

Issued By : Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,

Zhudong Township, Hsinchu County, Taiwan





The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Page : 2 of 9 Issued date : 2022/6/23 FCC ID : 2APLE18300408

REVISION HISTORY

Original Test Report No.: 4790209116-US-R1-V0

Rev.	Test report No. 4790209116-US-R1-V0	Date	Page revised	Contents
Original	4790209116-US-R1-V0	2022/6/23	-	Initial issue



Doc No: 17-EM-F0864 / 5.0

Page : 3 of 9
Issued date : 2022/6/23
FCC ID : 2APLE18300408

Table of Contents

1.	Attestation of Test Results	4
2.	Test Methodology and Reference Procedures	5
3.	Facilities and Accreditation	5
4.	Equipment Under Test	6
4	.1. Description of EUT	6
4	.2. Description of Available Antennas	7
5.	Requirement	8
6.	Radio Frequency Radiation Exposure Evaluation	9



Page : 4 of 9 Issued date : 2022/6/23 FCC ID : 2APLE18300408

1. Attestation of Test Results

APPLICANT: Arlo Technologies Inc

2200 Faraday Avenue, Suite 150, Carlsbad, CA 92008, USA

MANUFACTURER: Funing Precision Component co., Ltd

Lot B, Que vo Industrial Zone. Nam Son Ward, Bac Ninh city, Bac

Ninh province, Viet Nam

EUT DESCRIPTION: All-in-one Sensor

BRAND: Arlo

MODEL: MS1001

SAMPLE STAGE: Engineering Verification Test sample

APPLICABLE STANDARDS

STANDARD

Test Results

47 CFR FCC PART 2.1091

PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:

Approved and Authorized By:

Cindy Hsin Project Handler Date: 2022/6/23 Eric Lee Date: 2022/6/23

Senior Laboratory Engineer

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Page : 5 of 9 Issued date : 2022/6/23 FCC ID : 2APLE18300408

2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06 and KDB 447498 D04 Interim General RF Exposure Guidance v01.

3. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.		
Address	Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan		
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.		



Page : 6 of 9 Issued date : 2022/6/23 FCC ID : 2APLE18300408

4. Equipment Under Test

4.1. Description of EUT

Product Name	All-in-one Sensor
Brand Name	Arlo
Model Name	MS1001
Operating Frequency	904 MHz ~ 926 MHz
Modulation	O-QPSK
Number of Channel	12
Normal Voltage	3Vdc for battery
S/N	AB5U217LA00D0
Sample ID	Conducted Test: 4835371 Radiated Test: 4835369

Note:

1. The EUT provides one completed transmitters and one receivers.

Modulation Mode	Tx,Rx Function	
Sub-G	1TX,1RX	

2. The EUT contains following accessory devices:

Product Brand		Model	Description	
Battery	Panasonic	CR2477	3Vdc, 1000 mAh	

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.



Page : 7 of 9
Issued date : 2022/6/23
FCC ID : 2APLE18300408

4.2. Description of Available Antennas

Ant. No.	Transmitter Circuit	Brand Name	Model Name	Ant. Type	Maximum Gain (dBi)
1	Chain (0)	MASTER WAVE TECHNOLOGY CO., LTD.	JS907X01084X0	Coil	-3.41

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.



Page : 8 of 9 Issued date : 2022/6/23 FCC ID : 2APLE18300408

5. Requirement

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz) Electric Field Strength (E) (V/m) Electric Field Strength (H) Density (S) (E 2, H 2 or (mW/cm²) (minutes)						
0.3-1.34	614	1.63	*100	30		
1.34-30	824/f	2.19/f	*180/f ²	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/1500	30		
1500-100,000			1.0	30		

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

 $S=(P*G)/4\pi R^2$

where: $S = power density (in appropriate units, e.g. mW/cm^2)$

P = power input to the antenna (in appropriate units, e.g., mW)

G =power gain of the antenna in the direction of interest relative to an isotropic radiator R =distance to the center of radiation of the antenna (appropriate units, e.g., cm)



Page : 9 of 9
Issued date : 2022/6/23
FCC ID : 2APLE18300408

6. Radio Frequency Radiation Exposure Evaluation

Sub-G

Evaluation	Max. Average	Directional	Max.	Max.	Power density @	Limit
Frequency	power	Gain	EIRP	EIRP	20 cm	Lillit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	(mW/cm ²)
904 ~ 926	15.29	-3.41	11.88	15.417	0.00307	0.6

Note:

- 1. Max. EIRP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi)
- 2. Max. EIRP (mW) = $10^{(\text{Max. EIRP (dBm)}/10)}$
- 3. Power density (mW/cm²) = Max. EIRP (mW) / [$4 \times \pi \times (\text{calculated distance})^2$], the calculated distance is 20 cm.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

END OF REPORT