

Maximum Permissible Exposure Report

Product : Arlo Essential 2 Video Doorbell
Model Name : AVD4001
Series Model : AVD3001
FCC ID : 2APLE18300424
Test Regulation : 47 CFR FCC Part 2.1091
Received Date : 2023/4/7
Test Date : 2023/5/2 ~ 2023/5/8
Issued Date : 2023/6/27
Applicant : Arlo Technologies Inc
2200 Faraday Avenue, Suite 150, Carlsbad, CA 92008, USA
Issued By : Underwriters Laboratories Taiwan Co., Ltd.
Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,
Zhudong Township, Hsinchu County, Taiwan



The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Table of Contents

1. Attestation of Test Results	4
2. Test Methodology and Reference Procedures.....	5
3. Facilities and Accreditation	5
4. Equipment Under Test.....	6
4.1. Description of EUT	6
4.2. Description of Available Antennas.....	8
5. Requirement.....	9
6. General RF Exposure Test Exemption.....	10

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004725 (DCS:17-EM-F0864) / 5.1

1. Attestation of Test Results

APPLICANT: Arlo Technologies Inc
2200 Faraday Avenue, Suite 150, Carlsbad, CA 92008, USA

MANUFACTURER: Alpha Networks Vietnam Company Limited
Lot CN03, Dong Van 4 Industrial Part, Dai Cuong Commune, Kim Bang District, Ha Nam Province, Vietnam

EUT DESCRIPTION: Arlo Essential 2 Video Doorbell

BRAND: Arlo

MODEL: AVD4001

SERIES MODEL: AVD3001


SAMPLE STAGE: Design Verification Test sample

APPLICABLE STANDARDS	
STANDARD	Test Results
47 CFR FCC Part 2.1091	PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:



Cindy Hsin
Project Handler

Date : 2023/6/27

Approved and Authorized By:



Eric Lee
Senior Laboratory Engineer

Date : 2023/6/27

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D04 Interim General RF Exposure Guidance v01.

3. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.
Address	Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

4. Equipment Under Test

4.1. Description of EUT

Product Name	Arlo Essential 2 Video Doorbell	
Brand Name	Arlo	
Model Name	AVD4001	
Series Model	AVD3001	
Operating Frequency	NFC	13.56MHz
	Bluetooth LE	2402MHz ~ 2480MHz
	WLAN	2412MHz ~ 2462MHz
Modulation	NFC	ASK
	Bluetooth LE	GFSK
	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Number of Channel	NFC	1
	Bluetooth LE	40
	WLAN	11 for 802.11b, 802.11g, 802.11n (HT20)
Normal Voltage	5Vdc from host 3.69Vdc from battery 16.5Vac from adapter	
Sample ID	Conducted Test: 6029690 Radiated Test: 6029690	

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Note:

1. The models difference table as below:

Model	Main Board (PCBA Board)	LED Board (PCBA board)	Image Sensor (2K/FHD)	LED (IR)
AVD4001	PCB layout and circuit is the same except for image sensor	PCB layout and circuit is the same except for IR LED quantity	2K 2560 x 1440 Image Sensor : PixArt PS5420 (1:1)	YOI YC-1F1NI 4M FIXED I-LENS 3G3P W/ICR +XD-W04020GD32 (PS5420)
AVD3001			FHD 1920 x 1080 Image Sensor : PixArt PS5270 (1:1)	YOI YC-1F6NI 2M FIXED I-LENS 2G4P W/ICR +XD-W04020GD21 (PS5270)

2. The EUT provides one completed transmitters and one receivers.

Modulation Mode	Tx,Rx Function
802.11b	1TX,1RX
802.11g	1TX,1RX
802.11n (HT20)	1TX,1RX

3. The EUT contains following accessory devices:

Product	Brand	Model	Description
USB Cable	Network Giant	A220053	Length: 1 m
Battery	Arlo	A-17	3.69Vdc, 17.45Wh

4. For this report measurement uncertainty, statement of conformity, determining compliance, it is necessary to refer to the original measurement report of EUT.
5. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual, the laboratory shall not be held responsible.

Underwriters Laboratories Taiwan Co., Ltd.

4.2. Description of Available Antennas

Ant. No.	Transmitter Circuit	Brand Name	Model Name	Ant. Type	Frequency Band (MHz)	Maximum Gain (dBi)
1	Chain (0)	Arlo	AVD4001	Dipole	2400~2483	3.5
2	Chain (0)	N/A	N/A	Coil	13.56	-

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual, the laboratory shall not be held responsible.

5. Requirement

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

$$S = (P * G) / 4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

6. General RF Exposure Test Exemption

The corresponding Exclusion Threshold condition, listed below:

- 1) Blanket Exempt: Following 47 CFR 1.1307(b)(3)(i)(A), the available maximum time-averaged power is no more than 1 mW.
- 2) SAR Exempt: Following 47 CFR 1.1307(b)(3)(i)(B), the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz};$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004725 (DCS:17-EM-F0864) / 5.1

- 3) MPE Exempt: Following 47 CFR 1.1307(b)(3)(i)(C), using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Bluetooth LE & WLAN 2.4GHz

(1) General RF Exposure Test Exemption

Option	Evaluation Method	Clause
<input type="checkbox"/>	Blanket Exempt	47 CFR 1.1307(b)(3)(i)(A)
<input type="checkbox"/>	SAR Exempt	47 CFR 1.1307(b)(3)(i)(B)
<input checked="" type="checkbox"/>	MPE Exempt	47 CFR 1.1307(b)(3)(i)(C)

Note: Max. ERP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi) - 2.15 (dB)

For Bluetooth LE

Evaluation Frequency (MHz)	$\lambda/2\pi$ (m)	R (m)	Max. ERP (dBm)	Max. ERP (W)	Threshold ERP (W)
2402 ~ 2480	0.0199	0.2	8.63	0.007	0.768

For WLAN 2.4GHz

Evaluation Frequency (MHz)	$\lambda/2\pi$ (m)	R (m)	Max. ERP (dBm)	Max. ERP (W)	Threshold ERP (W)
2412 ~ 2462	0.0198	0.2	26.52	0.449	0.768

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
 Telephone : +886-2-7737-3000
 Facsimile (FAX) : +886-3-583-7948

NFC

(2) General RF Exposure Test Exemption

Option	Evaluation Method	Clause
<input checked="" type="checkbox"/>	Blanket Exempt	47 CFR 1.1307(b)(3)(i)(A)
<input type="checkbox"/>	SAR Exempt	47 CFR 1.1307(b)(3)(i)(B)
<input type="checkbox"/>	MPE Exempt	47 CFR 1.1307(b)(3)(i)(C)

Note: Max. ERP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi) - 2.15 (dB)

Evaluation Frequency	Radiated Field Strength	Max. EIRP	Max. EIRP	Threshold EIRP
(MHz)	(dBuV/m)@30m	(dBm)	(mW)	(mW)
13.56	24.78	-20.84	0.0082	1.00

Note:

- For $f < 30$ MHz, Calculate the EIRP from the radiated field strength in the far field using Equation:

$$EIRP = E_{Meas} + 40\log d_{Meas} - 104.7$$
 Where,
 EIRP is the equivalent isotropically radiated power, in dBm.
 E_{Meas} is the field strength of the emission at the measurement distance, in dBuV/m.
 d_{Meas} is the measurement distance, in m.
 For $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance
- For Example: $EIRP = 24.78 + 40\log(30) - 104.7 = -20.84$ dBm

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

END OF REPORT

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
 Telephone : +886-2-7737-3000
 Facsimile (FAX) : +886-3-583-7948