



588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666

Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM180300190103

Page: 1 of 8

1 Cover Page

RF Exposure REPORT

| | |
|---|---|
| Application No.: | SHEM1803001901CR |
| Applicant: | HAPE INTERNATIONAL (NINGBO) LTD |
| FCC ID: | 2APLME3726 |
| IC: | 23809-E3726 |
| Equipment Under Test (EUT): | |
| NOTE: The following sample(s) submitted was/were identified on behalf of the client as | |
| Product Name: | Remote Control Engine |
| Model No.(EUT): | E3726 |
| Standards: | FCC Rules 47 CFR §2.1093 KDB 447498 D01 General RF Exposure Guidance v06 |
| Date of Receipt: | 2018-04-11 |
| Date of Test: | 2018-05-02 to 2018-05-07 |
| Date of Issue: | 2018-05-11 |
| Test Result: | Pass* |

**In the configuration tested, the EUT detailed in this report complied with the standards specified above.



Parlam Zhan

E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



| Revision Record | | | |
|-----------------|-------------|------------|--------|
| Version | Description | Date | Remark |
| 00 | Original | 2018-05-11 | / |
| | | | |
| | | | |

| | | | |
|---------------------------------|--|---|--|
| Authorized for issue by: | | | |
| | |  | |
| | | <hr/> | |
| | | Vincent Zhu / Project Engineer | |
| | |  | |
| | | <hr/> | |
| | | Parlam Zhan / Reviewer | |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



2 Contents

| | Page |
|--|----------|
| 1 COVER PAGE | 1 |
| 2 CONTENTS..... | 3 |
| 3 GENERAL INFORMATION..... | 4 |
| 3.1 CLIENT INFORMATION | 4 |
| 3.2 GENERAL DESCRIPTION OF E.U.T. | 4 |
| 3.3 DETAILS OF E.U.T. | 4 |
| 3.4 TEST LOCATION | 5 |
| 3.5 TEST FACILITY | 5 |
| 4 TEST STANDARDS AND LIMITS..... | 6 |
| 4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS | 6 |
| 4.2 IC RADIOFREQUENCY RADIATION EXPOSURE LIMITS..... | 7 |
| 5 MEASUREMENT AND CALCULATION..... | 8 |
| 5.1 MAXIMUM TRANSMIT POWER..... | 8 |
| 5.2 RF EXPOSURE CALCULATION..... | 8 |

3 General Information

3.1 Client Information

| | |
|--------------------------|---|
| Applicant: | HAPE INTERNATIONAL (NINGBO) LTD |
| Address of Applicant: | 9-27 Nanhai Road, Dagang industrial City, Beilun, Ningbo, China |
| Manufacturer: | HAPE INTERNATIONAL (NINGBO) LTD |
| Address of Manufacturer: | 9-27 Nanhai Road, Dagang industrial City, Beilun, Ningbo, China |
| Factory: | HAPPY ARTS&CRAFTS (NINGBO) CO., LTD |
| Address of Factory: | 9-27 Nanhai Road, Dagang industrial City, Beilun, Ningbo, China |

3.2 General Description of E.U.T.

| | |
|---------------|---|
| Power supply: | DC 3.6V by Built-in lithium-ion polymer battery (400mAh) Supply the EUT with fully charged battery during the testing. |
| Cable: | DC Cable 30cm for USB Port |

3.3 Details of E.U.T.

| | |
|----------------------------|---|
| Antenna Gain | 1.2 dBi |
| Antenna Type | PIFA Antenna |
| Channel Spacing | 1MHz |
| Modulation Type | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Number of Channels | 79 |
| Operation Frequency | 2402MHz to 2480MHz |
| Spectrum Spread Technology | Frequency Hopping Spread Spectrum(FHSS) |



3.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

- **FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868,C-4336,T-12221,G-10830 respectively.

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max power of channel})/(\text{min test separation distance})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

For 2.4G band device, the limit of worse case is

$$P_{\text{max}} \leq 3.0 \cdot D_{\text{min}} / \sqrt{f} = 3.0 \cdot 5 / \sqrt{2.480} = 9.525 \text{mW}$$

4.2 IC Radiofrequency radiation exposure limits

According to RSS-102 section 2.5.1, SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance

| MHz | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | mm |
|------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| ≤300 | 71 | 101 | 132 | 162 | 193 | 223 | 254 | 284 | 315 | 345 | mW |
| 450 | 52 | 70 | 88 | 106 | 123 | 141 | 159 | 177 | 195 | 213 | |
| 835 | 17 | 30 | 42 | 55 | 67 | 80 | 92 | 105 | 117 | 130 | |
| 1900 | 7 | 10 | 18 | 34 | 60 | 99 | 153 | 225 | 316 | 431 | |
| 2450 | 4 | 7 | 15 | 30 | 52 | 83 | 123 | 173 | 235 | 309 | |
| 3500 | 2 | 6 | 16 | 32 | 55 | 86 | 124 | 170 | 225 | 290 | |
| 5800 | 1 | 6 | 15 | 27 | 41 | 56 | 71 | 85 | 97 | 106 | |

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power. For controlled use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation are multiplied by a factor of 5. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5. If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required.

For 2.4G band device, the limit is $P_{max} \leq 4mW$

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM180300190102.

Test Data:

| Test Mode | Test Channel | Power[dBm] | Peak Power (mW) |
|-----------|--------------|------------|-----------------|
| DH5 | 2402 | -1.28 | 0.74 |
| DH5 | 2441 | -3.42 | 0.45 |
| DH5 | 2480 | -3.56 | 0.44 |
| 2DH5 | 2402 | -2.92 | 0.51 |
| 2DH5 | 2441 | -2.33 | 0.58 |
| 2DH5 | 2480 | -2.48 | 0.56 |
| 3DH5 | 2402 | -2.88 | 0.52 |
| 3DH5 | 2441 | -2.22 | 0.60 |
| 3DH5 | 2480 | -2.42 | 0.57 |

5.2 RF Exposure Calculation

The Max Conducted Peak Output Power is 0.74mW. The best case gain of the antenna is 1.2dBi. 1.2dBi logarithmic terms convert to numeric result is nearly 1.32

According to the formula. calculate the EIRP test result:

$$\text{EIRP} = P \times G = 0.74 \text{ mW} \times 1.32 = 0.98\text{mW} < 4\text{mW} < 0.926\text{mW}$$

So the SAR report is not required.

--End of the Report--