



# FCC PART 15C TEST REPORT

For

## Shenzhen Xintuo Supply Chain LTD

F1 Building 2 Snow Industrial Park SnowElephant Community, Bantian Street Longgang,  
Shenzhen, Guangdong China

**FCC ID: 2APMD-PA044B**

<b>Report Type:</b> Original Report	<b>Product Name:</b> Wireless Charger Stand
<b>Report Number:</b>	RDG180906006-00
<b>Report Date:</b>	2018-10-11
<b>Reviewed By:</b>	Jerry Zhang EMC Manager <i>Jerry Zhang</i>
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “\*” .

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....3**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....3

    OBJECTIVE .....3

    RELATED SUBMITTAL(S)/GRANT(S).....3

    TEST METHODOLOGY .....3

    MEASUREMENT UNCERTAINTY .....4

    TEST FACILITY .....4

**SYSTEM TEST CONFIGURATION.....5**

    JUSTIFICATION .....5

    EUT EXERCISE SOFTWARE .....5

    SUPPORT EQUIPMENT LIST AND DETAILS .....5

    SUPPORT CABLE LIST AND DETAILS .....5

    BLOCK DIAGRAM OF TEST SETUP .....6

**SUMMARY OF TEST RESULTS .....7**

**FCC §1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....8**

    APPLICABLE STANDARD .....8

    BLOCK DIAGRAM OF TEST SETUP .....9

    TEST EQUIPMENT LIST AND DETAILS.....9

    TEST DATA .....9

**FCC§15.203 - ANTENNA REQUIREMENT.....11**

    APPLICABLE STANDARD .....11

    ANTENNA CONNECTED CONSTRUCTION .....11

**FCC §15.207 – AC LINE CONDUCTED EMISSION .....12**

    EUT SETUP.....12

    EMI TEST RECEIVER SETUP.....12

    TEST EQUIPMENT LIST AND DETAILS.....13

    TEST PROCEDURE .....13

    CORRECTED AMPLITUDE & MARGIN CALCULATION .....13

    TEST RESULTS SUMMARY .....14

    TEST DATA .....14

**FCC §15.205 & §15.209 - RADIATED EMISSIONS TEST .....17**

    APPLICABLE STANDARD .....17

    EUT SETUP .....17

    EMI TEST RECEIVER SETUP.....18

    CORRECTED AMPLITUDE & MARGIN CALCULATION .....18

    TEST EQUIPMENT LIST AND DETAILS.....18

    TEST RESULTS SUMMARY .....19

    TEST DATA .....19

## GENERAL INFORMATION

### Product Description for Equipment Under Test (EUT)

<b>EUT Name:</b>	Wireless Charger Stand
<b>EUT Model:</b>	PA044A
<b>Multiple Model:</b>	PA044B
<b>FCC ID:</b>	2APMD-PA044B
<b>Rated Input Voltage:</b>	DC 5V
<b>External Dimension:</b>	118mm(L)* 87.5mm(W)* 70mm(H)
<b>Serial Number:</b>	180906006
<b>EUT Received Date:</b>	2018.09.06

*Note: The series product, models PA044A, PA044B are electrically identical, we selected PA044A fully test, and please refer to the declaration letter for details.*

### Objective

This Type approval report is prepared on behalf of *Shenzhen Xintuo Supply Chain LTD* in accordance with Part 2, Subpart J, and Part 15, Subparts A and C of the Federal Communications Commission's rules.

The objective is to determine the compliance of the EUT with FCC rules, sec 15.203, 15.205, 15.207, 15.209.

### Related Submittal(s)/Grant(s)

No Related Submittal.

### Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
radiated Emissions	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 0.4\%$
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

## SYSTEM TEST CONFIGURATION

### Justification

The system was configured for testing in a test mode

The device is a wireless charger operation on frequency 110 kHz - 205 kHz.

### EUT Exercise Software

No software used in test.


### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Huawei	adapter	PS10J050K2000UU	/
APPLE	Phone	MQ8E2CH/A	FD3X40UEJCU0

### Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
USB Cable	no	no	0.8	adapter	EUT

**Block Diagram of Test Setup**



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
FCC§1.1310 & §2.1091	Maximum Permissible Exposure(MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emission	Compliance
§15.209 §15.205	Radiated Emission Test	Compliance

**FCC §1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According with KDB 680106 D01 RF Exposure Wireless Charging Apps v03 clause 3 c)


- c) For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

According to 680106 D01 RF Exposure Wireless Charging App v03 clause 5 b)

- b) Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC or a PAG for equipment approved using certification to address RF exposure compliance. However, the responsible party is required to keep a copy of the test report in accordance with KDB 865664 D02. A copy of the test report is to be submitted with the application if the device is approved using certification.
  - (1) Power transfer frequency is less than 1 MHz.
  - (2) Output power from each primary coil is less than or equal to 15 watts.
  - (3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
  - (4) Client device is placed directly in contact with the transmitter.
  - (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
  - (6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.



**Block Diagram of Test Setup**



**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Narda	Exposure Level Tester	ELT-400	N-0215	2018-02-22	2019-02-21
Isotropic Probe	ETS-Lindgren	HI-6005	00069461	2016-02-29	2019-02-28

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	49 %
<b>ATM Pressure:</b>	100.9 kPa

\* The testing was performed by Vern Shen on 2018-09-09.

Test mode: Transmitting

**H-Field Strength**

Frequency Range (kHz)	Position A (A/m)	Position B (A/m)	Position C (A/m)	Position D (A/m)	Position E (A/m)	50% Limit (A/m)	Limit Test (A/m)
110-205	0.191	0.188	0.189	0.191	0.192	0.815	1.63

Note: Test with 15cm distance from the center of the probe(s) to the edge of the device, stricter distance used for top surface test.

**E-Field Strength**

Frequency Range (kHz)	Position A (V/m)	Position B (V/m)	Position C (V/m)	Position D (V/m)	Position E (V/m)	50% Limit (V/m)	Limit Test (V/m)
110-205	4.854	6.222	4.568	3.025	5.083	307	614

Note: Test with 15cm distance from the center of the probe(s) to the edge of the device, stricter distance used for top surface test.

**Result: Compliance**

**Considerations of compliance 680106 D01 RF Exposure Wireless Charging App v03 clause 5 b:**

(1) Power transfer frequency is less than 1 MHz.

Yes, the operation frequency is 110-205 kHz.

(2) Output power from each primary coil is less than or equal to 15 watts.

Yes, the maximum output power of primary coil is 10Watts, less than 15 watts.

(3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.

Yes, the transfer system includes only single primary coils and secondary coils. This charging systems that have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.

(4) Client device is placed directly in contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter

(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Yes, mobile exposure conditions only

(6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Yes, the test result for H and E-field strength less than 50% of the MPE limit.

---

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.


### **Antenna Connected Construction**

The EUT has an integral antenna arrangement, which was permanently attached and fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

**FCC §15.207 – AC LINE CONDUCTED EMISSION**

**EUT Setup**



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with an AC 120V/60Hz power source.

**EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2017-12-11	2018-12-11
R&S	Two-line V-network	ENV 216	101614	2017-12-08	2018-12-08
N/A	Coaxial Cable	C-NJNJ-50	C-0200-01	2018-09-05	2019-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

According FCC publication number 174176, for a device with a permanent antenna operating at or below 30 MHz, the measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) perform the AC line conducted tests with the permanent antenna to determine compliance with the Section 15.207 limits outside the transmitter's fundamental emission band; (2) retest with a dummy load in lieu of the permanent antenna to determine compliance with the Section 15.207 limits within the transmitter's fundamental emission band.

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

$V_C$ : corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

$VDF$ : voltage division factor of AMN or ISN

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

### Test Data


#### Environmental Conditions

<b>Temperature:</b>	25.3 °C
<b>Relative Humidity:</b>	49 %
<b>ATM Pressure:</b>	100.4 kPa

*The testing was performed by Lily Xie on 2018-09-08.*

Test Mode: Transmitting


AC 120V, 60 Hz, Line:



Frequency (MHz)	Quasi Peak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.585926	42.9	9.000	L1	9.8	13.1	56.0	Compliance
0.644717	40.3	9.000	L1	9.8	15.7	56.0	Compliance
0.703777	39.2	9.000	L1	9.8	16.8	56.0	Compliance
0.825364	39.5	9.000	L1	9.8	16.5	56.0	Compliance
2.234662	38.8	9.000	L1	9.7	17.2	56.0	Compliance
3.302007	38.8	9.000	L1	9.8	17.2	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.585926	37.2	9.000	L1	9.8	8.8	46.0	Compliance
0.644717	35.1	9.000	L1	9.8	10.9	46.0	Compliance
0.825364	33.4	9.000	L1	9.8	12.6	46.0	Compliance
1.650866	33.6	9.000	L1	9.7	12.4	46.0	Compliance
3.302007	34.1	9.000	L1	9.8	11.9	46.0	Compliance
6.710662	38.4	9.000	L1	9.8	11.6	50.0	Compliance

**AC120 V, 60 Hz, Neutral:**



Frequency (MHz)	Quasi Peak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.585926	40.4	9.000	N	9.8	15.6	56.0	Compliance
0.614619	38.9	9.000	N	9.8	17.1	56.0	Compliance
0.644717	38.8	9.000	N	9.8	17.2	56.0	Compliance
2.478557	31.0	9.000	N	9.8	25.0	56.0	Compliance
3.302007	37.2	9.000	N	9.8	18.8	56.0	Compliance
4.127365	32.6	9.000	N	9.8	23.4	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.585926	38.0	9.000	N	9.8	8.0	46.0	Compliance
0.619536	32.7	9.000	N	9.8	13.3	46.0	Compliance
0.644717	34.6	9.000	N	9.8	11.4	46.0	Compliance
1.352690	30.2	9.000	N	9.8	15.8	46.0	Compliance
1.650866	30.9	9.000	N	9.8	15.1	46.0	Compliance
3.302007	33.5	9.000	N	9.8	12.5	46.0	Compliance



## FCC §15.205 & §15.209 - RADIATED EMISSIONS TEST

### Applicable Standard


As per FCC Part 15.209

(a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

### EUT Setup



The radiated emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part 15.209 limits.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver Setup

The system was investigated from 9 kHz to 1 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	Measurement
9 kHz – 150 kHz	200 Hz	1 kHz	QP/Average
150 kHz – 30 MHz	9 kHz	30 kHz	QP/Average
30 MHz – 1000 MHz	120 kHz	300 kHz	QP

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP/Average measurement

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corr. Ampl.}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunof Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
R&S	EMI Test Receiver	ESCI	100224	2017-12-11	2018-12-11
HP	Amplifier	8447D	2727A05902	2018-09-05	2019-09-05
EMCO	Passive Loop	6512	9706-1206	2017-03-05	2020-03-04
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2018-09-05	2019-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209.

### Test Data

#### Environmental Conditions


<b>Temperature:</b>	26.5~26.7 °C
<b>Relative Humidity:</b>	34~40 %
<b>ATM Pressure:</b>	100.3 kPa

*\* The testing was performed by Vern She, Blake Yang on 2018-09-11.*


*Test mode: Transmitting*

**For Power Transmission,**

1) 9 kHz~30MHz:




Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
0.0240	-5.12	peak	78.97	73.85	120.00	46.15
0.0354	-1.42	peak	75.90	74.48	116.62	42.14
0.1101	12.31	peak	66.16	78.47	106.77	28.30
0.1440	-2.75	peak	64.26	61.51	104.43	42.92



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
0.1500	40.81	peak	38.59	79.40	104.08	24.68
0.7170	32.30	peak	24.40	56.70	70.49	13.79
3.0156	42.59	peak	13.31	55.90	69.54	13.64
4.6573	42.87	peak	11.03	53.90	69.54	15.64
7.1946	26.13	peak	10.07	36.20	69.54	33.34


2) Above 30 MHz

**Horizontal**



Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30.9700	23.40	QP	0.80	24.20	40.00	15.80
55.2200	31.68	QP	-12.18	19.50	40.00	20.50
134.7600	28.61	QP	-5.11	23.50	43.50	20.00
153.1900	31.53	QP	-5.93	25.60	43.50	17.90
201.6900	30.14	QP	-5.84	24.30	43.50	19.20
326.8200	27.44	QP	-3.14	24.30	46.00	21.70

**Vertical**



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
32.9100	32.23	QP	-0.63	31.60	40.00	8.40
55.2200	37.78	QP	-12.18	25.60	40.00	14.40
152.2200	34.52	QP	-5.92	28.60	43.50	14.90
174.5300	34.03	QP	-6.83	27.20	43.50	16.30
184.2300	32.65	QP	-7.25	25.40	43.50	18.10
199.7500	28.97	QP	-5.87	23.10	43.50	20.40

\*\*\*\*\* END OF REPORT \*\*\*\*\*