

FCC ID: 2APMJ-AIRBUDS6

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT: Left

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-8.381	0.15	-9±1	-8	0.16	<5	0.04913	3.00	YES
	2.441	-7.96	0.16	-8±1	-7	0.20	<5	0.06235	3.00	YES
	2.480	-7.52	0.18	-8±1	-7	0.20	<5	0.06284	3.00	YES
π/4-DQPSK	2.402	-7.403	0.18	-8±1	-7	0.20	<5	0.06185	3.00	YES
	2.441	-7.167	0.19	-8±1	-7	0.20	<5	0.06235	3.00	YES
	2.480	-6.704	0.21	-7±1	-6	0.25	<5	0.07911	3.00	YES

BT: Right

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-8.107	0.15	-9±1	-8	0.16	<5	0.04913	3.00	YES
	2.441	-7.795	0.17	-8±1	-7	0.20	<5	0.06235	3.00	YES
	2.480	-7.411	0.18	-8±1	-7	0.20	<5	0.06284	3.00	YES
π/4-DQPSK	2.402	-6.769	0.21	-7±1	-6	0.25	<5	0.07786	3.00	YES
	2.441	-6.379	0.23	-7±1	-6	0.25	<5	0.07849	3.00	YES
	2.480	-6.871	0.21	-7±1	-6	0.25	<5	0.07911	3.00	YES

Conclusion:

For the max result : $0.07911 \leq 3.0$ for 1g SAR, SAR is not required.



Signature:

Date: 2021-10-14

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.